RAJALAKSHMI ENGINEERING COLLEGE

RAJALAKSHMI NAGAR, THANDALAM – 602 105

RAJALAKSHMI ENGINEERING COLLEGE

CS23331 - DESIGN AND ANALYSIS OF ALGORITHMS

Laboratory Record Note Book

Name ..... Prathiksha R .....

Year / Branch / ..... 2nd year - Computer Science and Design .....

University Register No. ..... 2116251701042 .....

College Roll No. ..... 251701042 .....

Semester ..... 3rd .....

Academic Year ..... 2025 - 2026 .....

INDEX PAGE

Exp.No	Name of the Experiment	Date of Completion
1.	Finding Complexity using Counter method	03/08/2026
2.	Finding Complexity using Counter method	03/08/2026
3.	Finding Complexity using Counter method	03/08/2026
4.	Finding Complexity using Counter method	30/08/2026
5.	Finding Complexity using Counter method	30/08/2026
6.	1-G Coin Problem	08/09/2026
7.	2-G Cookies Problem	08/09/2026
8.	3-G Burger Problem	08/09/2026
9.	4-G Array Sum max problem	08/09/2026
10.	5-G Product of Array elements-Minimum	08/09/2026
11.	1-Number of Zeros in a Given Array	28/09/2026
12.	2-Majority Element	28/09/2026
13.	3-Finding Floor Value	28/09/2026
14.	4-Two Elements sum to x	28/09/2026

15.	5-Implementation of Quick Sort	28/09/2026
16.	1-DP-Playing with Numbers	07/10/2026
17.	2-DP-Playing with Chessboard	07/10/2026
18.	3-DP-Longest Common Subsequence	07/10/2026
19.	4-DP-Longest non-decreasing Subsequence	07/10/2026
20.	1-Finding Duplicates-O(n^2) Time Complexity,O(1) space complexity	08/10/2026
21.	2-Finding Duplicates-O(n) Time Complexity,O(1) space complexity	08/10/2026
22.	3-Print Intersection of 2 sorted arrays-O(m*n) Time complexity,O(1) Space complexity	08/10/2026
23.	4-Print Intersection of 2 sorted arrays-O(m+n) Time complexity,O(1) Space complexity	08/10/2026
24.	5-Pair with Difference-O(n^2) Time complexity,O(1) Space	08/10/2026

	complexity	
25.	**6-Pair with Difference-O(n) Time complexity,O(1) Space complexity**	**08/10/2026**

Started on	Monday, 3 August 2026, 3:21 PM
State	Finished
Completed on	Monday, 3 August 2026, 3:46 PM
Time taken	24 mins 34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void function (int n)
{
    int i= 1;
    int s =1;
    while(s <= n)
    {
        i++;
        s += i;
    }
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

For example:

Input	Result
9	12

Answer: (penalty regime: 0 %)

Reset answer

```
#include<stdio.h>

int main()
{
    int n,i,s;
    int c = 0;
    scanf("%d", &n);

    i = 1;
    c ++;

    s = 1;
    c ++;

    while(s <= n)
    {
        c ++;

        i++;
        c++;

        s += i;
        c ++;
    }
    c ++;
    printf("%d",c);
```

```
27      return 0;
28  }
```

	Input	Expected	Got	
✔	9	12	12	✔
✔	4	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Monday, 3 August 2026, 3:57 PM
State	Finished
Completed on	Monday, 3 August 2026, 4:13 PM
Time taken	16 mins 15 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using the counter method.

```
void func(int n)
{
    if(n==1)
    {
      printf("*");
    }
    else
    {
     for(int i=1; i<=n; i++)
     {
       for(int j=1; j<=n; j++)
       {
          printf("*");
          printf("*");
          break;
       }
     }
   }
 }
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer: (penalty regime: 0 %)

Reset answer

```
#include<stdio.h>
void fn(int n)
{
    int c = 0;
    if(n == 1)
    {

    }
    else
    {
        int i = 1;
        c ++;
        while(i <= n)
        {
            c ++;
            int j = 1;
            c ++;

            if(j <= n)
            {
                c ++;


                c ++;
            }
```

```
            i ++;
            c ++;
        }
        c ++;
    }
    printf("%d", c);
}

int main()
{
    int n;
    scanf("%d", &n);
    fn(n);
    return 0;
}
```

	Input	Expected	Got	
✔	2	12	12	✔
✔	1000	5002	5002	✔
✔	143	717	717	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Monday, 24 August 2026, 5:09 PM
State	Finished
Completed on	Monday, 24 August 2026, 5:25 PM
Time taken	16 mins 23 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
Factor(num) {
{
   for (i = 1; i <= num;++i)
   {
    if (num % i== 0)
       {
         printf("%d ", i);
       }
    }
 }
```

Note: No need of counter increment for declarations and scanf() and counter variable printf() statement.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```c
#include<stdio.h>

int main()
{
    int num, i , c = 1;
    scanf("%d", &num);
    for(i = 1; i <= num; ++i)
    {
        c ++;
        if (num % i == 0)
        {
            c ++;
        }
        c ++;
    }
    printf("%d", c);

    return 0;
}
```

	Input	Expected	Got	
✔	12	31	31	✔
✔	25	54	54	✔

	Input	Expected	Got	
✔	4	12	12	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Sunday, 30 August 2026, 6:36 PM
State	Finished
Completed on	Sunday, 30 August 2026, 6:57 PM
Time taken	20 mins 7 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time

complexity using counter method.

```
void function(int n)
{
    int c= 0;
    for(int i=n/2; i<n; i++)
        for(int j=1; j<n; j = 2 * j)
            for(int k=1; k<n; k = k * 2)
                c++;
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```
#include<stdio.h>
int main()
{
    int n, c = 1;
    int i,j,k;
    scanf("%d", &n);

    i = n / 2;
    while(1)
    {
        c++;
        if (i >= n)
            break;
        j = 1;
        while(1)
        {
            c++;
            if (j >= n)
                break;
            k = 1;
            while(1)
            {
                c ++;
                if (k >= n)
                    break;
            c++;

            k = k * 2;
            }

            j = j * 2;
        }

        i ++;
    }
```

```
36      printf("%d", c);
37      return 0;
38  }
```

	Input	Expected	Got	
✔	4	30	30	✔
✔	10	212	212	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Sunday, 30 August 2026, 7:01 PM
State	Finished
Completed on	Sunday, 30 August 2026, 7:07 PM
Time taken	6 mins 24 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Convert the following algorithm into a program and find its time complexity using counter method.

```
void reverse(int n)
{
   int rev = 0, remainder;
   while (n != 0)
    {
        remainder = n % 10;
        rev = rev * 10 + remainder;
        n/= 10;

    }
print(rev);
}
```

Note: No need of counter increment for declarations and scanf() and count variable printf() statements.

Input:

A positive Integer n

Output:

Print the value of the counter variable

Answer:

Reset answer

```c
#include<stdio.h>
int main()
{
    int n;
    scanf("%d", &n);
    int c = 0;
    int rev = 0, rem;
    c ++;
    while(1)
    {
        c ++;
        if (n == 0)
            break;
        rem = n % 10;
        c ++;

        rev = rev * 10 + rem;
        c ++;
        n = n / 10;
        c ++;
    }
   // printf("%d", rev);
    c ++;

    printf("%d", c);
    return 0;
}
```

	Input	Expected	Got	
✔	12	11	11	✔
✔	1234	19	19	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

RAJALAKSHMI ENGINEERING COLLEGE

Prathiksha R 251701042-2025-CSD P2

Started on	Tuesday, 8 September 2026, 3:13 PM
State	Finished
Completed on	Tuesday, 8 September 2026, 3:19 PM
Time taken	5 mins 52 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a program to take value V and we want to make change for V Rs, and we have infinite supply of each of the denominations in Indian currency, i.e., we have infinite supply of { 1, 2, 5, 10, 20, 50, 100, 500, 1000} valued coins/notes, what is the minimum number of coins and/or notes needed to make the change.

Input Format:

Take an integer from stdin.

Output Format:

print the integer which is change of the number.

Example Input :

64

Output:

4

Explanaton:

We need a 50 Rs note and a 10 Rs note and two 2 rupee coins.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
int main()
{
    int V;
    int c = 0;

    scanf("%d", &V);

    c = c + V / 1000;
    V = V % 1000;

    c = c + V / 500;
    V = V % 500;

    c = c + V / 100;
    V = V % 100;

    c = c + V / 50;
    V = V % 50;

    c = c + V / 20;
    V = V % 20;

    c = c + V / 10;
    V = V % 10;

    c = c + V / 5;
    V = V % 5;

    c = c + V / 2;
    V = V % 2;

    c = c + V / 1;

    printf("%d", c);

    return 0;
}
```

	Input	Expected	Got	
✔	49	5	5	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Prathiksha R 251701042-2025-CSD

P2

Started on	Tuesday, 8 September 2026, 3:19 PM
State	Finished
Completed on	Tuesday, 8 September 2026, 3:37 PM
Time taken	17 mins 54 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Assume you are an awesome parent and want to give your children some cookies. But, you should give each child at most one cookie.

Each child i has a greed factor g[i], which is the minimum size of a cookie that the child will be content with; and each cookie j has a size s[j]. If s[j] >= g[i], we can assign the cookie j to the child i, and the child i will be content. Your goal is to maximize the number of your content children and output the maximum number.

Example 1:

Input:

3

1 2 3

2

1 1

Output:

1

Explanation: You have 3 children and 2 cookies. The greed factors of 3 children are 1, 2, 3.

And even though you have 2 cookies, since their size is both 1, you could only make the child whose greed factor is 1 content.

You need to output 1.

Constraints:

1 <= g.length <= 3 * 10^4

0 <= s.length <= 3 * 10^4

1 <= g[i], s[j] <= 2^31 - 1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
int main()
{
    int n,m;
    int G[30000], S[30000];
    int i,j = 0,  c = 0;
    int temp;

    scanf("%d", &n);

    for(i = 0;i < n; i ++)
    {
        scanf("%d", & G[i]);
    }
    scanf("%d", &m);

    for(i = 0;i < m; i ++)
    {
        scanf("%d", &S[i]);
    }

    for(i = 0; i < n - 1; i ++)
    {
        for(int k = i + 1; k < n; k ++)
        {
            if(G[i] > G[k])
            {
                temp = G[i];
                G[i] = G[k];
                G[k] = temp;
```

```
            }
        }
    }
    for(i = 0; i < m - 1; i ++)
    {
       for(int k = i + 1; k < m; k ++)
       {
           if(S[i] > S[k])
           {
               temp = S[i];
               S[i] = S[k];
               S[k] = temp;
           }
       }
    }
    i = 0;
    while(i < n && j < m)
    {
        if(S[i] >= G[i])
        {
            c ++;
            i ++;
```

	Input	Expected	Got	
✔	2 1 2 3 1 2 3	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Started on	Tuesday, 8 September 2026, 3:40 PM
State	Finished
Completed on	Tuesday, 8 September 2026, 4:26 PM
Time taken	45 mins 27 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

A person needs to eat burgers. Each burger contains a count of calorie. After eating the burger, the person needs to run a distance to burn out his calories.

If he has eaten i burgers with c calories each, then he has to run at least $3^i * c$ kilometers to burn out the calories. For example, if he ate 3

burgers with the count of calorie in the order: [1, 3, 2], the kilometers he needs to run are $(3^0 * 1) + (3^1 * 3) + (3^2 * 2) = 1 + 9 + 18 = 28$.

But this is not the minimum, so need to try out other orders of consumption and choose the minimum value. Determine the minimum distance

he needs to run. Note: He can eat burger in any order and use an efficient sorting algorithm.Apply greedy approach to solve the problem.

Input Format

First Line contains the number of burgers

Second line contains calories of each burger which is n space-separate integers

Output Format

Print: Minimum number of kilometers needed to run to burn out the calories

Sample Input

```
3
5 10 7
```

Sample Output

```
76
```

For example:

Test	Input	Result
Test Case 1	3 1 3 2	18

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <math.h>

int main()
{
    int n;
    scanf("%d", &n);

    long long cal[n];
    for(int i = 0; i < n; i ++)
    {
        scanf("%lld", &cal[i]);
    }
    for(int i = 0; i < n - 1; i ++)
    {
        for(int j = 0; j < n - i - 1; j ++)
        {
            if(cal[j] < cal[j + 1])
            {
                int temp = cal[j];
                cal[j] = cal[j + 1];
```

```
                cal[j + 1] = temp;
            }
        }
    }
    int result = 0;

    for(int i = 0; i < n; i ++)
    {
        int ans = pow(n,i);
        result += ans * cal[i];
    }
    printf("%d", result);
    return 0;
}
```

	Test	Input	Expected	Got	
✔	Test Case 1	3 1 3 2	18	18	✔
✔	Test Case 2	4 7 4 9 6	389	389	✔
✔	Test Case 3	3 5 10 7	76	76	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Tuesday, 8 September 2026, 4:28 PM
State	Finished
Completed on	Tuesday, 8 September 2026, 4:35 PM
Time taken	7 mins 33 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array of N integer, we have to maximize the sum of arr[i] * i, where i is the index of the element (i = 0, 1, 2, ..., N).Write an algorithm based on Greedy technique with a Complexity O(nlogn).

Input Format:

First line specifies the number of elements-n

The next n lines contain the array elements.

Output Format:

Maximum Array Sum to be printed.

Sample Input:

5

2 5 3 4 0

Sample output:

40

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int compare(const void *a, const void *b)
{
    return(*(int *)a - *(int *)b);
}

int main ()
{
    int n;
    scanf("%d", &n);
    int a[n];
    for(int i = 0; i < n; i ++)
    {
        scanf("%d", &a[i]);
    }

    qsort(a,n,sizeof(int),compare);

    long long s = 0;
    for(int i = 0; i < n; i ++)
    {
        s += (long long)a[i] * i;
    }
    printf("%lld", s);
    return 0;
}
```

	Input	Expected	Got	
✔	5 2 5 3 4 0	40	40	✔

	Input	Expected	Got	
✔	10 2 2 2 4 4 3 3 5 5 5	191	191	✔
✔	2 45 3	45	45	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Tuesday, 8 September 2026, 4:37 PM
State	Finished
Completed on	Tuesday, 8 September 2026, 4:46 PM
Time taken	8 mins 56 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two arrays array_One[] and array_Two[] of same size N. We need to first rearrange the arrays such that the sum of the product of pairs(1 element from each) is minimum. That is SUM (A[i] * B[i]) for all i is minimum.

For example:

Input	Result
3 1 2 3 4 5 6	28

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int asc(const void *a, const void *b)
{
    return *(int *)a - *(int *)b;
}
int desc(const void *a, const void *b)
{
    return *(int *)b - *(int *)a;
}

int main()
{
    int n;
    scanf("%d", &n);

    int A[n], B[n];
    for(int i = 0; i < n ; i ++)
    {
        scanf("%d", &A[i]);
    }
    for(int i = 0; i < n; i ++)
    {
        scanf("%d", &B[i]);
    }

    qsort(A,n,sizeof(int),asc);
    qsort(B,n,sizeof(int),desc);

    long long s = 0;
    for(int i = 0; i < n; i ++)
    {
        s += (long long) A[i] * B[i];
    }
    printf("%lld", s);
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 3 4 5 6	28	28	✔
✔	4 7 5 1 2 1 3 4 1	22	22	✔
✔	5 20 10 30 10 40 8 9 4 3 10	590	590	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

RAJALAKSHMI ENGINEERING COLLEGE

Prathiksha R 251701042-2025-CSD

P2

Started on	Monday, 28 September 2026, 3:23 PM
State	Finished
Completed on	Monday, 28 September 2026, 3:52 PM
Time taken	29 mins 9 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement

Given an array of 1s and 0s this has all 1s first followed by all 0s. Aim is to find the number of 0s. Write a program using Divide and Conquer to Count the number of zeroes in the given array.

Input Format

First Line Contains Integer m – Size of array

Next m lines Contains m numbers – Elements of an array

Output Format

First Line Contains Integer – Number of zeroes present in the given array.

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int countZero(int a[], int l, int r)
{
    if (l == r)
        return a[l] == 0;

    int mid = (l + r) / 2;

    return countZero(a, l, mid) +
           countZero(a, mid + 1, r);
}

int main()
{
    int n, a[100], i;

    scanf("%d", &n);

    for (i = 0; i < n; i++)
        scanf("%d", &a[i]);

    printf("%d", countZero(a, 0, n - 1));

    return 0;
}
```

	Input	Expected	Got	
✔	5 1 1 1 0 0	2	2	✔

	Input	Expected	Got	
✔	10 1 1 1 1 1 1 1 1 1 1	0	0	✔
✔	8 0 0 0 0 0 0 0 0	8	8	✔
✔	17 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 0 0	2	2	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

Prathiksha R 251701042-2025-CSD

P2

Started on	Monday, 28 September 2026, 3:52 PM
State	Finished
Completed on	Monday, 28 September 2026, 4:06 PM
Time taken	13 mins 8 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array `nums` of size `n`, return *the majority element*.

The majority element is the element that appears more than `⌊n / 2⌋` times. You may assume that the majority element always exists in the array.

Example 1:

```
Input: nums = [3,2,3]
Output: 3
```

Example 2:

```
Input: nums = [2,2,1,1,1,2,2]
Output: 2
```

Constraints:

- `n == nums.length`
- `1 <= n <= 5 * 10^4`
- `-2^31 <= nums[i] <= 2^31 - 1`

For example:

Input	Result
3 3 2 3	3
7 2 2 1 1 1 2 2	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int count(int a[], int l, int r, int x)
{
    int c = 0, i;
    for (i = l; i <= r; i++)
        if (a[i] == x)
            c++;
    return c;
}

int majority(int a[], int l, int r)
{
    if (l == r)
        return a[l];

    int mid = (l + r) / 2;

    int left = majority(a, l, mid);
    int right = majority(a, mid + 1, r);

    if (left == right)
        return left;

    int lc = count(a, l, r, left);
    int rc = count(a, l, r, right);
```

```
27
28      if (lc > rc)
29          return left;
30      else
31          return right;
32  }
33
34  int main()
35  {
36      int n, a[50000], i;
37
38      scanf("%d", &n);
39
40      for (i = 0; i < n; i++)
41          scanf("%d", &a[i]);
42
43      printf("%d", majority(a, 0, n - 1));
44
45      return 0;
46  }
```

	Input	Expected	Got	
✔	3 3 2 3	3	3	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

Started on	Wednesday, 30 September 2026, 9:42 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:48 PM
Time taken	5 mins 18 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array and a value x, the floor of x is the largest element in array smaller than or equal to x. Write divide and conquer algorithm to find floor of x.

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Value for x

Output Format

First Line Contains Integer – Floor value for x

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int floorvalue(int a[], int l, int r, int x)
{
    if(l > r)
    return -1;

    int mid = (l+r)/2;

    if (a[mid] < x)
    {
        int ans = floorvalue(a,mid+1,r,x);
        if(ans == -1)
        return a[mid];
        else
        return ans;
    }
    return floorvalue(a,l,mid-1,x);
}
int main()
{
    int n,x;
    scanf("%d", &n);
    int a[n];
    for(int i = 0; i < n; i ++)
    scanf("%d", &a[i]);
    scanf("%d", &x);
    printf("%d", floorvalue(a,0,n-1,x));
    return 0;
}
```

	Input	Expected	Got	
✔	6 1 2 8 10 12 19 5	2	2	✔

	Input	Expected	Got	
✔	5 10 22 85 108 129 100	85	85	✔
✔	7 3 5 7 9 11 13 15 10	9	9	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 30 September 2026, 9:49 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 9:54 PM
Time taken	4 mins 43 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem Statement:

Given a sorted array of integers say arr[] and a number x. Write a recursive program using divide and conquer strategy to check if there exist two elements in the array whose sum = x. If there exist such two elements then return the numbers, otherwise print as "No".

Note: Write a Divide and Conquer Solution

Input Format

First Line Contains Integer n – Size of array

Next n lines Contains n numbers – Elements of an array

Last Line Contains Integer x – Sum Value

Output Format

First Line Contains Integer – Element1

Second Line Contains Integer – Element2 (Element 1 and Elements 2 together sums to value "x")

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
int fp(int a[], int l, int r, int x)
{
    if(l >= r)
    return 0;
    int sum = a[l] + a[r];
    if(sum == x)
    {
        printf("%d\n%d", a[l], a[r]);
        return 1;
    }
    if(sum < x)
    return fp(a,l+1,r,x);
    else
    return fp(a,l,r-1,x);
}
int main()
{
    int n,x;
    scanf("%d", &n);
    int a[n];
    for(int i = 0; i < n; i ++)
    scanf("%d", &a[i]);
    scanf("%d", &x);
    if(!fp(a,0,n-1,x))
    printf("No");
    return 0;
}
```

	Input	Expected	Got	
✔	4 2 4 8 10 14	4 10	4 10	✔

	Input	Expected	Got	
✔	5 2 4 6 8 10 100	No	No	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 30 September 2026, 9:56 PM
State	Finished
Completed on	Wednesday, 30 September 2026, 10:04 PM
Time taken	8 mins 36 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a Program to Implement the Quick Sort Algorithm

Input Format:
The first line contains the no of elements in the list-n
The next n lines contain the elements.

Output:
Sorted list of elements

For example:

Input	Result
5 67 34 12 98 78	12 34 67 78 98

Answer:

```c
#include <stdio.h>
void qs(int a[], int low, int high)
{
    if(low < high)
    {
        int i = low;
        int j = high;
        int piv = a[low];
        while(i < j)
        {
            while(a[i] <= piv && i < high)
            i ++;
            while(a[j] > piv)
            j --;
            if(i < j)
            {
                int temp = a[i];
                a[i] = a[j];
                a[j] = temp;
            }
        }
        int temp = a[low];
        a[low] = a[j];
        a[j] = temp;
        qs(a,low,j-1);
        qs(a,j+1,high);
    }
}
int main()
{
    int n;
    scanf("%d", &n);
    int a[n];
    for(int i = 0; i < n; i ++)
    scanf("%d", &a[i]);
    qs(a,0,n-1);
    for(int i = 0; i < n; i ++)
    printf("%d ", a[i]);
    return 0;
}
```

	Input	Expected	Got	
✔	5 67 34 12 98 78	12 34 67 78 98	12 34 67 78 98	✔
✔	10 1 56 78 90 32 56 11 10 90 114	1 10 11 32 56 56 78 90 90 114	1 10 11 32 56 56 78 90 90 114	✔
✔	12 9 8 7 6 5 4 3 2 1 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	1 2 3 4 5 6 7 8 9 10 11 90	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 7 October 2026, 8:05 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 8:14 PM
Time taken	8 mins 25 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Numbers:

Ram and Sita are playing with numbers by giving puzzles to each other. Now it was Ram term, so he gave Sita a positive integer 'n' and two numbers 1 and 3. He asked her to find the possible ways by which the number n can be represented using 1 and 3.Write any efficient algorithm to find the possible ways.

Example 1:

Input: *6*

Output:*6*

Explanation: *There are 6 ways to 6 represent number with 1 and 3*

1+1+1+1+1+1

3+3

1+1+1+3

1+1+3+1

1+3+1+1

3+1+1+1

Input Format

First Line contains the number n

Output Format

Print: The number of possible ways 'n' can be represented using 1 and 3

Sample Input

6

Sample Output

6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n,i;
    scanf("%d", &n);
    long long dp[n + 1];
    dp[0] = 1;
    for (i = 1; i <= n; i ++)
    {
        dp[i] = 0;
        dp[i] = dp[i - 1];

        if (i >= 3)
        {
            dp[i] = dp[i] + dp[i - 3];
        }
    }

    printf("%lld", dp[n]);

    return 0;
}
```

	Input	Expected	Got	
✔	6	6	6	✔
✔	25	8641	8641	✔
✔	100	24382819596721629	24382819596721629	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Started on	Wednesday, 7 October 2026, 9:38 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 10:02 PM
Time taken	23 mins 31 secs
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 10.00 out of 10.00

Playing with Chessboard:

Ram is given with an n*n chessboard with each cell with a monetary value. Ram stands at the (0,0), that the position of the top left white rook. He is been given a task to reach the bottom right black rook position (n-1, n-1) constrained that he needs to reach the position by traveling the maximum monetary path under the condition that he can only travel one step right or one step down the board. Help ram to achieve it by providing an efficient DP algorithm.

Example:

Input

3

1 2 4

2 3 4

8 7 1

Output:

19

Explanation:

Totally there will be 6 paths among that the optimal is

Optimal path value:1+2+8+7+1=19

Input Format

First Line contains the integer n

The next n lines contain the n*n chessboard values

Output Format

Print Maximum monetary value of the path

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main ()
{
    int n;
    scanf("%d", &n);

    int a[n][n];

    for(int  i = 0; i < n; i ++)

        for(int j = 0; j < n; j ++)

            scanf("%d", &a[i][j]);

    for(int i = 0; i < n; i ++)
    {
        for(int j = 0; j < n; j ++)
        {
            if(i == 0 && j > 0)
            {
                a[i][j] += a[i][j - 1];
            }
            else if ( j == 0 && i > 0)
            {
                a[i][j] += a[i - 1][j];
            }
            else if ( i > 0 && j > 0)
            {
                a[i][j] += a[i - 1][j] > a[i][j - 1] ? a[i - 1][j] : a[i][j - 1];
```

```
            }
        }
    }

    printf("%d", a[n - 1][n - 1]);

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 2 4 2 3 4 8 7 1	19	19	✔
✔	3 1 3 1 1 5 1 4 2 1	12	12	✔
✔	4 1 1 3 4 1 5 7 8 2 3 4 6 1 6 9 0	28	28	✔

Passed all tests! ✔

Correct

Marks for this submission: 10.00/10.00.

Started on	Wednesday, 7 October 2026, 10:04 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 10:10 PM
Time taken	5 mins 50 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

s1	a	g	**g**	**t**	**a**	**b**	
s2	**g**	x	**t**	**x**	**a**	**y**	**b**

The length is 4

Solveing it using Dynamic Programming

For example:

Input	Result
aab azb	2

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <string.h>

int main()
{
    char a[100], b[100];
    int d[101][101] = {0},i,j;

    scanf("%s%s", a,b);

    for(i = 1; i <= strlen(a); i ++)
    {
        for(j = 1; j <= strlen(b); j ++)
        {
            d[i][j] = a[i - 1] == b[j - 1] ? d[i - 1][j - 1] + 1 : (d[i - 1][j] > d[i][j - 1] ? d[i - 1][j] : d[i
        }
    }

    printf("%d", d[i - 1][j - 1]);
}
```

	Input	Expected	Got	
✔	aab azb	2	2	✔

	Input	Expected	Got	
✔	ABCD ABCD	4	4	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 7 October 2026, 10:12 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 10:19 PM
Time taken	7 mins 18 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Problem statement:

Find the length of the Longest Non-decreasing Subsequence in a given Sequence.

Eg:

Input:9

Sequence:[-1,3,4,5,2,2,2,2,3]

the subsequence is [-1,2,2,2,2,3]

Output:6

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
int main()
{
    int n,a[100],d[100],m=0;
    scanf("%d", &n);

    for(int i = 0; i < n; i ++)
    {
        scanf("%d", &a[i]);
        d[i] = 1;
        for(int j = 0; j < i ; j ++)
        {
            if(a[j] <= a[i] && d[j] + 1 > d[i])
            {
                d[i] = d[j] + 1;
            }
        }
            if ( d[i] > m)
            {
                m = d[i];
            }
    }

    printf("%d", m);
}
```

	Input	Expected	Got	
✔	9 -1 3 4 5 2 2 2 2 3	6	6	✔
✔	7 1 2 2 4 5 7 6	6	6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Wednesday, 7 October 2026, 10:21 PM
State	Finished
Completed on	Wednesday, 7 October 2026, 10:23 PM
Time taken	2 mins 38 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```
#include <stdio.h>

int main()
{
    int n, a[100], c[101] = {0};

    scanf("%d", &n);

    for(int i = 0; i < n; i ++)
    {
        scanf("%d", &a[i]);
        if(++c[a[i]] == 2)
        {
            printf("%d", a[i]);
            break;
        }
    }

    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 1:29 PM
State	Finished
Completed on	Thursday, 8 October 2026, 1:34 PM
Time taken	5 mins 28 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main()
{
    int n;
    scanf("%d", &n);

    int a[100];

    for(int i = 0; i < n; i ++)
    {
        scanf("%d", &a[i]);
    }

    for(int i = 0; i <n; i ++)
    {
        for(int j = i + 1; j < n; j ++)
        {
            if (a[i] == a[j])
            {
                printf("%d", a[i]);
                return 0;
            }
        }
    }
    return 0;
}
```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 1:42 PM
State	Finished
Completed on	Thursday, 8 October 2026, 1:58 PM
Time taken	15 mins 54 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
    int T,n1,n2;
    scanf("%d", &T);
    while(T--)
    {
        scanf("%d", &n1);
        int a[n1];
        for(int i = 0; i < n1; i ++)
           scanf("%d", &a[i]);
       scanf("%d", &n2);
       int b[n2];
       for(int i = 0 ; i < n2; i ++)
```

```
        scanf("%d", &b[i]);

    int i = 0;
    int j = 0;

    while( i < n1 && j < n2)
    {
        if(a[i] == b[j])
        {
            printf("%d ",a[i]);
            i ++;
            j ++;
        }
        else if (a[i] < b[j])
        {
            i ++;
        }
        else
        {
            j ++;
        }
    }
    printf("\n");
    }
    return 0;
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 7:10 PM
State	Finished
Completed on	Thursday, 8 October 2026, 7:54 PM
Time taken	43 mins 34 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
   int n;
   scanf("%d", &n);
   while(n--)
   {
       int n1;
       scanf("%d", &n1);
       int a[n1];
       for(int i = 0; i < n1; i ++) scanf("%d", &a[i]);
       int n2;
       scanf("%d",&n2);
       int b[n2];
```

```
        for(int i = 0; i < n2; i ++) scanf("%d", &b[i]);
        int i= 0,j = 0;
        while(i < n1 && j < n2)
        {
            if(a[i] == b[j])
            {
                printf("%d ",a[i]);
                i++;
                j++;
            }
            else if(a[i] < b[j])
            i ++;
            else
            j ++;
        }
    }
}
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 7:56 PM
State	Finished
Completed on	Thursday, 8 October 2026, 8:01 PM
Time taken	4 mins 43 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
    int n,a[100];
    scanf("%d",&n);

    for(int i=0;i<n;i++)
    {
        scanf("%d", &a[i]);
    }

    int k;
    scanf("%d", &k);

    for (int i=0;i<n;i++)
        for(int j=i+1;j<n;j++)
            if(a[j]-a[i] == k)
            {
                printf("1");
                return 0;
            }
    printf("0");
    return 0;

}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 8:02 PM
State	Finished
Completed on	Thursday, 8 October 2026, 8:07 PM
Time taken	5 mins 20 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
    int n,i=0,j=1;
    int a[1000];
    scanf("%d",&n);

    for(int x = 0; x < n; x ++)
        scanf("%d", &a[x]);

    int k;
    scanf("%d", &k);

    while(j<n)
    {
        if(a[j]-a[i] == k)
        {
            printf("1");
            return 0;
        }
        if(a[j]-a[i] < k)
         j++;
        else
         i++;

        if(i==j)
         j++;
    }
    printf("0");
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Started on	Thursday, 8 October 2026, 8:09 PM
State	Finished
Completed on	Thursday, 8 October 2026, 8:14 PM
Time taken	4 mins 43 secs
Marks	2.00/2.00
Grade	**20.00** out of 20.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Write a C program to find the factorial of given n.

For example:

Input	Result
5	120

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
    int n,f=1;
    scanf("%d", &n);

    for(int i = 1; i <= n; i ++)
        f *= i;

    printf("%d",f);
    return 0;
}
```

	Input	Expected	Got	
✔	5	120	120	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Question 2 | Correct Mark 1.00 out of 1.00

Write a C program to find whether the given integer is odd or even?

For example:

Input	Result
12	Even
11	Odd

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
int main()
{
    int n;
    scanf("%d", &n);

    if(n % 2 == 0)
        printf("Even");
    else
        printf("Odd");

    return 0;
}
```

	Input	Expected	Got	
✔	12	Even	Even	✔
✔	11	Odd	Odd	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.