| | |
|---|---|
| **Started on** | Wednesday, 7 October 2026, 10:04 PM |
| **State** | Finished |
| **Completed on** | Wednesday, 7 October 2026, 10:10 PM |
| **Time taken** | 5 mins 50 secs |
| **Marks** | 1.00/1.00 |
| **Grade** | **10.00** out of 10.00 (**100**%) |

**Question 1** | Correct Mark 1.00 out of 1.00

Given two strings find the length of the common longest subsequence(need not be contiguous) between the two.

Example:

s1: ggtabe

s2: tgatasb

| | | | | | | | |
|---|---|---|---|---|---|---|---|
| s1 | a | g | **g** | **t** | **a** | **b** | |
| s2 | **g** | x | **t** | **x** | **a** | **y** | **b** |

**The length is 4**

Solveing it using Dynamic Programming

**For example:**

| Input | Result |
|---|---|
| aab<br>azb | 2 |

**Answer:** (penalty regime: 0 %)

```
#include <stdio.h>
#include <string.h>

int main()
{
    char a[100], b[100];
    int d[101][101] = {0},i,j;

    scanf("%s%s", a,b);

    for(i = 1; i <= strlen(a); i ++)
    {
        for(j = 1; j <= strlen(b); j ++)
        {
            d[i][j] = a[i - 1] == b[j - 1] ? d[i - 1][j - 1] + 1 : (d[i - 1][j] > d[i][j - 1] ? d[i - 1][j] : d[i
        }
    }

    printf("%d", d[i - 1][j - 1]);
}
```

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | aab<br>azb | 2 | 2 | ✔ |

| | Input | Expected | Got | |
|---|---|---|---|---|
| ✔ | ABCD<br>ABCD | 4 | 4 | ✔ |

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.