


Problem Set 1 — October 24, 2021

- 1. From a group of 5 assistant professors, 6 associate professors, and 4 professors, a group of 2 assistant professors, 2 associate professors, and 3 professors need to be chosen to form a thesis committee of 7 members; How many different such thesis committees are possible?
- 2. 9 computers are brought in for servicing (and machines are serviced one at a time). Of the 9 computers, 3 are PCs, 4 are Macs, and 2 are Linux machines. Assume that all computers of the same type are indistinguishable (i.e., all the PCs are indistinguishable, all the Macs are indistinguishable, etc.).
 - (a) In how many distinguishable ways can the computers be ordered for servicing?
 - (b) In how many distinguishable ways can the computers be ordered if the first 5 machines serviced must include all 4 Macs?
 - (c) In how many distinguishable ways can the computers be ordered if 2 PCs must be in the first three and 1 PC must be in the last three computers serviced?
- 3. Say you have 20 lakh rupees that must be invested among 4 possible companies. Each investment must be in integral units of 1 lakh rupees, and there are minimal investments that need to be made if one is to invest in these companies. The minimal investments are 1, 2, 3, and 4 lakh rupees, respectively for company 1, 2, 3, and 4. How many different investment strategies are available if:
 - (a) an investment must be made in each company?
 - (b) investments must be made in at least 3 of the 4 companies?
- 4. Eleven soccer players are to be divided into 4 functional groups: 3 forwards, 3 midfields, 4 defenses, and 1 goalie. There are only 2 people who can play goalie. Both of these two players can play any other position. Of the remaining 9, 4 can play only forward or midfield; the other 5 can play only defense or midfield. We want to calculate the number of possible ways to divide the team into the 4 functional groups. Follow the hint below and get to the answer:

- 5. In how many ways can r identical server requests be distributed among n servers so that the ith server receives at least m_i requests, for each i = 1, 2, ..., n? You can assume that $r \ge (m_1 + m_2 + \cdots + m_n)$.
- 6. Suppose a particle starting from the origin can move only up or down; the binomial option pricing model addresses stock price movements using such an idea.



Show that the number of ways the particle can move from the origin to position k in n steps is $\binom{n}{\frac{n+k}{2}}$. Assume that n+k is even.