Status	Finished
Started	Tuesday, 20 October 2026, 7:04 PM
Completed	Tuesday, 20 October 2026, 7:07 PM
Duration	3 mins 36 secs
Grade	**13.00** out of 15.00 (**86.67**%)

Question **1**

Incorrect

Mark 0.00 out of 1.00

What is the use of seek() method in files?

a. sets the file's current position at the offset

b. sets the file's previous position at the offset

c. none of the mentioned

d. sets the file's current position within the file ✗

The correct answer is:
sets the file's current position at the offset

Question **2**

Correct

Mark 1.00 out of 1.00

How do you check if a file is closed in Python?

a. file.closed()

b. file.isclosed()

c. file.is_closed()

d. file.closed ✓

The correct answer is: file.closed

Question **3**

Correct

Mark 1.00 out of 1.00

The readlines() method returns _____

a. str

b. a list of lines ✓

c. a list of integers

d. a list of single characters

The correct answer is:
a list of lines

Question **4**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in read mode ('r') that does not exist?

a. An empty file object is returned

b. An error is raised ✓

c. The operation is ignored

d. A new file is created

The correct answer is: An error is raised

Question **5**

Correct

Mark 1.00 out of 1.00

Default EOL character of text file in python is ,

a. space

b. \n ✓

c. \t

d. ,

The correct answer is:
\n

Question **6**

Correct

Mark 1.00 out of 1.00

To open a file c:\scores.txt for appending data, we use _____

a. outfile = open(file = "c:\scores.txt", "w")

b. outfile = open("c:\\scores.txt", "a") ✓

c. outfile = open("c:\\scores.txt", "rw")

d. outfile = open(file = "c:\\scores.txt", "w")

The correct answer is:
outfile = open("c:\\scores.txt", "a")

Question **7**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

a. None

b. An empty string ✓

c. EOFError

d. 0

The correct answer is: An empty string

Question **8**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. finish()

b. close() ✓

c. end()

d. terminate()

The correct answer is: close()

Question **9**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

a. Python Programming

b. Program

c. Python ✓

d. An error is raised

The correct answer is: Python

Question **10**

Incorrect

Mark 0.00 out of 1.00

To open a file c:\scores.txt for writing, we use ____

a. outfile = open("c:\\scores.txt", "w")

b. outfile = open(file = "c:\scores.txt", "w")

c. outfile = open("c:\scores.txt", "w")

d. outfile = open(file = "c:\\scores.txt", "w") ✗

The correct answer is:
outfile = open("c:\\scores.txt", "w")

Question **11**

Correct

Mark 1.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Opens an existing file in read mode

b. Appends to an existing file

c. Opens a file in binary mode

d. Creates a new file for writing ✓

The correct answer is: Creates a new file for writing

Question **12**

Correct

Mark 1.00 out of 1.00

What does the buffering parameter in the open() function control?

a. The file's read/write position

b. The access mode of the file

c. The encoding of the file

d. The buffer size for the file operations ✓

The correct answer is: The buffer size for the file operations

Question **13**

Correct

Mark 1.00 out of 1.00

If the file is opened in write mode and already exists, it truncates the existing content and places the filehandle at the beginning of the file.

Select one:

True ✓

False

The correct answer is 'True'.

Question **14**

Correct

Mark 1.00 out of 1.00

Which method is used to write data to a file?

- a. write() ✓
- b. insert()
- c. read()
- d. append()

The correct answer is: write()

Question **15**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

- a. infile = open(file, “a.txt”, “r”)
- b. infile = open(file = “a.txt”, “r”)
- c. infile = open(file = “a.txt”, “r”)
- d. infile = open(“a.txt”, “r”) ✓

The correct answer is:
infile = open(“a.txt”, “r”)