jupyter **Practical 9** Last Checkpoint: 3 hours ago (autosaved)

Logout

File Edit View Insert Cell Kernel Widgets Help | Not Trusted | Python 3 (ipykernel)

Run Code

In [1]:
```
import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
import seaborn as sns
%matplotlib inline
```

```
C:\ProgramData\Anaconda3\lib\site-packages\scipy\__init__.py:155: UserWarning: A NumPy version >=1.18.5 and <1.25.0 is required
for this version of SciPy (detected version 1.26.3
  warnings.warn(f"A NumPy version >={np_minversion} and <{np_maxversion}"
```

In [2]:
```
df = pd.read_csv("titanic.csv")
```

In [4]:
```
df.shape
```

Out[4]:
```
(891, 12)
```

In [5]:
```
df.head()
```

Out[5]:

	PassengerId	Survived	Pclass	Name	Sex	Age	SibSp	Parch	Ticket	Fare	Cabin	Embarked
0	1	0	3	Braund, Mr. Owen Harris	male	22.0	1	0	A/5 21171	7.2500	NaN	S
1	2	1	1	Cumings, Mrs. John Bradley (Florence Briggs Th...	female	38.0	1	0	PC 17599	71.2833	C85	C
2	3	1	3	Heikkinen, Miss. Laina	female	26.0	0	0	STON/O2. 3101282	7.9250	NaN	S
3	4	1	1	Futrelle, Mrs. Jacques Heath (Lily May Peel)	female	35.0	1	0	113803	53.1000	C123	S
4	5	0	3	Allen, Mr. William Henry	male	35.0	0	0	373450	8.0500	NaN	S

In [6]:
```
df.info()
```

```
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 891 entries, 0 to 890
Data columns (total 12 columns):
 #   Column       Non-Null Count  Dtype
---  ------       --------------  -----
 0   PassengerId  891 non-null    int64
 1   Survived     891 non-null    int64
 2   Pclass       891 non-null    int64
 3   Name         891 non-null    object
 4   Sex          891 non-null    object
 5   Age          714 non-null    float64
 6   SibSp        891 non-null    int64
 7   Parch        891 non-null    int64
 8   Ticket       891 non-null    object
 9   Fare         891 non-null    float64
 10  Cabin        204 non-null    object
 11  Embarked     889 non-null    object
dtypes: float64(2), int64(5), object(5)
memory usage: 83.7+ KB
```

jupyter **Practical 9** Last Checkpoint: 3 hours ago (autosaved)

Logout

File Edit View Insert Cell Kernel Widgets Help | Not Trusted | Python 3 (ipykernel)

Run Code

In [8]:
```
df.describe()
```

Out[8]:

	PassengerId	Survived	Pclass	Age	SibSp	Parch	Fare
count	891.000000	891.000000	891.000000	714.000000	891.000000	891.000000	891.000000
mean	446.000000	0.383838	2.308642	29.699118	0.523008	0.381594	32.204208
std	257.353842	0.486592	0.836071	14.526497	1.102743	0.806057	49.693429
min	1.000000	0.000000	1.000000	0.420000	0.000000	0.000000	0.000000
25%	223.500000	0.000000	2.000000	20.125000	0.000000	0.000000	7.910400
50%	446.000000	0.000000	3.000000	28.000000	0.000000	0.000000	14.454200
75%	668.500000	1.000000	3.000000	38.000000	1.000000	0.000000	31.000000
max	891.000000	1.000000	3.000000	80.000000	8.000000	6.000000	512.329200

In [9]:
```
df.isna().sum()
```

Out[9]:
```
PassengerId      0
Survived         0
Pclass           0
Name             0
Sex              0
Age            177
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin          687
Embarked         2
dtype: int64
```

In [10]:
```
df["Age"] = df["Age"].fillna(df["Age"].mean())
```

In [11]:
```
df.isna().sum()
```

Out[11]:
```
PassengerId      0
Survived         0
Pclass           0
Name             0
Sex              0
Age              0
SibSp            0
Parch            0
Ticket           0
Fare             0
Cabin          687
Embarked         2
dtype: int64
```

jupyter **Practical 9** Last Checkpoint: 3 hours ago (unsaved changes)

Logout

File Edit View Insert Cell Kernel Widgets Help

Not Trusted | Python 3 (ipykernel)

Run Code

In [10]:
```
#Visualization
def fun1(value):
    if (value == "male"):
        return 1
    else:
        return 0
```

In [11]:
```
def fun2(value):
    if (value == 'S'):
        return 0
    elif (value == 'C'):
        return 1
    elif (value == 'Q'):
        return 2
    else:
        return 0
```

In [12]:
```
df["Sex"] = df["Sex"].apply(fun1)
```

In [13]:
```
df["Embarked"] = df["Embarked"].apply(fun2)
```

In [14]:
```
df = df.drop("Cabin", axis=1)
```

In [15]:
```
df.shape
```

Out[15]: (891, 11)

In [16]:
```
import plotly.express as px
px.box(df["Sex"], df["Age"], color=df["Survived"])
```



jupyter **Practical 9** Last Checkpoint: 3 hours ago (unsaved changes)

Logout

File Edit View Insert Cell Kernel Widgets Help

Not Trusted | Python 3 (ipykernel)

Run Code

In [16]:
```
import plotly.express as px
px.box(df["Sex"], df["Age"], color=df["Survived"])
```



In [17]:
```
plt.figure(figsize=(10,7))
box = sns.boxplot(df["Sex"], df["Age"], hue=df["Survived"])
plt.show()
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\_decorators.py:36: FutureWarning:

Pass the following variables as keyword args: x, y. From version 0.12, the only valid positional argument will be `data`, and p
assing other arguments without an explicit keyword will result in an error or misinterpretation.
```

jupyter Practical 9 Last Checkpoint: 3 hours ago (unsaved changes)

Logout

File Edit View Insert Cell Kernel Widgets Help

Not Trusted | Python 3 (ipykernel)

Run Code

```
plt.show()
```

```
C:\ProgramData\Anaconda3\lib\site-packages\seaborn\_decorators.py:36: FutureWarning:

Pass the following variables as keyword args: x, y. From version 0.12, the only valid positional argument will be `data`, and p
assing other arguments without an explicit keyword will result in an error or misinterpretation.
```



In [ ]: