

Design of High PSRR Folded Cascode Operational Amplifier for LDO Applications

Harsh Gupta¹, Gaurav Kumar Mishra¹, Mr. Navaid Zafar Rizvi¹, and Dr. Santosh Kumar Patnaik²

School of Information and Communication Technology, Gautam Buddha University, Greater NOIDA 201308, India¹

Dept. of Electronics and Communication Engineering, NIST, Berhampur, Odisha, India²

gupta19harsh@gmail.com

Abstract— This paper presents a novel CMOS folded cascode operational amplifier that leads to high PSRR and provides gain nearly equal to that of a two stage op-amp. The proposed design is implemented in GPDK 0.18 μ m CMOS technology. This op-amp uses a folded cascode structure in the output stage combined with the differential amplifier having PMOS input transistors to achieve good input common mode range and lower flicker noise. It has an important feature that it allows the input common mode level close to supply voltage. The proposed topology improves the PSRR of op-amp which can be used for LDO applications. Simulations using Cadence under 1.8 V show a DC gain of 72.0404 dB and a phase margin of 62.4636 degree at a unity gain bandwidth of 13.33 MHz with the power consumption smaller than 0.13 mW along with a PSRR of 72.0966 dB. The layout of the design shows that the area acquired on the chip is approximately equal to 8897.27 μ m².

Keywords— *Folded Cascode Op-amp; Power Supply Rejection Ratio (PSRR); Input Common mode range.*

I. INTRODUCTION

Operational amplifier is an integral part of analog and mixed signal system. The design of high-performance op-amp has always been one of the hot spots of analog integrated circuit design as its performance directly affects the overall performance of circuits and system [1]. Hence, proper design of the op-amp is necessary according to the application where it is needed. With the continuous development of integrated circuit technology, high-performance op-amp is widely used in high-speed ADC, DAC, switched capacitor filter, band-gap voltage reference circuits, LDO regulators, precision comparators and other electronic devices.

With each generation of CMOS technology, the decrease in supply voltage and transistor length continuously brings more complex issue for the design of the op-amp [2]. Cascode amplifiers can have quite large gains and reduce significantly the Miller effect, which gives them an improved frequency response compared with that of other amplifiers [3]. The main aspects of folded cascode op-amp presented here are high DC gain and high PSRR. Therefore, among many op-amp topologies, folded cascode is one of the most common op-amp topologies that has high open-loop DC gain and proper frequency response. In [4, 5] authors have described that the folded cascode op-amp with PMOS input transistors has lower flicker noise than the folded cascode op-amp with NMOS input transistors which results in achieving high PSRR. This advantage makes this op-amp a main choice for LDO applications. MOS transistors provide DC gain and amplification in saturation region only. To ensure the device is

working under saturation region, bias potentials are tuned accordingly. Also, the current distribution in input and output stages along with the overdrive voltages of each branch is chosen according to meet the design specifications. The disadvantage of folded cascode op-amp compared with the telescopic cascode op-amp is higher current consumption. But the telescopic op-amp has lower input and output swing.

A complete analysis of fully differential folded cascode circuit along with layout is presented in this paper which shows how this circuit leads to a high PSRR and gain of a two stage op-amp in a single stage. Conventional architecture of folded cascode op-amp is introduced in Section II. In Section III design equations are developed in order to achieve dimensions of transistors and a sequence of design steps is established. Section IV includes simulation results which include graphical representation of gain and phase, slew rate and PSRR to visually illustrate design specifications. The results of simulations are shown to agree very well with the use of our design equations. Obtained results are also compared from previous work. It also describes good layout techniques that are implied for better protection of transistors against unavoidable mismatching issues during the fabrication process. Section V provides concluding remarks and future work that can be implemented on the proposed circuit.

II. FOLDED CASCODE AMPLIFIER

Folded cascode op-amp uses a cascoding in the output stage combined with an unusual implementation of differential amplifier to achieve good input common-mode input range. Thus, folded cascode op-amp offers self compensation, good input common mode range, and gain of a two stage op-amp [6]. In case of telescopic and cascode topology, although the current required is less as compared to folded cascode but to ensure every transistor to be in saturation region is quite harder than in folded cascode topology. The name “folded cascode” comes from folding down n- channel cascode active loads of a diff-pair and changing the MOSFETs to p-channels. This op-amp has good PSRR as compared to two-stage op-amp and telescopic op-amp [7].

As shown in Fig. 1 [8], M_1 and M_{1A} form one cascode structure and M_2 and M_{2A} form another. The current mirror converts the differential signal into single-ended output by sending variations in the drain current of M_{1A} to the output. The resulting op-amp is folded cascode op-amp. Bias is realized by making the currents in current sources M_{11} and M_{12} larger than $|I_{D5}|/2$. Thus,

$$I_{D1A} = I_{D2A} = I_{D11} - |I_{D5}|/2 = I_{D12} - |I_{D5}|/2 = I_{BIAS} - I_{TAIL}/2 \quad (1)$$




Fig. 1. Folded cascode op-amp with PMOS inputs.

Since M_3 and M_{3A} are diode connected, the voltage from V_{DD} to the gate of M_{4A} is $2|V_{tp}| + 2|V_{ov}|$. Therefore, the source-drain voltage of M_4 is $|V_{tp}| + |V_{ov}|$, and the maximum output for which both M_4 and M_{4A} operate in the saturation region is $V_{OUT(max)} = V_{DD} - |V_{tp}| - 2|V_{ov}|$. To find minimum output voltage, V_{BIAS2} is assumed such that M_{12} operates at the edge of saturation region. Then V_{DS} of M_{12} is equal to V_{ov} and $V_{OUT(min)} = -V_{SS} + 2V_{ov}$. Small signal voltage gain at low frequencies of this circuit is $A_v = G_m R_o$ where G_m is the transconductance of differential pair and R_o is the output resistance.




Fig. 2. Circuit for calculating output resistance R_o .

As shown in Fig. 2, the output resistance R_o will be,

$$R_o = (R_{out|M_{2A}}) \parallel (R_{out|M_{4A}}) \quad (2)$$

$$R_{out|M_{2A}} = (r_{o2} \parallel r_{o12}) + r_{o2A} [1 + (g_{m2A} + g_{mb2A})(r_{o2} \parallel r_{o12})] \approx [g_{m2A}(r_{o2} \parallel r_{o12})] r_{o2A} \quad (3)$$

$$R_{out|M_{4A}} = r_{o4} + r_{o4A} [1 + (g_{m4A} + g_{mb4A})(r_{o4})] \approx (g_{m4A} r_{o4}) r_{o4A} \quad (4)$$

Optimizing the amplifier for minimal power dissipation requires reducing the drain currents through the transistors, yet on the other hand, the gain is proportional to the drain current because,

$$g_m = 2I_D / (V_{GS} - V_{TH}) \quad (5)$$

Therefore the only compromise is to reduce the overdrive voltage of each device, but in doing so allow just enough voltage to prevent any devices from leaving the saturation region [9]. Hence trade-off is required between saturation current and overdrive voltage in order to optimize the gain.

III. PROPOSED DESIGN

The main part of folded cascode op-amp is the differential pair which acts as an input stage. Hence proper matching of the differential pair is quite important. Generally an op-amp consists of a differential pair in the first stage and a common source in the second stage so as to increase the overall gain of op-amp. But this requires an additional capacitance for the frequency compensation. Moreover, additional capacitance introduces a second pole in the amplifier system. The proposed design shown here, is set to achieve overall gain in the first stage. Also this op-amp helps in the rejection of different noise components present in the input signal and in the supply voltage.

Fig. 3 illustrates the complete schematic of the proposed design. It is composed of p-channel differential input pair (M_1, M_2), followed by common-gate stages (M_7, M_8) and current sources (M_5, M_6), and a self-biased cascode current mirror ($M_9 - M_{12}$) that inverts the current signal. M_3 and M_4 form a current mirror that provides bias current for differential input pair. Bias voltages V_{b1} and V_{b2} are provided to M_5-M_6 and M_7-M_8 respectively in order to meet the current specifications at the cascode stage so as to keep all the transistors in saturation region. The current flowing through M_7 and M_8 i.e. I_a is $I_b - I_{ref}/2$. Therefore, I_b must be higher than $I_{ref}/2$. For proper biasing of differential pair, I_{ref} taken here is equal to $40 \mu A$. A biasing circuit can also be used in this design. As the source terminals of M_5 and M_6 are grounded, hence their gate voltages i.e. V_{b1} can be calculated using overdrive voltage of that transistor. Hence, by adjusting the bias potentials V_{b1} and V_{b2} , I_b is set to $30 \mu A$. I_a will be equal to $10 \mu A$. The output current at load will be $2I_a$ i.e. $20 \mu A$. The W/L ratio of each transistor can be calculated with the help of design specifications given in table I and the saturation current equation given as;

$$I_D = (1/2) \mu_{n,p} C_{OX} (W/L)_i (V_{ov})^2 ; \text{ where } i = 1, 2, 3 \dots \quad (6)$$

Allocating appropriate overdrive voltages for each branch the bias voltages V_{b1} and V_{b2} can be found out. For NMOS and PMOS transistor V_t is chosen to be 470 mV and 450 mV respectively. The device parameters can be found in the cadence library. Calculated values of W/L are not enough to make op-amp work under saturation region and hence need to be tuned accordingly. Tuning is generally done through a series of simulations under different input values. A summary of aspect ratios of the transistors are tabulated in table II.




Fig. 6. Test setup for slew rate measurement.




Fig. 7. Plot of slew rate.

The slew rate of the op-amp is calculated as dV_{out} / dt . Using a pulse input with voltage variation from 0 V to 1.8 V the transient response of the circuit as shown in Fig. 6, gives the slew rate of 11.63 V/ μ sec. The power consumed by the circuit under 1.8 V is 129.553 μ W.

PSRR can be calculated by simulating the test circuit as shown in Fig. 7. An AC magnitude of 1 V is fed in the Vdd and Vin- is connected to the output. The AC analysis plot shown in Fig. 8 shows PSRR of -72.0966 dB.




Fig. 8. Test setup for PSRR measurement.




Fig. 9. PSRR curve.

TABLE III. COMPARISON OF THE PROPOSED FOLDED CASCODE OP-AMP WITH PRIOR DESIGNS

Parameters	[2]	[7]	[9]	[10]	[11]	[12]	[13]	Proposed
Technology	0.18 μ m	0.35 μ m	0.5 μ m	0.18 μ m	0.18 μ m	1.25 μ m	0.18 μ m	0.18 μ m
Supply Voltage (V)	3.3	2	3	1.2	\pm 1.65	\pm 2.5	1	1.8
Gain (dB)	96.29	85	67	50.9	77	73.6	67.81	72.04
PM (deg)	83.5	46	68	77.2	63	-	45.9	62.4
UGB (MHz)	-	230	270	490	140	9.5	0.9643	13.33
PSRR (dB)	-	85	-	-	77	25	-	72.49
Power (mW)	<0.1	-	<2.1	0.661	3.39	-	0.00724	<0.13

V. CONCLUSIONS AND FUTURE WORK

The op-amp proposed in this paper is implemented in GPDK 0.18 μ m CMOS technology which produces a gain of two stage op-amp in a single stage without the need of frequency compensation. High PSRR of 72.0966 dB is achieved under 1.8 V supply voltage. PMOS inputs used in differential pair are responsible for high PSRR of the amplifier. Results clearly indicate that the proposed design can be used in LDO applications.

To increase input and output swing further the current mirror used here can be replaced with high swing cascode current mirror. Stability of this amplifier can be increased using a common mode feedback circuit. For high gain applications gain boosting technique can be used.

Acknowledgments

This research work is made possible through the help and support from all my teachers and especially my mentor Dr. Santosh Kumar Patnaik. I would like to thank my mentor for discussions on layout design, post layout simulations and stability.

References

- [1] B. Razavi, Design of Analog CMOS Integrated Circuits, International ed. Singapore: McGraw-Hill, 2001.
- [2] Zhang Kun, Wu Di and Liu Zhangfa, "A High-performance Folded Cascode Amplifier," in Int. Conf. on Computer and Automation Engineering, Singapore, 2012, © IACSIT Press, doi: 10.7763/IPCST.2012.V44.8.
- [3] B. Grebene, Bipolar and MOS Analog Integrated Circuit Design, Hoboken, NJ: Wiley Interscience, 2003.
- [4] Akbari, M, Hashemipour, O., & Javid, A, "An ultra-low voltage, ultra-low power fully recycling folded cascode amplifier," The 22nd Iranian Conference on Electrical Engineering, ICEE 2014, pp. 514–518.
- [5] Assaad, R. S., & Silva-Martinez, J, "The recycling folded cascode: a general enhancement of the folded cascode amplifier," IEEE Journal of Solid-State Circuits, 2009, vol. 44, pp. 2535–2542.
- [6] P. E. Allen, D. R. Holdberg "CMOS Operational Amplifiers," in CMOS Analog Circuit Design, 2nd ed. New York, USA: Oxford Univ. Press, 2002, ch. 6, sec. 6.5, pp. 302-303.
- [7] H. Daoud, S. Ben Salem, S. Zouari, M. Loulou, "Folded Cascode OTA Design for Wide Band Applications," International Conference on Design and Test of Integrated Systems in Nanoscale Technology, 2006, pp. 437-440.
- [8] P.R. Gray, P.J. Hurst, S.H. Lewis and R.G. Meyer, "Operational Amplifiers with Single-Ended Outputs," in Analysis and Design of Analog Integrated Circuits, 5th ed. USA: Wiley, 2009, ch. 6, sec. 6.6, pp. 442-446.
- [9] A. Luxton & R. Hasan, "A low power high gain CMOS folded cascode amplifier," Institute of Information & Mathematical Sciences.
- [10] A. Arash, T. Pooya, "An Enhanced Bulk-Driven Folded-Cascode Amplifier in 0.18 μ m CMOS Technology," Journal of Scientific Research on Circuits and Systems, 2012, pp. 187 -191.
- [11] B. Krishna, D. Arun kumar, "Low Power High Speed Folded cascode Amplifier With PMOS Inputs," Int. Journal of Engineering Research and Applications, Vol. 4, Issue. 3, pp. 732-734.
- [12] Er. Rajni, "Design of High Gain Folded cascode Operational Amplifier Using 1.25 μ m CMOS Technology", International Journal of Scientific & Engineering Research Volume 2, Issue 11.
- [13] Raghav, H.S., Singh, B.P., Maheshwari. S, "Design of Low Voltage OTA for Bio-medical Application," in Int. Conf. on Microelectronics, Communication and Renewable Energy, 2013 © IEEE pp. 1-5.