



## COPPER RING TYPE TERMINAL

Paragon Ring Type Light Duty Cable Lugs used for Cable Wire Harness and Low Voltage Application. The terminal barrel is brazed and soft annealed, Which means that the terminal can be crimped either direction. All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection.

**PRODUCT DESCRIPTION:** SHEET METAL RING TYPE LUG  
STANDARD TYPE, BRAZED SEAM

**MATERIAL :** ETP GRADE COPPER  
**STANDARD :** BS 1897  
**RANGE :** 0.5 TO 150 SQMM





| PCL CAT NO.  | Size mm <sup>2</sup> | Stud Hole E | A   | C   | D   | F   | B | H   | L-1  | J    |
|--------------|----------------------|-------------|-----|-----|-----|-----|---|-----|------|------|
| PCLR-0.5 E-3 | 0.5                  | 3.2         | 1.2 | 2.8 | 6   | 0.8 | 5 | 6   | 10.5 | 14   |
| PCLR-0.5 E-4 | 0.5                  | 4.2         | 1.2 | 2.8 | 8   | 0.8 | 5 | 7   | 12   | 16   |
| PCLR-0.5 E-5 | 0.5                  | 5.2         | 1.2 | 2.8 | 8   | 0.8 | 5 | 7   | 12   | 16   |
| PCLR-001     | 1                    | 4.2         | 1.3 | 2.9 | 7   | 0.8 | 5 | 4   | 10.5 | 14   |
| PCLR-7153    | 1.5                  | 3.2         | 1.6 | 3.2 | 6.8 | 0.8 | 5 | 3.6 | 9.6  | 13   |
| PCLR-7048    | 1.5                  | 3.7         | 1.6 | 3.2 | 6.8 | 0.8 | 5 | 3.6 | 9.6  | 13   |
| PCLR-7049    | 1.5                  | 4.2         | 1.6 | 3.2 | 6.8 | 0.8 | 5 | 3.6 | 9.6  | 13   |
| PCLR-7154    | 1.5                  | 4.2         | 1.6 | 3.2 | 7   | 0.8 | 5 | 5   | 11   | 14.5 |
| PCLR-7103    | 1.5                  | 2.2         | 1.6 | 3.2 | 6   | 0.8 | 5 | 4   | 11   | 14   |
| PCLR-7000    | 1.5                  | 2.6         | 1.6 | 3.2 | 6   | 0.8 | 5 | 4   | 11   | 14   |
| PCLR-7001    | 1.5                  | 3.2         | 1.6 | 3.2 | 6   | 0.8 | 5 | 4   | 11   | 14   |
| PCLR-7002    | 1.5                  | 3.7         | 1.6 | 3.2 | 6   | 0.8 | 5 | 4   | 11   | 14   |
| PCLR-7003    | 1.5                  | 4.2         | 1.6 | 3.2 | 6   | 0.8 | 5 | 4   | 11   | 14   |
| PCLR-7104    | 1.5                  | 3.2         | 1.6 | 3.2 | 8   | 0.8 | 5 | 5   | 12   | 16   |
| PCLR-7004    | 1.5                  | 4.2         | 1.6 | 3.2 | 8   | 0.8 | 5 | 5   | 12   | 16   |
| PCLR-7005    | 1.5                  | 5.2         | 1.6 | 3.2 | 8   | 0.8 | 5 | 5   | 12   | 16   |
| PCLR-7105    | 1.5                  | 4.2         | 1.6 | 3.2 | 10  | 0.8 | 5 | 6   | 13   | 18   |
| PCLR-7006    | 1.5                  | 5.2         | 1.6 | 3.2 | 10  | 0.8 | 5 | 6   | 13   | 18   |
| PCLR-7007    | 1.5                  | 6.4         | 1.6 | 3.2 | 10  | 0.8 | 5 | 6   | 13   | 18   |
| PCLR-7106    | 1.5                  | 6.4         | 1.6 | 3.2 | 12  | 0.8 | 5 | 6   | 12   | 18   |
| PCLR-1.5-8   | 1.5                  | 8.2         | 1.6 | 3.2 | 12  | 0.8 | 5 | 9   | 16   | 22   |
| PCLR-7107    | 2.5                  | 3.2         | 2.3 | 3.9 | 6.5 | 0.8 | 5 | 3.5 | 9.5  | 12.7 |
| PCLR-7008    | 2.5                  | 3.7         | 2.3 | 3.9 | 6.5 | 0.8 | 5 | 3.5 | 9.5  | 12.7 |
| PCLR-7108    | 2.5                  | 3.7         | 2.3 | 3.9 | 8   | 0.8 | 5 | 5   | 12   | 16   |
| PCLR-7009    | 2.5                  | 4.2         | 2.3 | 3.9 | 8   | 0.8 | 5 | 5   | 12   | 16   |
| PCLR-7010    | 2.5                  | 5.2         | 2.3 | 3.9 | 8   | 0.8 | 5 | 5   | 12   | 16   |
| PCLR-7109    | 2.5                  | 5.2         | 2.3 | 3.9 | 10  | 0.8 | 5 | 7   | 13   | 18   |
| PCLR-7011    | 2.5                  | 6.4         | 2.3 | 3.9 | 10  | 0.8 | 5 | 7   | 13   | 18   |
| PCLR-7110    | 2.5                  | 5.2         | 2.3 | 3.9 | 12  | 0.8 | 5 | 9   | 16   | 22   |
| PCLR-7012    | 2.5                  | 6.4         | 2.3 | 3.9 | 12  | 0.8 | 5 | 9   | 16   | 22   |
| PCLR-7013    | 2.5                  | 8.2         | 2.3 | 3.9 | 12  | 0.8 | 5 | 9   | 16   | 22   |
| PCLR-7111    | 2.5                  | 6.4         | 2.3 | 3.9 | 16  | 0.8 | 5 | 10  | 17   | 25   |
| PCLR-7014    | 2.5                  | 8.2         | 2.3 | 3.9 | 16  | 0.8 | 5 | 10  | 17   | 25   |
| PCLR-7015    | 2.5                  | 10.2        | 2.3 | 3.9 | 16  | 0.8 | 5 | 10  | 17   | 25   |
| PCLR-7151    | 2.5                  | 10.2        | 2.3 | 3.9 | 18  | 0.8 | 5 | 14  | 20   | 29   |
| PCLR-7047    | 2.5                  | 12.7        | 2.3 | 3.9 | 18  | 0.8 | 5 | 14  | 20   | 29   |
| PCLR-7050    | 4-6                  | 5.2         | 3.5 | 5.5 | 8   | 1   | 6 | 5   | 13   | 17   |
| PCLR-7155    | 4-6                  | 4.2         | 3.5 | 5.5 | 8   | 1   | 6 | 5   | 13   | 17   |

## COPPER RING TYPE TERMINAL

Paragon Ring Type Light Duty Cable Lugs used for Cable Wire Harness and Low Voltage Application. The terminal barrel is brazed and soft annealed, Which means that the terminal can be crimped either direction. All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection.

**PRODUCT DESCRIPTION:** SHEET METAL RING TYPE LUG  
STANDARD TYPE, BRAZED SEAM

**MATERIAL :** ETP GRADE COPPER  
**STANDARD :** BS 1897  
**RANGE :** 0.5 TO 150 SQMM





| PCL CAT NO. | Size mm <sup>2</sup> | Stud Hole E | A   | C    | D  | F   | B  | H    | L-1  | J    |
|-------------|----------------------|-------------|-----|------|----|-----|----|------|------|------|
| PCLR-7112   | 4-6                  | 4.2         | 3.5 | 5.5  | 10 | 1   | 6  | 5    | 14   | 19   |
| PCLR-7016   | 4-6                  | 5.2         | 3.5 | 5.5  | 10 | 1   | 6  | 5    | 14   | 19   |
| PCLR-7113   | 4-6                  | 5.2         | 3.5 | 5.5  | 12 | 1   | 6  | 6    | 14   | 20   |
| PCLR-7017   | 4-6                  | 6.4         | 3.5 | 5.5  | 12 | 1   | 6  | 6    | 14   | 20   |
| PCLR-7018   | 4-6                  | 8.2         | 3.5 | 5.5  | 12 | 1   | 6  | 6    | 14   | 20   |
| PCLR-7114   | 4-6                  | 5.2         | 3.5 | 5.5  | 12 | 1   | 6  | 7    | 16   | 22   |
| PCLR-7019   | 4-6                  | 6.4         | 3.5 | 5.5  | 12 | 1   | 6  | 7    | 16   | 22   |
| PCLR-7157   | 4-6                  | 5.2         | 3.5 | 5.5  | 8  | 1   | 6  | 9.8  | 18.8 | 22.8 |
| PCLR-7115   | 4-6                  | 6.4         | 3.5 | 5.5  | 14 | 1   | 6  | 10.5 | 18.5 | 25.5 |
| PCLR-7020   | 4-6                  | 8.2         | 3.5 | 5.5  | 14 | 1   | 6  | 10.5 | 18.5 | 25.5 |
| PCLR-7021   | 4-6                  | 9.7         | 3.5 | 5.5  | 14 | 1   | 6  | 10.5 | 18.5 | 25.5 |
| PCLR-7116   | 4-6                  | 8.2         | 3.5 | 5.5  | 16 | 1   | 6  | 13   | 22   | 30   |
| PCLR-7022   | 4-6                  | 10.2        | 3.5 | 5.5  | 16 | 1   | 6  | 13   | 22   | 30   |
| PCLR-7117   | 4-6                  | 8.2         | 3.5 | 5.5  | 18 | 1   | 6  | 12   | 21   | 30   |
| PCLR-7023   | 4-6                  | 10.2        | 3.5 | 5.5  | 18 | 1   | 6  | 12   | 21   | 30   |
| PCLR-7024   | 4-6                  | 12.7        | 3.5 | 5.5  | 18 | 1   | 6  | 12   | 21   | 30   |
| PCLR-7119   | 10                   | 4.2         | 4.3 | 6.3  | 10 | 1   | 8  | 4    | 15   | 20   |
| PCLR-7026   | 10                   | 5.2         | 4.3 | 6.3  | 10 | 1   | 8  | 4    | 15   | 20   |
| PCLR-7118   | 10                   | 4.2         | 4.3 | 6.3  | 10 | 1   | 8  | 7    | 17   | 22   |
| PCLR-7025   | 10                   | 5.2         | 4.3 | 6.3  | 10 | 1   | 8  | 7    | 17   | 22   |
| PCLR-7120   | 10                   | 6.4         | 4.3 | 6.3  | 12 | 1   | 8  | 7    | 17   | 23   |
| PCLR-7121   | 10                   | 8.2         | 4.3 | 6.3  | 16 | 1   | 8  | 7    | 19   | 27   |
| PCLR-7122   | 10                   | 8.2         | 4.3 | 6.3  | 18 | 1   | 8  | 9    | 21   | 30   |
| PCLR-7027   | 10                   | 10.2        | 4.3 | 6.3  | 18 | 1   | 8  | 9    | 21   | 30   |
| PCLR-7028   | 10                   | 12.7        | 4.3 | 6.3  | 22 | 1   | 8  | 10   | 23   | 34   |
| PCLR-7123   | 10                   | 10.2        | 4.3 | 6.3  | 22 | 1   | 8  | 10   | 23   | 34   |
| PCLR-7124   | 16                   | 5.2         | 5.6 | 8    | 10 | 1.2 | 10 | 6    | 19   | 24   |
| PCLR-7125   | 16                   | 5.2         | 5.6 | 8    | 12 | 1.2 | 10 | 6    | 20   | 26   |
| PCLR-7029   | 16                   | 6.4         | 5.6 | 8    | 12 | 1.2 | 10 | 6    | 20   | 26   |
| PCLR-7126   | 16                   | 6.4         | 5.6 | 8    | 16 | 1.2 | 10 | 8    | 22   | 30   |
| PCLR-7030   | 16                   | 8.2         | 5.6 | 8    | 16 | 1.2 | 10 | 8    | 22   | 30   |
| PCLR-7031   | 16                   | 9.7         | 5.6 | 8    | 16 | 1.2 | 10 | 8    | 22   | 30   |
| PCLR-7127   | 16                   | 8.2         | 5.6 | 8    | 18 | 1.2 | 10 | 10   | 24   | 33   |
| PCLR-7032   | 16                   | 10.2        | 5.6 | 8    | 18 | 1.2 | 10 | 10   | 24   | 33   |
| PCLR-7128   | 16                   | 10.2        | 5.6 | 8    | 22 | 1.2 | 10 | 8    | 24   | 35   |
| PCLR-7033   | 16                   | 12.7        | 5.6 | 8    | 22 | 1.2 | 10 | 8    | 24   | 35   |
| PCLR-7129   | 25                   | 6.4         | 7.5 | 11.1 | 16 | 1.8 | 11 | 6    | 22   | 30   |
| PCLR-7034   | 25                   | 8.2         | 7.5 | 11.1 | 16 | 1.8 | 11 | 6    | 22   | 30   |

## COPPER RING TYPE TERMINAL

Paragon Ring Type Light Duty Cable Lugs used for Cable Wire Harness and Low Voltage Application. The terminal barrel is brazed and soft annealed, Which means that the terminal can be crimped either direction. All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection.

**PRODUCT DESCRIPTION:** SHEET METAL RING TYPE LUG  
STANDARD TYPE, BRAZED SEAM

**MATERIAL :** ETP GRADE COPPER  
**STANDARD :** BS 1897  
**RANGE :** 0.5 TO 150 SQMM



| PCL CAT NO. | Size mm <sup>2</sup> | Stud Hole E | A    | C    | D  | F   | B  | H  | L-1 | J  |
|-------------|----------------------|-------------|------|------|----|-----|----|----|-----|----|
| PCLR-7035   | 25                   | 10.2        | 7.5  | 11.1 | 16 | 1.8 | 11 | 6  | 22  | 30 |
| PCLR-7156   | 25                   | 6.4         | 7.5  | 11.1 | 12 | 1.8 | 11 | 10 | 25  | 31 |
| PCLR-7051   | 25                   | 8.2         | 7.5  | 11.1 | 12 | 1.8 | 11 | 10 | 25  | 31 |
| PCLR-7130   | 25                   | 6.4         | 7.5  | 11.1 | 16 | 1.8 | 11 | 10 | 25  | 33 |
| PCLR-7036   | 25                   | 8.2         | 7.5  | 11.1 | 16 | 1.8 | 11 | 10 | 25  | 33 |
| PCLR-7131   | 25                   | 10.2        | 7.5  | 11.1 | 18 | 1.8 | 11 | 9  | 25  | 34 |
| PCLR-7132   | 25                   | 10.2        | 7.5  | 11.1 | 22 | 1.8 | 11 | 14 | 31  | 42 |
| PCLR-7037   | 25                   | 12.7        | 7.5  | 11.1 | 22 | 1.8 | 11 | 14 | 31  | 42 |
| PCLR-7133   | 35                   | 6.4         | 9    | 12.6 | 16 | 1.8 | 12 | 6  | 23  | 31 |
| PCLR-7038   | 35                   | 8.2         | 9    | 12.6 | 16 | 1.8 | 12 | 6  | 23  | 31 |
| PCLR-7134   | 35                   | 8.2         | 9    | 12.6 | 18 | 1.8 | 12 | 10 | 27  | 36 |
| PCLR-7039   | 35                   | 10.2        | 9    | 12.6 | 18 | 1.8 | 12 | 10 | 27  | 36 |
| PCLR-7135   | 35                   | 10.2        | 9    | 12.6 | 22 | 1.8 | 12 | 15 | 31  | 42 |
| PCLR-7040   | 35                   | 12.7        | 9    | 12.6 | 22 | 1.8 | 12 | 15 | 31  | 42 |
| PCLR-7136   | 50                   | 8.2         | 10.5 | 14.1 | 18 | 1.8 | 16 | 12 | 34  | 43 |
| PCLR-7041   | 50                   | 10.2        | 10.5 | 14.1 | 18 | 1.8 | 16 | 12 | 34  | 43 |
| PCLR-7137   | 50                   | 10.2        | 10.5 | 14.1 | 22 | 1.8 | 16 | 9  | 32  | 43 |
| PCLR-7138   | 50                   | 10.2        | 10.5 | 14.1 | 24 | 1.8 | 16 | 14 | 36  | 48 |
| PCLR-7042   | 50                   | 12.7        | 10.5 | 14.1 | 24 | 1.8 | 16 | 14 | 36  | 48 |
| PCLR-7139   | 50                   | 16.2        | 10.5 | 14.1 | 32 | 1.8 | 16 | 15 | 38  | 54 |
| PCLR-7140   | 70                   | 10.2        | 12   | 16   | 22 | 2   | 18 | 11 | 36  | 47 |
| PCLR-7043   | 70                   | 12.7        | 12   | 16   | 22 | 2   | 18 | 11 | 36  | 47 |
| PCLR-7141   | 70                   | 12.7        | 12   | 16   | 24 | 2   | 18 | 10 | 36  | 48 |
| PCLR-7142   | 70                   | 16.2        | 12   | 16   | 28 | 2   | 18 | 16 | 40  | 54 |
| PCLR-7143   | 95                   | 10.2        | 13.5 | 18.1 | 22 | 2.3 | 20 | 10 | 35  | 46 |
| PCLR-7144   | 95                   | 10.2        | 13.5 | 18.1 | 24 | 2.3 | 20 | 12 | 38  | 50 |
| PCLR-7044   | 95                   | 12.7        | 13.5 | 18.1 | 24 | 2.3 | 20 | 12 | 38  | 50 |
| PCLR-7145   | 95                   | 16.2        | 13.5 | 18.1 | 28 | 2.3 | 20 | 17 | 44  | 58 |
| PCLR-7146/A | 120                  | 10.2        | 15   | 20.2 | 26 | 2.6 | 22 | 7  | 39  | 52 |
| PCLR-7146   | 120                  | 12.7        | 15   | 20.2 | 26 | 2.6 | 22 | 7  | 39  | 52 |
| PCLR-7147   | 120                  | 16.2        | 15   | 20.2 | 32 | 2.6 | 22 | 19 | 48  | 64 |
| PCLR-7148   | 120                  | 20.3        | 15   | 20.2 | 40 | 2.6 | 22 | 20 | 52  | 72 |
| PCLR-7149   | 150                  | 12.7        | 16.5 | 23.7 | 34 | 3.6 | 24 | 16 | 49  | 66 |
| PCLR-7045   | 150                  | 16.2        | 16.5 | 23.7 | 34 | 3.6 | 24 | 16 | 49  | 66 |
| PCLR-7150   | 150                  | 16.2        | 16.5 | 23.7 | 40 | 3.6 | 24 | 20 | 54  | 74 |
| PCLR-7046   | 150                  | 20          | 16.5 | 23.7 | 40 | 3.6 | 24 | 20 | 54  | 74 |