

Logic Building Assignment : 31

1. Accept number of rows and number of columns from user and display below pattern.

Input : iRow = 4 iCol = 4

Output : *

 * *

 * * *

 * * * *

Program Layout :

```
#include<stdio.h>
```

```
void Pattern(int iRow, int iCol)
{
    // Logic
}
```

```
int main()
{
    int iValue1 = 0, iValue2 = 0;

    printf("Enter number of rows and columns");
    scanf("%d %d",&iValue1, &iValue2);

    Pattern(iValue1, iValue2);

    return 0;
}
```

2. Accept number of rows and number of columns from user and display below pattern.

Input : iRow = 4 iCol = 4

Output : * * * *
 * * *
 * *
 *

Program Layout :

```
#include<stdio.h>
```


```
void Pattern(int iRow, int iCol)
{
    // Logic
}
```

```
int main()
{
    int iValue1 = 0, iValue2 = 0;

    printf("Enter number of rows and columns");
    scanf("%d %d",&iValue1, &iValue2);

    Pattern(iValue1, iValue2);

    return 0;
}
```



3. Accept number of rows and number of columns from user and display below pattern.

Input : iRow = 5 iCol = 5

Output :

\$	*	*	*	*
#	\$	*	*	*
#	#	\$	*	*
#	#	#	\$	*
#	#	#	#	\$

Program Layout :

```
#include<stdio.h>
```

```
void Pattern(int iRow, int iCol)
{
    // Logic
}
```

```
int main()
{
    int iValue1 = 0, iValue2 = 0;

    printf("Enter number of rows and columns");
    scanf("%d %d",&iValue1, &iValue2);

    Pattern(iValue1, iValue2);

    return 0;
}
```

4. Accept number of rows and number of columns from user and display below pattern.

Input : iRow = 6 iCol = 6

Output :

```
*   *   *   *   *   *
*   *           *           *
*           *           *
*           *           *
*           *           *
*   *   *   *   *   *
```

Program Layout :

```
#include<stdio.h>
```

```
void Pattern(int iRow, int iCol)
{
    // Logic
}
```

```
int main()
{
    int iValue1 = 0, iValue2 = 0;

    printf("Enter number of rows and columns");
    scanf("%d %d",&iValue1, &iValue2);

    Pattern(iValue1, iValue2);

    return 0;
}
```

5. Accept number of rows and number of columns from user and display below pattern.

Input : iRow = 4 iCol = 4

Output : 1 2 3 4
 2 3 4
 3 4
 4

Program Layout :

```
#include<stdio.h>
```

```
void Pattern(int iRow, int iCol)
{
    // Logic
}
```

```
int main()
{
    int iValue1 = 0, iValue2 = 0;

    printf("Enter number of rows and columns");
    scanf("%d %d",&iValue1, &iValue2);

    Pattern(iValue1, iValue2);

    return 0;
}
```

