

Chapter No. 03 : Event Handling

1. Which statement is false?
 - a) An event is an object that describes a state change in a source.
 - b) An event can be generated as a consequence of a person interacting with the elements in a graphical user interface.
 - c) **An event can be disabled by Java Runtime Environment.**
 - d) Entering a character via the keyboard generates an event.
2. How to remove the event listener?
 - a) Using removeListener() method.
 - b) **Using removeTypeListener() method.**
 - c) Using removeEvent() method.
 - d) It is not possible to remove the event listener.
3. At the root of Java event hierarchy, which class is located?
 - a) AWTEvent
 - b) Event
 - c) **EventObject**
 - d) Events
4. Action event is generated when...
 - a) Label is dragged
 - b) **Button is pressed**
 - c) Mouse is dragged
 - d) Window is opened
5. How to obtain the command name for invoking ActionEvent?
 - a) **Using getActionCommand() method.**
 - b) Using getCommand() method.
 - c) Using getAction() method.
 - d) Using obtainAction() method.
6. When slider of scrollbar was dragged, which event is generated?
 - a) **TRACK**
 - b) DRAGGED
 - c) DRAG
 - d) SCROLLBAR_MOVED
7. FocusEvent is subclass of ...
 - a) ContainerEvent
 - b) **ComponentEvent**
 - c) ItemEvent

- d) KeyEvent
8. When the InputEvent is not generated?
- a) Key is entered through keyboard
 - b) **Mouse is dragged**
 - c) Mouse wheel is moved
 - d) None of the above
9. TextEvent defines the integer constant...
- a) TEXT_CHANGED
 - b) **TEXT_VALUE_CHANGED**
 - c) TEXT_ADDED
 - d) TEXT_VALUE_ADDED
10. Which of the following is not event source?
- a) MenuItem
 - b) CheckboxGroup
 - c) Window
11. Till now, two models have been introduced in Java for
- a. **Receiving and Processing events**
 - b. Deleting and Processing events
 - c. Receiving and Deleting events
 - d. Modifying and Receiving events
12. An event is generated when the internal state of the event source is _____
- a. Not changed
 - b. **Changed**
 - c. Either changed or not
 - d. None of these
13. EventObject class belongs to:
- a. **java.util**
 - b. **java.awt**
 - c. java.lang
 - d. java.sql
14. The _____ interface handles list events:
- a. ContainerListener
 - b. FocusListener
 - c. ActionListener
 - d. **ItemListener**
15. The _____ interface handles choice events:
- a. ContainerListener
 - b. **ItemListener**
 - c. ActionListener
 - d. WindowListener
16. The _____ interface is used to handle checkbox events:
- a. ContainerListener
 - b. **ItemListener**

- c. ActionListener
 - d. WindowListener
17. The _____ interface is used to handle button events:
- a. ContainerListener
 - b. ItemListener
 - c. **ActionListener**
 - d. WindowListener
18. A push button is an active control that has a _____ appearance
- a. One dimensional
 - b. Two dimensional
 - c. **Three dimensional**
 - d. None of these
19. ItemListener is defined by the _____ method:
- a. itemChangedState()
 - b. **itemStateChanged()**
 - c. itemChanged()
 - d. itemState()
20. _____ is a superclass of TextField and TextArea classes that is used to create single-line or multiline textfields respectively:
- a. TextBox
 - b. CheckBox
 - c. **TextComponent**
 - d. Choice
21. A label is a simple control which is used to display _____ on the window:
- a. **Text(non-editable)**
 - b. Text(editable)
 - c. Both a & b
 - d. None of these
22. The Delegation Event Model defines a _____ approach to handle events:
- a. **Logical**
 - b. Physical
 - c. Both a & b
 - d. None of these
23. The Delegation Event Model is based on the concept of _____
- a. Source
 - b. Listener
 - c. **Both a & b**
 - d. None of these
24. A source generates an event and sends it to _____ listeners that can handle the event:
- a. One
 - b. Two
 - c. **One or more**
 - d. None of these
25. Applet is a small program written in the Java programming language that performs:
- a. A specific task
 - b. May or may not be a part of a larger program

- c. **Both a & b**
 - d. None of these
26. _____ generates action events when an item is double-clicked, generate action events when an item is selected or deselected.
- a. **List**
 - b. Check box
 - c. Menu item
 - d. Text box Label
27. ItemListener event defines this method...
- a) itemEventChanged()
 - b) itemEventOccurred()
 - c) itemValueChanged()
 - d) **itemStateChanged()**
28. KeyEvent is generated in following sequence...
- a) **Key typed, pressed, released**
 - b) Key released, typed, pressed
 - c) Key pressed, typed, released
 - d) Key pressed, released, typed
29. Which method is not defined by MouseListener interface?
- a) **mouseDragged()**
 - b) mouseMoved()
 - c) mouseEntered()
 - d) mouseReleased()
30. What is anonymous inner class?
- a) **An anonymous inner class is one that is not assigned a name.**
 - b) An anonymous inner class is one that is not used for creating the objects
 - c) An anonymous inner class is one for which we can not create the object.
 - d) An anonymous inner class is one that which is declared but not used anywhere in the program.
31. ___package contains all the classes and methods required for Event handling in java.
- (a) java.applet
 - (b) java.awt**
 - (c) java.event
 - (d) java.awt.event
32. What is an event is delegation event model used by Java programming Language?
- a) **An event is an object that describes a state change in a source.**
 - b) An event is an object that describes a state change in a processing.

- c) An event is an object that describes any change by the user and System
- d) An event is a class used for defining object, to create events.

34. method are used to register a keyboard event listener.

- (a) **KeyListener()**
- (b) addKistener()
- (c) addKeyListener()
- (d) eventKeyboardListener()

35. _____method are used to register a mouse motion listener.

- (a) addMouseO
- (b) addMouseListenerO
- (c) **addMouseMotionListnerO**
- (d) eventMouseMotionListenerO

36. What is a listener in context to event handling?

- (a) A listener is a variable that is notified when an event occurs.
- (b) **A listener is a object that is notified when an event occurs.**
- (c) A listener is a method that is notified when an event occurs.
- (d) None of the mentioned

37. In which library event class is defined ?

- (a) java.io
- (b) **java.util**
- (c) java.lang
- (d) java.net

38. Which of these methods can be used to determine the type of event ?

- (a) **getSoureeO**
- (b) getEventO
- (c) getIDO
- (d) getEventObjeeetO

39 _____is super class of all the events.

- (a) **EventObjeeet**
- (b) EventClass
- (c) AetionEvent
- (d) ItemEvent

40. If scroll bar is manipulated_____event will be notified.

- (a) AetionEvent
- (b) ComponentEvent
- (c) **AdjustmentEvent**
- (d) WindowEvent

41. if we close an applet's window generated.____event will be

- (a) ActionEvent
- (b) ComponentEvent
- (c) AdjustmentEvent
- (d) **WindowEvent**

42. Which of these events is generated when a button is pressed?

- (a) **ActionEvent** (b) KeyEvent
(c) Window Event (d) AdjustmentEvent

43. ____ method can be used to obtain the command name for invoking ActionEvent object.

- (a) getCommand() (b) **getActionCommand()**
(c) getActionEvent() (d) getActionEventCommand()

44. Which of these are integer constants defined in ActionEvent class?

- (a) ALT_MASK (b) CTRL_MASK
(c) SHIFT_MASK (d) **All of the mentioned**

45. Which of these methods can be used to determine type of Event

- (a) getID() (b) getSource()
(c) **getEvent()** (d) getEventObject()

46. ____ method can be used to determine the type of adjustment event.

- (a) getType() (b) getEventType()
(c) **getAdjustmentType()** (d) getEventObjectType()

47. ____ method can be used to know the degree of adjustment made by the user.

- (a) **getValue()** (b) getAdjustmentType()
(c) getAdjustmentValue() (d) getAdjustmentAmount()

48. What are the KeyListener Interface?

- (a) keyPressed (b) keyReleased
(c) keyTyped (d) **All three.**

49. Which of these constant value will change when the button at the end of scroll bar was clicked to increase its value?

- (a) BLOCK_DECREMENT
(b) BLOCK_INCREMENT
(c) UNIT_DECREMENT
(d) **UNIT_INCREMENT**

50. When the size of component is changed, ____ event is generated.

- (a) **ComponentEvent** (b) ContainerEvent
(c) FocusEvent (d) InputEvent

51. When the component is added or removed ? Which of these events is generated ?

- (a) ComponentEvent (b) **ContainerEvent**
(c) FocusEvent (d) InputEvent

52. ____ method can be used to obtain the reference to the container that generated a ContainerEvent.

- (a) getContainerO (b) **getContainerCommandO**
(c) getActionEventO (d) getContainerEventO

53. Which is the constant used for always providing the vertical scrollbar

- (a) VERTICAL_SCROLLBAR_ALWAYS
- (b) VERTICAL_SCROLLBAR_AS_NEEDED

54. Which is the method used for WindowsClosing Event?

- (a) windowOpened()
- (b) windowClosed()
- (c) windowClosing()
- (d) windowDeactivated()

55. __event is generated when computer gains or losses input focus.

- (a) ComponentEvent
- (b) ContainerEvent
- (c) FocusEvent
- (d) InputEvent

56. FocusEvent is subclass of which of these classes?

- (a) ComponentEvent
- (b) ContainerEvent
- (c) ItemEvent
- (d) InputEvent

56. __ can be used to know the type of focus change.

- (a) typeFocus()
- (b) typeEventFocus()
- (c) isTemporary()
- (d) isPermanent()

57. __ is superclass of Container Event class.

- (a) WindowEvent
- (b) ComponentEvent
- (c) ItemEvent
- (d) InputEvent

58. Which of the following method can be used to obtain the coordinates of a mouse?

- (a) getPoint()
- (b) getCoordinates()
- (c) getMouseXY()
- (d) getMouseCoordinates()

59. __ method can be used to change location of an event.

- (a) ChangePoint()
- (b) TranslatePoint()
- (c) ChangeCoordinates()
- (d) TranslateCoordinates()

60. Which of the following is integer constants of TextEvent class?

- a. TEXT_CHANGED
- b. TEXT_FORMAT_CHANGED
- c. TEXT_VALUE_CHANGED
- d. TEXT_SIZE_CHANGED

61. _____ is used to obtain the object that generated a Window Event.

- (a) getMethod()
- (b) getWindow()
- (c) getWindowEvent()
- (d) getWindowObject()

62. MouseEvent is subclass of which of these classes?

- a) ComponentEvent
- b) ContainerEvent

- c) ItemEvent
- d) **InputEvent**

63. ___method is used to get x coordinate of the mouse.

- (a) **getX()**
- (b) getXCoordinate()
- (c) getCoordinateX()
- (d) getPointX()

64. Which of these are constants defined in WindowEvent class?

- a. WINDOW_ACTIVATED
- b. WINDOW_CLOSED
- c. WINDOW_DEICONIFIED
- d. **All of the mentioned**

65. _____is superclass of Window Event class.

- (a) WindowEvent
- (b) **ComponentEvent**
- (c) ItemEvent
- (d) InputEvent

66. Which of these packages contains all the event handling interfaces?

- (a) java.lang
- (b) **java.awt**
- (c) java.awt.event
- (d) java.event

67. When a component is added to a container which of these interfaces handles the event?

- a. **ComponentListener**
- b. ContainerListener
- c. FocusListener
- d. InputListener

68. _____interface define a method actionPerformed().

- (a) ComponentListener
- (b) ContainerListener
- (c) **ActionListener**
- (d) InputListener

69. Which method is used to set an icon to an Label?

- (a) **setIcon()**
- (b) setImage()
- (c) getImage()
- (d) setIconImage()

70. _____interfaces define a method itemStateChanged()

- (a) **ComponentListner**
- (b) ContainerListener
- (c) ActionListener
- (d) ItemListener

71. Which method from the following methods will respond when you click any button by mouse?

- (a) mouseClicked()
- (b) mouseEntered()
- (c) mousePressed()
- (d) **All of the mentioned**

72. _____ methods will be invoked if a character is entered.
- (a) keyPressed()
 - (b) keyReleased()
 - (c) keyTyped()
 - (d) keyEntered()
73. _____ methods is defined in MouseMotionAdapter class.
- (a) mouseDragged()
 - (b) mousePressed()
 - (c) mouseReleased()
 - (d) mouseClicked()
74. Which method is used to have rollover icon?
- (a) setDisabledIcon()
 - (b) setDisabled()
 - (c) setRollover()
 - (d) setRolloverIcon()
75. _____ is the superclass of all Adapter classes.
- (a) Applet
 - (b) ComponentEvent
 - (c) Event
 - (d) InputEvent
76. In Java, events are all the activities that occur between:
- (a) The user
 - (b) The application
 - (c) Both (a) and (b)
 - (d) None of the above
77. EventObject class belongs to:
- (a) java.util
 - (b) java.awt
 - (c) java.lang
 - (d) java.sql
78. The Component class is an abstract class and so its are used to create components.
- (a) Subclasses
 - (b) Superclasses
 - (c) Both (a) and (b)
 - (d) None of these.
79. The AWT classes can be roughly categorized into the following groups:
- a. GUI component
 - b. Layouts
 - c. Graphics tools
 - d. All of these
80. Window is used for___ windows.
- a) Creating
 - b) Handling
 - c) Modifying
 - d) Both (a) and (b)

81. The ___ interface is used to handle the menu events.
- ContainerListener
 - FocusListener
 - ActionListener**
 - WindowListner
82. The constructor that is defined by the Text Event class is:
- TextEvenet(Object source, int event_type)**
 - textevent (Object source, int event_type)
 - textevent (object Source, float event_type)
 - textevent (Object source, string event_type)
83. The name of the event classes are:
- ActionEvent, ComponentEvent
 - ContainerEvent, FocusEvent
 - ItemEvevt, KeyEvent
 - All of these**
84. Java packages such as _____ support the Event handling mechanism.
- Java.util
 - Java.awt
 - Java.awt.event
 - All of these
85. An event is generated when the internal state of the event source is
- (a) Not changed
 - (b) Changed
 - (c) Either changed or not
 - (d) None of these.
86. The ___ interface handles list events:
- (a) ContainerListener
 - (b) ItemListener
 - (c) FocusListener
 - (d) ActionListener**
87. Which of the following are true?
- a. The event-inheritance model has replaced theevent- delegation model.
 - b. The event-inheritance model is more efficient than the event-delegation model.
 - c. **The Event Delegation Model uses event listeners to define the methods of event Handling classes**
 - d. The event delegation model uses handleEvent() method to support event handling.
88. Which of the following is the highest class in the event- delegation model ?
- a. java.util.EventListener
 - b. java.util.EventObject
 - c. **java.awt.A WTEvent**
 - d. java.awt.event.A WTEvent
89. When two or more objects are added as listeners for the same event, which listener is first invoked to handle the event?
- (a) The first object that was added as listener.**
 - (b) The last object that was added as listener.
 - (c) There is no way to determine which listener will be invoked first.
 - (d) It is impossible to have more than one listener for a given event.

90. Which of the following are true?

- a. A TextField object may generate an ActionEvent.
- b. A Button object may generate an ActionEvent.
- c. A MenuItem object may generate an ActionEvent.
- d. All of above

91. Which of the following are true?

- a. The MouseListener interface defines methods for handling mouse clicks.
- b. The MouseMotionListener interface defines methods for handling mouse clicks.
- c. The ActionListener interface defines methods for handling the clicking of a button.
- d. Option (a) and (c)

92. Suppose that you want to have an object "eh" to handle the TextEvent of a TextArea object. How should you add eh as the event handler to it?

- a) t.addTextListener(eh);
- b) eh.addTextListener(t);
- c) addTextListener(eh.t);
- d) addTextListener(t,eh);

93. What is the preferred way to handle an object's events in Java 2?

- a. Override the object's handleEvent() method.
- b. Add one or more event listeners to handle the events.
- c. Have the object override its processEvent() methods
- d. Have the object override its dispatchEvent() methods.

94. Which of the following are true?

- (a) A component may handle its own events by adding itself as an event listener.
- (b) A component may handle its own events by overriding its event-dispatching method.
- (c) A component may not handle its own events.
- (d) Option (a) and (b)

95. The event delegation model, introduced in release 1.1 of the JDK, is fully compatible with the event model.

- (a) True
- (b) False

96. A component subclass that has executed enableEvents() to enable processing of a certain kind of event cannot also use an adapter as a listener for the same kind of event.

- (a) True
- (b) False