```
mysql> use anudip
Database changed
mysql> create table company(c_id int primary key not null,c_name varchar(20),c_city varchar(20));
Query OK, 0 rows affected (0.04 sec)

mysql> insert into company values(1,"dominos","los angeles");
Query OK, 1 row affected (0.02 sec)

mysql> insert into company values(2,"pizza hut","san francisco");
Query OK, 1 row affected (0.00 sec)

mysql> insert into company values(3,"papa johns","san diego");
Query OK, 1 row affected (0.02 sec)

mysql> insert into company values(4,"ah pizza","fremont");
Query OK, 1 row affected (0.02 sec)

mysql> insert into company values(5,"nino pizza","las vegas");
Query OK, 1 row affected (0.02 sec)

mysql> insert into company values(6,"pizzaeria","boston");
Query OK, 1 row affected (0.02 sec)

mysql> insert into company values(7,"chuck e cheese","chicago");
Query OK, 1 row affected (0.02 sec)
```

```
mysql> select * from company;
+------+---------------+---------------+
| c_id | c_name        | c_city        |
+------+---------------+---------------+
|    1 | dominos       | los angeles   |
|    2 | pizza hut     | san francisco |
|    3 | papa johns    | san diego     |
|    4 | ah pizza      | fremont       |
|    5 | nino pizza    | las vegas     |
|    6 | pizzaeria     | boston        |
|    7 | chuck e cheese | chicago      |
+------+---------------+---------------+
7 rows in set (0.00 sec)
```

```
mysql> create table item(i_id int primary key not null,item_name varchar(20),units_sold int,c_id int not null,foreign key(c_id) references company(c_id));
Query OK, 0 rows affected (0.04 sec)

mysql> insert into item values(1,"large pizza",5,2);
Query OK, 1 row affected (0.02 sec)

mysql> insert into item values(2,"garlic knots",6,3);
Query OK, 1 row affected (0.02 sec)

mysql> insert into item values(3,"large pizza",3,3);
Query OK, 1 row affected (0.02 sec)

mysql> insert into item values(4,"medium pizza",8,4);
Query OK, 1 row affected (0.02 sec)

mysql> insert into item values(5,"bread sticks"7,1);
ERROR 1064 (42000): You have an error in your SQL syntax; check the manual that corresponds to your MySQL server version for the right syntax to use near '7,1
)' at line 1
mysql> insert into item values(5,"bread sticks",7,1);
Query OK, 1 row affected (0.02 sec)

mysql> insert into item values(6,"medium pizza",11,1);
Query OK, 1 row affected (0.02 sec)

mysql> insert into item values(7,"small pizza",9,6);
Query OK, 1 row affected (0.00 sec)

mysql> insert into item values(8,"small pizza",6,7);
Query OK, 1 row affected (0.00 sec)
```

```
mysql> select * from item;
+------+--------------+------------+------+
| i_id | item_name    | units_sold | c_id |
+------+--------------+------------+------+
|    1 | large pizza  |          5 |    2 |
|    2 | garlic knots |          6 |    3 |
|    3 | large pizza  |          3 |    3 |
|    4 | medium pizza |          8 |    4 |
|    5 | bread sticks |          7 |    1 |
|    6 | medium pizza |         11 |    1 |
|    7 | small pizza  |          9 |    6 |
|    8 | small pizza  |          6 |    7 |
+------+--------------+------------+------+
8 rows in set (0.00 sec)
```