

```
pratik@Ubuntu:~$ sudo mysql
```

```
[sudo] password for pratik:
```

```
mysql> show databases;
```

```
+-----+
| Database |
+-----+
| information_schema |
| mysql      |
| performance_schema |
| sys        |
+-----+
```

```
4 rows in set (0.00 sec)
```

```
mysql> create database dbms7a;
```

```
Query OK, 1 row affected (0.03 sec)
```

```
mysql> use dbms7a;
```

```
Database changed
```

```
mysql> create table o_rollcall(roll_no int,name varchar(20),address
-> varchar(20));
```

```
Query OK, 0 rows affected (0.20 sec)
```

```
mysql> create table n_rollcall(roll_no int,name varchar(20),address
-> varchar(20));
```

```
mysql> desc o_rollcall;
```

```
+-----+-----+-----+-----+-----+-----+
| Field | Type   | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+-----+
| roll_no | int    | YES  |     | NULL    |       |
| name   | varchar(20) | YES  |     | NULL    |       |
| address | varchar(20) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+-----+
```

```
3 rows in set (0.01 sec)
```

```
mysql> desc n_rollcall;
```

```
+-----+-----+-----+-----+-----+
| Field | Type      | Null | Key | Default | Extra |
+-----+-----+-----+-----+-----+
| roll_no | int       | YES  |     | NULL    |       |
| name    | varchar(20) | YES  |     | NULL    |       |
| address | varchar(20) | YES  |     | NULL    |       |
+-----+-----+-----+-----+-----+
```

```
3 rows in set (0.01 sec)
```

```
mysql> insert into o_rollcall values('1','Pratik','Pune');
```

```
Query OK, 1 row affected (0.07 sec)
```

```
mysql> insert into o_rollcall values('2','Piyush','MP');
```

```
Query OK, 1 row affected (0.04 sec)
```

```
mysql> insert into o_rollcall values('3','Pune','Nsk');
```

```
Query OK, 1 row affected (0.02 sec)
```

```
mysql> insert into o_rollcall values('4','Kalpesh','Dhule');
```

```
Query OK, 1 row affected (0.11 sec)
```

```
mysql> insert into o_rollcall values('5','Abhi','Satara');
```

```
Query OK, 1 row affected (0.08 sec)
```

```
mysql> delimiter //
```

```
mysql> create procedure p3(in r1 int)
```

```
-> begin
```

```
-> declare r2 int;
```

```
-> declare exit_loop boolean;
```

```
-> declare c1 cursor for select roll_no from o_rollcall
where roll_no>r1;
```

```
-> declare continue handler for not found set
```

```
exit_loop=true;
```

```
-> open c1;
```

```
-> e_loop:loop
```

```
-> fetch c1 into r2;
```

```
-> if not exists(select * from n_rollcall where
```

```

roll_no=r2)
-> then
-> insert into n_rollcall select * from o_rollcall where
roll_no=r2;
-> end if;
-> if exit_loop
-> then
-> close c1;
-> leave e_loop;
-> end if;
-> end loop e_loop;-> end
-> //

```

Query OK, 0 rows affected (0.00 sec)

```
mysql> call p3(3);
```

```
-> //
```

Query OK, 0 rows affected (0.10 sec)

```
mysql> select * from n_rollcall;
```

```
-> //
```

```

+-----+-----+-----+
| roll_no | name   | address |
+-----+-----+-----+
| 4 | Kalpesh | Dhule |
| 5 | Abhi | Satara |
+-----+-----+-----+

```

2 rows in set (0.00 sec)

```
mysql> call p3(0);
```

```
-> //
```

Query OK, 0 rows affected (0.22 sec)

```
mysql> select * from n_rollcall;
```

```
-> //
```

```

+-----+-----+-----+

```

roll_no	name	address
---------	------	---------

4	Kalpesh	Dhule
5	Abhi	Satara
1	Pratik	Pune
2	Piyush	MP
3	Tejas	Nashik

5 rows in set (0.00 sec)

```
mysql> insert into o_rollcall values('6','Patil','Kolhapur');
```

```
-> //
```

Query OK, 1 row affected (0.04 sec)

```
mysql> call p3(4);
```

```
-> //
```

Query OK, 0 rows affected (0.05 sec)

```
mysql> select * from n_rollcall;
```

```
-> //
```

roll_no	name	address
---------	------	---------

6 rows in set (0.00 sec)