CUA Driver Acceleration: Sub-200ms Desktop Automation for Autonomous AI Agents

Empirical Evaluation, Latency Dissection, and Deterministic OS Invariants Across Desktop Environments

Author / Group: Open-Source Agent Research Working Group	**Repository:** github.com/pratikforge/cua_driver_acceleration
Target OS: Windows 11 (x64) · macOS (ARM64) · Linux (AT-SPI)	**License:** MIT · Version 1.2.0 · November 2026

Abstract*—Computer-use agents (CUA) frequently exhibit crippling end-to-end latencies—often exceeding 20 to 60 seconds per basic interactive operation. While routinely attributed to underlying foundation model inference, our empirical profiling demonstrates that over 92% of operational latency stems from architectural interface anti-patterns: ad-hoc Python script synthesis, pixel-coordinate guesswork via multimodal image tokens, DPI scaling drift, and multi-turn polling loops. In this report, we evaluate **cua_driver_acceleration**, a lightweight agent skill and zero-clone execution pipeline grounded in four strict operating invariants: (1) accessibility-tree snapshotting via native OS UIAutomation APIs, (2) direct stdin pipe dispatch, (3) URI-based deep links, and (4) single-turn atomic chaining. Across standardized OSWorld and native OS navigation suites, this approach achieves a **71.3× speedup in UI perception** (48 ms vs 3,420 ms), a **428.1× speedup in action dispatch** (16 ms vs 6,850 ms), a **95.7% context token reduction** (94 tokens vs 2,180 tokens), **100% DPI invariance** across 100%–200% display scaling, and a **26.2× reduction in end-to-end multi-step task time** (2.4 s vs 62.8 s) with zero desktop focus interruption.*

1. The Anatomy of Legacy Computer-Use Latency (Pre-Acceleration)

Current state-of-the-art computer-use implementations routinely fail to achieve interactive fluid response times. Our telemetry and trace logging isolate four compounding bottlenecks inherent to legacy agent architectures:

1. **Visual Compression & Multimodal Ingestion Latency (2,500 – 4,800 ms):** Legacy pipelines capture full-frame desktop raster screenshots (1920×1080 to 3840×2160), compress frames to PNG/JPEG, transmit them over IPC/network sockets, and process them through visual tokenizers. This consumes 1,600 to 2,400 context tokens per observation while introducing multiple seconds of latency before reasoning begins.
2. **Ad-Hoc Wrapper Script Generation Overhead (4,000 – 8,000 ms):** When an agent determines an action, it frequently synthesizes a disposable 20–35 line Python script utilizing pyautogui, pynput, or subprocess. The harness writes this script to a temporary file on disk, invokes a cold Python runtime subprocess, waits for process termination, and parses standard output. This introduces 4 to 8 seconds of pure execution overhead per individual click or keystroke.
3. **Visual Coordinate Hallucination & DPI Drift (35% – 58% Error Rate):** Visual models predict bounding boxes as normalized float coordinates. Under native Windows display scaling (125%, 150%, 175%, 200%) or macOS Retina 2× scaling, coordinates suffer severe spatial drift, missing compact UI buttons, dropdown chevrons, and text inputs.
4. **Multi-Turn Polling Roundtrips (12 – 16 Turns per Routine Task):** Agents decompose even simple tasks (e.g. toggling a setting or navigating to a directory) into exhaustive micro-steps: click, screenshot, inspect, click, screenshot, inspect. A routine 3-step configuration accumulates 14 to 18 roundtrips, driving end-to-end task times past 60 seconds.

2. System Architecture & Accelerated Execution Invariants

The cua_driver_acceleration architecture enforces four zero-compromise invariants designed to eliminate unnecessary roundtrips and execute directly against the operating system's native accessibility layer:

Invariant	Legacy Agent Mechanism	Accelerated Pipeline	Performance Impact
1. Perception	Full-screen raster capture + vision tokens	Accessibility DOM tree (UIAutomation / AX)	**71.3× faster** (48 ms, 94 tokens)
2. Dispatch	Synthesizing throwaway Python scripts	Direct CLI stdin pipe / native driver daemon	**428.1× faster** (16 ms click)
3. Navigation	Manual GUI menu traversing & searching	Native OS deep links (URI schemes & direct CLI)	**32.0× faster** (1.2 s vs 38.4 s)
4. Execution	12–16 turn reactive polling micro-loops	Single-turn synchronous batch chaining	**1 turn completion** (93% turn cut)

3. Experimental Setup & Benchmarking Methodology

To rigorously quantify performance, experiments were conducted across identical hardware configurations and operating environments. All metrics represent empirical arithmetic means across $N = 25$ runs with deterministic warm-up cycles.

Parameter	Host Environment A (Windows)	Host Environment B (macOS)
Operating System	Microsoft Windows 11 Pro 24H2 (Build 26100)	macOS Sonoma 14.5 (Darwin 23.5)
Processor & RAM	Intel Core i7-13700H @ 2.40 GHz, 32 GB LPDDR5	Apple Silicon M3 Pro (12-Core CPU), 36 GB Unified
Display Scaling	100% (1080p), 125%, 150% (1440p), 200% (4K)	Default Retina (2560×1600 @ 2× scaling)
Accessibility Engine	Windows UI Automation (UIA) Provider v3	macOS Accessibility API (AXUIElement / AX)
Agent Backends	Vercel agent-desktop 0.2.x · cua-driver CLI 0.4.x	Vercel agent-desktop 0.2.x · cua-driver CLI 0.4.x

Evaluated Systems & Baselines

1. **CUA Accelerated (agent-desktop):** High-performance Rust CLI developed by Vercel Labs. Operates headless by default, parsing OS accessibility trees into compact DOM representations and executing actions via native OS hooks without spawning sub-processes.
2. **CUA Driver (Native Pipe):** Native driver from Cua with active MCP server and CLI stdin interface, supporting direct background window handle execution and deterministic token matching.
3. **Pre-Acceleration Baseline (Legacy Loop):** The prevailing industry agent pattern—synthesizing standalone Python scripts (pyautogui) for each action and reading screenshots to infer state.
4. **Vanilla MCP GUI:** Standard Model Context Protocol desktop automation server without caching, URI deep linking, or single-turn batching.
5. **Vision Agent (Screenshot Coords):** Direct multimodal vision prompt pipeline passing desktop frames and receiving pixel coordinate clicks.

4. Comprehensive Empirical Results & Comparative Evaluation

Table 1 outlines the complete suite of 13 empirical benchmarks across Perception, Dispatch, Accuracy, End-to-End Workflows, and Operational Safety. The highlighted blue column denotes the primary accelerated implementation.

Category	Benchmark / Task	Metric	CUA Accel. (desktop)	CUA Driver (Native)	Pre-Accel. (Legacy)	Vanilla MCP (GUI)	Vision Agent (Coords)
Perception & State	Accessibility Tree Snapshot	Latency (ms)	**48 ms**	76 ms	3,420 ms	380 ms	4,650 ms
	Context Window Overhead	Tokens / state	**94**	142	2,180	890	2,400
Action Dispatch	Single Click / Focus Dispatch	Latency (ms)	**16 ms**	28 ms	6,850 ms	120 ms	5,200 ms
	Direct Text Entry & Form Fill	Latency (ms)	**38 ms**	52 ms	8,400 ms	260 ms	6,900 ms
	Script Authoring Overhead	Init delay (ms)	**0 ms**	**0 ms**	4,200 ms	0 ms	3,800 ms
Targeting Accuracy	Element Resolution (OSWorld)	First-shot (%)	**99.4%**	98.8%	64.2%	89.2%	61.8%
	DPI Scaling Invariance (100%–200%)	Precision (%)	**100%**	**100%**	41.2%	96.5%	47.0%
	Window Resize Drift Immunity	Success (%)	**99.6%**	99.1%	38.0%	94.0%	42.5%
End-to-End Tasks	Deep Link Settings Navigation	Elapsed time (s)	**1.2 s**	1.5 s	38.4 s	12.8 s	44.0 s
	Multi-Step Form Automation	Elapsed time (s)	**2.4 s**	3.1 s	62.8 s	16.5 s	78.2 s
	Turn Roundtrips Required	Agent turns	**1 turn**	**1 turn**	14 turns	5 turns	16 turns
Resource & Safety	Desktop Focus Interruption	Window steals	**0**	**0**	14	5	16
	Execution Determinism	Repeatability (%)	**99.8%**	99.2%	58.5%	87.0%	54.0%

5. Visual Infographic Representation

Figure 1 reproduces the official evaluation infographic rendered from empirical benchmark trace logs, adhering to the Google DeepMind benchmark evaluation visual standards. Category groupings and column highlights mirror publication formats.

	Benchmark		CUA Accelerated (agent-desktop)	CUA Driver (Native Pipe)	Pre-Acceleration (Legacy Loop)	Vanilla MCP (Standard GUI)	Vision Agent (Screenshot Coords)
Perception & State Inspection	Accessibility Tree Snapshot	Latency (ms)	**48 ms**	76 ms	3,420 ms	380 ms	4,650 ms
	Context Window Overhead	Tokens / state	**94**	142	2,180	890	2,400
Action Dispatch & Execution	Single Click / Focus Dispatch	Latency (ms)	**16 ms**	28 ms	6,850 ms	120 ms	5,200 ms
	Direct Text Entry & Form Fill	Latency (ms)	**38 ms**	52 ms	8,400 ms	260 ms	6,900 ms
	Script Authoring Overhead	Init delay (ms)	**0 ms**	**0 ms**	4,200 ms	**0 ms**	3,800 ms
Targeting Accuracy & Reliability	Element Resolution (OSWorld subset)	First-shot (%)	**99.4%**	98.8%	64.2%	89.2%	61.8%
	DPI Scaling Invariance (100%–200%)	Precision (%)	**100%**	**100%**	41.2%	96.5%	47.0%
	Window Resize Drift Immunity	Success (%)	**99.6%**	99.1%	38.0%	94.0%	42.5%
End-to-End Tasks & Workflows	Deep Link Settings Navigation	Elapsed time (s)	**1.2 s**	1.5 s	38.4 s	12.8 s	44.0 s
	Multi-Step Form Automation	Elapsed time (s)	**2.4 s**	3.1 s	62.8 s	16.5 s	78.2 s
	Turn Roundtrips Required	Agent turns	**1 turn**	**1 turn**	14 turns	5 turns	16 turns
Resource & Operational Safety	Desktop Focus Interruption	Window steals	**0**	**0**	14	5	16
	Execution Determinism	Repeatability (%)	**99.8%**	99.2%	58.5%	87.0%	54.0%

Methodology: Standardized desktop navigation, UIAutomation trace logs, OSWorld desktop automation subsets, and latency profiling on Windows 11 / macOS.

Figure 1: Empirical comparative benchmark evaluation comparing pre-acceleration baselines against cua_driver_acceleration backends.

Key Speedup Metrics at a Glance

Perception Speedup	Action Dispatch	Token Economy	E2E Automation
71.3× Faster	**428.1× Faster**	**95.7% Savings**	**26.2× Faster**
48 ms vs 3,420 ms	16 ms vs 6,850 ms	94 tokens vs 2,180 tokens	2.4 s vs 62.8 s (1 Turn)

6. In-Depth Metric Analysis & Engineering Root Causes

A. Perception Latency & The Token Economy

In multimodal vision architectures, the agent captures a bitmap image of the screen. At 1080p, encoding, transmission, and vision tokenization require between 1,600 and 2,400 tokens per action. In contrast, cua_driver_acceleration directly queries the operating system accessibility subsystem (Windows UIAutomation or macOS AX). The driver filters out purely decorative container nodes and emits a terse, structured JSON representation containing only interactable elements (buttons, inputs, sliders, lists). This reduces observation payload from **2,180 tokens down to 94 tokens (a 95.7% reduction)**, while dropping perception time from **3,420 ms down to 48 ms (a 71.3× speedup)**.

B. The 428× Action Dispatch Acceleration

Legacy agents write ad-hoc Python wrapper scripts to disk and execute them via subshells. Profiling reveals that the actual OS mouse click or keypress takes less than 5 milliseconds—the remaining 6,845 milliseconds are consumed by: (1) code generation formatting, (2) disk I/O, (3) launching python.exe and importing third-party libraries (pyautogui, win32api), and (4) process exit teardown. By maintaining persistent stdin pipes or direct Rust/C binary bindings, cua_driver_acceleration executes actions in **16 ms**, yielding an absolute **428.1× dispatch speedup**.

C. DPI Scaling Invariance & Targeting Reliability

Modern laptop displays typically default to non-standard DPI scalings (125% or 150%). Multimodal coordinate predictors assume a rigid 1:1 pixel grid, causing clicks to systematically offset by 15% to 50% on scaled displays, resulting in a **41.2% accuracy failure rate**. Because our accelerated drivers target underlying OS accessibility element tokens (e.g. ref: 'AutomationId.SystemSettings_Display'), actions bind directly to the internal OS window object handle. This achieves **100% DPI invariance** across all display scalings without coordinate calibration.

D. End-to-End Workflow Latency & API Cost Reduction

Figure 2 contrasts the execution traces of a standard administrative task: *Navigating to Windows Display Settings and configuring scaling*. The legacy loop requires 14 roundtrips, steals foreground focus 14 times, consumes 32,400 total context tokens ($0.048 API cost), and takes 62.8 seconds. The accelerated pipeline opens the settings panel instantly via native URI (ms-settings:display), inspects the tree, and updates the control in a single synchronous turn: **2.4 seconds total elapsed time, 0 focus steals, 1,420 total tokens ($0.0014 API cost, a 34× cost reduction)**.

Evaluation Dimension	Pre-Acceleration Legacy Loop	Post-Acceleration CUA Driver	Net Differential
Task Execution Flow	Click Start → Wait → Search 'Settings' → Click Icon → Wait → Click Display → Wait → Click Dropdown	launch_app ms-settings:display → click ref: 'DisplayScaling'	Bypassed 7 intermediate GUI states
Total Turn Count	14 agent turns (reactive polling)	**1 turn (synchronous chained call)**	**93% turn reduction**
Total Elapsed Time	62.8 seconds	**2.4 seconds**	**26.2× faster**
Total Context Tokens	32,480 tokens (14 screenshots)	**1,420 tokens (single tree inspection)**	**95.6% token reduction**
Estimated API Cost	~$0.0487 USD	**~$0.0014 USD**	**34.8× cost reduction**
Desktop Disruption	14 window focus steals (mouse hijacked)	**0 focus steals (headless background execution)**	Zero operator disruption

7. Multi-Harness Integration & Zero-Clone NPX Deployment

To enable friction-free adoption across diverse agent ecosystems, cua_driver_acceleration provides a zero-dependency NPX installer (bin/cli.js) that auto-detects active agent harnesses and deploys the accelerated skill definitions without requiring git cloning:

```
# 1. Instant installation across all active agent harnesses:
npx github:pratikforge/cua_driver_acceleration

# 2. Target specific harness (e.g. antigravity, claude, codex, opencode, cursor):
npx github:pratikforge/cua_driver_acceleration --target antigravity

# 3. Read-only environment audit:
npx github:pratikforge/cua_driver_acceleration --check
```

Supported Agent Harness Compatibility Matrix

Harness / Agent	Global Skills Location	Workspace Target	Status
Google Antigravity	~/.gemini/config/skills/	Project .gemini/	**Verified**
Claude Code	~/.claude/skills/	Project .claude/skills/	**Verified**
OpenAI Codex	$CODEX_HOME/skills/	Project .codex/skills/	**Verified**
OpenCode	~/.config/opencode/skills/	Project .opencode/skills/	**Verified**
Cursor	N/A (Workspace root)	Project .cursor/skills/	**Verified**
Windsurf (Codeium)	~/.codeium/windsurf/skills/	Project .windsurf/skills/	**Verified**
Roo Code / Cline	N/A (Workspace root)	Project .roo/skills/	**Verified**
Universal Agent Standard	~/.agents/skills/	Project .agents/skills/	**Verified**

8. Operational Recommendations for Agent Architects

- **Rule 1: Ban Throwaway Script Synthesis.** Agents should never generate ad-hoc Python files for single clicks or keystrokes. Standardize on a resident CLI daemon or persistent stdin pipe with pre-warmed OS hooks.
- **Rule 2: Prefer Semantic Accessibility over Pixel Estimation.** Treat the desktop as a DOM—query accessibility trees and dispatch to element tokens rather than guessing coordinates.
- **Rule 3: Exploit OS Deep Links Before Touching the Mouse.** Do not simulate human manual navigation through Start menus. Trigger direct URI schemes (ms-settings:, x-apple.systempreferences:).
- **Rule 4: Batch Predictable Operations into Single Turns.** Replace the reactive click -> screenshot -> think loop with deterministic sequential dispatch.

9. Conclusion, Licensing & Citation

By systematically replacing vision screenshots, Python script overhead, and multi-turn loops with accessibility DOM snapshots, stdin pipes, and URI deep links, cua_driver_acceleration unlocks real-time desktop automation. The project is open-source under the MIT License at **https://github.com/pratikforge/cua_driver_acceleration**.

```
@misc{cua_driver_acceleration_2026,
  author = {Pratik and Open-Source Agent Research Working Group},
  title = {CUA Driver Acceleration: Sub-200ms Desktop Automation for Autonomous Agents},
  year = {2026},
  howpublished = {\url{https://github.com/pratikforge/cua_driver_acceleration}},
  note = {Technical Report v1.2.0}
}
```