

SSO and EUA Self Serve Flow


SSO Self-Service Flow Enhancements (May 2026)

1. Certificate Metadata Display

What: When an admin pastes or uploads an X.509 cert during SSO setup, parse it and show key fields inline — no more leaving Whatfix to verify.

Show these fields immediately below the cert field:

- Common Name (CN), SAN, Valid From, Valid To, Serial Number
- **Active cert:** green check next to dates
- **Expiring within 30 days:** amber warning with the expiry date
- **Expired:** red warning — "Expired — this cert will block SSO"
- **Unreadable cert:** inline error — "Not a valid PEM-encoded X.509 cert"



The screenshot shows a web interface for uploading a certificate. At the top, there is a text input field containing a truncated X.509 certificate (starting with '-----BEGIN CERTIFICATE-----'). Below this field is a section titled 'Certificate Information:' which lists several fields, each preceded by a green checkmark icon, indicating successful parsing:

- ✓ Common Name: marrssoprod-signer-internal.marriott.com
- ✓ Subject Alternative Names: marrssoprod-signer-internal.marriott.com
- ✓ Organization: Internal Marriott International Inc.
- ✓ Organization Unit:
- ✓ Locality: Bethesda
- ✓ State: Maryland
- ✓ Country: US
- ✓ Valid From: March 11, 2025
- ✓ Valid To: March 10, 2027
- ✓ Serial Number: 1709682121 (0x65e7adc9)

At the bottom of the interface, there is a dark grey footer bar with the text: '© 2026 SSL Shopper™ Cheapest All-Inclusive Resorts | All Rights Reserved'.

example

Also show on the SSO summary screen (read-only view after setup): same 4 fields below the truncated cert, with expiry warnings if applicable. Values come from the last saved parse.

XML upload path: same panel after XML parse. If no cert in the XML: "No certificate found — you can add one manually."

Engineering: parse client-side (WebCrypto / JS X.509 lib), no server round trip needed for display. Store parsed values at save time.


2. SSO Test- Retry CTA

What: The test failure state (Step 3) currently shows 'Test failed' with no action. Admin has to click Back, re-walk Steps 1 and 2, and return to Step 3 to try again. Add a retry CTA.

On test failure, show the CTAs below the failure message:

- **Run test again** (primary) — re-fires the test immediately, no navigation

Also show a specific failure reason where possible (e.g. "Issuer URL mismatch", "Certificate validation failed", "Sign-on URL unreachable"). Generic fallback: "Check your IdP configuration and try again." No raw SAML codes.



current exp

3. State Retention

What: Two gaps. (a) Editing a saved SSO config always defaults to 'Upload XML', ignoring what method was used. (b) Clicking Back within setup (Step 2 → Step 1) resets fields.

On edit (already-saved config):

- Pre-select the entry method used at save time (Upload XML or Enter manually) — not the UI default
- Pre-select the identity provider dropdown (Okta, Azure AD, etc.) stored at save time
- All field values pre-filled as today — unchanged

- **Edge case — XML file no longer available:** show values in Enter manually mode with notice "Values extracted from previously uploaded XML"

Within an active setup session (Back navigation):

- Going Back from Step 2 to Step 1 does not reset Step 1 fields — and vice versa
- Session-scoped (in-memory): closing the tab restores last saved state, not the mid-session draft

Scope: only retain state for already-completed/saved setups. Partial setups (abandoned mid-flow) start fresh on return.

Engineering: hold wizard state in a parent-level component or React context. No new API calls required.

Errors During Testing (after IdP information is entered)

- **Generic failure (no response from IdP)**

"Something went wrong while connecting to your Identity Provider. Please recheck your IdP configuration."

- Trigger: IdP tab closes without sending a response.
- Case: User closes the IdP tab manually OR IdP fails silently.
- Whatfix only knows that no SAML response came back.

- **Issuer or SSO URL is incorrect**

- User will be shown the **IdP's own error page** (e.g., "Bad Request" or "Invalid URL").
- Whatfix cannot intercept or rewrite this, but after the tab closes:

"No response received from your IdP. Please verify the Issuer and Single Sign-On URL."

- **Wrong Whatfix information on IdP** (e.g., ACS URL misconfigured)

- IdP will show its own error page.
- Whatfix side (after tab closes):

“We could not validate the SAML response. Please recheck the ACS URL you entered in your IdP configuration.”

Errors Where Whatfix Knows the Cause

• **Certificate invalid or expired**

“The certificate provided is invalid or expired. Please upload a valid X.509 certificate.”

- Expired certificates can be flagged immediately when input.

• **SAML Identity Location misconfigured**

“We are not able to fetch the email address from the SAML Assertion/Response. Please reconfigure your Identity Provider settings.”

- Triggered if required NameID/attributes not found.
-

Setup Errors Before Testing

• **Wrong XML file uploaded**

“The metadata file could not be read. Please upload a valid IdP metadata XML file.”

• **Invalid Metadata URL provided**

“We were unable to fetch configuration from this Metadata URL. Please check the URL and try again.”

Errors with Mixed Visibility

• **ACS URL mismatch**

- Sometimes Whatfix can detect and show:

“The ACS URL configured in your IdP does not match Whatfix. Please recheck the ACS URL.”

- Other times, this error will only appear on an invalid page (the URL that they would have configured instead of whatfix) and Whatfix will only know no response came back.
-

Key Notes for Design Team

1. **Two types of errors** need to be supported:

- **Errors we can show proactively** (certificate expired, missing attributes, invalid metadata)
 - **Errors we can only surface after tab closes** (wrong Issuer, SSO URL, ACS mismatch)
2. **Error states should have actionable guidance** (e.g., “Recheck Issuer value in your IdP settings”).
 3. **Differentiate between Whatfix-detected vs. IdP-side errors** so users know when to check Whatfix config vs. IdP config.