

schwz

Generated automatically from event-based-new

Generated by Doxygen 1.8.13

Contents

1	Main Page	1
2	# Installation Instructions	3
3	Testing Instructions	5
4	Benchmarking.	7
5	Module Documentation	11
5.1	Communicate	11
5.1.1	Detailed Description	11
5.2	Initialization	12
5.2.1	Detailed Description	12
5.3	Schwarz Class	13
5.3.1	Detailed Description	13
5.4	Solve	14
5.4.1	Detailed Description	14
5.5	Utils	15
5.5.1	Detailed Description	15
6	Namespace Documentation	17
6.1	ProcessTopology Namespace Reference	17
6.1.1	Detailed Description	17
6.2	schwz Namespace Reference	17
6.2.1	Detailed Description	18
6.3	schwz::CommHelpers Namespace Reference	18
6.3.1	Detailed Description	18
6.4	schwz::conv_tools Namespace Reference	18
6.4.1	Detailed Description	18
6.5	schwz::PartitionTools Namespace Reference	19
6.5.1	Detailed Description	19
6.6	schwz::SolverTools Namespace Reference	19
6.6.1	Detailed Description	19

7	Class Documentation	21
7.1	BadDimension Class Reference	21
7.1.1	Detailed Description	21
7.1.2	Constructor & Destructor Documentation	21
7.1.2.1	BadDimension()	21
7.2	schwz::Settings::comm_settings Struct Reference	22
7.2.1	Detailed Description	23
7.3	schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct Struct Reference	23
7.3.1	Detailed Description	25
7.3.2	Member Data Documentation	25
7.3.2.1	global_get	25
7.3.2.2	global_put	25
7.3.2.3	is_local_neighbor	26
7.3.2.4	local_get	26
7.3.2.5	local_put	26
7.3.2.6	remote_get	26
7.3.2.7	remote_put	27
7.4	schwz::Communicate< ValueType, IndexType, MixedValueType > Class Template Reference	27
7.4.1	Detailed Description	28
7.4.2	Member Function Documentation	28
7.4.2.1	exchange_boundary()	28
7.4.2.2	local_to_global_vector()	28
7.4.2.3	setup_windows()	29
7.4.2.4	update_boundary()	30
7.5	schwz::Settings::convergence_settings Struct Reference	30
7.5.1	Detailed Description	30
7.6	CudaError Class Reference	31
7.6.1	Detailed Description	31
7.6.2	Constructor & Destructor Documentation	31
7.6.2.1	CudaError()	31

7.7	CuspsetError Class Reference	32
7.7.1	Detailed Description	32
7.7.2	Constructor & Destructor Documentation	32
7.7.2.1	CuspsetError()	32
7.8	schwz::device_guard Class Reference	33
7.8.1	Detailed Description	33
7.9	schwz::Initialize< ValueType, IndexType > Class Template Reference	33
7.9.1	Detailed Description	34
7.9.2	Member Function Documentation	34
7.9.2.1	generate_dipole_rhs()	34
7.9.2.2	generate_rhs()	35
7.9.2.3	generate_sin_rhs()	35
7.9.2.4	partition()	36
7.9.2.5	setup_global_matrix()	37
7.9.2.6	setup_local_matrices()	38
7.9.2.7	setup_vectors()	39
7.10	schwz::Metadata< ValueType, IndexType > Struct Template Reference	40
7.10.1	Detailed Description	42
7.10.2	Member Data Documentation	43
7.10.2.1	local_solver_tolerance	43
7.10.2.2	tolerance	43
7.11	MetisError Class Reference	43
7.11.1	Detailed Description	43
7.11.2	Constructor & Destructor Documentation	44
7.11.2.1	MetisError()	44
7.12	schwz::Metadata< ValueType, IndexType >::post_process_data Struct Reference	44
7.12.1	Detailed Description	44
7.13	schwz::SchwarzBase< ValueType, IndexType, MixedValueType > Class Template Reference	45
7.13.1	Detailed Description	46
7.13.2	Constructor & Destructor Documentation	46

7.13.2.1	SchwarzBase()	46
7.13.3	Member Function Documentation	47
7.13.3.1	print_matrix()	47
7.13.3.2	print_vector()	48
7.13.3.3	run()	48
7.14	schwz::Settings Struct Reference	51
7.14.1	Detailed Description	53
7.14.2	Member Data Documentation	53
7.14.2.1	enable_logging	53
7.14.2.2	explicit_laplacian	53
7.14.2.3	naturally_ordered_factor	54
7.14.2.4	norm_type	54
7.14.2.5	thres_type	54
7.15	schwz::Solve< ValueType, IndexType, MixedValueType > Class Template Reference	54
7.15.1	Detailed Description	54
7.16	schwz::SolverRAS< ValueType, IndexType, MixedValueType > Class Template Reference	55
7.16.1	Detailed Description	55
7.16.2	Constructor & Destructor Documentation	56
7.16.2.1	SolverRAS()	56
7.16.3	Member Function Documentation	56
7.16.3.1	exchange_boundary()	56
7.16.3.2	setup_local_matrices()	57
7.16.3.3	setup_windows()	61
7.16.3.4	update_boundary()	63
7.17	UmfpackError Class Reference	64
7.17.1	Detailed Description	64
7.17.2	Constructor & Destructor Documentation	65
7.17.2.1	UmfpackError()	65
7.18	schwz::Utils< ValueType, IndexType > Struct Template Reference	65
7.18.1	Detailed Description	65

Chapter 1

Main Page

This is the main page for the Schwarz library pdf documentation. The repository is hosted on [github](#). Documentation on aspects such as the build system, can be found at the [# Installation Instructions](#) page.

Modules

The structure of the Schwarz Library code is divided into different [modules](#) :

- [Initialization](#) : Handles the initialization of the problem and the solver.
- [Communicate](#) : Handles the communication.
- [Solve](#) : Handles the local solution and the convergence detection.
- [Schwarz Class](#) : The Classes related to the Schwarz solvers.
- [Utils](#) : Provides some basic utilities.

Chapter 2

Installation Instructions

Building

Use the standard cmake build procedure:

```
mkdir build; cd build
cmake -G "Unix Makefiles" [OPTIONS] .. && make
```

Replace [OPTIONS] with desired cmake options for your build. The library adds the following additional switches to control what is being built:

- `-DSCHWARZ_BUILD_BENCHMARKING={ON, OFF}` Builds some example benchmarks. Default is ON
- `-DSCHWARZ_BUILD_METIS={ON, OFF}` Builds with support for the METIS partitioner. User needs to provide the path to the installation of the METIS library in `METIS_DIR`, preferably as an environment variable. Default is OFF
- `-DSCHWARZ_BUILD_CHOLMOD={ON, OFF}` Builds with support for the CHOLMOD module from the Suitesparse library. User needs to set an environment variable `CHOLMOD_DIR` to the path containing the CHOLMOD installation. Default is OFF
- `-DSCHWARZ_BUILD_CUDA={ON, OFF}` Builds with CUDA support. Though Ginkgo provides most of the required CUDA support, we do need to link to CUDA for explicit setting of GPU affinities, some custom gather and scatter operations. Default is OFF.
- `-DSCHWARZ_BUILD_CLANG_TIDY={ON, OFF}` Builds with support for clang-tidy Default is OFF
- `-DSCHWARZ_BUILD_DEALII={ON, OFF}` Builds with support for the finite element library deal.ii Default is OFF
- `-DSCHWARZ_WITH_HWLOC={ON, OFF}` Builds with support for the hardware locality library used for binding hardware. hwloc is distributed as a part of the Open-MPI project. Default is ON
- `-DSCHWARZ_DEVEL_TOOLS={ON, OFF}` Builds with some developer tools support. Default is ON. In particular uses `git-cmake-format` to automatically format the source files with `clang-format`.

Tips

- If you are having CUDA problems and you are not using CUDA, then feel free to switch the CUDA module off with `-DSCHWARZ_BUILD_CUDA=off`.
- Installing CHOLMOD can be a bit annoying. TODO add some details on fixing Suitesparse compilation.
- When doing merge commits it is possible that make format does not work. You can run `cmake -DSCHWARZ_DEVEL_TOOLS=OFF ..` to temporarily switch off the formatting. Please switch it on again when committing normally.

Chapter 3

Testing Instructions

Chapter 4

Benchmarking.

The flag `-DSCHWARZ_BUILD_BENCHMARKING` (default ON) enables the examples and benchmarking snippets.

If `schwarz-lib` has been built with `deal.ii`, then the `deal.ii` examples, `ex_6` and `ex_9` are also built, else only the `bench_ras` example is built. The following command line options are available for this example. This is setup using `gflags`.

The executable is run in the following fashion:

```
[MPI_COMMAND] [MPI_OPTIONS] PATH_TO_EXECUTABLE [FLAGS]
```

Where `FLAGS` are the options below with the template `flag_name [type] [default_value]`. For example, to set the number of iterations of the RAS solver to 100 one would add `--num_iters=100` to the executable command above.

Generic settings

- `executor [std::string][reference]` : The executor used to run the solver, one of `reference`, `cuda` or `omp`.
- `explicit_laplacian [bool][false]` : Use the explicit laplacian instead of `deal.ii`'s matrix.
- `set_1d_laplacian_size [uint32][16]` : The number of grid points in one dimension for the 2D laplacian problem.
- `enable_random_rhs [bool][false]` : Use a random rhs instead of the default 1.0's .
- `overlap [uint32][2]` : Overlap between the domains.
- `timings_file [std::string][null]` : The filename for the timings.
- `partition [std::string][regular]` : The partitioner used. The choices are `metis`, `regular` or `regular2d`.
- `metis_objtype [std::string][null]` : The objective type to minimize for the metis partitioner. The choices are `edgcut` and `totalvol`.
- `num_threads [uint32][1]` : Number of threads to bind to a process.
- `non_symmetric_matrix [bool][false]` : Explicitly state that the matrix is non-symmetric so that the local GMRES solver is used.
- `use_mixed_precision [bool][false]` : Use mixed precision in the communication.

Input settings

- `matrix_filename` [std::string][null] : The matrix file to read the global system matrix from.

Output settings

- `enable_debug_write` [bool][false] : Enable some debugging outputs to stdout.
- `write_comm_data` [bool][false] : Write the number of sends and recvs of each subdomain to files.
- `write_perm_data` [bool][false] : Write the permutation data from CHOLMOD to a file.
- `print_config` [bool][true] : Print the configuration of the run.
- `print_matrices` [bool][false] : Print the local system matrices to a file.
- `debug` [bool][false] : Enable some possible expensive debug checks.
- `enable_logging` [bool][false] : Enable some possible expensive logging from Ginkgo.

Solver settings**Generic settings**

- `num_iters` [uint32][100] : The number of outer iterations for the RAS solver.
- `set_tol` [double][1e-6] : The Outer tolerance for the RAS solver.
- `local_tol` [double][1e-12] : The Inner tolerance for the local iterative solver.

Communication settings

- `enable_onesided` [bool][false] : Enable the onesided asynchronous communication.
- `enable_twosided` [bool][true] : Enable the twosided asynchronous communication. A dummy flag.
- `enable_one_by_one` [bool][false] : Enable putting/getting of each element in onesided communication.
- `enable_put_all_local_residual_norms` [bool][false] : Enable putting of all local residual norms"
- `enable_comm_overlap` [bool][false] : Enable overlap of communication and computation.
- `flush_type` [std::string][flush-all] : The window flush strategy. The choices are `flush-local` and `flush-all`.
- `lock_type` [std::string][lock-all] : The window lock strategy. The choices are `lock-local` and `lock-all`.
- `remote_comm_type` [std::string][get] : The type of the remote communication. `get` uses `MPI_Get` and `put` uses `MPI_Put`.

Convergence settings

- `enable_global_check` [bool][false] : Use the global convergence check for twosided.
- `global_convergence_type` [std::string][centralized-tree] : Choose the convergence detection algorithm for onesided.
- `enable_decentralized_accumulate` [bool][false] : Use accumulate strategy for decentralized convergence check..
- `enable_global_check_iter_offset` [bool][false] : Enable global convergence check only after a certain number of iterations.

Local solver settings

- `local_solver` [std::string][iterative-ginkgo] : The local solver used in the local domains. The current choices are `direct-cholmod`, `direct-ginkgo` or `iterative-ginkgo`.
- `local_factorization` [std::string][cholmod] : The factorization for the local direct solver "cholmod" or "umfpack".
- `local_reordering` [std::string][none] : The reordering for the local direct solver "none", "metis_reordering" or "rcm_reordering".
- `factor_ordering_natural` [bool][false] : If true uses natural ordering instead of the default optimized ordering. This is needed for CUDA runs as the factorization ordering needs to be given to the solver.
- `enable_local_precond` [bool][false] : If true uses the Block jacobi preconditioning for the local iterative solver.
- `precond_max_block_size` [uint32][16] : Maximum size of the blocks for the block jacobi preconditioner
- `shifted_iter` [uint32][1] : The number of iterations to communicate for the local subdomains.
- `local_max_iters` [int32][-1] : The maximum number of iterations for the local iterative solver.
- `restart_iter` [uint32][1] : The restart iter for the GMRES solver.
- `reset_local_crit_iter` [int32][-1] : The RAS iteration to reset the local iteration count.

Poisson solver using Restricted Additive Schwarz with overlap.

This example runs is written within the `benchmarking/bench_ras.cpp` file. This demonstrates the basic capabilities of `schwarz-lib`. You can use it to solve the 2D Poisson equation with a 5 point stencil or solve a generic matrix by providing it a matrix file.

Examples with deal.ii

These examples use `deal.ii`'s capabilities to generate a matrix and solution is computed with the RAS method.

Possible settings are:

- `num_refine_cycles` [uint32][1][disabled] : The number of refinement cycles when used with `deal.ii`.
- `init_refine_level` [uint32][4] : The initial refinement level of the problem. This sets the initial number of dof's.
- `dealii_orig` [bool][false] : Solve with the `deal.ii` iterative CG instead of the RAS solver.
- `vis_sol` [bool][false] : Print the solution for visualization.

Solving the n-dimensional Poisson equation with FEM.

The `benchmarking/dealii_ex_6.cpp` demonstrates the solution of the Poisson equation with adaptive refinement as explained on the [deal.ii example documentation page](#)

Solving the Advection equation with FEM.

The `benchmarking/dealii_ex_9.cpp` demonstrates the solution of the Advection equation with adaptive refinement as explained on the [deal.ii example documentation page](#)

Chapter 5

Module Documentation

5.1 Communicate

A module dedicated to the Communication interface in schwarz-lib.

Namespaces

- [schwz::CommHelpers](#)
The CommHelper namespace .
- [ProcessTopology](#)
The ProcessTopology namespace .

Classes

- class [schwz::Communicate< ValueType, IndexType, MixedValueType >](#)
The communication class that provides the methods for the communication between the subdomains.
- struct [schwz::Metadata< ValueType, IndexType >](#)
The solver metadata struct.

5.1.1 Detailed Description

A module dedicated to the Communication interface in schwarz-lib.

5.2 Initialization

A module dedicated to the initialization and setup and usage of the solvers in schwarz-lib.

Namespaces

- [schwz::PartitionTools](#)
The [PartitionTools](#) namespace .
- [ProcessTopology](#)
The [ProcessTopology](#) namespace .

Classes

- class [schwz::device_guard](#)
This class defines a device guard for the cuda functions and the cuda module.
- class [schwz::Initialize< ValueType, IndexType >](#)
The initialization class that provides methods for initialization of the solver.
- struct [schwz::Settings](#)
The struct that contains the solver settings and the parameters to be set by the user.
- struct [schwz::Metadata< ValueType, IndexType >](#)
The solver metadata struct.

5.2.1 Detailed Description

A module dedicated to the initialization and setup and usage of the solvers in schwarz-lib.

5.3 Schwarz Class

A module dedicated to the Schwarz solver classes in schwarz-lib.

Classes

- class [schwz::SolverRAS< ValueType, IndexType, MixedValueType >](#)
An implementation of the solver interface using the RAS solver.
- class [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >](#)
The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.

5.3.1 Detailed Description

A module dedicated to the Schwarz solver classes in schwarz-lib.

5.4 Solve

A module dedicated to the solvers including local solution and convergence detection in schwarz-lib.

Namespaces

- [schwz::conv_tools](#)
The [conv_tools](#) namespace .
- [schwz::SolverTools](#)
The [SolverTools](#) namespace .

Classes

- struct [schwz::Metadata](#)< [ValueType](#), [IndexType](#) >
The solver metadata struct.
- class [schwz::Solve](#)< [ValueType](#), [IndexType](#), [MixedValueType](#) >
The Solver class the provides the solver and the convergence checking methods.

5.4.1 Detailed Description

A module dedicated to the solvers including local solution and convergence detection in schwarz-lib.

5.5 Utils

A module dedicated to the utilities in schwarz-lib.

Classes

- struct `schwz::Utils< ValueType, IndexType >`
The utilities class which provides some checks and basic utilities.

5.5.1 Detailed Description

A module dedicated to the utilities in schwarz-lib.

Chapter 6

Namespace Documentation

6.1 ProcessTopology Namespace Reference

The [ProcessTopology](#) namespace .

6.1.1 Detailed Description

The [ProcessTopology](#) namespace .

proc_topo

6.2 schwz Namespace Reference

The Schwarz wrappers namespace.

Namespaces

- [CommHelpers](#)
The CommHelper namespace .
- [conv_tools](#)
The conv_tools namespace .
- [PartitionTools](#)
The PartitionTools namespace .
- [SolverTools](#)
The SolverTools namespace .

Classes

- class [Communicate](#)
The communication class that provides the methods for the communication between the subdomains.
- class [device_guard](#)
This class defines a device guard for the cuda functions and the cuda module.
- class [Initialize](#)
The initialization class that provides methods for initialization of the solver.
- struct [Metadata](#)
The solver metadata struct.
- class [SchwarzBase](#)
The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.
- struct [Settings](#)
The struct that contains the solver settings and the parameters to be set by the user.
- class [Solve](#)
The Solver class the provides the solver and the convergence checking methods.
- class [SolverRAS](#)
An implementation of the solver interface using the RAS solver.
- struct [Utils](#)
The utilities class which provides some checks and basic utilities.

6.2.1 Detailed Description

The Schwarz wrappers namespace.

6.3 schwz::CommHelpers Namespace Reference

The CommHelper namespace .

6.3.1 Detailed Description

The CommHelper namespace .

comm_helpers

6.4 schwz::conv_tools Namespace Reference

The [conv_tools](#) namespace .

6.4.1 Detailed Description

The [conv_tools](#) namespace .

[conv_tools](#)

6.5 schwz::PartitionTools Namespace Reference

The [PartitionTools](#) namespace .

6.5.1 Detailed Description

The [PartitionTools](#) namespace .

part_tools

6.6 schwz::SolverTools Namespace Reference

The [SolverTools](#) namespace .

6.6.1 Detailed Description

The [SolverTools](#) namespace .

solver_tools

Chapter 7

Class Documentation

7.1 BadDimension Class Reference

[BadDimension](#) is thrown if an operation is being applied to a LinOp with bad dimensions.

```
#include <exception.hpp>
```

Public Member Functions

- [BadDimension](#) (const std::string &file, int line, const std::string &func, const std::string &op_name, std::size_t op_num_rows, std::size_t op_num_cols, const std::string &clarification)
Initializes a bad dimension error.

7.1.1 Detailed Description

[BadDimension](#) is thrown if an operation is being applied to a LinOp with bad dimensions.

7.1.2 Constructor & Destructor Documentation

7.1.2.1 BadDimension()

```
BadDimension::BadDimension (
    const std::string & file,
    int line,
    const std::string & func,
    const std::string & op_name,
    std::size_t op_num_rows,
    std::size_t op_num_cols,
    const std::string & clarification ) [inline]
```

Initializes a bad dimension error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The function name where the error occurred
<i>op_name</i>	The name of the operator
<i>op_num_rows</i>	The row dimension of the operator
<i>op_num_cols</i>	The column dimension of the operator
<i>clarification</i>	An additional message further describing the error

```

115         : Error(file, line,
116               func + ": Object " + op_name + " has dimensions [" +
117                   std::to_string(op_num_rows) + " x " +
118                   std::to_string(op_num_cols) + "]: " + clarification)
119     {}

```

The documentation for this class was generated from the following file:

- exception.hpp (35a1195)

7.2 schwz::Settings::comm_settings Struct Reference

The settings for the various available communication paradigms.

```
#include <settings.hpp>
```

Public Attributes

- bool `enable_onesided` = false
Enable one-sided communication.
- bool `enable_overlap` = false
Enable explicit overlap between communication and computation.
- bool `enable_put` = false
Put the data to the window using MPI_Put rather than get.
- bool `enable_get` = true
Get the data to the window using MPI_Get rather than put.
- bool `enable_one_by_one` = false
Push each element separately directly into the buffer.
- bool `enable_flush_local` = false
Use local flush.
- bool `enable_flush_all` = true
Use flush all.
- bool `enable_lock_local` = false
Use local locks.
- bool `enable_lock_all` = true
Use lock all.

7.2.1 Detailed Description

The settings for the various available communication paradigms.

The documentation for this struct was generated from the following file:

- settings.hpp (1a4d86f)

7.3 schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct Struct Reference

The communication struct used to store the communication data.

```
#include <communicate.hpp>
```

Public Attributes

- int [num_neighbors_in](#)
The number of neighbors this subdomain has to receive data from.
- int [num_neighbors_out](#)
The number of neighbors this subdomain has to send data to.
- int [num_rcv](#)
The total number of elements received from all neighbors.
- int [num_send](#)
The total number of elements sent to all neighbors.
- std::shared_ptr< gko::Array< IndexType > > [neighbors_in](#)
The neighbors this subdomain has to receive data from.
- std::shared_ptr< gko::Array< IndexType > > [neighbors_out](#)
The neighbors this subdomain has to send data to.
- std::vector< bool > [is_local_neighbor](#)
The bool vector which is true if the neighbors of a subdomain are in one node.
- int [local_num_neighbors_in](#)
The number of neighbors this subdomain has to receive data from.
- int [local_num_neighbors_out](#)
The number of neighbors this subdomain has to send data to.
- std::shared_ptr< gko::Array< IndexType > > [local_neighbors_in](#)
The neighbors this subdomain has to receive data from.
- std::shared_ptr< gko::Array< IndexType > > [local_neighbors_out](#)
The neighbors this subdomain has to send data to.
- std::shared_ptr< gko::Array< IndexType * > > [global_put](#)
The array containing the number of elements that each subdomain sends from the other.
- std::shared_ptr< gko::Array< IndexType * > > [local_put](#)
The array containing the number of elements that each subdomain sends from the other.
- std::shared_ptr< gko::Array< IndexType * > > [remote_put](#)
The array containing the number of elements that each subdomain sends from the other.
- std::shared_ptr< gko::Array< IndexType * > > [global_get](#)
The array containing the number of elements that each subdomain gets from the other.
- std::shared_ptr< gko::Array< IndexType * > > [local_get](#)

- The array containing the number of elements that each subdomain gets from the other.*

 - `std::shared_ptr< gko::Array< IndexType * > >` [remote_get](#)
- The array containing the number of elements that each subdomain gets from the other.*

 - `std::shared_ptr< gko::Array< IndexType > >` [window_ids](#)
- The RDMA window ids.*

 - `std::shared_ptr< gko::Array< IndexType > >` [windows_from](#)
- The RDMA window ids to receive data from.*

 - `std::shared_ptr< gko::Array< IndexType > >` [windows_to](#)
- The RDMA window ids to send data to.*

 - `std::shared_ptr< gko::Array< MPI_Request > >` [put_request](#)
- The put request array.*

 - `std::shared_ptr< gko::Array< MPI_Request > >` [get_request](#)
- The get request array.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [send_buffer](#)
- The send buffer used for the actual communication for both one-sided and two-sided (always allocated).*

 - `std::shared_ptr< gko::matrix::Dense< MixedValueType > >` [mixedt_send_buffer](#)
- The mixed send buffer used for the actual communication for both one-sided and two-sided.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [recv_buffer](#)
- The recv buffer used for the actual communication for both one-sided and two-sided (always allocated).*

 - `std::shared_ptr< gko::matrix::Dense< MixedValueType > >` [mixedt_recv_buffer](#)
- The mixed precision recv buffer used for the actual communication for both one-sided and two-sided.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [extra_buffer](#)
- The extrapolation buffer used for extrapolation of values at the receiver.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [last_recv_bdy](#)
- The last received boundary values for each of the in neighbors for extrapolation.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [curr_send_avg](#)
- Average of values in the send buffer for each of the out neighbors.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [last_send_avg](#)
- Average of values in the last send buffer for each of the out neighbors.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [curr_recv_avg](#)
- Average of values in the recv buffer for each of the out neighbors.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [last_recv_avg](#)
- Average of values in the last recv buffer for each of the out neighbors.*

 - `std::shared_ptr< gko::Array< IndexType > >` [msg_count](#)
- Number of messages sent.*

 - `std::shared_ptr< gko::Array< IndexType > >` [last_recv_iter](#)
- Iteration stamp of last received values.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [last_recv_slopes](#)
- Last recv slopes.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [last_sent_slopes_avg](#)
- Last sent slopes.*

 - `std::shared_ptr< gko::Array< IndexType > >` [last_sent_iter](#)
- Iteration stamp of last received values.*

 - `std::shared_ptr< gko::matrix::Dense< ValueType > >` [thres](#)
- Threshold.*

 - `std::shared_ptr< gko::Array< IndexType > >` [get_displacements](#)
- The displacements for the receiving of the buffer.*

 - `std::shared_ptr< gko::Array< IndexType > >` [put_displacements](#)
- The displacements for the sending of the buffer.*

 - `MPI_Win` [window_recv_buffer](#)
- The RDMA window for the recv buffer.*

- MPI_Win [window_send_buffer](#)
The RDMA window for the send buffer.
- MPI_Win [window_x](#)
The RDMA window for the solution vector.

7.3.1 Detailed Description

```
template<typename ValueType, typename IndexType, typename MixedValueType>
struct schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct
```

The communication struct used to store the communication data.

7.3.2 Member Data Documentation

7.3.2.1 global_get

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType, Mixed←
ValueType >::comm_struct::global_get
```

The array containing the number of elements that each subdomain gets from the other.

For example. `global_get[p][0]` contains the overall number of elements to be received to subdomain `p` and `global←_put[p][i]` contains the index of the solution vector to be received from subdomain `p`.

Referenced by `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize()`, `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows()`.

7.3.2.2 global_put

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType, Mixed←
ValueType >::comm_struct::global_put
```

The array containing the number of elements that each subdomain sends from the other.

For example. `global_put[p][0]` contains the overall number of elements to be sent to subdomain `p` and `global_put[p][i]` contains the index of the solution vector to be sent to subdomain `p`.

Referenced by `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize()`, `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows()`.

7.3.2.3 is_local_neighbor

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::vector<bool> schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct←
::is_local_neighbor
```

The bool vector which is true if the neighbors of a subdomain are in one node.

Referenced by schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize(), schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers(), and schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows().

7.3.2.4 local_get

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType, Mixed←
ValueType >::comm_struct::local_get
```

The array containing the number of elements that each subdomain gets from the other.

For example. global_get[p][0] contains the overall number of elements to be received to subdomain p and global←_put[p][i] contains the index of the solution vector to be received from subdomain p.

Referenced by schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers(), and schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows().

7.3.2.5 local_put

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType, Mixed←
ValueType >::comm_struct::local_put
```

The array containing the number of elements that each subdomain sends from the other.

For example. global_put[p][0] contains the overall number of elements to be sent to subdomain p and global_put[p][i] contains the index of the solution vector to be sent to subdomain p.

Referenced by schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers(), and schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows().

7.3.2.6 remote_get

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType, Mixed←
ValueType >::comm_struct::remote_get
```

The array containing the number of elements that each subdomain gets from the other.

For example. global_get[p][0] contains the overall number of elements to be received to subdomain p and global←_put[p][i] contains the index of the solution vector to be received from subdomain p.

Referenced by schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers(), and schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows().

7.3.2.7 remote_put

```
template<typename ValueType , typename IndexType , typename MixedValueType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::remote_put
```

The array containing the number of elements that each subdomain sends from the other.

For example. `global_put[p][0]` contains the overall number of elements to be sent to subdomain `p` and `global_put[p][i]` contains the index of the solution vector to be sent to subdomain `p`.

Referenced by `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows()`.

The documentation for this struct was generated from the following file:

- `communicate.hpp` (1bdbc6b)

7.4 schwz::Communicate< ValueType, IndexType, MixedValueType > Class Template Reference

The communication class that provides the methods for the communication between the subdomains.

```
#include <communicate.hpp>
```

Classes

- struct `comm_struct`
The communication struct used to store the communication data.

Public Member Functions

- virtual void `setup_comm_buffers` ()=0
Sets up the communication buffers needed for the boundary exchange.
- virtual void `setup_windows` (const `Settings` &settings, const `Metadata`< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &main_buffer)=0
Sets up the windows needed for the asynchronous communication.
- virtual void `exchange_boundary` (const `Settings` &settings, const `Metadata`< ValueType, IndexType > &metadata, const std::shared_ptr< gko::matrix::Dense< ValueType >> &prev_global_solution, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_solution, std::shared_ptr< gko::matrix::Dense< ValueType >> &prev_event_solution, std::ofstream &fps, std::ofstream &fpr)=0
Exchanges the elements of the solution vector.
- void `local_to_global_vector` (const `Settings` &settings, const `Metadata`< ValueType, IndexType > &metadata, const std::shared_ptr< gko::matrix::Dense< ValueType >> &local_vector, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_vector)
Transforms data from a local vector to a global vector.
- virtual void `update_boundary` (const `Settings` &settings, const `Metadata`< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &local_solution, const std::shared_ptr< gko::matrix::Dense< ValueType >> &local_rhs, const std::shared_ptr< gko::matrix::Dense< ValueType >> &global_solution, const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &interface_matrix)=0
Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.
- void `clear` (`Settings` &settings)
Clears the data.

7.4.1 Detailed Description

```
template<typename ValueType, typename IndexType, typename MixedValueType>
class schwz::Communicate< ValueType, IndexType, MixedValueType >
```

The communication class that provides the methods for the communication between the subdomains.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Communicate

7.4.2 Member Function Documentation

7.4.2.1 exchange_boundary()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::Communicate< ValueType, IndexType, MixedValueType >::exchange_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & prev_global_solution,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & prev_event_solution,
    std::ofstream & fps,
    std::ofstream & fpr ) [pure virtual]
```

Exchanges the elements of the solution vector.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>global_solution</i>	The solution vector being exchanged between the subdomains.

Implemented in [schwz::SolverRAS< ValueType, IndexType, MixedValueType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::run\(\)](#).

7.4.2.2 local_to_global_vector()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::Communicate< ValueType, IndexType, MixedValueType >::local_to_global_vector (
```

```

const Settings & settings,
const Metadata< ValueType, IndexType > & metadata,
const std::shared_ptr< gko::matrix::Dense< ValueType >> & local_vector,
std::shared_ptr< gko::matrix::Dense< ValueType >> & global_vector )

```

Transforms data from a local vector to a global vector.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_vector</i>	The local vector in question.
<i>global_vector</i>	The global vector in question.

Referenced by schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::run().

```

72 {
73     using vec = gko::matrix::Dense<ValueType>;
74     auto alpha = gko::initialize<gko::matrix::Dense<ValueType>>(
75         {1.0}, settings.executor);
76     auto temp_vector = vec::create(
77         settings.executor, gko::dim<2>(metadata.local_size, 1),
78         gko::Array<ValueType>::view(
79             settings.executor, metadata.local_size,
80             &global_vector->get_values()[metadata.first_row
81                                     ->get_data()[metadata.my_rank]]),
82         1);
83
84     auto temp_vector2 = vec::create(
85         settings.executor, gko::dim<2>(metadata.local_size, 1),
86         gko::Array<ValueType>::view(settings.executor, metadata.local_size,
87                                     local_vector->get_values()),
88         1);
89     if (settings.convergence_settings.convergence_crit ==
90         Settings::convergence_settings::local_convergence_crit::
91             residual_based) {
92         local_vector->add_scaled(alpha.get(), temp_vector.get());
93         temp_vector->add_scaled(alpha.get(), local_vector.get());
94     } else {
95         temp_vector->copy_from(temp_vector2.get());
96     }
97 }

```

7.4.2.3 setup_windows()

```

template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::Communicate< ValueType, IndexType, MixedValueType >::setup_windows (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & main_buffer ) [pure virtual]

```

Sets up the windows needed for the asynchronous communication.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>main_buffer</i>	The main buffer being exchanged between the subdomains.

Implemented in [schwz::SolverRAS< ValueType, IndexType, MixedValueType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::run\(\)](#).

7.4.2.4 update_boundary()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::Communicate< ValueType, IndexType, MixedValueType >::update_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_solution,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & local_rhs,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution,
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_↵
matrix ) [pure virtual]
```

Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_solution</i>	The local solution vector in the subdomain.
<i>local_rhs</i>	The local right hand side vector in the subdomain.
<i>global_solution</i>	The workspace solution vector.
<i>global_old_solution</i>	The global solution vector of the previous iteration.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.

Implemented in [schwz::SolverRAS< ValueType, IndexType, MixedValueType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::run\(\)](#).

The documentation for this class was generated from the following files:

- [communicate.hpp](#) (1bdbc6b)
- [/home/runner/work/schwarz-lib/schwarz-lib/source/communicate.cpp](#) (c6f2d70)

7.5 schwz::Settings::convergence_settings Struct Reference

The various convergence settings available.

```
#include <settings.hpp>
```

7.5.1 Detailed Description

The various convergence settings available.

The documentation for this struct was generated from the following file:

- [settings.hpp](#) (1a4d86f)

7.6 CudaError Class Reference

[CudaError](#) is thrown when a CUDA routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [CudaError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a CUDA error.

7.6.1 Detailed Description

[CudaError](#) is thrown when a CUDA routine throws a non-zero error code.

7.6.2 Constructor & Destructor Documentation

7.6.2.1 CudaError()

```
CudaError::CudaError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]
```

Initializes a CUDA error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the CUDA routine that failed
<i>error_code</i>	The resulting CUDA error code

```
137         : Error(file, line, func + ": " + get_error(error_code))
138     {}
```

The documentation for this class was generated from the following files:

- exception.hpp (35a1195)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (35a1195)

7.7 CusparsedError Class Reference

[CusparsedError](#) is thrown when a cuSPARSE routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [CusparsedError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a cuSPARSE error.

7.7.1 Detailed Description

[CusparsedError](#) is thrown when a cuSPARSE routine throws a non-zero error code.

7.7.2 Constructor & Destructor Documentation

7.7.2.1 CusparsedError()

```
CusparsedError::CusparsedError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]
```

Initializes a cuSPARSE error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the cuSPARSE routine that failed
<i>error_code</i>	The resulting cuSPARSE error code

```
159         : Error(file, line, func + ": " + get_error(error_code))
160     {}
```

The documentation for this class was generated from the following files:

- exception.hpp (35a1195)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (35a1195)

7.8 schwz::device_guard Class Reference

This class defines a device guard for the cuda functions and the cuda module.

```
#include <device_guard.hpp>
```

7.8.1 Detailed Description

This class defines a device guard for the cuda functions and the cuda module.

The guard is used to make sure that the device code is run on the correct cuda device, when run with multiple devices. The class records the current device id and uses `cudaSetDevice` to set the device id to the one being passed in. After the scope has been exited, the destructor sets the `device_id` back to the one before entering the scope.

The documentation for this class was generated from the following file:

- `device_guard.hpp` (5a15602)

7.9 schwz::Initialize< ValueType, IndexType > Class Template Reference

The initialization class that provides methods for initialization of the solver.

```
#include <initialization.hpp>
```

Public Member Functions

- void `generate_rhs` (std::vector< ValueType > &rhs)
Generates the right hand side vector.
- void `generate_dipole_rhs` (std::vector< ValueType > &rhs)
Generates a dipole right hand side vector.
- void `generate_sin_rhs` (std::vector< ValueType > &rhs)
Generates a sinusoidal right hand side vector.
- void `setup_global_matrix` (const std::string &filename, const gko::size_type &oned_laplacian_size, std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &global_matrix)
Generates the 2D global laplacian matrix.
- void `partition` (const Settings &settings, const Metadata< ValueType, IndexType > &metadata, const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &global_matrix, std::vector< unsigned int > &partition_indices)
The partitioning function.
- void `setup_vectors` (const Settings &settings, const Metadata< ValueType, IndexType > &metadata, std::vector< ValueType > &rhs, std::shared_ptr< gko::matrix::Dense< ValueType >> &local_rhs, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_rhs, std::shared_ptr< gko::matrix::Dense< ValueType >> &local_solution)
Setup the vectors with default values and allocate memory if not allocated.
- virtual void `setup_local_matrices` (Settings &settings, Metadata< ValueType, IndexType > &metadata, std::vector< unsigned int > &partition_indices, std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &global_matrix, std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &local_matrix, std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &interface_matrix)=0
Sets up the local and the interface matrices from the global matrix and the partition indices.

Public Attributes

- `std::vector< unsigned int >` [partition_indices](#)
The partition indices containing the subdomains to which each row(vertex) of the matrix(graph) belongs to.
- `std::vector< unsigned int >` [cell_weights](#)
The cell weights for the partition algorithm.

Additional Inherited Members

7.9.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
class schwz::Initialize< ValueType, IndexType >
```

The initialization class that provides methods for initialization of the solver.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Initialization

7.9.2 Member Function Documentation

7.9.2.1 generate_dipole_rhs()

```
template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::generate_dipole_rhs (
    std::vector< ValueType > & rhs )
```

Generates a dipole right hand side vector.

Parameters

<i>rhs</i>	The rhs vector.
------------	-----------------

Referenced by `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize()`.

```
101 {
102     auto oned_laplacian_size = metadata.oned_laplacian_size;
103
104     // Placing dipole at 1/4 and 3/4 of Y-dim at the middle of X-dim
105     for (int i = 0; i < oned_laplacian_size; i++) {
106         for (int j = 0; j < oned_laplacian_size; j++) {
107             if (i == oned_laplacian_size / 4 && j == oned_laplacian_size / 2)
108                 rhs[i * oned_laplacian_size + j] = 100.0;
```



```

109         else if (i == 3 * oned_laplacian_size / 4 &&
110                j == oned_laplacian_size / 2)
111             rhs[i * oned_laplacian_size + j] = -100.0;
112         else
113             rhs[i * oned_laplacian_size + j] = 0.0;
114     }
115 }
116 }

```

7.9.2.2 generate_rhs()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::generate_rhs (
    std::vector< ValueType > & rhs )

```

Generates the right hand side vector.

Parameters

<i>rhs</i>	The rhs vector.
------------	-----------------

Referenced by schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize().

```

90 {
91     std::uniform_real_distribution<double> unif(0.0, 1.0);
92     std::default_random_engine engine;
93     for (gko::size_type i = 0; i < rhs.size(); ++i) {
94         rhs[i] = unif(engine);
95     }
96 }

```

7.9.2.3 generate_sin_rhs()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::generate_sin_rhs (
    std::vector< ValueType > & rhs )

```

Generates a sinusoidal right hand side vector.

Parameters

<i>rhs</i>	The rhs vector.
------------	-----------------

References schwz::Initialize< ValueType, IndexType >::setup_global_matrix().

Referenced by schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize().

```

121 {
122     auto PI = (ValueType)(atan(1.0) * 4);
123     auto oned_laplacian_size = metadata.oned_laplacian_size;

```

```

124
125     // Source = sin(x)sin(y)
126     for (int i = 0; i < oned_laplacian_size; i++) {
127         for (int j = 0; j < oned_laplacian_size; j++) {
128             rhs[i * oned_laplacian_size + j] =
129                 sin(2 * PI * i / oned_laplacian_size) *
130                 sin(2 * PI * j / oned_laplacian_size);
131         }
132     }
133 }

```

7.9.2.4 partition()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::partition (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_↵
matrix,
    std::vector< unsigned int > & partition_indices )

```

The partitioning function.

Allows the partition of the global matrix depending with METIS and a regular 1D decomposition.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>global_matrix</i>	The global matrix.
<i>partition_indices</i>	The partition indices [OUTPUT].

References `schwz::Metadata< ValueType, IndexType >::global_size`, `schwz::Metadata< ValueType, IndexType >::my_rank`, `schwz::Metadata< ValueType, IndexType >::num_subdomains`, and `schwz::Settings::write_debug_↵` out.

Referenced by `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize()`.

```

320 {
321     partition_indices.resize(metadata.global_size);
322     if (metadata.my_rank == 0) {
323         auto partition_settings =
324             (Settings::partition_settings::partition_zoltan |
325              Settings::partition_settings::partition_metis |
326              Settings::partition_settings::partition_regular |
327              Settings::partition_settings::partition_regular2d |
328              Settings::partition_settings::partition_custom) &
329             settings.partition;
330
331         if (partition_settings ==
332             Settings::partition_settings::partition_zoltan) {
333             SCHWARZ_NOT_IMPLEMENTED;
334         } else if (partition_settings ==
335             Settings::partition_settings::partition_metis) {
336             if (metadata.my_rank == 0) {
337                 std::cout << " METIS partition" << std::endl;
338             }
339             PartitionTools::PartitionMetis(
340                 settings, global_matrix, this->cell_weights,
341                 metadata.num_subdomains, partition_indices);
342         } else if (partition_settings ==
343             Settings::partition_settings::partition_regular) {

```

```

344         if (metadata.my_rank == 0) {
345             std::cout << " Regular 1D partition" << std::endl;
346         }
347         PartitionTools::PartitionRegular(
348             global_matrix, metadata.num_subdomains, partition_indices);
349     } else if (partition_settings ==
350         Settings::partition_settings::partition_regular2d) {
351         if (metadata.my_rank == 0) {
352             std::cout << " Regular 2D partition" << std::endl;
353         }
354         PartitionTools::PartitionRegular2D(
355             global_matrix, settings.write_debug_out,
356             metadata.num_subdomains, partition_indices);
357     } else if (partition_settings ==
358         Settings::partition_settings::partition_custom) {
359         // User partitions mesh manually
360         SCHWARZ_NOT_IMPLEMENTED;
361     } else {
362         SCHWARZ_NOT_IMPLEMENTED;
363     }
364 }
365 }

```

7.9.2.5 setup_global_matrix()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::setup_global_matrix (
    const std::string & filename,
    const gko::size_type & oned_laplacian_size,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_matrix )

```

Generates the 2D global laplacian matrix.

Parameters

<i>oned_laplacian_size</i>	The size of the one d laplacian grid.
<i>global_matrix</i>	The global matrix.

Referenced by `schwz::Initialize< ValueType, IndexType >::generate_sin_rhs()`, and `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize()`.

```

236 {
237     using index_type = IndexType;
238     using value_type = ValueType;
239     using mtx = gko::matrix::Csr<value_type, index_type>;
240     if (settings.matrix_filename != "null") {
241         auto input_file = std::ifstream(filename, std::ios::in);
242         if (!input_file) {
243             std::cerr << "Could not find the file \"" << filename
244                 << "\", which is required for this test.\n";
245         }
246         global_matrix =
247             gko::read<mtx>(input_file, settings.executor->get_master());
248         global_matrix->sort_by_column_index();
249         std::cout << "Matrix from file " << filename << std::endl;
250     } else if (settings.matrix_filename == "null" &&
251         settings.explicit_laplacian) {
252         std::cout << "Laplacian 2D Matrix (generated in house) " << std::endl;
253         gko::size_type global_size = oned_laplacian_size *
254             oned_laplacian_size;
255         global_matrix = mtx::create(settings.executor->get_master(),
256             gko::dim<2>(global_size), 5 * global_size);
257         value_type *values = global_matrix->get_values();
258         index_type *row_ptrs = global_matrix->get_row_ptrs();
259         index_type *col_idxs = global_matrix->get_col_idxs();
260     }

```

```

261     std::vector<gko::size_type> exclusion_set;
262
263     std::map<IndexType, ValueType> stencil_map = {
264         {-oned_laplacian_size, -1}, {-1, -1}, {0, 4}, {1, -1},
265         {oned_laplacian_size, -1},
266     };
267     for (auto i = 2; i < global_size; ++i) {
268         gko::size_type index = (i - 1) * oned_laplacian_size;
269         if (index * index < global_size * global_size) {
270             exclusion_set.push_back(
271                 linearize_index(index, index - 1, global_size));
272             exclusion_set.push_back(
273                 linearize_index(index - 1, index, global_size));
274         }
275     }
276
277     std::sort(exclusion_set.begin(),
278             exclusion_set.begin() + exclusion_set.size());
279
280     IndexType pos = 0;
281     IndexType col_idx = 0;
282     row_ptrs[0] = pos;
283     gko::size_type cur_idx = 0;
284     for (IndexType i = 0; i < global_size; ++i) {
285         for (auto ofs : stencil_map) {
286             auto in_exclusion_flag =
287                 (exclusion_set[cur_idx] ==
288                  linearize_index(i, i + ofs.first, global_size));
289             if (0 <= i + ofs.first && i + ofs.first < global_size &&
290                 !in_exclusion_flag) {
291                 values[pos] = ofs.second;
292                 col_idxs[pos] = i + ofs.first;
293                 ++pos;
294             }
295             if (in_exclusion_flag) {
296                 cur_idx++;
297             }
298             col_idx = row_ptrs[i + 1] - pos;
299         }
300         row_ptrs[i + 1] = pos;
301     }
302 } else {
303     std::cerr << " Need to provide a matrix or enable the default "
304               << "laplacian matrix."
305               << std::endl;
306     std::exit(-1);
307 }
308 }

```

7.9.2.6 setup_local_matrices()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::setup_local_matrices (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata,
    std::vector< unsigned int > & partition_indices,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & local_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_matrix )
[pure virtual]

```

Sets up the local and the interface matrices from the global matrix and the partition indices.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>partition_indices</i>	The array containing the partition indices.
<i>global_matrix</i>	The global system matrix.

Parameters

<i>local_matrix</i>	The local system matrix.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.
<i>local_perm</i>	The local permutation, obtained through RCM or METIS.

Implemented in [schwz::SolverRAS< ValueType, IndexType, MixedValueType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize\(\)](#).

7.9.2.7 setup_vectors()

```
template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::setup_vectors (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::vector< ValueType > & rhs,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_rhs,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_rhs,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_solution )
```

Setup the vectors with default values and allocate mameory if not allocated.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_rhs</i>	The local right hand side vector in the subdomain.
<i>global_rhs</i>	The global right hand side vector.
<i>local_solution</i>	The local solution vector in the subdomain.

References [schwz::Settings::executor](#), [schwz::Metadata< ValueType, IndexType >::first_row](#), [schwz::Metadata< ValueType, IndexType >::local_size_x](#), and [schwz::Metadata< ValueType, IndexType >::my_rank](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize\(\)](#).

```
375 {
376     using vec = gko::matrix::Dense<ValueType>;
377     auto my_rank = metadata.my_rank;
378     auto first_row = metadata.first_row->get_data()[my_rank];
379
380     // Copy the global rhs vector to the required executor.
381     gko::Array<ValueType> temp_rhs(settings.executor->get_master(), rhs.begin(),
382                                   rhs.end());
383     global_rhs = vec::create(settings.executor,
384                             gko::dim<2>(metadata.global_size, 1), temp_rhs, 1);
385
386     local_rhs =
387         vec::create(settings.executor, gko::dim<2>(metadata.local_size_x, 1));
388     // Extract the local rhs from the global rhs. Also takes into account the
389     // overlap.
390     SolverTools::extract_local_vector(settings, metadata, local_rhs.get(),
391                                       global_rhs.get(), first_row);
392
393     local_solution =
394         vec::create(settings.executor, gko::dim<2>(metadata.local_size_x, 1));
395 }
```

The documentation for this class was generated from the following files:

- initialization.hpp (b74805c)
- /home/runner/work/schwarz-lib/schwarz-lib/source/initialization.cpp (55ad704)

7.10 schwz::Metadata< ValueType, IndexType > Struct Template Reference

The solver metadata struct.

```
#include <settings.hpp>
```

Classes

- struct [post_process_data](#)
The struct used for storing data for post-processing.

Public Attributes

- MPI_Comm [mpi_communicator](#)
The MPI communicator.
- gko::size_type [global_size](#) = 0
The size of the global matrix.
- gko::size_type [oned_laplacian_size](#) = 0
The size of the 1 dimensional laplacian grid.
- gko::size_type [local_size](#) = 0
The size of the local subdomain matrix.
- gko::size_type [local_size_x](#) = 0
The size of the local subdomain matrix + the overlap.
- gko::size_type [local_size_o](#) = 0
The size of the local subdomain matrix + the overlap.
- gko::size_type [overlap_size](#) = 0
The size of the overlap between the subdomains.
- gko::size_type [num_subdomains](#) = 1
The number of subdomains used within the solver.
- int [my_rank](#)
The rank of the subdomain.
- int [my_local_rank](#)
The local rank of the subdomain.
- int [local_num_procs](#)
The local number of procs in the subdomain.
- int [comm_size](#)
The number of subdomains used within the solver, size of the communicator.
- int [num_threads](#)
The number of threads used within the solver for each subdomain.
- IndexType [iter_count](#)
The iteration count of the solver.
- ValueType [tolerance](#)
The tolerance of the complete solver.

- ValueType [local_solver_tolerance](#)
The tolerance of the local solver in case of an iterative solve.
- IndexType [max_iters](#)
The maximum iteration count of the Schwarz solver.
- IndexType [local_max_iters](#)
The maximum iteration count of the local iterative solver.
- IndexType [updated_max_iters](#)
The updated maximum iteration count of the local iterative solver.
- std::string [local_precond](#)
Local preconditioner.
- unsigned int [precond_max_block_size](#)
The maximum block size for the preconditioner.
- ValueType [current_residual_norm](#) = -1.0
The current residual norm of the subdomain.
- ValueType [min_residual_norm](#) = -1.0
The minimum residual norm of the subdomain.
- ValueType [constant](#) = 0.0
Value of constant for event threshold Relevant for cgammak threshold.
- ValueType [gamma](#) = 0.0
Value of gamma for event threshold Relevant for cgammak threshold.
- ValueType [horizon](#) = 0.0
Value of horizon for the event threshold Relevant for slope-based threshold.
- ValueType [decay_param](#) = 0.0
Value of decay parameter for the event threshold Relevant for slope-based threshold.
- IndexType [sent_history](#) = 0
Value of history at the sender.
- IndexType [recv_history](#) = 0
Value of history at the receiver.
- IndexType [comm_start_iters](#) = 0
Number of iterations to communicate before event comm.
- std::vector< std::tuple< int, int, int, std::string, std::vector< ValueType > > > [time_struct](#)
The struct used to measure the timings of each function within the solver loop.
- std::vector< std::tuple< int, std::vector< std::tuple< int, int > >, std::vector< std::tuple< int, int > >, int, int > > [comm_data_struct](#)
The struct used to measure the timings of each function within the solver loop.
- std::shared_ptr< gko::Array< IndexType > > [global_to_local](#)
The mapping containing the global to local indices.
- std::shared_ptr< gko::Array< IndexType > > [local_to_global](#)
The mapping containing the local to global indices.
- std::shared_ptr< gko::Array< IndexType > > [overlap_row](#)
The overlap row indices.
- std::shared_ptr< gko::Array< IndexType > > [first_row](#)
The starting row of each subdomain in the matrix.
- std::shared_ptr< gko::Array< IndexType > > [permutation](#)
The permutation used for the re-ordering.
- std::shared_ptr< gko::Array< IndexType > > [i_permutation](#)
The inverse permutation used for the re-ordering.

7.10.1 Detailed Description

```
template<typename ValueType, typename IndexType>  
struct schwz::Metadata< ValueType, IndexType >
```

The solver metadata struct.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

7.10.2 Member Data Documentation

7.10.2.1 local_solver_tolerance

```
template<typename ValueType, typename IndexType>
ValueType schwz::Metadata< ValueType, IndexType >::local_solver_tolerance
```

The tolerance of the local solver in case of an iterative solve.

The residual norm reduction required.

7.10.2.2 tolerance

```
template<typename ValueType, typename IndexType>
ValueType schwz::Metadata< ValueType, IndexType >::tolerance
```

The tolerance of the complete solver.

The residual norm reduction required.

The documentation for this struct was generated from the following file:

- settings.hpp (1a4d86f)

7.11 MetisError Class Reference

[MetisError](#) is thrown when a METIS routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [MetisError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a METIS error.

7.11.1 Detailed Description

[MetisError](#) is thrown when a METIS routine throws a non-zero error code.

7.11.2 Constructor & Destructor Documentation

7.11.2.1 MetisError()

```
MetisError::MetisError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]
```

Initializes a METIS error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the METIS routine that failed
<i>error_code</i>	The resulting METIS error code

```
182         : Error(file, line, func + ": " + get_error(error_code))
183     {}
```

The documentation for this class was generated from the following files:

- exception.hpp (35a1195)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (35a1195)

7.12 schwz::Metadata< ValueType, IndexType >::post_process_data Struct Reference

The struct used for storing data for post-processing.

```
#include <settings.hpp>
```

7.12.1 Detailed Description

```
template<typename ValueType, typename IndexType>
struct schwz::Metadata< ValueType, IndexType >::post_process_data
```

The struct used for storing data for post-processing.

The documentation for this struct was generated from the following file:

- settings.hpp (1a4d86f)

7.13 schwz::SchwarzBase< ValueType, IndexType, MixedValueType > Class Template Reference

The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.

```
#include <schwarz_base.hpp>
```

Public Member Functions

- [SchwarzBase](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata)
The constructor that takes in the user settings and a metadata struct containing the solver metadata.
- void [initialize](#) ()
Initialize the matrix and vectors.
- void [run](#) (std::shared_ptr< gko::matrix::Dense< ValueType >> &solution)
The function that runs the actual solver and obtains the final solution.
- void [print_vector](#) (const std::shared_ptr< gko::matrix::Dense< ValueType >> &vector, int subd, std::string name)
The auxiliary function that prints a passed in vector.
- void [print_matrix](#) (const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &matrix, int rank, std::string name)
The auxiliary function that prints a passed in CSR matrix.

Public Attributes

- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [local_matrix](#)
The local subdomain matrix.
- std::shared_ptr< gko::matrix::Permutation< IndexType >> [local_perm](#)
The local subdomain permutation matrix/array.
- std::shared_ptr< gko::matrix::Permutation< IndexType >> [local_inv_perm](#)
The local subdomain inverse permutation matrix/array.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [triangular_factor_l](#)
The local lower triangular factor used for the triangular solves.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [triangular_factor_u](#)
The local upper triangular factor used for the triangular solves.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [interface_matrix](#)
The local interface matrix.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [global_matrix](#)
The global matrix.
- std::shared_ptr< gko::matrix::Dense< ValueType >> [local_rhs](#)
The local right hand side.
- std::shared_ptr< gko::matrix::Dense< ValueType >> [global_rhs](#)
The global right hand side.
- std::shared_ptr< gko::matrix::Dense< ValueType >> [local_solution](#)
The local solution vector.
- std::shared_ptr< gko::matrix::Dense< ValueType >> [prev_event_solution](#)
The (local+overlap) solution vector at time of previous event of communication The size of this vector is considered global_size to account for overlap.
- std::shared_ptr< gko::matrix::Dense< ValueType >> [global_solution](#)
The global solution vector.
- std::vector< ValueType > [local_residual_vector_out](#)
The global residual vector.
- std::vector< std::vector< ValueType >> [global_residual_vector_out](#)
The local residual vector.

Additional Inherited Members

7.13.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32, typename MixedValueType = gko::default_precision>
class schwz::SchwarzBase< ValueType, IndexType, MixedValueType >
```

The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.

It derives from the Initialization class, the Communication class and the [Solve](#) class all of which are templated.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

7.13.2 Constructor & Destructor Documentation

7.13.2.1 SchwarzBase()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::SchwarzBase (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata )
```

The constructor that takes in the user settings and a metadata struct containing the solver metadata.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.

References [schwz::Settings::cuda_device_guard](#), [schwz::Settings::executor](#), [schwz::Settings::executor_string](#), [schwz::Metadata< ValueType, IndexType >::local_num_procs](#), [schwz::Metadata< ValueType, IndexType >::mpi_communicator](#), [schwz::Metadata< ValueType, IndexType >::my_local_rank](#), and [schwz::Metadata< ValueType, IndexType >::my_rank](#).

```
76 : Initialize<ValueType, IndexType>(settings, metadata),
77   settings(settings),
78   metadata(metadata)
79 {
80     using vec_itype = gko::Array<IndexType>;
81     using vec_vecshared = gko::Array<IndexType *>;
82     metadata.my_local_rank =
83         Utils<ValueType, IndexType>::get_local_rank(metadata.mpi_communicator);
84     metadata.local_num_procs = Utils<ValueType, IndexType>::get_local_num_procs(
85         metadata.mpi_communicator);
86     auto my_local_rank = metadata.my_local_rank;
```

```

87     if (settings.executor_string == "omp") {
88         settings.executor = gko::OmpExecutor::create();
89         auto exec_info =
90             static_cast<gko::OmpExecutor *>(settings.executor.get())
91             ->get_exec_info();
92         exec_info->bind_to_core(metadata.my_local_rank);
93     }
94     } else if (settings.executor_string == "cuda") {
95         int num_devices = 0;
96         #if SCHW_HAVE_CUDA
97             SCHWARZ_ASSERT_NO_CUDA_ERRORS(cudaGetDeviceCount(&num_devices));
98         #else
99             SCHWARZ_NOT_IMPLEMENTED;
100        #endif
101        Utils<ValueType, IndexType>::assert_correct_cuda_devices(
102            num_devices, metadata.my_rank);
103        settings.executor = gko::CudaExecutor::create(
104            my_local_rank, gko::OmpExecutor::create());
105        auto exec_info = static_cast<gko::OmpExecutor *>(
106            settings.executor->get_master().get())
107            ->get_exec_info();
108        exec_info->bind_to_core(my_local_rank);
109        settings.cuda_device_guard =
110            std::make_shared<schwz::device_guard>(my_local_rank);
111
112        std::cout << " Rank " << metadata.my_rank << " with local rank "
113            << my_local_rank << " has "
114            << (static_cast<gko::CudaExecutor *>(settings.executor.get()))
115            ->get_device_id()
116            << " id of gpu" << std::endl;
117        MPI_Barrier(metadata.mpi_communicator);
118    } else if (settings.executor_string == "reference") {
119        settings.executor = gko::ReferenceExecutor::create();
120        auto exec_info =
121            static_cast<gko::ReferenceExecutor *>(settings.executor.get())
122            ->get_exec_info();
123        exec_info->bind_to_core(my_local_rank);
124    }
125 }

```

7.13.3 Member Function Documentation

7.13.3.1 print_matrix()

template<typename ValueType = gko::default_precision, typename IndexType = gko::int32, typename MixedValueType = gko::default_precision>

```

void schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::print_matrix (
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & matrix,
    int rank,
    std::string name )

```

The auxiliary function that prints a passed in CSR matrix.

Parameters

<i>matrix</i>	The matrix to be printed.
<i>subd</i>	The subdomain on which the vector exists.
<i>name</i>	The name of the matrix as a string.

7.13.3.2 print_vector()

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32, typename
MixedValueType = gko::default_precision>
void schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::print_vector (
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & vector,
    int subd,
    std::string name )
```

The auxiliary function that prints a passed in vector.

Parameters

<i>vector</i>	The vector to be printed.
<i>subd</i>	The subdomain on which the vector exists.
<i>name</i>	The name of the vector as a string.

7.13.3.3 run()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::run (
    std::shared_ptr< gko::matrix::Dense< ValueType >> & solution )
```

The function that runs the actual solver and obtains the final solution.

Parameters

<i>solution</i>	The solution vector.
-----------------	----------------------

References schwz::Settings::debug_print, schwz::Communicate< ValueType, IndexType, MixedValueType >::exchange_boundary(), schwz::Settings::executor, schwz::Settings::executor_string, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::global_matrix, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::global_rhs, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::global_solution, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::interface_matrix, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_inv_perm, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_matrix, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_perm, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_rhs, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_solution, schwz::Communicate< ValueType, IndexType, MixedValueType >::local_to_global_vector(), schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::msg_count, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::neighbors_out, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::num_neighbors_out, schwz::Settings::overlap, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::prev_event_solution, schwz::Communicate< ValueType, IndexType, MixedValueType >::setup_windows(), schwz::Settings::thres_type, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::triangular_factor_l, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::triangular_factor_u, schwz::Communicate< ValueType, IndexType, MixedValueType >::update_boundary(), and schwz::Settings::write_iters_and_residuals.

```
328 {
329     using vec_vtype = gko::matrix::Dense<ValueType>;
330     if (!solution.get()) {
331         solution =
332             vec_vtype::create(settings.executor->get_master(),
```

```

333         gko::dim<2>(this->metadata.global_size, 1));
334     }
335     MixedValueType dummy1 = 0.0;
336     ValueType dummy2 = 1.0;
337
338     auto num_neighbors_out = this->comm_struct.num_neighbors_out;
339     auto neighbors_out = this->comm_struct.neighbors_out->get_data();
340
341     if (metadata.my_rank == 0) {
342         std::cout << " MixedValueType: " << typeid(dummy1).name()
343             << " ValueType: " << typeid(dummy2).name() << std::endl;
344     }
345     // The main solution vector
346     std::shared_ptr<vec_vtype> global_solution = vec_vtype::create(
347         this->settings.executor, gko::dim<2>(this->metadata.global_size, 1));
348
349     // The previous iteration solution vector
350     std::shared_ptr<vec_vtype> prev_global_solution = vec_vtype::create(
351         this->settings.executor, gko::dim<2>(this->metadata.global_size, 1));
352
353     // The solution vector at the previous event of communication
354     std::shared_ptr<vec_vtype> prev_event_solution = vec_vtype::create(
355         settings.executor, gko::dim<2>(metadata.global_size, 1));
356
357     // A work vector.
358     std::shared_ptr<vec_vtype> work_vector = vec_vtype::create(
359         settings.executor, gko::dim<2>(2 * this->metadata.local_size_x, 1));
360
361     // An initial guess.
362     std::shared_ptr<vec_vtype> init_guess = vec_vtype::create(
363         settings.executor, gko::dim<2>(this->metadata.local_size_x, 1));
364     // init_guess->copy_from(local_rhs.get());
365
366     if (settings.executor_string == "omp") {
367         ValueType sum_rhs = std::accumulate(
368             local_rhs->get_values(),
369             local_rhs->get_values() + local_rhs->get_size()[0], 0.0);
370         std::cout << " Rank " << this->metadata.my_rank << " sum local rhs "
371             << sum_rhs << std::endl;
372     }
373
374     // Initialize all vectors - tbd
375
376     // std::vector<IndexType> local_converged_iter_count;
377
378     // Setup the windows for the onesided communication.
379     this->setup_windows(this->settings, this->metadata, global_solution);
380
381     const auto solver_settings =
382         (Settings::local_solver_settings::direct_solver_cholmod |
383          Settings::local_solver_settings::direct_solver_umfpack |
384          Settings::local_solver_settings::direct_solver_ginkgo |
385          Settings::local_solver_settings::iterative_solver_dealii |
386          Settings::local_solver_settings::iterative_solver_ginkgo) &
387         settings.local_solver;
388     prev_global_solution->copy_from(gko::lend(global_solution));
389
390     ValueType local_residual_norm = -1.0, local_residual_norm0 = -1.0,
391         global_residual_norm = 0.0, global_residual_norm0 = -1.0;
392     metadata.iter_count = 0;
393     int num_converged_procs = 0;
394
395     std::ofstream fps; // file for sending log
396     std::ofstream fpr; // file for receiving log
397
398     if (settings.debug_print) {
399         // Opening files for event logs
400         char send_name[30], recv_name[30], pe_str[3];
401         sprintf(pe_str, "%d", metadata.my_rank);
402
403         strcpy(send_name, "send");
404         strcat(send_name, pe_str);
405         strcat(send_name, ".txt");
406
407         strcpy(recv_name, "recv");
408         strcat(recv_name, pe_str);
409         strcat(recv_name, ".txt");
410
411         fps.open(send_name);
412         fpr.open(recv_name);
413     }
414
415     if (metadata.my_rank == 0) {
416         std::cout << "Send history - " << metadata.sent_history
417             << ", Recv history - " << metadata.recv_history << std::endl;
418         std::cout << "Thres type - " << settings.thres_type << std::endl;
419         std::cout << "Overlap - " << settings.overlap << std::endl;

```

```

420     }
421
422     auto start_time = std::chrono::steady_clock::now();
423
424     for (; metadata.iter_count < metadata.max_iters; ++(metadata.iter_count)) {
425         // Exchange the boundary values. The communication part.
426         MEASURE_ELAPSED_FUNC_TIME(
427             this->exchange_boundary(settings, metadata, prev_global_solution,
428                                     global_solution, prev_event_solution, fps, fpr),
429             0, metadata.my_rank, boundary_exchange, metadata.iter_count);
430         prev_global_solution->copy_from(gko::lend(global_solution));
431
432         // Update the boundary and interior values after the exchanging from
433         // other processes.
434         MEASURE_ELAPSED_FUNC_TIME(
435             this->update_boundary(settings, metadata, this->
local_solution,
436                                     this->local_rhs, global_solution,
437                                     this->interface_matrix),
438             1, metadata.my_rank, boundary_update, metadata.iter_count);
439
440         // Check for the convergence of the solver.
441         // num_converged_procs = 0;
442         MEASURE_ELAPSED_FUNC_TIME(
443             (Solve<ValueType, IndexType, MixedValueType>::check_convergence(
444                 settings, metadata, this->comm_struct, this->convergence_vector,
445                 global_solution, this->local_solution, this->
local_matrix,
446                 work_vector, local_residual_norm, local_residual_norm0,
447                 global_residual_norm, global_residual_norm0,
448                 num_converged_procs)),
449             2, metadata.my_rank, convergence_check, metadata.iter_count);
450
451         // break if the solution diverges.
452         if (std::isnan(global_residual_norm) || global_residual_norm > 1e12) {
453             std::cout << " Rank " << metadata.my_rank << " diverged in "
454                 << metadata.iter_count << " iters " << std::endl;
455             std::exit(-1);
456         }
457
458         // break if all processes detect that all other processes have
459         // converged otherwise continue iterations.
460         if (num_converged_procs == metadata.num_subdomains) {
461             break;
462         } else {
463             MEASURE_ELAPSED_FUNC_TIME(
464                 (Solve<ValueType, IndexType, MixedValueType>::local_solve(
465                     settings, metadata, this->local_matrix,
466                     this->triangular_factor_l, this->
triangular_factor_u,
467                     this->local_perm, this->local_inv_perm, work_vector,
468                     init_guess, this->local_solution)),
469                 3, metadata.my_rank, local_solve, metadata.iter_count);
470
471             // Gather the local vector into the locally global vector for
472             // communication.
473             MEASURE_ELAPSED_FUNC_TIME(
474                 (Communicate<ValueType, IndexType, MixedValueType>::
475                     local_to_global_vector(settings, metadata,
476                     this->local_solution,
477                     global_solution)),
478                 4, metadata.my_rank, expand_local_vec, metadata.iter_count);
479         }
480     }
481     MPI_Barrier(MPI_COMM_WORLD);
482     auto elapsed_time = std::chrono::duration<ValueType>(
483         std::chrono::steady_clock::now() - start_time);
484
485     if (settings.debug_print) {
486         // Closing event log files
487         fps.close();
488         fpr.close();
489     }
490
491     // adding 1 to include the 0-th iteration
492     metadata.iter_count = metadata.iter_count + 1;
493
494     // number of messages a PE would send without event-based
495     int noevent_msg_count = metadata.iter_count * num_neighbors_out;
496
497     int total_events = 0;
498
499     // Printing msg count
500     for (int k = 0; k < num_neighbors_out; k++) {
501         std::cout << " Rank: " << metadata.my_rank << " to " << neighbors_out[k]
502             << " : " << this->comm_struct.msg_count->get_data()[k];
503         total_events += this->comm_struct.msg_count->get_data()[k];

```



```

504     }
505     std::cout << std::endl;
506
507     // Total no of messages in all PEs
508     MPI_Allreduce(MPI_IN_PLACE, &total_events, 1, MPI_INT, MPI_SUM,
509                 MPI_COMM_WORLD);
510     MPI_Allreduce(MPI_IN_PLACE, &noevent_msg_count, 1, MPI_INT, MPI_SUM,
511                 MPI_COMM_WORLD);
512
513     if (metadata.my_rank == 0) {
514         std::cout << "Total number of events - " << total_events << std::endl;
515         std::cout << "Total number of msgs without event - "
516                 << noevent_msg_count << std::endl;
517     }
518
519     // Write the residuals and iterations to files
520     if (settings.write_iters_and_residuals &&
521         solver_settings ==
522         Settings::local_solver_settings::iterative_solver_ginkgo) {
523         std::string rank_string = std::to_string(metadata.my_rank);
524         if (metadata.my_rank < 10) {
525             rank_string = "0" + std::to_string(metadata.my_rank);
526         }
527         std::string filename = "iter_res_" + rank_string + ".csv";
528         write_iters_and_residuals(
529             metadata.num_subdomains, metadata.my_rank,
530             metadata.post_process_data.local_residual_vector_out.size(),
531             metadata.post_process_data.local_residual_vector_out,
532             metadata.post_process_data.local_converged_iter_count,
533             metadata.post_process_data.local_converged_resnorm,
534             metadata.post_process_data.local_timestamp, filename);
535     }
536     if (num_converged_procs < metadata.num_subdomains) {
537         std::cout << "Rank " << metadata.my_rank << " did not converge in "
538                 << metadata.iter_count << " iterations." << std::endl;
539     } else {
540         std::cout << " Rank " << metadata.my_rank << " converged in "
541                 << metadata.iter_count << " iterations " << std::endl;
542         ValueType mat_norm = -1.0, rhs_norm = -1.0, sol_norm = -1.0,
543                 residual_norm = -1.0;
544
545         // Compute the final residual norm. Also gathers the solution from all
546         // subdomains.
547         Solve<ValueType, IndexType, MixedValueType>::compute_residual_norm(
548             settings, metadata, global_matrix, global_rhs, global_solution,
549             mat_norm, rhs_norm, sol_norm, residual_norm);
550         gather_comm_data<ValueType, IndexType, MixedValueType>(
551             metadata.num_subdomains, this->comm_struct,
552             metadata.comm_data_struct);
553         // clang-format off
554         if (metadata.my_rank == 0)
555         {
556             std::cout
557                 << " residual norm " << residual_norm << "\n"
558                 << " relative residual norm of solution " << residual_norm/rhs_norm << "\n"
559                 << " Time taken for solve " << elapsed_time.count()
560                 << std::endl;
561         }
562         // clang-format on
563     }
564     if (metadata.my_rank == 0) {
565         solution->copy_from(global_solution.get());
566     }
567
568     // Communicate<ValueType, IndexType>::clear(settings);
569 }

```

The documentation for this class was generated from the following files:

- schwarz_base.hpp (1bdbc6b)
- /home/runner/work/schwarz-lib/schwarz-lib/source/schwarz_base.cpp (4be4b37)

7.14 schwz::Settings Struct Reference

The struct that contains the solver settings and the parameters to be set by the user.

```
#include <settings.hpp>
```

Classes

- struct [comm_settings](#)
The settings for the various available communication paradigms.
- struct [convergence_settings](#)
The various convergence settings available.

Public Types

- enum [partition_settings](#)
The partition algorithm to be used for partitioning the matrix.
- enum [local_solver_settings](#)
The local solver algorithm for the local subdomain solves.

Public Attributes

- std::string [executor_string](#)
The string that contains the ginkgo executor paradigm.
- std::shared_ptr< gko::Executor > [executor](#) = gko::ReferenceExecutor::create()
The ginkgo executor the code is to be executed on.
- std::shared_ptr< [device_guard](#) > [cuda_device_guard](#)
The ginkgo executor the code is to be executed on.
- gko::int32 [overlap](#) = 2
The overlap between the subdomains.
- std::string [matrix_filename](#) = "null"
The string that contains the matrix file name to read from .
- bool [explicit_laplacian](#) = true
Flag if the laplacian matrix should be generated within the library.
- bool [use_mixed_precision](#) = false
Flag if mixed precision should be used.
- bool [enable_random_rhs](#) = false
Flag to enable a random rhs.
- std::string [rhs_type](#) = "ones"
Flag to enable a random rhs.
- std::string [thres_type](#) = "cgammak"
Flag to choose thres type.
- std::string [norm_type](#) = "L1"
Flag to choose norm type.
- bool [print_matrices](#) = false
Flag to enable printing of matrices.
- bool [debug_print](#) = false
Flag to enable some debug printing.
- bool [non_symmetric_matrix](#) = false
Is the matrix non-symmetric ? , Use GMRES for local solves.
- int [restart_iter](#) = 1
The restart iter for the GMRES solver.
- int [reset_local_crit_iter](#) = -1
The global iter at which to reset the local solver criterion.
- bool [naturally_ordered_factor](#) = false

- Disables the re-ordering of the matrix before computing the triangular factors during the CHOLMOD factorization.*

 - `std::string metis_objtype`
This setting defines the objective type for the metis partitioning.
 - `bool use_precond = false`
Enable the block jacobi local preconditioner for the local solver.
 - `bool write_debug_out = false`
Enable the writing of debug out to file.
 - `bool write_iters_and_residuals = false`
Enable writing the iters and residuals to a file.
 - `bool enable_logging = false`
Flag to enable logging for local iterative solvers.
 - `bool write_perm_data = false`
Enable the local permutations from CHOLMOD to a file.
 - `int shifted_iter = 1`
Iteration shift for node local communication.
 - `std::string factorization = "cholmod"`
The factorization for the local direct solver.
 - `std::string reorder`
The reordering for the local solve.

7.14.1 Detailed Description

The struct that contains the solver settings and the parameters to be set by the user.

settings

7.14.2 Member Data Documentation

7.14.2.1 enable_logging

```
bool schwz::Settings::enable_logging = false
```

Flag to enable logging for local iterative solvers.

Note: Probably will have a significant performance hit.

7.14.2.2 explicit_laplacian

```
bool schwz::Settings::explicit_laplacian = true
```

Flag if the laplacian matrix should be generated within the library.

If false, an external matrix and rhs needs to be provided

Referenced by `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::initialize()`.

7.14.2.3 naturally_ordered_factor

```
bool schwz::Settings::naturally_ordered_factor = false
```

Disables the re-ordering of the matrix before computing the triangular factors during the CHOLMOD factorization.

Note

This is mainly to allow compatibility with GPU solution.

7.14.2.4 norm_type

```
std::string schwz::Settings::norm_type = "L1"
```

Flag to choose norm type.

Choices are "L1" or "L2"

Referenced by `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows()`.

7.14.2.5 thres_type

```
std::string schwz::Settings::thres_type = "cgammak"
```

Flag to choose thres type.

Choices are "cgammak" or "slope"

Referenced by `schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::run()`, and `schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows()`.

The documentation for this struct was generated from the following file:

- settings.hpp (1a4d86f)

7.15 schwz::Solve< ValueType, IndexType, MixedValueType > Class Template Reference

The Solver class the provides the solver and the convergence checking methods.

```
#include <solve.hpp>
```

Additional Inherited Members

7.15.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32, typename MixedValueType = gko::
::default_precision>
class schwz::Solve< ValueType, IndexType, MixedValueType >
```

The Solver class the provides the solver and the convergence checking methods.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Solve

The documentation for this class was generated from the following files:

- solve.hpp (46471fd)
- /home/runner/work/schwarz-lib/schwarz-lib/source/solve.cpp (92dbd95)

7.16 schwz::SolverRAS< ValueType, IndexType, MixedValueType > Class Template Reference

An implementation of the solver interface using the RAS solver.

```
#include <restricted_schwarz.hpp>
```

Public Member Functions

- [SolverRAS](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata)
The constructor that takes in the user settings and a metadata struct containing the solver metadata.
- void [setup_local_matrices](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata, std::vector< unsigned int > &[partition_indices](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[global_matrix](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[local_matrix](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[interface_matrix](#)) override
Sets up the local and the interface matrices from the global matrix and the partition indices.
- void [setup_comm_buffers](#) () override
Sets up the communication buffers needed for the boundary exchange.
- void [setup_windows](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &[main_buffer](#)) override
Sets up the windows needed for the asynchronous communication.
- void [exchange_boundary](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, const std::shared_ptr< gko::matrix::Dense< ValueType >> &[prev_global_solution](#), std::shared_ptr< gko::matrix::Dense< ValueType >> &[global_solution](#), std::shared_ptr< gko::matrix::Dense< ValueType >> &[prev_event_solution](#), std::ofstream &fps, std::ofstream &fpr) override
Exchanges the elements of the solution vector.
- void [update_boundary](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &[local_solution](#), const std::shared_ptr< gko::matrix::Dense< ValueType >> &[local_rhs](#), const std::shared_ptr< gko::matrix::Dense< ValueType >> &[global_solution](#), const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[interface_matrix](#)) override
Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.

Additional Inherited Members

7.16.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32, typename MixedValueType = gko::default_precision>
class schwz::SolverRAS< ValueType, IndexType, MixedValueType >
```

An implementation of the solver interface using the RAS solver.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

7.16.2 Constructor & Destructor Documentation

7.16.2.1 SolverRAS()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
schwz::SolverRAS< ValueType, IndexType, MixedValueType >::SolverRAS (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata )
```

The constructor that takes in the user settings and a metadata struct containing the solver metadata.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>data</i>	The additional data struct.

```
51      : SchwarzBase<ValueType, IndexType, MixedValueType>(settings, metadata)
52 {}
```

7.16.3 Member Function Documentation

7.16.3.1 exchange_boundary()

```
template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::SolverRAS< ValueType, IndexType, MixedValueType >::exchange_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & prev_global_solution,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & prev_event_solution,
    std::ofstream & fps,
    std::ofstream & fpr ) [override], [virtual]
```

Exchanges the elements of the solution vector.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>global_solution</i>	The solution vector being exchanged between the subdomains.

Implements [schwz::Communicate< ValueType, IndexType, MixedValueType >](#).

References [schwz::Settings::comm_settings::enable_onesided](#), [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::global_solution](#), and [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::prev←_event_solution](#).

```

1347 {
1348     if (settings.comm_settings.enable_onesided) {
1349         exchange_boundary_onesided<ValueType, IndexType, MixedValueType>(
1350             settings, metadata, this->comm_struct, prev_global_solution,
1351             global_solution, prev_event_solution, fps, fpr);
1352     } else {
1353         exchange_boundary_twosided<ValueType, IndexType, MixedValueType>(
1354             settings, metadata, this->comm_struct, prev_global_solution,
1355             global_solution);
1356     }
1357 }
```

7.16.3.2 setup_local_matrices()

```

template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_local_matrices (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata,
    std::vector< unsigned int > & partition_indices,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & local_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_matrix )
[override], [virtual]
```

Sets up the local and the interface matrices from the global matrix and the partition indices.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>partition_indices</i>	The array containing the partition indices.
<i>global_matrix</i>	The global system matrix.
<i>local_matrix</i>	The local system matrix.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.
<i>local_perm</i>	The local permutation, obtained through RCM or METIS.

Implements [schwz::Initialize< ValueType, IndexType >](#).

References [schwz::Metadata< ValueType, IndexType >::comm_size](#), [schwz::Settings::executor](#), [schwz::Metadata< ValueType, IndexType >::first_row](#), [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >←](#)

::global_matrix, schwz::Metadata< ValueType, IndexType >::global_size, schwz::Metadata< ValueType, IndexType >::global_to_local, schwz::Metadata< ValueType, IndexType >::i_permutation, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::interface_matrix, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_matrix, schwz::Metadata< ValueType, IndexType >::local_size, schwz::Metadata< ValueType, IndexType >::local_size_o, schwz::Metadata< ValueType, IndexType >::local_size_x, schwz::Metadata< ValueType, IndexType >::local_to_global, schwz::Metadata< ValueType, IndexType >::my_rank, schwz::Metadata< ValueType, IndexType >::num_subdomains, schwz::Settings::overlap, schwz::Metadata< ValueType, IndexType >::overlap_row, schwz::Metadata< ValueType, IndexType >::overlap_size, and schwz::Metadata< ValueType, IndexType >::permutation.

```

62 {
63     using mtx = gko::matrix::Csr<ValueType, IndexType>;
64     using vec_itype = gko::Array<IndexType>;
65     using perm_type = gko::matrix::Permutation<IndexType>;
66     using arr = gko::Array<IndexType>;
67     auto my_rank = metadata.my_rank;
68     auto comm_size = metadata.comm_size;
69     auto num_subdomains = metadata.num_subdomains;
70     auto global_size = metadata.global_size;
71     auto mpi_itype = schwz::mpi::get_mpi_datatype(*partition_indices.data());
72
73     MPI_Bcast(partition_indices.data(), global_size, mpi_itype, 0,
74             MPI_COMM_WORLD);
75
76     std::vector<IndexType> local_p_size(num_subdomains);
77     auto global_to_local = metadata.global_to_local->get_data();
78     auto local_to_global = metadata.local_to_global->get_data();
79
80     auto first_row = metadata.first_row->get_data();
81     auto permutation = metadata.permutation->get_data();
82     auto i_permutation = metadata.i_permutation->get_data();
83
84     auto nb = (global_size + num_subdomains - 1) /
num_subdomains;
85     auto partition_settings =
86         (Settings::partition_settings::partition_zoltan |
87          Settings::partition_settings::partitionmetis |
88          Settings::partition_settings::partition_regular |
89          Settings::partition_settings::partition_regular2d |
90          Settings::partition_settings::partition_custom) &
91         settings.partition;
92
93     IndexType *gmat_row_ptrs = global_matrix->get_row_ptrs();
94     IndexType *gmat_col_idxes = global_matrix->get_col_idxes();
95     ValueType *gmat_values = global_matrix->get_values();
96
97     // default local p size set for 1 subdomain.
98     first_row[0] = 0;
99     for (auto p = 0; p < num_subdomains; ++p) {
100         local_p_size[p] = std::min(global_size - first_row[p], nb);
101         first_row[p + 1] = first_row[p] + local_p_size[p];
102     }
103
104
105     if (partition_settings == Settings::partition_settings::partitionmetis ||
106         partition_settings ==
107         Settings::partition_settings::partition_regular2d) {
108         if (num_subdomains > 1) {
109             for (auto p = 0; p < num_subdomains; p++) {
110                 local_p_size[p] = 0;
111             }
112             for (auto i = 0; i < global_size; i++) {
113                 local_p_size[partition_indices[i]]++;
114             }
115             first_row[0] = 0;
116             for (auto p = 0; p < num_subdomains; ++p) {
117                 first_row[p + 1] = first_row[p] + local_p_size[p];
118             }
119             // permutation
120             for (auto i = 0; i < global_size; i++) {
121                 permutation[first_row[partition_indices[i]]] = i;
122                 first_row[partition_indices[i]]++;
123             }
124             for (auto p = num_subdomains; p > 0; p--) {
125                 first_row[p] = first_row[p - 1];
126             }
127             first_row[0] = 0;
128
129             // iperm
130             for (auto i = 0; i < global_size; i++) {
131                 i_permutation[permutation[i]] = i;
132             }

```



```

133     }
134
135     auto gmat_temp = mtx::create(settings.executor->get_master(),
136                                 global_matrix->get_size(),
137                                 global_matrix->get_num_stored_elements());
138
139     auto nnz = 0;
140     gmat_temp->get_row_ptrs()[0] = 0;
141     for (auto row = 0; row < metadata.global_size; ++row) {
142         for (auto col = gmat_row_ptrs[permutation[row]];
143              col < gmat_row_ptrs[permutation[row] + 1]; ++col) {
144             gmat_temp->get_col_idxs()[nnz] =
145                 i_permutation[gmat_col_idxs[col]];
146             gmat_temp->get_values()[nnz] = gmat_values[col];
147             nnz++;
148         }
149         gmat_temp->get_row_ptrs()[row + 1] = nnz;
150     }
151     global_matrix->copy_from(gmat_temp.get());
152 }
153
154
155 for (auto i = 0; i < global_size; i++) {
156     global_to_local[i] = 0;
157     local_to_global[i] = 0;
158 }
159 auto num = 0;
160 for (auto i = first_row[my_rank]; i < first_row[
my_rank + 1]; i++) {
161     global_to_local[i] = 1 + num;
162     local_to_global[num] = i;
163     num++;
164 }
165
166 IndexType old = 0;
167 for (auto k = 1; k < settings.overlap; k++) {
168     auto now = num;
169     for (auto i = old; i < now; i++) {
170         for (auto j = gmat_row_ptrs[local_to_global[i]];
171              j < gmat_row_ptrs[local_to_global[i] + 1]; j++) {
172             if (global_to_local[gmat_col_idxs[j]] == 0) {
173                 local_to_global[num] = gmat_col_idxs[j];
174                 global_to_local[gmat_col_idxs[j]] = 1 + num;
175                 num++;
176             }
177         }
178     }
179     old = now;
180 }
181 metadata.local_size = local_p_size[my_rank];
182 metadata.local_size_x = num;
183 metadata.local_size_o = global_size;
184 auto local_size = metadata.local_size;
185 auto local_size_x = metadata.local_size_x;
186
187 metadata.overlap_size = num - metadata.local_size;
188 metadata.overlap_row = std::shared_ptr<vec_itype>(
189     new vec_itype(gko::Array<IndexType>::view(
190         settings.executor, metadata.overlap_size,
191         &(metadata.local_to_global->get_data()[metadata.local_size]))),
192     std::default_delete<vec_itype>());
193
194 auto nnz_local = 0;
195 auto nnz_interface = 0;
196
197 for (auto i = first_row[my_rank]; i < first_row[my_rank + 1]; ++i) {
198     for (auto j = gmat_row_ptrs[i]; j < gmat_row_ptrs[i + 1]; j++) {
199         if (global_to_local[gmat_col_idxs[j]] != 0) {
200             nnz_local++;
201         } else {
202             std::cout << " debug: invalid edge?" << std::endl;
203         }
204     }
205 }
206 auto temp = 0;
207 for (auto k = 0; k < metadata.overlap_size; k++) {
208     temp = metadata.overlap_row->get_data()[k];
209     for (auto j = gmat_row_ptrs[temp]; j < gmat_row_ptrs[temp + 1]; j++) {
210         if (global_to_local[gmat_col_idxs[j]] != 0) {
211             nnz_local++;
212         } else {
213             nnz_interface++;
214         }
215     }
216 }
217
218 std::shared_ptr<mtx> local_matrix_compute;

```

```

219     local_matrix_compute = mtx::create(settings.executor->get_master(),
220                                       gko::dim<2>(local_size_x), nnz_local);
221     IndexType *lmat_row_ptrs = local_matrix_compute->get_row_ptrs();
222     IndexType *lmat_col_idxes = local_matrix_compute->get_col_idxes();
223     ValueType *lmat_values = local_matrix_compute->get_values();
224
225     std::shared_ptr<mtx> interface_matrix_compute;
226     if (nnz_interface > 0) {
227         interface_matrix_compute =
228             mtx::create(settings.executor->get_master(),
229                         gko::dim<2>(local_size_x), nnz_interface);
230     } else {
231         interface_matrix_compute = mtx::create(settings.executor->get_master());
232     }
233
234     IndexType *imat_row_ptrs = interface_matrix_compute->get_row_ptrs();
235     IndexType *imat_col_idxes = interface_matrix_compute->get_col_idxes();
236     ValueType *imat_values = interface_matrix_compute->get_values();
237
238     num = 0;
239     nnz_local = 0;
240     auto nnz_interface_temp = 0;
241     lmat_row_ptrs[0] = nnz_local;
242     if (nnz_interface > 0) {
243         imat_row_ptrs[0] = nnz_interface_temp;
244     }
245     // Local interior matrix
246     for (auto i = first_row[my_rank]; i < first_row[my_rank + 1]; ++i) {
247         for (auto j = gmat_row_ptrs[i]; j < gmat_row_ptrs[i + 1]; ++j) {
248             if (global_to_local[gmat_col_idxes[j]] != 0) {
249                 lmat_col_idxes[nnz_local] =
250                     global_to_local[gmat_col_idxes[j]] - 1;
251                 lmat_values[nnz_local] = gmat_values[j];
252                 nnz_local++;
253             }
254         }
255         if (nnz_interface > 0) {
256             imat_row_ptrs[num + 1] = nnz_interface_temp;
257         }
258         lmat_row_ptrs[num + 1] = nnz_local;
259         num++;
260     }
261
262     // Interface matrix
263     if (nnz_interface > 0) {
264         nnz_interface = 0;
265         for (auto k = 0; k < metadata.overlap_size; k++) {
266             temp = metadata.overlap_row->get_data()[k];
267             for (auto j = gmat_row_ptrs[temp]; j < gmat_row_ptrs[temp + 1];
268                  j++) {
269                 if (global_to_local[gmat_col_idxes[j]] != 0) {
270                     lmat_col_idxes[nnz_local] =
271                         global_to_local[gmat_col_idxes[j]] - 1;
272                     lmat_values[nnz_local] = gmat_values[j];
273                     nnz_local++;
274                 } else {
275                     imat_col_idxes[nnz_interface] = gmat_col_idxes[j];
276                     imat_values[nnz_interface] = gmat_values[j];
277                     nnz_interface++;
278                 }
279             }
280             lmat_row_ptrs[num + 1] = nnz_local;
281             imat_row_ptrs[num + 1] = nnz_interface;
282             num++;
283         }
284     }
285     auto now = num;
286     for (auto i = old; i < now; i++) {
287         for (auto j = gmat_row_ptrs[local_to_global[i]];
288              j < gmat_row_ptrs[local_to_global[i] + 1]; j++) {
289             if (global_to_local[gmat_col_idxes[j]] == 0) {
290                 local_to_global[num] = gmat_col_idxes[j];
291                 global_to_local[gmat_col_idxes[j]] = 1 + num;
292                 num++;
293             }
294         }
295     }
296
297     local_matrix_compute->sort_by_column_index();
298     interface_matrix_compute->sort_by_column_index();
299
300     local_matrix = mtx::create(settings.executor);
301     local_matrix->copy_from(gko::lend(local_matrix_compute));
302     interface_matrix = mtx::create(settings.executor);
303     interface_matrix->copy_from(gko::lend(interface_matrix_compute));
304 }

```

```
template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::SolverRAS< ValueType, IndexType, MixedValueType >::setup_windows (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & main_buffer ) [override],
[virtual]
```

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>main_buffer</i>	The main buffer being exchanged between the subdomains.

```
References schwz::Metadata< ValueType, IndexType >::comm_start_iters, schwz::Metadata< ValueType, IndexType >::constant, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::curr_rcv_avg, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::curr_send_avg, schwz::Settings::debug_print, schwz::Metadata< ValueType, IndexType >::decay_param, schwz::Settings::comm_settings::enable_get, schwz::Settings::comm_settings::enable_lock_all, schwz::Settings::comm_settings::enable_one_by_one, schwz::Settings::comm_settings::enable_onesided, schwz::Settings::comm_settings::enable_overlap, schwz::Settings::comm_settings::enable_put, schwz::Settings::executor, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::extra_buffer, schwz::Metadata< ValueType, IndexType >::gamma, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::get_displacements, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::get_request, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::global_get, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::global_put, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::global_solution, schwz::Metadata< ValueType, IndexType >::horizon, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::is_local_neighbor, schwz::Metadata< ValueType, IndexType >::iter_count, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_rcv_avg, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_rcv_bdy, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_rcv_iter, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_rcv_slopes, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_send_avg, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_sent_iter, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::last_sent_slopes_avg, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::local_get, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::local_neighbors_in, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::local_neighbors_out, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::local_num_neighbors_in, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::local_num_neighbors_out, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::local_put, schwz::Metadata< ValueType, IndexType >::local_size_o, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::mixedt_rcv_buffer, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::mixedt_send_buffer, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::msg_count, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::neighbors_in, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::neighbors_out, schwz::Settings::norm_type, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::num_neighbors_in, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::num_neighbors_out, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::num_rcv, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::num_send
```

schwz::Metadata< ValueType, IndexType >::num_subdomains, schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::prev_event_solution, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::put_displacements, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::put_request, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::recv_buffer, schwz::Metadata< ValueType, IndexType >::recv_history, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::remote_get, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::remote_put, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::send_buffer, schwz::Metadata< ValueType, IndexType >::sent_history, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::thres, schwz::Settings::thres_type, schwz::Settings::use_mixed_precision, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::window_recv_buffer, schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::window_send_buffer, and schwz::Communicate< ValueType, IndexType, MixedValueType >::comm_struct::window_x.

```

667 {
668     using vec_itype = gko::Array<IndexType>;
669     using vec_vtype = gko::matrix::Dense<ValueType>;
670     auto num_subdomains = metadata.num_subdomains;
671     auto local_size_o = metadata.local_size_o;
672     auto neighbors_in = this->comm_struct.neighbors_in->get_data();
673     auto global_get = this->comm_struct.global_get->get_data();
674     auto neighbors_out = this->comm_struct.neighbors_out->get_data();
675     auto global_put = this->comm_struct.global_put->get_data();
676
677     // set displacement for the MPI buffer
678     auto get_displacements = this->comm_struct.get_displacements->get_data();
679     auto put_displacements = this->comm_struct.put_displacements->get_data();
680     {
681         std::vector<IndexType> tmp_num_comm_elems(num_subdomains + 1, 0);
682         tmp_num_comm_elems[0] = 0;
683         for (auto j = 0; j < this->comm_struct.num_neighbors_in; j++) {
684             if ((global_get[j])[0] > 0) {
685                 int p = neighbors_in[j];
686                 tmp_num_comm_elems[p + 1] = (global_get[j])[0];
687             }
688         }
689         for (auto j = 0; j < num_subdomains; j++) {
690             tmp_num_comm_elems[j + 1] += tmp_num_comm_elems[j];
691         }
692
693         auto mpi_itype = schwz::mpi::get_mpi_datatype(tmp_num_comm_elems[0]);
694         MPI_Alltoall(tmp_num_comm_elems.data(), 1, mpi_itype, put_displacements,
695                     1, mpi_itype, MPI_COMM_WORLD);
696     }
697
698     {
699         std::vector<IndexType> tmp_num_comm_elems(num_subdomains + 1, 0);
700         tmp_num_comm_elems[0] = 0;
701         for (auto j = 0; j < this->comm_struct.num_neighbors_out; j++) {
702             if ((global_put[j])[0] > 0) {
703                 int p = neighbors_out[j];
704                 tmp_num_comm_elems[p + 1] = (global_put[j])[0];
705             }
706         }
707         for (auto j = 0; j < num_subdomains; j++) {
708             tmp_num_comm_elems[j + 1] += tmp_num_comm_elems[j];
709         }
710
711         auto mpi_itype = schwz::mpi::get_mpi_datatype(tmp_num_comm_elems[0]);
712         MPI_Alltoall(tmp_num_comm_elems.data(), 1, mpi_itype, get_displacements,
713                     1, mpi_itype, MPI_COMM_WORLD);
714     }
715
716     // setup windows
717     if (settings.comm_settings.enable_onesided) {
718         // Onesided
719
720         for (int i = 0; i < main_buffer->get_size()[0]; i++) {
721             main_buffer->get_values()[i] = 0.0;
722         }
723
724         MPI_Win_create(main_buffer->get_values(),
725                        main_buffer->get_size()[0] * sizeof(ValueType),
726                        sizeof(ValueType), MPI_INFO_NULL, MPI_COMM_WORLD,
727                        &(this->comm_struct.window_x));
728     }
729
730
731     if (settings.comm_settings.enable_onesided) {
732         // MPI_Alloc_mem ? Custom allocator ? TODO
733     }

```

```

734     for (int i = 0; i < num_subdomains; i++) {
735         this->local_residual_vector->get_values()[i] = 0.0;
736     }
737
738     MPI_Win_create(this->local_residual_vector->get_values(),
739                   (num_subdomains) * sizeof(ValueType), sizeof(ValueType),
740                   MPI_INFO_NULL, MPI_COMM_WORLD,
741                   &(this->>window_residual_vector));
742     std::vector<IndexType> zero_vec(num_subdomains, 0);
743     gko::Array<IndexType> temp_array(settings.executor->get_master(),
744                                     zero_vec.begin(), zero_vec.end());
745     this->convergence_vector = std::shared_ptr<vec_itype>{
746         new vec_itype(settings.executor->get_master(), temp_array),
747         std::default_delete<vec_itype>()};
748     this->convergence_sent = std::shared_ptr<vec_itype>{
749         new vec_itype(settings.executor->get_master(), num_subdomains),
750         std::default_delete<vec_itype>()};
751     this->convergence_local = std::shared_ptr<vec_itype>{
752         new vec_itype(settings.executor->get_master(), num_subdomains),
753         std::default_delete<vec_itype>()};
754
755     for (int i = 0; i < num_subdomains; i++) {
756         this->convergence_vector->get_data()[i] = 0;
757         this->convergence_sent->get_data()[i] = 0;
758         this->convergence_local->get_data()[i] = 0;
759     }
760
761     MPI_Win_create(this->convergence_vector->get_data(),
762                   (num_subdomains) * sizeof(IndexType), sizeof(IndexType),
763                   MPI_INFO_NULL, MPI_COMM_WORLD,
764                   &(this->window_convergence));
765 }
766
767 if (settings.comm_settings.enable_onesided && num_subdomains > 1) {
768     // Lock all windows.
769     if (settings.comm_settings.enable_get &&
770         settings.comm_settings.enable_lock_all) {
771         MPI_Win_lock_all(0, this->comm_struct.window_send_buffer);
772     }
773     if (settings.comm_settings.enable_put &&
774         settings.comm_settings.enable_lock_all) {
775         MPI_Win_lock_all(0, this->comm_struct.window_recv_buffer);
776     }
777     if (settings.comm_settings.enable_one_by_one &&
778         settings.comm_settings.enable_lock_all) {
779         MPI_Win_lock_all(0, this->comm_struct.window_x);
780     }
781     MPI_Win_lock_all(0, this->window_residual_vector);
782     MPI_Win_lock_all(0, this->window_convergence);
783 }
784 }

```

7.16.3.4 update_boundary()

```

template<typename ValueType , typename IndexType , typename MixedValueType >
void schwz::SolverRAS< ValueType, IndexType, MixedValueType >::update_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_solution,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & local_rhs,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution,
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_↵
matrix ) [override], [virtual]

```

Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.

Parameters

<i>local_solution</i>	The local solution vector in the subdomain.
<i>local_rhs</i>	The local right hand side vector in the subdomain.
<i>global_solution</i>	The workspace solution vector.
<i>global_old_solution</i>	The global solution vector of the previous iteration.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.

Implements [schwz::Communicate< ValueType, IndexType, MixedValueType >](#).

References [schwz::Settings::executor](#), [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::global_←_solution](#), [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::interface_matrix](#), [schwz::Schwarz←_Base< ValueType, IndexType, MixedValueType >::local_rhs](#), [schwz::Metadata< ValueType, IndexType >::local_←_size_x](#), [schwz::SchwarzBase< ValueType, IndexType, MixedValueType >::local_solution](#), [schwz::Metadata< ValueType, IndexType >::num_subdomains](#), and [schwz::Settings::overlap](#).

```

1368 {
1369     using vec_vtype = gko::matrix::Dense<ValueType>;
1370     auto one = gko::initialize<gko::matrix::Dense<ValueType>>(
1371         {1.0}, settings.executor);
1372     auto neg_one = gko::initialize<gko::matrix::Dense<ValueType>>(
1373         {-1.0}, settings.executor);
1374     auto local_size_x = metadata.local_size_x;
1375     local_solution->copy_from(local_rhs.get());
1376     if (metadata.num_subdomains > 1 && settings.overlap > 0) {
1377         auto temp_solution = vec_vtype::create(
1378             settings.executor, local_solution->get_size(),
1379             gko::Array<ValueType>::view(settings.executor,
1380                 local_solution->get_size()[0],
1381                 global_solution->get_values()),
1382             1);
1383         interface_matrix->apply(neg_one.get(), temp_solution.get(), one.get(),
1384             local_solution.get());
1385     }
1386 }
```

The documentation for this class was generated from the following files:

- [restricted_schwarz.hpp](#) (1bdb6b)
- [/home/runner/work/schwarz-lib/schwarz-lib/source/restricted_schwarz.cpp](#) (9814c51)

7.17 UmfpackError Class Reference

[UmfpackError](#) is thrown when a METIS routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [UmfpackError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a METIS error.

7.17.1 Detailed Description

[UmfpackError](#) is thrown when a METIS routine throws a non-zero error code.

7.17.2 Constructor & Destructor Documentation

7.17.2.1 UmfpackError()

```
UmfpackError::UmfpackError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]
```

Initializes a METIS error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the METIS routine that failed
<i>error_code</i>	The resulting METIS error code

```
205         : Error(file, line, func + ": " + get_error(error_code))
206     {}
```

The documentation for this class was generated from the following files:

- exception.hpp (35a1195)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (35a1195)

7.18 schwz::Utils< ValueType, IndexType > Struct Template Reference

The utilities class which provides some checks and basic utilities.

```
#include <utils.hpp>
```

7.18.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
struct schwz::Utils< ValueType, IndexType >
```

The utilities class which provides some checks and basic utilities.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Utils

The documentation for this struct was generated from the following files:

- `utils.hpp` (1cd0e3b)
- `/home/runner/work/schwarz-lib/schwarz-lib/source/utils.cpp` (f366659)

Index

- BadDimension, [21](#)
 - BadDimension, [21](#)
- Communicate, [11](#)
- CudaError, [31](#)
 - CudaError, [31](#)
- CusparsError, [32](#)
 - CusparsError, [32](#)
- enable_logging
 - schwz::Settings, [53](#)
- exchange_boundary
 - schwz::Communicate, [28](#)
 - schwz::SolverRAS, [56](#)
- explicit_laplacian
 - schwz::Settings, [53](#)
- generate_dipole_rhs
 - schwz::Initialize, [34](#)
- generate_rhs
 - schwz::Initialize, [35](#)
- generate_sin_rhs
 - schwz::Initialize, [35](#)
- global_get
 - schwz::Communicate::comm_struct, [25](#)
- global_put
 - schwz::Communicate::comm_struct, [25](#)
- Initialization, [12](#)
- is_local_neighbor
 - schwz::Communicate::comm_struct, [25](#)
- local_get
 - schwz::Communicate::comm_struct, [26](#)
- local_put
 - schwz::Communicate::comm_struct, [26](#)
- local_solver_tolerance
 - schwz::Metadata, [43](#)
- local_to_global_vector
 - schwz::Communicate, [28](#)
- MetisError, [43](#)
 - MetisError, [44](#)
- naturally_ordered_factor
 - schwz::Settings, [53](#)
- norm_type
 - schwz::Settings, [54](#)
- partition
 - schwz::Initialize, [36](#)
- print_matrix
 - schwz::SchwarzBase, [47](#)
- print_vector
 - schwz::SchwarzBase, [47](#)
- ProcessTopology, [17](#)
- remote_get
 - schwz::Communicate::comm_struct, [26](#)
- remote_put
 - schwz::Communicate::comm_struct, [26](#)
- run
 - schwz::SchwarzBase, [48](#)
- Schwarz Class, [13](#)
- SchwarzBase
 - schwz::SchwarzBase, [46](#)
- schwz, [17](#)
- schwz::CommHelpers, [18](#)
- schwz::Communicate
 - exchange_boundary, [28](#)
 - local_to_global_vector, [28](#)
 - setup_windows, [29](#)
 - update_boundary, [30](#)
- schwz::Communicate< ValueType, IndexType, Mixed↔ValueType >, [27](#)
- schwz::Communicate< ValueType, IndexType, Mixed↔ValueType >::comm_struct, [23](#)
- schwz::Communicate::comm_struct
 - global_get, [25](#)
 - global_put, [25](#)
 - is_local_neighbor, [25](#)
 - local_get, [26](#)
 - local_put, [26](#)
 - remote_get, [26](#)
 - remote_put, [26](#)
- schwz::Initialize
 - generate_dipole_rhs, [34](#)
 - generate_rhs, [35](#)
 - generate_sin_rhs, [35](#)
 - partition, [36](#)
 - setup_global_matrix, [37](#)
 - setup_local_matrices, [38](#)
 - setup_vectors, [39](#)
- schwz::Initialize< ValueType, IndexType >, [33](#)
- schwz::Metadata
 - local_solver_tolerance, [43](#)
 - tolerance, [43](#)
- schwz::Metadata< ValueType, IndexType >, [40](#)
- schwz::Metadata< ValueType, IndexType >::post_↔process_data, [44](#)

- schwz::PartitionTools, [19](#)
- schwz::SchwarzBase
 - print_matrix, [47](#)
 - print_vector, [47](#)
 - run, [48](#)
 - SchwarzBase, [46](#)
- schwz::SchwarzBase< ValueType, IndexType, Mixed↔
 - ValueType >, [45](#)
- schwz::Settings, [51](#)
 - enable_logging, [53](#)
 - explicit_laplacian, [53](#)
 - naturally_ordered_factor, [53](#)
 - norm_type, [54](#)
 - thres_type, [54](#)
- schwz::Settings::comm_settings, [22](#)
- schwz::Settings::convergence_settings, [30](#)
- schwz::Solve< ValueType, IndexType, MixedValueType
 - >, [54](#)
- schwz::SolverRAS< ValueType, IndexType, Mixed↔
 - ValueType >, [55](#)
- schwz::SolverRAS
 - exchange_boundary, [56](#)
 - setup_local_matrices, [57](#)
 - setup_windows, [61](#)
 - SolverRAS, [56](#)
 - update_boundary, [63](#)
- schwz::SolverTools, [19](#)
- schwz::Utils< ValueType, IndexType >, [65](#)
- schwz::conv_tools, [18](#)
- schwz::device_guard, [33](#)
- setup_global_matrix
 - schwz::Initialize, [37](#)
- setup_local_matrices
 - schwz::Initialize, [38](#)
 - schwz::SolverRAS, [57](#)
- setup_vectors
 - schwz::Initialize, [39](#)
- setup_windows
 - schwz::Communicate, [29](#)
 - schwz::SolverRAS, [61](#)
- Solve, [14](#)
- SolverRAS
 - schwz::SolverRAS, [56](#)
- thres_type
 - schwz::Settings, [54](#)
- tolerance
 - schwz::Metadata, [43](#)
- UmfpackError, [64](#)
 - UmfpackError, [65](#)
- update_boundary
 - schwz::Communicate, [30](#)
 - schwz::SolverRAS, [63](#)
- Utils, [15](#)