

schwz

Generated automatically from develop

Generated by Doxygen 1.8.13

Contents

1	Main Page	1
2	# Installation Instructions	3
3	Testing Instructions	5
4	Benchmarking.	7
5	Module Documentation	9
5.1	Communicate	9
5.1.1	Detailed Description	9
5.2	Initialization	10
5.2.1	Detailed Description	10
5.3	Schwarz Class	11
5.3.1	Detailed Description	11
5.4	Solve	12
5.4.1	Detailed Description	12
5.5	Utils	13
5.5.1	Detailed Description	13
6	Namespace Documentation	15
6.1	ProcessTopology Namespace Reference	15
6.1.1	Detailed Description	15
6.2	schwz Namespace Reference	15
6.2.1	Detailed Description	16
6.3	schwz::CommHelpers Namespace Reference	16
6.3.1	Detailed Description	16
6.4	schwz::conv_tools Namespace Reference	16
6.4.1	Detailed Description	16
6.5	schwz::PartitionTools Namespace Reference	17
6.5.1	Detailed Description	17
6.6	schwz::SolverTools Namespace Reference	17
6.6.1	Detailed Description	17

7	Class Documentation	19
7.1	BadDimension Class Reference	19
7.1.1	Detailed Description	19
7.1.2	Constructor & Destructor Documentation	19
7.1.2.1	BadDimension()	19
7.2	schwz::Settings::comm_settings Struct Reference	20
7.2.1	Detailed Description	21
7.3	schwz::Communicate< ValueType, IndexType >::comm_struct Struct Reference	21
7.3.1	Detailed Description	22
7.3.2	Member Data Documentation	22
7.3.2.1	global_get	22
7.3.2.2	global_put	23
7.3.2.3	is_local_neighbor	23
7.3.2.4	local_get	23
7.3.2.5	local_put	23
7.3.2.6	remote_get	24
7.3.2.7	remote_put	24
7.4	schwz::Communicate< ValueType, IndexType > Class Template Reference	24
7.4.1	Detailed Description	25
7.4.2	Member Function Documentation	25
7.4.2.1	exchange_boundary()	25
7.4.2.2	local_to_global_vector()	26
7.4.2.3	setup_windows()	27
7.4.2.4	update_boundary()	27
7.5	schwz::Settings::convergence_settings Struct Reference	28
7.5.1	Detailed Description	28
7.6	CudaError Class Reference	28
7.6.1	Detailed Description	28
7.6.2	Constructor & Destructor Documentation	28
7.6.2.1	CudaError()	28

7.7	CusparsedError Class Reference	29
7.7.1	Detailed Description	29
7.7.2	Constructor & Destructor Documentation	29
7.7.2.1	CusparsedError()	29
7.8	schwz::device_guard Class Reference	30
7.8.1	Detailed Description	30
7.9	schwz::Initialize< ValueType, IndexType > Class Template Reference	30
7.9.1	Detailed Description	31
7.9.2	Member Function Documentation	31
7.9.2.1	generate_rhs()	32
7.9.2.2	partition()	32
7.9.2.3	setup_global_matrix()	33
7.9.2.4	setup_local_matrices()	34
7.9.2.5	setup_vectors()	35
7.10	schwz::Metadata< ValueType, IndexType > Struct Template Reference	36
7.10.1	Detailed Description	38
7.10.2	Member Data Documentation	38
7.10.2.1	local_solver_tolerance	38
7.10.2.2	tolerance	38
7.11	MetisError Class Reference	38
7.11.1	Detailed Description	39
7.11.2	Constructor & Destructor Documentation	39
7.11.2.1	MetisError()	39
7.12	schwz::Metadata< ValueType, IndexType >::post_process_data Struct Reference	39
7.12.1	Detailed Description	40
7.13	schwz::SchwarzBase< ValueType, IndexType > Class Template Reference	40
7.13.1	Detailed Description	41
7.13.2	Constructor & Destructor Documentation	41
7.13.2.1	SchwarzBase()	41
7.13.3	Member Function Documentation	42

7.13.3.1	print_matrix()	42
7.13.3.2	print_vector()	43
7.13.3.3	run()	43
7.14	schwz::Settings Struct Reference	45
7.14.1	Detailed Description	46
7.14.2	Member Data Documentation	47
7.14.2.1	explicit_laplacian	47
7.14.2.2	naturally_ordered_factor	47
7.15	schwz::Solve< ValueType, IndexType > Class Template Reference	47
7.15.1	Detailed Description	47
7.16	schwz::SolverRAS< ValueType, IndexType > Class Template Reference	48
7.16.1	Detailed Description	48
7.16.2	Constructor & Destructor Documentation	49
7.16.2.1	SolverRAS()	49
7.16.3	Member Function Documentation	49
7.16.3.1	exchange_boundary()	49
7.16.3.2	setup_local_matrices()	50
7.16.3.3	setup_windows()	53
7.16.3.4	update_boundary()	55
7.17	UmfpackError Class Reference	56
7.17.1	Detailed Description	57
7.17.2	Constructor & Destructor Documentation	57
7.17.2.1	UmfpackError()	57
7.18	schwz::Utils< ValueType, IndexType > Struct Template Reference	57
7.18.1	Detailed Description	58
Index		61

Chapter 1

Main Page

This is the main page for the Schwarz library pdf documentation. The repository is hosted on [github](#). Documentation on aspects such as the build system, can be found at the [# Installation Instructions](#) page.

Modules

The structure of the Schwarz Library code is divided into different [modules](#) :

- [Initialization](#) : Handles the initialization of the problem and the solver.
- [Communicate](#) : Handles the communication.
- [Solve](#) : Handles the local solution and the convergence detection.
- [Schwarz Class](#) : The Classes related to the Schwarz solvers.
- [Utils](#) : Provides some basic utilities.

Chapter 2

Installation Instructions

Building

Use the standard cmake build procedure:

```
mkdir build; cd build
cmake -G "Unix Makefiles" [OPTIONS] .. && make
```

Replace [OPTIONS] with desired cmake options for your build. The library adds the following additional switches to control what is being built:

- `-DSCHWARZ_BUILD_BENCHMARKING={ON, OFF}` Builds some example benchmarks. Default is ON
- `-DSCHWARZ_BUILD_METIS={ON, OFF}` Builds with support for the METIS partitioner. User needs to provide the path to the installation of the METIS library in `METIS_DIR`, preferably as an environment variable. Default is OFF
- `-DSCHWARZ_BUILD_CHOLMOD={ON, OFF}` Builds with support for the CHOLMOD module from the Suitesparse library. User needs to set an environment variable `CHOLMOD_DIR` to the path containing the CHOLMOD installation. Default is OFF
- `-DSCHWARZ_BUILD_CUDA={ON, OFF}` Builds with CUDA support. Though Ginkgo provides most of the required CUDA support, we do need to link to CUDA for explicit setting of GPU affinities, some custom gather and scatter operations. Default is OFF.
- `-DSCHWARZ_BUILD_CLANG_TIDY={ON, OFF}` Builds with support for clang-tidy Default is OFF
- `-DSCHWARZ_BUILD DEAL_II={ON, OFF}` Builds with support for the finite element library deal.ii Default is OFF
- `-DSCHWARZ_WITH_HWLOC={ON, OFF}` Builds with support for the hardware locality library used for binding hardware. hwloc is distributed as a part of the Open-MPI project. Default is ON
- `-DSCHWARZ_DEVEL_TOOLS={ON, OFF}` Builds with some developer tools support. Default is ON. In particular uses `git-cmake-format` to automatically format the source files with `clang-format`.

Tips

- If you are having CUDA problems and you are not using CUDA, then feel free to switch the CUDA module off with `-DSCHWARZ_BUILD_CUDA=off`.
- Installing CHOLMOD can be a bit annoying. TODO add some details on fixing Suitesparse compilation.
- When doing merge commits it is possible that make format does not work. You can run `cmake -DSCHWARZ_DEVEL_TOOLS=OFF ..` to temporarily switch off the formatting. Please switch it on again when committing normally.

Chapter 3

Testing Instructions

Chapter 4

Benchmarking.

Benchmark example 1.

Poisson solver using Restricted Additive Schwarz with overlap.

The flag `-DSCHWARZ_BUILD_BENCHMARKING` (default ON) enables the example and benchmarking snippets. The following command line options are available for this example. This is setup using `gflags`.

The executable is run in the following fashion:

```
“sh [MPI_COMMAND] [MPI_OPTIONS]
```


Chapter 5

Module Documentation

5.1 Communicate

A module dedicated to the Communication interface in schwarz-lib.

Namespaces

- [schwz::CommHelpers](#)
The CommHelper namespace .
- [ProcessTopology](#)
The ProcessTopology namespace .

Classes

- class [schwz::Communicate< ValueType, IndexType >](#)
The communication class that provides the methods for the communication between the subdomains.
- struct [schwz::Metadata< ValueType, IndexType >](#)
The solver metadata struct.

5.1.1 Detailed Description

A module dedicated to the Communication interface in schwarz-lib.

5.2 Initialization

A module dedicated to the initialization and setup and usage of the solvers in schwarz-lib.

Namespaces

- [schwz::PartitionTools](#)
The [PartitionTools](#) namespace .
- [ProcessTopology](#)
The [ProcessTopology](#) namespace .

Classes

- class [schwz::device_guard](#)
This class defines a device guard for the cuda functions and the cuda module.
- class [schwz::Initialize< ValueType, IndexType >](#)
The initialization class that provides methods for initialization of the solver.
- struct [schwz::Settings](#)
The struct that contains the solver settings and the parameters to be set by the user.
- struct [schwz::Metadata< ValueType, IndexType >](#)
The solver metadata struct.

5.2.1 Detailed Description

A module dedicated to the initialization and setup and usage of the solvers in schwarz-lib.

5.3 Schwarz Class

A module dedicated to the Schwarz solver classes in schwarz-lib.

Classes

- class `schwz::SolverRAS< ValueType, IndexType >`
An implementation of the solver interface using the RAS solver.
- class `schwz::SchwarzBase< ValueType, IndexType >`
The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.

5.3.1 Detailed Description

A module dedicated to the Schwarz solver classes in schwarz-lib.

5.4 Solve

A module dedicated to the solvers including local solution and convergence detection in schwarz-lib.

Namespaces

- [schwz::conv_tools](#)
The [conv_tools](#) namespace .
- [schwz::SolverTools](#)
The [SolverTools](#) namespace .

Classes

- struct [schwz::Metadata< ValueType, IndexType >](#)
The solver metadata struct.
- class [schwz::Solve< ValueType, IndexType >](#)
The Solver class the provides the solver and the convergence checking methods.

5.4.1 Detailed Description

A module dedicated to the solvers including local solution and convergence detection in schwarz-lib.

5.5 Utils

A module dedicated to the utilities in schwarz-lib.

Classes

- struct `schwz::Utils< ValueType, IndexType >`
The utilities class which provides some checks and basic utilities.

5.5.1 Detailed Description

A module dedicated to the utilities in schwarz-lib.

Chapter 6

Namespace Documentation

6.1 ProcessTopology Namespace Reference

The [ProcessTopology](#) namespace .

6.1.1 Detailed Description

The [ProcessTopology](#) namespace .

proc_topo

6.2 schwz Namespace Reference

The Schwarz wrappers namespace.

Namespaces

- [CommHelpers](#)
The CommHelper namespace .
- [conv_tools](#)
The conv_tools namespace .
- [PartitionTools](#)
The PartitionTools namespace .
- [SolverTools](#)
The SolverTools namespace .

Classes

- class [Communicate](#)
The communication class that provides the methods for the communication between the subdomains.
- class [device_guard](#)
This class defines a device guard for the cuda functions and the cuda module.
- class [Initialize](#)
The initialization class that provides methods for initialization of the solver.
- struct [Metadata](#)
The solver metadata struct.
- class [SchwarzBase](#)
The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.
- struct [Settings](#)
The struct that contains the solver settings and the parameters to be set by the user.
- class [Solve](#)
The Solver class the provides the solver and the convergence checking methods.
- class [SolverRAS](#)
An implementation of the solver interface using the RAS solver.
- struct [Utils](#)
The utilities class which provides some checks and basic utilities.

6.2.1 Detailed Description

The Schwarz wrappers namespace.

6.3 schwz::CommHelpers Namespace Reference

The CommHelper namespace .

6.3.1 Detailed Description

The CommHelper namespace .

comm_helpers

6.4 schwz::conv_tools Namespace Reference

The [conv_tools](#) namespace .

6.4.1 Detailed Description

The [conv_tools](#) namespace .

[conv_tools](#)

6.5 schwz::PartitionTools Namespace Reference

The [PartitionTools](#) namespace .

6.5.1 Detailed Description

The [PartitionTools](#) namespace .

part_tools

6.6 schwz::SolverTools Namespace Reference

The [SolverTools](#) namespace .

6.6.1 Detailed Description

The [SolverTools](#) namespace .

solver_tools

Chapter 7

Class Documentation

7.1 BadDimension Class Reference

[BadDimension](#) is thrown if an operation is being applied to a LinOp with bad dimensions.

```
#include <exception.hpp>
```

Public Member Functions

- [BadDimension](#) (const std::string &file, int line, const std::string &func, const std::string &op_name, std::size_t op_num_rows, std::size_t op_num_cols, const std::string &clarification)
Initializes a bad dimension error.

7.1.1 Detailed Description

[BadDimension](#) is thrown if an operation is being applied to a LinOp with bad dimensions.

7.1.2 Constructor & Destructor Documentation

7.1.2.1 BadDimension()

```
BadDimension::BadDimension (
    const std::string & file,
    int line,
    const std::string & func,
    const std::string & op_name,
    std::size_t op_num_rows,
    std::size_t op_num_cols,
    const std::string & clarification ) [inline]
```

Initializes a bad dimension error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The function name where the error occurred
<i>op_name</i>	The name of the operator
<i>op_num_rows</i>	The row dimension of the operator
<i>op_num_cols</i>	The column dimension of the operator
<i>clarification</i>	An additional message further describing the error

```

115         : Error(file, line,
116               func + ": Object " + op_name + " has dimensions [" +
117                   std::to_string(op_num_rows) + " x " +
118                   std::to_string(op_num_cols) + "]: " + clarification)
119     {}

```

The documentation for this class was generated from the following file:

- exception.hpp (04a42d4)

7.2 schwz::Settings::comm_settings Struct Reference

The settings for the various available communication paradigms.

```
#include <settings.hpp>
```

Public Attributes

- bool [enable_onesided](#) = false
Enable one-sided communication.
- bool [enable_overlap](#) = false
Enable explicit overlap between communication and computation.
- bool [enable_put](#) = false
Put the data to the window using MPI_Put rather than get.
- bool [enable_get](#) = true
Get the data to the window using MPI_Get rather than put.
- bool [enable_one_by_one](#) = false
Push each element separately directly into the buffer.
- bool [enable_flush_local](#) = false
Use local flush.
- bool [enable_flush_all](#) = true
Use flush all.
- bool [enable_lock_local](#) = false
Use local locks.
- bool [enable_lock_all](#) = true
Use lock all.

7.2.1 Detailed Description

The settings for the various available communication paradigms.

The documentation for this struct was generated from the following file:

- settings.hpp (04a42d4)

7.3 schwz::Communicate< ValueType, IndexType >::comm_struct Struct Reference

The communication struct used to store the communication data.

```
#include <communicate.hpp>
```

Public Attributes

- int [num_neighbors_in](#)
The number of neighbors this subdomain has to receive data from.
- int [num_neighbors_out](#)
The number of neighbors this subdomain has to send data to.
- std::shared_ptr< gko::Array< IndexType > > [neighbors_in](#)
The neighbors this subdomain has to receive data from.
- std::shared_ptr< gko::Array< IndexType > > [neighbors_out](#)
The neighbors this subdomain has to send data to.
- std::vector< bool > [is_local_neighbor](#)
The bool vector which is true if the neighbors of a subdomain are in one node.
- int [local_num_neighbors_in](#)
The number of neighbors this subdomain has to receive data from.
- int [local_num_neighbors_out](#)
The number of neighbors this subdomain has to send data to.
- std::shared_ptr< gko::Array< IndexType > > [local_neighbors_in](#)
The neighbors this subdomain has to receive data from.
- std::shared_ptr< gko::Array< IndexType > > [local_neighbors_out](#)
The neighbors this subdomain has to send data to.
- std::shared_ptr< gko::Array< IndexType * > > [global_put](#)
The array containing the number of elements that each subdomain sends from the other.
- std::shared_ptr< gko::Array< IndexType * > > [local_put](#)
The array containing the number of elements that each subdomain sends from the other.
- std::shared_ptr< gko::Array< IndexType * > > [remote_put](#)
The array containing the number of elements that each subdomain sends from the other.
- std::shared_ptr< gko::Array< IndexType * > > [global_get](#)
The array containing the number of elements that each subdomain gets from the other.
- std::shared_ptr< gko::Array< IndexType * > > [local_get](#)
The array containing the number of elements that each subdomain gets from the other.
- std::shared_ptr< gko::Array< IndexType * > > [remote_get](#)
The array containing the number of elements that each subdomain gets from the other.
- std::shared_ptr< gko::Array< IndexType > > [window_ids](#)
The RDMA window ids.

- `std::shared_ptr< gko::Array< IndexType > >` [windows_from](#)
The RDMA window ids to receive data from.
- `std::shared_ptr< gko::Array< IndexType > >` [windows_to](#)
The RDMA window ids to send data to.
- `std::shared_ptr< gko::Array< MPI_Request > >` [put_request](#)
The put request array.
- `std::shared_ptr< gko::Array< MPI_Request > >` [get_request](#)
The get request array.
- `std::shared_ptr< gko::matrix::Dense< ValueType > >` [send_buffer](#)
The send buffer used for the actual communication for both one-sided and two-sided.
- `std::shared_ptr< gko::matrix::Dense< ValueType > >` [recv_buffer](#)
The recv buffer used for the actual communication for both one-sided and two-sided.
- `std::shared_ptr< gko::Array< IndexType > >` [get_displacements](#)
The displacements for the receiving of the buffer.
- `std::shared_ptr< gko::Array< IndexType > >` [put_displacements](#)
The displacements for the sending of the buffer.
- `MPI_Win` [window_recv_buffer](#)
The RDMA window for the recv buffer.
- `MPI_Win` [window_send_buffer](#)
The RDMA window for the send buffer.
- `MPI_Win` [window_x](#)
The RDMA window for the solution vector.

7.3.1 Detailed Description

```
template<typename ValueType, typename IndexType>
struct schwz::Communicate< ValueType, IndexType >::comm_struct
```

The communication struct used to store the communication data.

7.3.2 Member Data Documentation

7.3.2.1 global_get

```
template<typename ValueType , typename IndexType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType >::comm←
\_struct::global\_get
```

The array containing the number of elements that each subdomain gets from the other.

For example. `global_get[p][0]` contains the overall number of elements to be received to subdomain `p` and `global←
_put[p][i]` contains the index of the solution vector to be received from subdomain `p`.

Referenced by `schwz::SchwarzBase< ValueType, IndexType >::initialize()`, `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

7.3.2.2 global_put

```
template<typename ValueType , typename IndexType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType >::comm←
_struct::global_put
```

The array containing the number of elements that each subdomain sends from the other.

For example. `global_put[p][0]` contains the overall number of elements to be sent to subdomain `p` and `global_put[p][i]` contains the index of the solution vector to be sent to subdomain `p`.

Referenced by `schwz::SchwarzBase< ValueType, IndexType >::initialize()`, `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

7.3.2.3 is_local_neighbor

```
template<typename ValueType , typename IndexType >
std::vector<bool> schwz::Communicate< ValueType, IndexType >::comm_struct::is_local_neighbor
```

The bool vector which is true if the neighbors of a subdomain are in one node.

Referenced by `schwz::SchwarzBase< ValueType, IndexType >::initialize()`, `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

7.3.2.4 local_get

```
template<typename ValueType , typename IndexType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType >::comm←
_struct::local_get
```

The array containing the number of elements that each subdomain gets from the other.

For example. `global_get[p][0]` contains the overall number of elements to be received to subdomain `p` and `global←_put[p][i]` contains the index of the solution vector to be received from subdomain `p`.

Referenced by `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

7.3.2.5 local_put

```
template<typename ValueType , typename IndexType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType >::comm←
_struct::local_put
```

The array containing the number of elements that each subdomain sends from the other.

For example. `global_put[p][0]` contains the overall number of elements to be sent to subdomain `p` and `global_put[p][i]` contains the index of the solution vector to be sent to subdomain `p`.

Referenced by `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

7.3.2.6 remote_get

```
template<typename ValueType , typename IndexType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType >::comm←
_struct::remote_get
```

The array containing the number of elements that each subdomain gets from the other.

For example. `global_get[p][0]` contains the overall number of elements to be received to subdomain `p` and `global←_put[p][i]` contains the index of the solution vector to be received from subdomain `p`.

Referenced by `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

7.3.2.7 remote_put

```
template<typename ValueType , typename IndexType >
std::shared_ptr<gko::Array<IndexType *> > schwz::Communicate< ValueType, IndexType >::comm←
_struct::remote_put
```

The array containing the number of elements that each subdomain sends from the other.

For example. `global_put[p][0]` contains the overall number of elements to be sent to subdomain `p` and `global_put[p][i]` contains the index of the solution vector to be sent to subdomain `p`.

Referenced by `schwz::SolverRAS< ValueType, IndexType >::setup_comm_buffers()`, and `schwz::SolverRAS< ValueType, IndexType >::setup_windows()`.

The documentation for this struct was generated from the following file:

- `communicate.hpp` (04a42d4)

7.4 schwz::Communicate< ValueType, IndexType > Class Template Reference

The communication class that provides the methods for the communication between the subdomains.

```
#include <communicate.hpp>
```

Classes

- struct `comm_struct`

The communication struct used to store the communication data.

Public Member Functions

- virtual void [setup_comm_buffers](#) ()=0
Sets up the communication buffers needed for the boundary exchange.
- virtual void [setup_windows](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &main_buffer)=0
Sets up the windows needed for the asynchronous communication.
- virtual void [exchange_boundary](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_solution)=0
Exchanges the elements of the solution vector.
- void [local_to_global_vector](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, const std::shared_ptr< gko::matrix::Dense< ValueType >> &local_vector, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_vector)
Transforms data from a local vector to a global vector.
- virtual void [update_boundary](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &local_solution, const std::shared_ptr< gko::matrix::Dense< ValueType >> &local_rhs, const std::shared_ptr< gko::matrix::Dense< ValueType >> &global_solution, const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &interface_matrix)=0
Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.
- void [clear](#) ([Settings](#) &settings)
Clears the data.

7.4.1 Detailed Description

```
template<typename ValueType, typename IndexType>
class schwz::Communicate< ValueType, IndexType >
```

The communication class that provides the methods for the communication between the subdomains.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Communicate

7.4.2 Member Function Documentation

7.4.2.1 exchange_boundary()

```
template<typename ValueType , typename IndexType >
void schwz::Communicate< ValueType, IndexType >::exchange_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution ) [pure
virtual]
```

Exchanges the elements of the solution vector.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>global_solution</i>	The solution vector being exchanged between the subdomains.

Implemented in [schwz::SolverRAS< ValueType, IndexType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType >::run\(\)](#).

7.4.2.2 local_to_global_vector()

```
template<typename ValueType , typename IndexType >
void schwz::Communicate< ValueType, IndexType >::local_to_global_vector (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & local_vector,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_vector )
```

Transforms data from a local vector to a global vector.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_vector</i>	The local vector in question.
<i>global_vector</i>	The global vector in question.

```
69 {
70     using vec = gko::matrix::Dense<ValueType>;
71     auto alpha = gko::initialize<gko::matrix::Dense<ValueType>>>(
72         {1.0}, settings.executor);
73     auto temp_vector = vec::create(
74         settings.executor, gko::dim<2>(metadata.local_size, 1),
75         gko::Array<ValueType>::view(
76             settings.executor, metadata.local_size,
77             &global_vector->get_values()[metadata.first_row
78                 ->get_data()[metadata.my_rank]]),
79         1);
80
81     auto temp_vector2 = vec::create(
82         settings.executor, gko::dim<2>(metadata.local_size, 1),
83         gko::Array<ValueType>::view(settings.executor, metadata.local_size,
84             local_vector->get_values()),
85         1);
86     if (settings.convergence_settings.convergence_crit ==
87         Settings::convergence_settings::local_convergence_crit::
88             residual_based) {
89         local_vector->add_scaled(alpha.get(), temp_vector.get());
90         temp_vector->add_scaled(alpha.get(), local_vector.get());
91     } else {
92         temp_vector->copy_from(temp_vector2.get());
93     }
94 }
```


7.4.2.3 setup_windows()

```
template<typename ValueType , typename IndexType >
void schwz::Communicate< ValueType, IndexType >::setup_windows (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & main_buffer ) [pure virtual]
```

Sets up the windows needed for the asynchronous communication.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>main_buffer</i>	The main buffer being exchanged between the subdomains.

Implemented in [schwz::SolverRAS< ValueType, IndexType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType >::run\(\)](#).

7.4.2.4 update_boundary()

```
template<typename ValueType , typename IndexType >
void schwz::Communicate< ValueType, IndexType >::update_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_solution,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & local_rhs,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution,
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_↵
matrix ) [pure virtual]
```

Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_solution</i>	The local solution vector in the subdomain.
<i>local_rhs</i>	The local right hand side vector in the subdomain.
<i>global_solution</i>	The workspace solution vector.
<i>global_old_solution</i>	The global solution vector of the previous iteration.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.

Implemented in [schwz::SolverRAS< ValueType, IndexType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType >::run\(\)](#).

The documentation for this class was generated from the following files:

- [communicate.hpp](#) (04a42d4)
- [/home/runner/work/schwarz-lib/schwarz-lib/source/communicate.cpp](#) (04a42d4)

7.5 schwz::Settings::convergence_settings Struct Reference

The various convergence settings available.

```
#include <settings.hpp>
```

7.5.1 Detailed Description

The various convergence settings available.

The documentation for this struct was generated from the following file:

- [settings.hpp](#) (04a42d4)

7.6 CudaError Class Reference

[CudaError](#) is thrown when a CUDA routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [CudaError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a CUDA error.

7.6.1 Detailed Description

[CudaError](#) is thrown when a CUDA routine throws a non-zero error code.

7.6.2 Constructor & Destructor Documentation

7.6.2.1 CudaError()

```
CudaError::CudaError (  
    const std::string & file,  
    int line,  
    const std::string & func,  
    int error_code ) [inline]
```

Initializes a CUDA error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the CUDA routine that failed
<i>error_code</i>	The resulting CUDA error code

```

137         : Error(file, line, func + ": " + get_error(error_code))
138     {}

```

The documentation for this class was generated from the following files:

- exception.hpp (04a42d4)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (04a42d4)

7.7 CusparsedError Class Reference

[CusparsedError](#) is thrown when a cuSPARSE routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [CusparsedError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a cuSPARSE error.

7.7.1 Detailed Description

[CusparsedError](#) is thrown when a cuSPARSE routine throws a non-zero error code.

7.7.2 Constructor & Destructor Documentation

7.7.2.1 CusparsedError()

```

CusparsedError::CusparsedError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]

```

Initializes a cuSPARSE error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the cuSPARSE routine that failed
<i>error_code</i>	The resulting cuSPARSE error code

```

159         : Error(file, line, func + ": " + get_error(error_code))
160     {}

```

The documentation for this class was generated from the following files:

- exception.hpp (04a42d4)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (04a42d4)

7.8 schwz::device_guard Class Reference

This class defines a device guard for the cuda functions and the cuda module.

```
#include <device_guard.hpp>
```

7.8.1 Detailed Description

This class defines a device guard for the cuda functions and the cuda module.

The guard is used to make sure that the device code is run on the correct cuda device, when run with multiple devices. The class records the current device id and uses `cudaSetDevice` to set the device id to the one being passed in. After the scope has been exited, the destructor sets the `device_id` back to the one before entering the scope.

The documentation for this class was generated from the following file:

- device_guard.hpp (04a42d4)

7.9 schwz::Initialize< ValueType, IndexType > Class Template Reference

The initialization class that provides methods for initialization of the solver.

```
#include <initialization.hpp>
```

Public Member Functions

- void [generate_rhs](#) (std::vector< ValueType > &rhs)
Generates the right hand side vector.
- void [setup_global_matrix](#) (const std::string &filename, const gko::size_type &[oned_laplacian_size](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &global_matrix)
Generates the 2D global laplacian matrix.
- void [partition](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &global_matrix, std::vector< unsigned int > &[partition_indices](#))
The partitioning function.
- void [setup_vectors](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::vector< ValueType > &rhs, std::shared_ptr< gko::matrix::Dense< ValueType >> &local_rhs, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_rhs, std::shared_ptr< gko::matrix::Dense< ValueType >> &local_solution, std::shared_ptr< gko::matrix::Dense< ValueType >> &global_solution)
Setup the vectors with default values and allocate memory if not allocated.
- virtual void [setup_local_matrices](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata, std::vector< unsigned int > &[partition_indices](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &global_matrix, std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &local_matrix, std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &interface_matrix)=0
Sets up the local and the interface matrices from the global matrix and the partition indices.

Public Attributes

- std::vector< unsigned int > [partition_indices](#)
The partition indices containing the subdomains to which each row(vertex) of the matrix(graph) belongs to.
- std::vector< unsigned int > [cell_weights](#)
The cell weights for the partition algorithm.

Additional Inherited Members

7.9.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
class schwz::Initialize< ValueType, IndexType >
```

The initialization class that provides methods for initialization of the solver.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Initialization

7.9.2 Member Function Documentation

7.9.2.1 generate_rhs()

```
template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::generate_rhs (
    std::vector< ValueType > & rhs )
```

Generates the right hand side vector.

Parameters

<i>rhs</i>	The rhs vector.
------------	-----------------

References `schwz::Initialize< ValueType, IndexType >::setup_global_matrix()`.

Referenced by `schwz::SchwarzBase< ValueType, IndexType >::initialize()`.

```
81 {
82     std::uniform_real_distribution<double> unif(0.0, 1.0);
83     std::default_random_engine engine;
84     for (gko::size_type i = 0; i < rhs.size(); ++i) {
85         rhs[i] = unif(engine);
86     }
87 }
```

7.9.2.2 partition()

```
template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::partition (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_↵
matrix,
    std::vector< unsigned int > & partition_indices )
```

The partitioning function.

Allows the partition of the global matrix depending with METIS and a regular 1D decomposition.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>global_matrix</i>	The global matrix.
<i>partition_indices</i>	The partition indices [OUTPUT].

References `schwz::Metadata< ValueType, IndexType >::global_size`, `schwz::Metadata< ValueType, IndexType >::my_rank`, `schwz::Metadata< ValueType, IndexType >::num_subdomains`, and `schwz::Settings::write_debug_↵` out.

Referenced by `schwz::SchwarzBase< ValueType, IndexType >::initialize()`.

```

279 {
280     partition_indices.resize(metadata.global_size);
281     if (metadata.my_rank == 0) {
282         auto partition_settings =
283             (Settings::partition_settings::partition_zoltan |
284              Settings::partition_settings::partition_metis |
285              Settings::partition_settings::partition_regular |
286              Settings::partition_settings::partition_regular2d |
287              Settings::partition_settings::partition_custom) &
288             settings.partition;
289
290         if (partition_settings ==
291             Settings::partition_settings::partition_zoltan) {
292             SCHWARZ_NOT_IMPLEMENTED;
293         } else if (partition_settings ==
294             Settings::partition_settings::partition_metis) {
295             if (metadata.my_rank == 0) {
296                 std::cout << " METIS partition" << std::endl;
297             }
298             PartitionTools::PartitionMetis(
299                 settings, global_matrix, this->cell_weights,
300                 metadata.num_subdomains, partition_indices);
301         } else if (partition_settings ==
302             Settings::partition_settings::partition_regular) {
303             if (metadata.my_rank == 0) {
304                 std::cout << " Regular 1D partition" << std::endl;
305             }
306             PartitionTools::PartitionRegular(
307                 global_matrix, metadata.num_subdomains, partition_indices);
308         } else if (partition_settings ==
309             Settings::partition_settings::partition_regular2d) {
310             if (metadata.my_rank == 0) {
311                 std::cout << " Regular 2D partition" << std::endl;
312             }
313             PartitionTools::PartitionRegular2D(
314                 global_matrix, settings.write_debug_out,
315                 metadata.num_subdomains, partition_indices);
316         } else if (partition_settings ==
317             Settings::partition_settings::partition_custom) {
318             // User partitions mesh manually
319             SCHWARZ_NOT_IMPLEMENTED;
320         } else {
321             SCHWARZ_NOT_IMPLEMENTED;
322         }
323     }
324 }

```

7.9.2.3 setup_global_matrix()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::setup_global_matrix (
    const std::string & filename,
    const gko::size_type & oned_laplacian_size,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_matrix )

```

Generates the 2D global laplacian matrix.

Parameters

<i>oned_laplacian_size</i>	The size of the one d laplacian grid.
<i>global_matrix</i>	The global matrix.

Referenced by schwz::Initialize< ValueType, IndexType >::generate_rhs(), and schwz::SchwarzBase< ValueType, IndexType >::initialize().

```

198 {
199     using index_type = IndexType;

```

```

200     using value_type = ValueType;
201     using mtx = gko::matrix::Csr<value_type, index_type>;
202     if (settings.matrix_filename != "null") {
203         auto input_file = std::ifstream(filename, std::ios::in);
204         if (!input_file) {
205             std::cerr << "Could not find the file \"" << filename
206                 << "\", which is required for this test.\n";
207         }
208         global_matrix =
209             gko::read<mtx>(input_file, settings.executor->get_master());
210         global_matrix->sort_by_column_index();
211         std::cout << "Matrix from file " << filename << std::endl;
212     } else if (settings.matrix_filename == "null" &&
213               settings.explicit_laplacian) {
214         std::cout << "Laplacian 2D Matrix (generated in house) " << std::endl;
215         gko::size_type global_size = oned_laplacian_size *
216             oned_laplacian_size;
217         global_matrix = mtx::create(settings.executor->get_master(),
218             gko::dim<2>(global_size), 5 * global_size);
219         value_type *values = global_matrix->get_values();
220         index_type *row_ptrs = global_matrix->get_row_ptrs();
221         index_type *col_idxs = global_matrix->get_col_idxs();
222
223         std::vector<gko::size_type> exclusion_set;
224
225         std::map<IndexType, ValueType> stencil_map = {
226             {-oned_laplacian_size, -1}, {-1, -1}, {0, 4}, {1, -1},
227             {oned_laplacian_size, -1},
228         };
229         for (auto i = 2; i < global_size; ++i) {
230             gko::size_type index = (i - 1) * oned_laplacian_size;
231             if (index * index < global_size * global_size) {
232                 exclusion_set.push_back(
233                     linearize_index(index, index - 1, global_size));
234                 exclusion_set.push_back(
235                     linearize_index(index - 1, index, global_size));
236             }
237         }
238
239         std::sort(exclusion_set.begin(),
240             exclusion_set.begin() + exclusion_set.size());
241
242         IndexType pos = 0;
243         IndexType col_idx = 0;
244         row_ptrs[0] = pos;
245         gko::size_type cur_idx = 0;
246         for (IndexType i = 0; i < global_size; ++i) {
247             for (auto ofs : stencil_map) {
248                 auto in_exclusion_flag =
249                     (exclusion_set[cur_idx] ==
250                     linearize_index(i, i + ofs.first, global_size));
251                 if (0 <= i + ofs.first && i + ofs.first < global_size &&
252                     !in_exclusion_flag) {
253                     values[pos] = ofs.second;
254                     col_idxs[pos] = i + ofs.first;
255                     ++pos;
256                 }
257                 if (in_exclusion_flag) {
258                     cur_idx++;
259                 }
260                 col_idx = row_ptrs[i + 1] - pos;
261             }
262             row_ptrs[i + 1] = pos;
263         }
264     } else {
265         std::cerr << " Need to provide a matrix or enable the default "
266             "laplacian matrix."
267             << std::endl;
268         std::exit(-1);
269     }
270 }

```

7.9.2.4 setup_local_matrices()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::setup_local_matrices (

```



```

    Settings & settings,
    Metadata< ValueType, IndexType > & metadata,
    std::vector< unsigned int > & partition_indices,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & local_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_matrix )
[pure virtual]

```

Sets up the local and the interface matrices from the global matrix and the partition indices.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>partition_indices</i>	The array containing the partition indices.
<i>global_matrix</i>	The global system matrix.
<i>local_matrix</i>	The local system matrix.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.
<i>local_perm</i>	The local permutation, obtained through RCM or METIS.

Implemented in [schwz::SolverRAS< ValueType, IndexType >](#).

Referenced by [schwz::SchwarzBase< ValueType, IndexType >::initialize\(\)](#).

7.9.2.5 setup_vectors()

```

template<typename ValueType , typename IndexType >
void schwz::Initialize< ValueType, IndexType >::setup_vectors (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::vector< ValueType > & rhs,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_rhs,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_rhs,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_solution,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution )

```

Setup the vectors with default values and allocate mameory if not allocated.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_rhs</i>	The local right hand side vector in the subdomain.
<i>global_rhs</i>	The global right hand side vector.
<i>local_solution</i>	The local solution vector in the subdomain.
<i>global_solution</i>	The global solution vector.

References [schwz::Settings::executor](#), [schwz::Metadata< ValueType, IndexType >::first_row](#), [schwz::Metadata<](#)

`ValueType`, `IndexType >::global_size`, `schwz::Metadata< ValueType, IndexType >::local_size_x`, and `schwz::Metadata< ValueType, IndexType >::my_rank`.

Referenced by `schwz::SchwarzBase< ValueType, IndexType >::initialize()`.

```

335 {
336     using vec = gko::matrix::Dense<ValueType>;
337     auto my_rank = metadata.my_rank;
338     auto first_row = metadata.first_row->get_data()[my_rank];
339
340     // Copy the global rhs vector to the required executor.
341     gko::Array<ValueType> temp_rhs(settings.executor->get_master(), rhs.begin(),
342                                   rhs.end());
343     global_rhs = vec::create(settings.executor,
344                             gko::dim<2>{metadata.global_size, 1}, temp_rhs, 1);
345     global_solution = vec::create(settings.executor->get_master(),
346                                  gko::dim<2>(metadata.global_size, 1));
347
348     local_rhs =
349         vec::create(settings.executor, gko::dim<2>(metadata.local_size_x, 1));
350     // Extract the local rhs from the global rhs. Also takes into account the
351     // overlap.
352     SolverTools::extract_local_vector(settings, metadata, local_rhs.get(),
353                                       global_rhs.get(), first_row);
354
355     local_solution =
356         vec::create(settings.executor, gko::dim<2>(metadata.local_size_x, 1));
357 }
```

The documentation for this class was generated from the following files:

- `initialization.hpp` (04a42d4)
- `/home/runner/work/schwarz-lib/schwarz-lib/source/initialization.cpp` (04a42d4)

7.10 `schwz::Metadata< ValueType, IndexType >` Struct Template Reference

The solver metadata struct.

```
#include <settings.hpp>
```

Classes

- struct `post_process_data`
The struct used for storing data for post-processing.

Public Attributes

- `MPI_Comm` `mpi_communicator`
The MPI communicator.
- `gko::size_type` `global_size` = 0
The size of the global matrix.
- `gko::size_type` `oned_laplacian_size` = 0
The size of the 1 dimensional laplacian grid.
- `gko::size_type` `local_size` = 0
The size of the local subdomain matrix.
- `gko::size_type` `local_size_x` = 0
The size of the local subdomain matrix + the overlap.

- gko::size_type [local_size_o](#) = 0
The size of the local subdomain matrix + the overlap.
- gko::size_type [overlap_size](#) = 0
The size of the overlap between the subdomains.
- gko::size_type [num_subdomains](#) = 1
The number of subdomains used within the solver.
- int [my_rank](#)
The rank of the subdomain.
- int [my_local_rank](#)
The local rank of the subdomain.
- int [local_num_procs](#)
The local number of procs in the subdomain.
- int [comm_size](#)
The number of subdomains used within the solver, size of the communicator.
- int [num_threads](#)
The number of threads used within the solver for each subdomain.
- IndexType [iter_count](#)
The iteration count of the solver.
- ValueType [tolerance](#)
The tolerance of the complete solver.
- ValueType [local_solver_tolerance](#)
The tolerance of the local solver in case of an iterative solve.
- IndexType [max_iters](#)
The maximum iteration count of the Schwarz solver.
- IndexType [local_max_iters](#)
The maximum iteration count of the local iterative solver.
- std::string [local_precond](#)
Local preconditioner.
- unsigned int [precond_max_block_size](#)
The maximum block size for the preconditioner.
- ValueType [current_residual_norm](#) = -1.0
The current residual norm of the subdomain.
- ValueType [min_residual_norm](#) = -1.0
The minimum residual norm of the subdomain.
- std::vector< std::tuple< int, int, int, std::string, std::vector< ValueType > > > [time_struct](#)
The struct used to measure the timings of each function within the solver loop.
- std::vector< std::tuple< int, std::vector< std::tuple< int, int > >, std::vector< std::tuple< int, int > >, int, int > > [comm_data_struct](#)
The struct used to measure the timings of each function within the solver loop.
- std::shared_ptr< gko::Array< IndexType > > [global_to_local](#)
The mapping containing the global to local indices.
- std::shared_ptr< gko::Array< IndexType > > [local_to_global](#)
The mapping containing the local to global indices.
- std::shared_ptr< gko::Array< IndexType > > [overlap_row](#)
The overlap row indices.
- std::shared_ptr< gko::Array< IndexType > > [first_row](#)
The starting row of each subdomain in the matrix.
- std::shared_ptr< gko::Array< IndexType > > [permutation](#)
The permutation used for the re-ordering.
- std::shared_ptr< gko::Array< IndexType > > [i_permutation](#)
The inverse permutation used for the re-ordering.

7.10.1 Detailed Description

```
template<typename ValueType, typename IndexType>
struct schwz::Metadata< ValueType, IndexType >
```

The solver metadata struct.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

7.10.2 Member Data Documentation

7.10.2.1 local_solver_tolerance

```
template<typename ValueType, typename IndexType>
ValueType schwz::Metadata< ValueType, IndexType >::local_solver_tolerance
```

The tolerance of the local solver in case of an iterative solve.

The residual norm reduction required.

7.10.2.2 tolerance

```
template<typename ValueType, typename IndexType>
ValueType schwz::Metadata< ValueType, IndexType >::tolerance
```

The tolerance of the complete solver.

The residual norm reduction required.

The documentation for this struct was generated from the following file:

- settings.hpp (04a42d4)

7.11 MetisError Class Reference

[MetisError](#) is thrown when a METIS routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [MetisError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a METIS error.

7.11.1 Detailed Description

[MetisError](#) is thrown when a METIS routine throws a non-zero error code.

7.11.2 Constructor & Destructor Documentation

7.11.2.1 MetisError()

```
MetisError::MetisError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]
```

Initializes a METIS error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the METIS routine that failed
<i>error_code</i>	The resulting METIS error code

```
182         : Error(file, line, func + ": " + get_error(error_code))
183     {}
```

The documentation for this class was generated from the following files:

- exception.hpp (04a42d4)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (04a42d4)

7.12 schwz::Metadata< ValueType, IndexType >::post_process_data Struct Reference

The struct used for storing data for post-processing.

```
#include <settings.hpp>
```

7.12.1 Detailed Description

```
template<typename ValueType, typename IndexType>
struct schwz::Metadata< ValueType, IndexType >::post_process_data
```

The struct used for storing data for post-processing.

The documentation for this struct was generated from the following file:

- settings.hpp (04a42d4)

7.13 schwz::SchwarzBase< ValueType, IndexType > Class Template Reference

The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.

```
#include <schwarz_base.hpp>
```

Public Member Functions

- [SchwarzBase](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata)
The constructor that takes in the user settings and a metadata struct containing the solver metadata.
- void [initialize](#) ()
Initialize the matrix and vectors.
- void [run](#) (std::shared_ptr< gko::matrix::Dense< ValueType >> &solution)
The function that runs the actual solver and obtains the final solution.
- void [print_vector](#) (const std::shared_ptr< gko::matrix::Dense< ValueType >> &vector, int subd, std::string name)
The auxiliary function that prints a passed in vector.
- void [print_matrix](#) (const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &matrix, int rank, std::string name)
The auxiliary function that prints a passed in CSR matrix.

Public Attributes

- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [local_matrix](#)
The local subdomain matrix.
- std::shared_ptr< gko::matrix::Permutation< IndexType >> [local_perm](#)
The local subdomain permutation matrix/array.
- std::shared_ptr< gko::matrix::Permutation< IndexType >> [local_inv_perm](#)
The local subdomain inverse permutation matrix/array.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [triangular_factor_l](#)
The local lower triangular factor used for the triangular solves.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [triangular_factor_u](#)
The local upper triangular factor used for the triangular solves.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [interface_matrix](#)
The local interface matrix.
- std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> [global_matrix](#)

- The global matrix.*
- `std::shared_ptr< gko::matrix::Dense< ValueType > >` [local_rhs](#)
- The local right hand side.*
- `std::shared_ptr< gko::matrix::Dense< ValueType > >` [global_rhs](#)
- The global right hand side.*
- `std::shared_ptr< gko::matrix::Dense< ValueType > >` [local_solution](#)
- The local solution vector.*
- `std::shared_ptr< gko::matrix::Dense< ValueType > >` [global_solution](#)
- The global solution vector.*
- `std::vector< ValueType >` [local_residual_vector_out](#)
- The global residual vector.*
- `std::vector< std::vector< ValueType > >` [global_residual_vector_out](#)
- The local residual vector.*

Additional Inherited Members

7.13.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
class schwz::SchwarzBase< ValueType, IndexType >
```

The Base solver class is meant to be the class implementing the common implementations for all the schwarz methods.

It derives from the Initialization class, the Communication class and the [Solve](#) class all of which are templated.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

7.13.2 Constructor & Destructor Documentation

7.13.2.1 SchwarzBase()

```
template<typename ValueType , typename IndexType >
schwz::SchwarzBase< ValueType, IndexType >::SchwarzBase (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata )
```

The constructor that takes in the user settings and a metadata struct containing the solver metadata.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.

References `schwz::Settings::cuda_device_guard`, `schwz::Settings::executor`, `schwz::Settings::executor_string`, `schwz::Metadata< ValueType, IndexType >::local_num_procs`, `schwz::Metadata< ValueType, IndexType >::mpi_communicator`, `schwz::Metadata< ValueType, IndexType >::my_local_rank`, and `schwz::Metadata< ValueType, IndexType >::my_rank`.

```

71     : Initialize<ValueType, IndexType>(settings, metadata),
72     settings(settings),
73     metadata(metadata)
74 {
75     using vec_itype = gko::Array<IndexType>;
76     using vec_vecshared = gko::Array<IndexType *>;
77     metadata.my_local_rank =
78         Utils<ValueType, IndexType>::get_local_rank(metadata.mpi_communicator);
79     metadata.local_num_procs = Utils<ValueType, IndexType>::get_local_num_procs(
80         metadata.mpi_communicator);
81     auto my_local_rank = metadata.my_local_rank;
82     if (settings.executor_string == "omp") {
83         settings.executor = gko::OmpExecutor::create();
84         auto exec_info =
85             static_cast<gko::OmpExecutor *>(settings.executor.get())
86             ->get_exec_info();
87         exec_info->bind_to_core(metadata.my_local_rank);
88     } else if (settings.executor_string == "cuda") {
89         int num_devices = 0;
90         #if SCHW_HAVE_CUDA
91         SCHWARZ_ASSERT_NO_CUDA_ERRORS(cudaGetDeviceCount(&num_devices));
92         #else
93         SCHWARZ_NOT_IMPLEMENTED;
94         #endif
95         Utils<ValueType, IndexType>::assert_correct_cuda_devices(
96             num_devices, metadata.my_rank);
97         settings.executor = gko::CudaExecutor::create(
98             my_local_rank, gko::OmpExecutor::create());
99         auto exec_info = static_cast<gko::OmpExecutor *>(
100             settings.executor->get_master().get())
101             ->get_exec_info();
102         exec_info->bind_to_core(my_local_rank);
103         settings.cuda_device_guard =
104             std::make_shared<schwz::device_guard>(my_local_rank);
105
106         std::cout << " Rank " << metadata.my_rank << " with local rank "
107             << my_local_rank << " has "
108             << (static_cast<gko::CudaExecutor *>(settings.executor.get()))
109             ->get_device_id()
110             << " id of gpu" << std::endl;
111         MPI_Barrier(metadata.mpi_communicator);
112     } else if (settings.executor_string == "reference") {
113         settings.executor = gko::ReferenceExecutor::create();
114         auto exec_info =
115             static_cast<gko::ReferenceExecutor *>(settings.executor.get())
116             ->get_exec_info();
117         exec_info->bind_to_core(my_local_rank);
118     }
119 }
120 }

```

7.13.3 Member Function Documentation

7.13.3.1 print_matrix()

```

template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
void schwz::SchwarzBase< ValueType, IndexType >::print_matrix (
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & matrix,
    int rank,
    std::string name )

```

The auxiliary function that prints a passed in CSR matrix.

Parameters

<i>matrix</i>	The matrix to be printed.
<i>subd</i>	The subdomain on which the vector exists.
<i>name</i>	The name of the matrix as a string.

7.13.3.2 print_vector()

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
void schwz::SchwarzBase< ValueType, IndexType >::print_vector (
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & vector,
    int subd,
    std::string name )
```

The auxiliary function that prints a passed in vector.

Parameters

<i>vector</i>	The vector to be printed.
<i>subd</i>	The subdomain on which the vector exists.
<i>name</i>	The name of the vector as a string.

7.13.3.3 run()

```
template<typename ValueType , typename IndexType >
void schwz::SchwarzBase< ValueType, IndexType >::run (
    std::shared_ptr< gko::matrix::Dense< ValueType >> & solution )
```

The function that runs the actual solver and obtains the final solution.

Parameters

<i>solution</i>	The solution vector.
-----------------	----------------------

References schwz::Communicate< ValueType, IndexType >::exchange_boundary(), schwz::Settings::executor, schwz::SchwarzBase< ValueType, IndexType >::global_matrix, schwz::SchwarzBase< ValueType, IndexType >::global_rhs, schwz::SchwarzBase< ValueType, IndexType >::global_solution, schwz::SchwarzBase< ValueType, IndexType >::interface_matrix, schwz::SchwarzBase< ValueType, IndexType >::local_inv_perm, schwz::SchwarzBase< ValueType, IndexType >::local_matrix, schwz::SchwarzBase< ValueType, IndexType >::local_perm, schwz::SchwarzBase< ValueType, IndexType >::local_rhs, schwz::SchwarzBase< ValueType, IndexType >::local_solution, schwz::Communicate< ValueType, IndexType >::setup_windows(), schwz::SchwarzBase< ValueType, IndexType >::triangular_factor_l, schwz::SchwarzBase< ValueType, IndexType >::triangular_factor_u, schwz::Communicate< ValueType, IndexType >::update_boundary(), and schwz::Settings::write_iters_and_residuals.

```

308     using vec_vtype = gko::matrix::Dense<ValueType>;
309
310     solution = vec_vtype::create(settings.executor->get_master(),
311                                 gko::dim<2>(this->metadata.global_size, 1));
312     // The main solution vector
313     std::shared_ptr<vec_vtype> global_solution = vec_vtype::create(
314         this->settings.executor, gko::dim<2>(this->metadata.global_size, 1));
315     // A work vector.
316     std::shared_ptr<vec_vtype> work_vector = vec_vtype::create(
317         settings.executor, gko::dim<2>(2 * this->metadata.local_size_x, 1));
318     // An initial guess.
319     std::shared_ptr<vec_vtype> init_guess = vec_vtype::create(
320         settings.executor, gko::dim<2>(this->metadata.local_size_x, 1));
321     init_guess->copy_from(local_rhs.get());
322
323     // std::vector<IndexType> local_converged_iter_count;
324
325     // Setup the windows for the onesided communication.
326     this->setup_windows(this->settings, this->metadata, global_solution);
327
328     const auto solver_settings =
329         (Settings::local_solver_settings::direct_solver_cholmod |
330          Settings::local_solver_settings::direct_solver_umfpack |
331          Settings::local_solver_settings::direct_solver_ginkgo |
332          Settings::local_solver_settings::iterative_solver_dealii |
333          Settings::local_solver_settings::iterative_solver_ginkgo) &
334         settings.local_solver;
335
336     ValueType local_residual_norm = -1.0, local_residual_norm0 = -1.0,
337             global_residual_norm = 0.0, global_residual_norm0 = -1.0;
338     metadata.iter_count = 0;
339     auto start_time = std::chrono::steady_clock::now();
340     int num_converged_procs = 0;
341
342     for (; metadata.iter_count < metadata.max_iters; ++(metadata.iter_count)) {
343         // Exchange the boundary values. The communication part.
344         MEASURE_ELAPSED_FUNC_TIME(
345             this->exchange_boundary(settings, metadata, global_solution), 0,
346             metadata.my_rank, boundary_exchange, metadata.iter_count);
347
348         // Update the boundary and interior values after the exchanging from
349         // other processes.
350         MEASURE_ELAPSED_FUNC_TIME(
351             this->update_boundary(settings, metadata, this->
local_solution,
352                                 this->local_rhs, global_solution,
353                                 this->interface_matrix),
354             1, metadata.my_rank, boundary_update, metadata.iter_count);
355
356         // Check for the convergence of the solver.
357         // num_converged_procs = 0;
358         MEASURE_ELAPSED_FUNC_TIME(
359             (Solve<ValueType, IndexType>::check_convergence(
360                 settings, metadata, this->comm_struct, this->convergence_vector,
361                 global_solution, this->local_solution, this->
local_matrix,
362                 work_vector, local_residual_norm, local_residual_norm0,
363                 global_residual_norm, global_residual_norm0,
364                 num_converged_procs)),
365             2, metadata.my_rank, convergence_check, metadata.iter_count);
366
367         // break if the solution diverges.
368         if (std::isnan(global_residual_norm) || global_residual_norm > 1e12) {
369             std::cout << " Rank " << metadata.my_rank << " diverged in "
370                 << metadata.iter_count << " iters " << std::endl;
371             std::exit(-1);
372         }
373
374         // break if all processes detect that all other processes have
375         // converged otherwise continue iterations.
376         if (num_converged_procs == metadata.num_subdomains) {
377             break;
378         } else {
379             MEASURE_ELAPSED_FUNC_TIME(
380                 (Solve<ValueType, IndexType>::local_solve(
381                     settings, metadata, this->local_matrix,
382                     this->triangular_factor_l, this->
triangular_factor_u,
383                     this->local_perm, this->local_inv_perm, work_vector,
384                     init_guess, this->local_solution)),
385                 3, metadata.my_rank, local_solve, metadata.iter_count);
386             // Gather the local vector into the locally global vector for
387             // communication.
388             MEASURE_ELAPSED_FUNC_TIME(
389                 (Communicate<ValueType, IndexType>::local_to_global_vector
390                     (
391                         settings, metadata, this->local_solution, global_solution)),

```

```

391         4, metadata.my_rank, expand_local_vec, metadata.iter_count);
392     }
393 }
394 MPI_Barrier(MPI_COMM_WORLD);
395 auto elapsed_time = std::chrono::duration<ValueType>(
396     std::chrono::steady_clock::now() - start_time);
397 std::cout << " Rank " << metadata.my_rank << " converged in "
398     << metadata.iter_count << " iters " << std::endl;
399 ValueType mat_norm = -1.0, rhs_norm = -1.0, sol_norm = -1.0,
400     residual_norm = -1.0;
401 // Write the residuals and iterations to files
402 if (settings.write_iters_and_residuals &&
403     solver_settings ==
404     Settings::local_solver_settings::iterative_solver_ginkgo) {
405     std::string rank_string = std::to_string(metadata.my_rank);
406     if (metadata.my_rank < 10) {
407         rank_string = "0" + std::to_string(metadata.my_rank);
408     }
409     std::string filename = "iter_res_" + rank_string + ".csv";
410     write_iters_and_residuals(
411         metadata.num_subdomains, metadata.my_rank,
412         metadata.post_process_data.local_residual_vector_out.size(),
413         metadata.post_process_data.local_residual_vector_out,
414         metadata.post_process_data.local_converged_iter_count,
415         metadata.post_process_data.local_converged_resnorm, filename);
416 }
417
418 // Compute the final residual norm. Also gathers the solution from all
419 // subdomains.
420 Solve<ValueType, IndexType>::compute_residual_norm(
421     settings, metadata, global_matrix, global_rhs, global_solution,
422     mat_norm, rhs_norm, sol_norm, residual_norm);
423 gather_comm_data<ValueType, IndexType>(
424     metadata.num_subdomains, this->comm_struct, metadata.comm_data_struct);
425 // clang-format off
426 if (metadata.my_rank == 0)
427 {
428     std::cout
429         << " residual norm " << residual_norm << "\n"
430         << " relative residual norm of solution " << residual_norm/rhs_norm << "\n"
431         << " Time taken for solve " << elapsed_time.count()
432         << std::endl;
433     if (num_converged_procs < metadata.num_subdomains)
434     {
435         std::cout << " Did not converge in " << metadata.iter_count
436             << " iterations."
437             << std::endl;
438     }
439 }
440 // clang-format on
441 if (metadata.my_rank == 0) {
442     solution->copy_from(global_solution.get());
443 }
444
445 // Communicate<ValueType, IndexType>::clear(settings);
446 }

```

The documentation for this class was generated from the following files:

- `schwarz_base.hpp` (04a42d4)
- `/home/runner/work/schwarz-lib/schwarz-lib/source/schwarz_base.cpp` (04a42d4)

7.14 schwz::Settings Struct Reference

The struct that contains the solver settings and the parameters to be set by the user.

```
#include <settings.hpp>
```

Classes

- struct `comm_settings`
The settings for the various available communication paradigms.
- struct `convergence_settings`
The various convergence settings available.

Public Types

- enum [partition_settings](#)
The partition algorithm to be used for partitioning the matrix.
- enum [local_solver_settings](#)
The local solver algorithm for the local subdomain solves.

Public Attributes

- std::string [executor_string](#)
The string that contains the ginkgo executor paradigm.
- std::shared_ptr< gko::Executor > [executor](#) = gko::ReferenceExecutor::create()
The ginkgo executor the code is to be executed on.
- std::shared_ptr< [device_guard](#) > [cuda_device_guard](#)
The ginkgo executor the code is to be executed on.
- gko::int32 [overlap](#) = 2
The overlap between the subdomains.
- std::string [matrix_filename](#) = "null"
The string that contains the matrix file name to read from .
- bool [explicit_laplacian](#) = true
Flag if the laplacian matrix should be generated within the library.
- bool [enable_random_rhs](#) = false
Flag to enable a random rhs.
- bool [print_matrices](#) = false
Flag to enable printing of matrices.
- bool [debug_print](#) = false
Flag to enable some debug printing.
- bool [naturally_ordered_factor](#) = false
Disables the re-ordering of the matrix before computing the triangular factors during the CHOLMOD factorization.
- std::string [metis_objtype](#)
This setting defines the objective type for the metis partitioning.
- bool [use_precond](#) = false
Enable the block jacobi local preconditioner for the local solver.
- bool [write_debug_out](#) = false
Enable the writing of debug out to file.
- bool [write_iters_and_residuals](#) = false
Enable writing the iters and residuals to a file.
- bool [write_perm_data](#) = false
Enable the local permutations from CHOLMOD to a file.
- int [shifted_iter](#) = 1
Iteration shift for node local communication.
- std::string [factorization](#) = "cholmod"
The factorization for the local direct solver.
- std::string [reorder](#)
The reordering for the local solve.

7.14.1 Detailed Description

The struct that contains the solver settings and the parameters to be set by the user.

settings

7.14.2 Member Data Documentation

7.14.2.1 explicit_laplacian

```
bool schwz::Settings::explicit_laplacian = true
```

Flag if the laplacian matrix should be generated within the library.

If false, an external matrix and rhs needs to be provided

Referenced by schwz::SchwarzBase< ValueType, IndexType >::initialize().

7.14.2.2 naturally_ordered_factor

```
bool schwz::Settings::naturally_ordered_factor = false
```

Disables the re-ordering of the matrix before computing the triangular factors during the CHOLMOD factorization.

Note

This is mainly to allow compatibility with GPU solution.

The documentation for this struct was generated from the following file:

- settings.hpp (04a42d4)

7.15 schwz::Solve< ValueType, IndexType > Class Template Reference

The Solver class the provides the solver and the convergence checking methods.

```
#include <solve.hpp>
```

Additional Inherited Members

7.15.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
class schwz::Solve< ValueType, IndexType >
```

The Solver class the provides the solver and the convergence checking methods.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

Solve

The documentation for this class was generated from the following files:

- solve.hpp (04a42d4)
- /home/runner/work/schwarz-lib/schwarz-lib/source/solve.cpp (04a42d4)

7.16 schwz::SolverRAS< ValueType, IndexType > Class Template Reference

An implementation of the solver interface using the RAS solver.

```
#include <restricted_schwarz.hpp>
```

Public Member Functions

- [SolverRAS](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata)
The constructor that takes in the user settings and a metadata struct containing the solver metadata.
- void [setup_local_matrices](#) ([Settings](#) &settings, [Metadata](#)< ValueType, IndexType > &metadata, std::vector< unsigned int > &[partition_indices](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[global_matrix](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[local_matrix](#), std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[interface_matrix](#)) override
Sets up the local and the interface matrices from the global matrix and the partition indices.
- void [setup_comm_buffers](#) () override
Sets up the communication buffers needed for the boundary exchange.
- void [setup_windows](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &[main_buffer](#)) override
Sets up the windows needed for the asynchronous communication.
- void [exchange_boundary](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &[global_solution](#)) override
Exchanges the elements of the solution vector.
- void [update_boundary](#) (const [Settings](#) &settings, const [Metadata](#)< ValueType, IndexType > &metadata, std::shared_ptr< gko::matrix::Dense< ValueType >> &[local_solution](#), const std::shared_ptr< gko::matrix::Dense< ValueType >> &[local_rhs](#), const std::shared_ptr< gko::matrix::Dense< ValueType >> &[global_solution](#), const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> &[interface_matrix](#)) override
Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.

Additional Inherited Members

7.16.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>
class schwz::SolverRAS< ValueType, IndexType >
```

An implementation of the solver interface using the RAS solver.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

7.16.2 Constructor & Destructor Documentation

7.16.2.1 SolverRAS()

```
template<typename ValueType , typename IndexType >
schwz::SolverRAS< ValueType, IndexType >::SolverRAS (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata )
```

The constructor that takes in the user settings and a metadata struct containing the solver metadata.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>data</i>	The additional data struct.

```
50      : SchwarzBase<ValueType, IndexType>(settings, metadata)
51 {}
```

7.16.3 Member Function Documentation

7.16.3.1 exchange_boundary()

```
template<typename ValueType , typename IndexType >
void schwz::SolverRAS< ValueType, IndexType >::exchange_boundary (
    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution ) [override],
[virtual]
```

Exchanges the elements of the solution vector.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>global_solution</i>	The solution vector being exchanged between the subdomains.

Implements [schwz::Communicate< ValueType, IndexType >](#).

References [schwz::Settings::comm_settings::enable_onesided](#), and [schwz::SchwarzBase< ValueType, IndexType >::global_solution](#).

```

798 {
799     if (settings.comm_settings.enable_onesided) {
800         exchange_boundary_onesided<ValueType, IndexType>(
801             settings, metadata, this->comm_struct, global\_solution);
802     } else {
803         exchange_boundary_twosided<ValueType, IndexType>(
804             settings, metadata, this->comm_struct, global\_solution);
805     }
806 }
```

7.16.3.2 setup_local_matrices()

```

template<typename ValueType , typename IndexType >
void schwz::SolverRAS< ValueType, IndexType >::setup\_local\_matrices (
    Settings & settings,
    Metadata< ValueType, IndexType > & metadata,
    std::vector< unsigned int > & partition_indices,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & global_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & local_matrix,
    std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_matrix )
[override], [virtual]
```

Sets up the local and the interface matrices from the global matrix and the partition indices.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>partition_indices</i>	The array containing the partition indices.
<i>global_matrix</i>	The global system matrix.
<i>local_matrix</i>	The local system matrix.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.
<i>local_perm</i>	The local permutation, obtained through RCM or METIS.

Implements [schwz::Initialize< ValueType, IndexType >](#).

References [schwz::Metadata< ValueType, IndexType >::comm_size](#), [schwz::Settings::executor](#), [schwz::Metadata< ValueType, IndexType >::first_row](#), [schwz::SchwarzBase< ValueType, IndexType >::global_matrix](#), [schwz::Metadata< ValueType, IndexType >::global_size](#), [schwz::Metadata< ValueType, IndexType >::global_to_local](#), [schwz::Metadata< ValueType, IndexType >::i_permutation](#), [schwz::SchwarzBase< ValueType, IndexType >::interface_matrix](#), [schwz::SchwarzBase< ValueType, IndexType >::local_matrix](#), [schwz::Metadata< ValueType, IndexType >::local_size](#), [schwz::Metadata< ValueType, IndexType >::local_size_o](#), [schwz::Metadata< ValueType, IndexType >::local_size_x](#), [schwz::Metadata< ValueType, IndexType >::local_to_global](#), [schwz::Metadata< ValueType, IndexType >::my_rank](#), [schwz::Metadata< ValueType, IndexType >::num_subdomains](#), [schwz::Settings::overlap](#), [schwz::Metadata< ValueType, IndexType >::overlap_row](#), [schwz::Metadata< ValueType, IndexType >::overlap_size](#), and [schwz::Metadata< ValueType, IndexType >::permutation](#).


```

61 {
62     using mtx = gko::matrix::Csr<ValueType, IndexType>;
63     using vec_itype = gko::Array<IndexType>;
64     using perm_type = gko::matrix::Permutation<IndexType>;
65     using arr = gko::Array<IndexType>;
66     auto my_rank = metadata.my_rank;
67     auto comm_size = metadata.comm_size;
68     auto num_subdomains = metadata.num_subdomains;
69     auto global_size = metadata.global_size;
70     auto mpi_itype = boost::mpi::get_mpi_datatype(*partition_indices.data());
71
72     MPI_Bcast(partition_indices.data(), global_size, mpi_itype, 0,
73             MPI_COMM_WORLD);
74
75     std::vector<IndexType> local_p_size(num_subdomains);
76     auto global_to_local = metadata.global_to_local->get_data();
77     auto local_to_global = metadata.local_to_global->get_data();
78
79     auto first_row = metadata.first_row->get_data();
80     auto permutation = metadata.permutation->get_data();
81     auto i_permutation = metadata.i_permutation->get_data();
82
83     auto nb = (global_size + num_subdomains - 1) /
num_subdomains;
84     auto partition_settings =
85         (Settings::partition_settings::partition_zoltan |
86          Settings::partition_settings::partitionmetis |
87          Settings::partition_settings::partition_regular |
88          Settings::partition_settings::partition_regular2d |
89          Settings::partition_settings::partition_custom) &
90         settings.partition;
91
92     IndexType *gmat_row_ptrs = global_matrix->get_row_ptrs();
93     IndexType *gmat_col_idxs = global_matrix->get_col_idxs();
94     ValueType *gmat_values = global_matrix->get_values();
95
96     // default local p size set for 1 subdomain.
97     first_row[0] = 0;
98     for (auto p = 0; p < num_subdomains; ++p) {
99         local_p_size[p] = std::min(global_size - first_row[p], nb);
100         first_row[p + 1] = first_row[p] + local_p_size[p];
101     }
102
103
104     if (partition_settings == Settings::partition_settings::partitionmetis ||
105         partition_settings ==
106         Settings::partition_settings::partition_regular2d) {
107         if (num_subdomains > 1) {
108             for (auto p = 0; p < num_subdomains; p++) {
109                 local_p_size[p] = 0;
110             }
111             for (auto i = 0; i < global_size; i++) {
112                 local_p_size[partition_indices[i]]++;
113             }
114             first_row[0] = 0;
115             for (auto p = 0; p < num_subdomains; ++p) {
116                 first_row[p + 1] = first_row[p] + local_p_size[p];
117             }
118             // permutation
119             for (auto i = 0; i < global_size; i++) {
120                 permutation[first_row[partition_indices[i]]] = i;
121                 first_row[partition_indices[i]]++;
122             }
123             for (auto p = num_subdomains; p > 0; p--) {
124                 first_row[p] = first_row[p - 1];
125             }
126             first_row[0] = 0;
127
128             // iperm
129             for (auto i = 0; i < global_size; i++) {
130                 i_permutation[permutation[i]] = i;
131             }
132         }
133
134         auto gmat_temp = mtx::create(settings.executor->get_master(),
135                                     global_matrix->get_size(),
136                                     global_matrix->get_num_stored_elements());
137
138         auto nnz = 0;
139         gmat_temp->get_row_ptrs()[0] = 0;
140         for (auto row = 0; row < metadata.global_size; ++row) {
141             for (auto col = gmat_row_ptrs[permutation[row]];
142                  col < gmat_row_ptrs[permutation[row] + 1]; ++col) {
143                 gmat_temp->get_col_idxs()[nnz] =
144                     i_permutation[gmat_col_idxs[col]];
145                 gmat_temp->get_values()[nnz] = gmat_values[col];
146                 nnz++;

```

```

147         }
148         gmat_temp->get_row_ptrs()[row + 1] = nnz;
149     }
150     global_matrix->copy_from(gmat_temp.get());
151 }
152
153
154     for (auto i = 0; i < global_size; i++) {
155         global_to_local[i] = 0;
156         local_to_global[i] = 0;
157     }
158     auto num = 0;
159     for (auto i = first_row[my_rank]; i < first_row[
my_rank + 1]; i++) {
160         global_to_local[i] = 1 + num;
161         local_to_global[num] = i;
162         num++;
163     }
164
165     IndexType old = 0;
166     for (auto k = 1; k < settings.overlap; k++) {
167         auto now = num;
168         for (auto i = old; i < now; i++) {
169             for (auto j = gmat_row_ptrs[local_to_global[i]];
170                  j < gmat_row_ptrs[local_to_global[i] + 1]; j++) {
171                 if (global_to_local[gmat_col_idxs[j]] == 0) {
172                     local_to_global[num] = gmat_col_idxs[j];
173                     global_to_local[gmat_col_idxs[j]] = 1 + num;
174                     num++;
175                 }
176             }
177             old = now;
178         }
179     }
180     metadata.local_size = local_p_size[my_rank];
181     metadata.local_size_x = num;
182     metadata.local_size_o = global_size;
183     auto local_size = metadata.local_size;
184     auto local_size_x = metadata.local_size_x;
185
186     metadata.overlap_size = num - metadata.local_size;
187     metadata.overlap_row = std::shared_ptr<vec_itype>(
188         new vec_itype(gko::Array<IndexType>::view(
189             settings.executor, metadata.overlap_size,
190             &(metadata.local_to_global->get_data()[metadata.local_size])),
191         std::default_delete<vec_itype>());
192
193     auto nnz_local = 0;
194     auto nnz_interface = 0;
195
196     for (auto i = first_row[my_rank]; i < first_row[my_rank + 1]; ++i) {
197         for (auto j = gmat_row_ptrs[i]; j < gmat_row_ptrs[i + 1]; j++) {
198             if (global_to_local[gmat_col_idxs[j]] != 0) {
199                 nnz_local++;
200             } else {
201                 std::cout << " debug: invalid edge?" << std::endl;
202             }
203         }
204     }
205     auto temp = 0;
206     for (auto k = 0; k < metadata.overlap_size; k++) {
207         temp = metadata.overlap_row->get_data()[k];
208         for (auto j = gmat_row_ptrs[temp]; j < gmat_row_ptrs[temp + 1]; j++) {
209             if (global_to_local[gmat_col_idxs[j]] != 0) {
210                 nnz_local++;
211             } else {
212                 nnz_interface++;
213             }
214         }
215     }
216
217     std::shared_ptr<mtx> local_matrix_compute;
218     local_matrix_compute = mtx::create(settings.executor->get_master(),
219                                       gko::dim<2>(local_size_x), nnz_local);
220     IndexType *lmat_row_ptrs = local_matrix_compute->get_row_ptrs();
221     IndexType *lmat_col_idxs = local_matrix_compute->get_col_idxs();
222     ValueType *lmat_values = local_matrix_compute->get_values();
223
224     std::shared_ptr<mtx> interface_matrix_compute;
225     if (nnz_interface > 0) {
226         interface_matrix_compute =
227             mtx::create(settings.executor->get_master(),
228                       gko::dim<2>(local_size_x), nnz_interface);
229     } else {
230         interface_matrix_compute = mtx::create(settings.executor->get_master());
231     }
232

```

```

233     IndexType *imat_row_ptrs = interface_matrix_compute->get_row_ptrs();
234     IndexType *imat_col_idxes = interface_matrix_compute->get_col_idxes();
235     ValueType *imat_values = interface_matrix_compute->get_values();
236
237     num = 0;
238     nnz_local = 0;
239     auto nnz_interface_temp = 0;
240     lmat_row_ptrs[0] = nnz_local;
241     if (nnz_interface > 0) {
242         imat_row_ptrs[0] = nnz_interface_temp;
243     }
244     // Local interior matrix
245     for (auto i = first_row[my_rank]; i < first_row[my_rank + 1]; ++i) {
246         for (auto j = gmat_row_ptrs[i]; j < gmat_row_ptrs[i + 1]; ++j) {
247             if (global_to_local[gmat_col_idxes[j]] != 0) {
248                 lmat_col_idxes[nnz_local] =
249                     global_to_local[gmat_col_idxes[j]] - 1;
250                 lmat_values[nnz_local] = gmat_values[j];
251                 nnz_local++;
252             }
253         }
254         if (nnz_interface > 0) {
255             imat_row_ptrs[num + 1] = nnz_interface_temp;
256         }
257         lmat_row_ptrs[num + 1] = nnz_local;
258         num++;
259     }
260
261     // Interface matrix
262     if (nnz_interface > 0) {
263         nnz_interface = 0;
264         for (auto k = 0; k < metadata.overlap_size; k++) {
265             temp = metadata.overlap_row->get_data()[k];
266             for (auto j = gmat_row_ptrs[temp]; j < gmat_row_ptrs[temp + 1];
267                 j++) {
268                 if (global_to_local[gmat_col_idxes[j]] != 0) {
269                     lmat_col_idxes[nnz_local] =
270                         global_to_local[gmat_col_idxes[j]] - 1;
271                     lmat_values[nnz_local] = gmat_values[j];
272                     nnz_local++;
273                 } else {
274                     imat_col_idxes[nnz_interface] = gmat_col_idxes[j];
275                     imat_values[nnz_interface] = gmat_values[j];
276                     nnz_interface++;
277                 }
278             }
279             lmat_row_ptrs[num + 1] = nnz_local;
280             imat_row_ptrs[num + 1] = nnz_interface;
281             num++;
282         }
283     }
284     auto now = num;
285     for (auto i = old; i < now; i++) {
286         for (auto j = gmat_row_ptrs[local_to_global[i]];
287             j < gmat_row_ptrs[local_to_global[i] + 1]; j++) {
288             if (global_to_local[gmat_col_idxes[j]] == 0) {
289                 local_to_global[num] = gmat_col_idxes[j];
290                 global_to_local[gmat_col_idxes[j]] = 1 + num;
291                 num++;
292             }
293         }
294     }
295
296     local_matrix = mtx::create(settings.executor);
297     local_matrix->copy_from(gko::lend(local_matrix_compute));
298     interface_matrix = mtx::create(settings.executor);
299     interface_matrix->copy_from(gko::lend(interface_matrix_compute));
300
301     local_matrix->sort_by_column_index();
302     interface_matrix->sort_by_column_index();
303 }

```

7.16.3.3 setup_windows()

```

template<typename ValueType , typename IndexType >
void schwz::SolverRAS< ValueType, IndexType >::setup_windows (
    const Settings & settings,

```

```

const Metadata< ValueType, IndexType > & metadata,
std::shared_ptr< gko::matrix::Dense< ValueType >> & main_buffer ) [override],
[virtual]

```

Sets up the windows needed for the asynchronous communication.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>main_buffer</i>	The main buffer being exchanged between the subdomains.

Implements [schwz::Communicate< ValueType, IndexType >](#).

References [schwz::Settings::comm_settings::enable_get](#), [schwz::Settings::comm_settings::enable_lock](#), [all](#), [schwz::Settings::comm_settings::enable_one_by_one](#), [schwz::Settings::comm_settings::enable_onesided](#), [schwz::Settings::comm_settings::enable_overlap](#), [schwz::Settings::comm_settings::enable_put](#), [schwz::Settings::executor](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::get_displacements](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::get_request](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::global_get](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::global_put](#), [schwz::SchwarzBase< ValueType, IndexType >::global_solution](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::is_local_neighbor](#), [schwz::Metadata< ValueType, IndexType >::iter_count](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::local_get](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::local_neighbors_in](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::local_neighbors_out](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::local_num_neighbors_in](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::local_num_neighbors_out](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::local_put](#), [schwz::Metadata< ValueType, IndexType >::local_size_o](#), [schwz::SchwarzBase< ValueType, IndexType >::local_solution](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::neighbors_in](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::neighbors_out](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::num_neighbors_in](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::num_neighbors_out](#), [schwz::Metadata< ValueType, IndexType >::num_subdomains](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::put_displacements](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::put_request](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::recv_buffer](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::remote_get](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::remote_put](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::send_buffer](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::window_recv_buffer](#), [schwz::Communicate< ValueType, IndexType >::comm_struct::window_send_buffer](#), and [schwz::Communicate< ValueType, IndexType >::comm_struct::window_x](#).

```

507 {
508     using vec_itype = gko::Array<IndexType>;
509     using vec_vtype = gko::matrix::Dense<ValueType>;
510     auto num_subdomains = metadata.num_subdomains;
511     auto local_size_o = metadata.local_size_o;
512     auto neighbors_in = this->comm_struct.neighbors_in->get_data();
513     auto global_get = this->comm_struct.global_get->get_data();
514     auto neighbors_out = this->comm_struct.neighbors_out->get_data();
515     auto global_put = this->comm_struct.global_put->get_data();
516
517     // set displacement for the MPI buffer
518     auto get_displacements = this->comm_struct.get_displacements->get_data();
519     auto put_displacements = this->comm_struct.put_displacements->get_data();
520     {
521         std::vector<IndexType> tmp_num_comm_elems(num_subdomains + 1, 0);
522         tmp_num_comm_elems[0] = 0;
523         for (auto j = 0; j < this->comm_struct.num_neighbors_in; j++) {
524             if ((global_get[j])[0] > 0) {
525                 int p = neighbors_in[j];
526                 tmp_num_comm_elems[p + 1] = (global_get[j])[0];
527             }
528         }
529         for (auto j = 0; j < num_subdomains; j++) {
530             tmp_num_comm_elems[j + 1] += tmp_num_comm_elems[j];
531         }
532     }

```

```

533     auto mpi_itype = boost::mpi::get_mpi_datatype(tmp_num_comm_elems[0]);
534     MPI_Alltoall(tmp_num_comm_elems.data(), 1, mpi_itype, put_displacements,
535                 1, mpi_itype, MPI_COMM_WORLD);
536 }
537
538 {
539     std::vector<IndexType> tmp_num_comm_elems(num_subdomains + 1, 0);
540     tmp_num_comm_elems[0] = 0;
541     for (auto j = 0; j < this->comm_struct.num_neighbors_out; j++) {
542         if ((global_put[j])[0] > 0) {
543             int p = neighbors_out[j];
544             tmp_num_comm_elems[p + 1] = (global_put[j])[0];
545         }
546     }
547     for (auto j = 0; j < num_subdomains; j++) {
548         tmp_num_comm_elems[j + 1] += tmp_num_comm_elems[j];
549     }
550
551     auto mpi_itype = boost::mpi::get_mpi_datatype(tmp_num_comm_elems[0]);
552     MPI_Alltoall(tmp_num_comm_elems.data(), 1, mpi_itype, get_displacements,
553                 1, mpi_itype, MPI_COMM_WORLD);
554 }
555
556 // setup windows
557 if (settings.comm_settings.enable_onesided) {
558     // Onesided
559     MPI_Win_create(main_buffer->get_values(),
560                   main_buffer->get_size()[0] * sizeof(ValueType),
561                   sizeof(ValueType), MPI_INFO_NULL, MPI_COMM_WORLD,
562                   &(this->comm_struct.window_x));
563 }
564
565
566 if (settings.comm_settings.enable_onesided) {
567     // MPI_Alloc_mem ? Custom allocator ? TODO
568     MPI_Win_create(this->local_residual_vector->get_values(),
569                   (num_subdomains) * sizeof(ValueType), sizeof(ValueType),
570                   MPI_INFO_NULL, MPI_COMM_WORLD,
571                   &(this->window_residual_vector));
572     std::vector<IndexType> zero_vec(num_subdomains, 0);
573     gko::Array<IndexType> temp_array(settings.executor->get_master(),
574                                     zero_vec.begin(), zero_vec.end());
575     this->convergence_vector = std::shared_ptr<vec_itype>(
576         new vec_itype(settings.executor->get_master(), temp_array),
577         std::default_delete<vec_itype>());
578     this->convergence_sent = std::shared_ptr<vec_itype>(
579         new vec_itype(settings.executor->get_master(), num_subdomains),
580         std::default_delete<vec_itype>());
581     this->convergence_local = std::shared_ptr<vec_itype>(
582         new vec_itype(settings.executor->get_master(), num_subdomains),
583         std::default_delete<vec_itype>());
584     MPI_Win_create(this->convergence_vector->get_data(),
585                   (num_subdomains) * sizeof(IndexType), sizeof(IndexType),
586                   MPI_INFO_NULL, MPI_COMM_WORLD,
587                   &(this->window_convergence));
588 }
589
590 if (settings.comm_settings.enable_onesided && num_subdomains > 1) {
591     // Lock all windows.
592     if (settings.comm_settings.enable_get &&
593         settings.comm_settings.enable_lock_all) {
594         MPI_Win_lock_all(0, this->comm_struct.window_send_buffer);
595     }
596     if (settings.comm_settings.enable_put &&
597         settings.comm_settings.enable_lock_all) {
598         MPI_Win_lock_all(0, this->comm_struct.window_recv_buffer);
599     }
600     if (settings.comm_settings.enable_one_by_one &&
601         settings.comm_settings.enable_lock_all) {
602         MPI_Win_lock_all(0, this->comm_struct.window_x);
603     }
604     MPI_Win_lock_all(0, this->window_residual_vector);
605     MPI_Win_lock_all(0, this->window_convergence);
606 }
607 }

```

7.16.3.4 update_boundary()

```

template<typename ValueType , typename IndexType >
void schwz::SolverRAS< ValueType, IndexType >::update_boundary (

```

```

    const Settings & settings,
    const Metadata< ValueType, IndexType > & metadata,
    std::shared_ptr< gko::matrix::Dense< ValueType >> & local_solution,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & local_rhs,
    const std::shared_ptr< gko::matrix::Dense< ValueType >> & global_solution,
    const std::shared_ptr< gko::matrix::Csr< ValueType, IndexType >> & interface_←
matrix ) [override], [virtual]

```

Update the values into local vector from obtained from the neighboring sub-domains using the interface matrix.

Parameters

<i>settings</i>	The settings struct.
<i>metadata</i>	The metadata struct.
<i>local_solution</i>	The local solution vector in the subdomain.
<i>local_rhs</i>	The local right hand side vector in the subdomain.
<i>global_solution</i>	The workspace solution vector.
<i>global_old_solution</i>	The global solution vector of the previous iteration.
<i>interface_matrix</i>	The interface matrix containing the interface and the overlap data mainly used for exchanging values between different sub-domains.

Implements [schwz::Communicate< ValueType, IndexType >](#).

References [schwz::Settings::executor](#), [schwz::SchwarzBase< ValueType, IndexType >::global_solution](#), [schwz::SchwarzBase< ValueType, IndexType >::interface_matrix](#), [schwz::SchwarzBase< ValueType, IndexType >::local_rhs](#), [schwz::Metadata< ValueType, IndexType >::local_size_x](#), [schwz::SchwarzBase< ValueType, IndexType >::local_solution](#), [schwz::Metadata< ValueType, IndexType >::num_subdomains](#), and [schwz::Settings::overlap](#).

```

817 {
818     using vec_vtype = gko::matrix::Dense<ValueType>;
819     auto one = gko::initialize<gko::matrix::Dense<ValueType>>(
820         {1.0}, settings.executor);
821     auto neg_one = gko::initialize<gko::matrix::Dense<ValueType>>(
822         {-1.0}, settings.executor);
823     auto local_size_x = metadata.local_size_x;
824     local_solution->copy_from(local_rhs.get());
825     if (metadata.num_subdomains > 1 && settings.overlap > 0) {
826         auto temp_solution = vec_vtype::create(
827             settings.executor, local_solution->get_size(),
828             gko::Array<ValueType>::view(settings.executor,
829                 local_solution->get_size()[0],
830                 global_solution->get_values()),
831             1);
832         interface_matrix->apply(neg_one.get(), temp_solution.get(), one.get(),
833             local_solution.get());
834     }
835 }

```

The documentation for this class was generated from the following files:

- [restricted_schwarz.hpp \(04a42d4\)](#)
- [/home/runner/work/schwarz-lib/schwarz-lib/source/restricted_schwarz.cpp \(04a42d4\)](#)

7.17 UmfpackError Class Reference

[UmfpackError](#) is thrown when a METIS routine throws a non-zero error code.

```
#include <exception.hpp>
```

Public Member Functions

- [UmfpackError](#) (const std::string &file, int line, const std::string &func, int error_code)
Initializes a METIS error.

7.17.1 Detailed Description

[UmfpackError](#) is thrown when a METIS routine throws a non-zero error code.

7.17.2 Constructor & Destructor Documentation

7.17.2.1 UmfpackError()

```
UmfpackError::UmfpackError (
    const std::string & file,
    int line,
    const std::string & func,
    int error_code ) [inline]
```

Initializes a METIS error.

Parameters

<i>file</i>	The name of the offending source file
<i>line</i>	The source code line number where the error occurred
<i>func</i>	The name of the METIS routine that failed
<i>error_code</i>	The resulting METIS error code

```
205         : Error(file, line, func + ": " + get_error(error_code))
206     {}
```

The documentation for this class was generated from the following files:

- exception.hpp (04a42d4)
- /home/runner/work/schwarz-lib/schwarz-lib/source/exception.cpp (04a42d4)

7.18 schwz::Utils< ValueType, IndexType > Struct Template Reference

The utilities class which provides some checks and basic utilities.

```
#include <utils.hpp>
```

7.18.1 Detailed Description

```
template<typename ValueType = gko::default_precision, typename IndexType = gko::int32>  
struct schwz::Utils< ValueType, IndexType >
```

The utilities class which provides some checks and basic utilities.

Template Parameters

<i>ValueType</i>	The type of the floating point values.
<i>IndexType</i>	The type of the index type values.

[Utils](#)

The documentation for this struct was generated from the following files:

- `utils.hpp` (04a42d4)
- `/home/runner/work/schwarz-lib/schwarz-lib/source/utils.cpp` (04a42d4)

Index

- BadDimension, [19](#)
 - BadDimension, [19](#)
- Communicate, [9](#)
- CudaError, [28](#)
 - CudaError, [28](#)
- CusparsError, [29](#)
 - CusparsError, [29](#)
- exchange_boundary
 - schwz::Communicate, [25](#)
 - schwz::SolverRAS, [49](#)
- explicit_laplacian
 - schwz::Settings, [47](#)
- generate_rhs
 - schwz::Initialize, [31](#)
- global_get
 - schwz::Communicate::comm_struct, [22](#)
- global_put
 - schwz::Communicate::comm_struct, [22](#)
- Initialization, [10](#)
- is_local_neighbor
 - schwz::Communicate::comm_struct, [23](#)
- local_get
 - schwz::Communicate::comm_struct, [23](#)
- local_put
 - schwz::Communicate::comm_struct, [23](#)
- local_solver_tolerance
 - schwz::Metadata, [38](#)
- local_to_global_vector
 - schwz::Communicate, [26](#)
- MetisError, [38](#)
 - MetisError, [39](#)
- naturally_ordered_factor
 - schwz::Settings, [47](#)
- partition
 - schwz::Initialize, [32](#)
- print_matrix
 - schwz::SchwarzBase, [42](#)
- print_vector
 - schwz::SchwarzBase, [43](#)
- ProcessTopology, [15](#)
- remote_get
 - schwz::Communicate::comm_struct, [23](#)
- remote_put
 - schwz::Communicate::comm_struct, [24](#)
- run
 - schwz::SchwarzBase, [43](#)
- Schwarz Class, [11](#)
- SchwarzBase
 - schwz::SchwarzBase, [41](#)
- schwz, [15](#)
- schwz::CommHelpers, [16](#)
- schwz::Communicate
 - exchange_boundary, [25](#)
 - local_to_global_vector, [26](#)
 - setup_windows, [26](#)
 - update_boundary, [27](#)
- schwz::Communicate< ValueType, IndexType >, [24](#)
- schwz::Communicate< ValueType, IndexType >↔
 - ::comm_struct, [21](#)
- schwz::Communicate::comm_struct
 - global_get, [22](#)
 - global_put, [22](#)
 - is_local_neighbor, [23](#)
 - local_get, [23](#)
 - local_put, [23](#)
 - remote_get, [23](#)
 - remote_put, [24](#)
- schwz::Initialize
 - generate_rhs, [31](#)
 - partition, [32](#)
 - setup_global_matrix, [33](#)
 - setup_local_matrices, [34](#)
 - setup_vectors, [35](#)
- schwz::Initialize< ValueType, IndexType >, [30](#)
- schwz::Metadata
 - local_solver_tolerance, [38](#)
 - tolerance, [38](#)
- schwz::Metadata< ValueType, IndexType >, [36](#)
- schwz::Metadata< ValueType, IndexType >::post_↔
 - process_data, [39](#)
- schwz::PartitionTools, [17](#)
- schwz::SchwarzBase
 - print_matrix, [42](#)
 - print_vector, [43](#)
 - run, [43](#)
 - SchwarzBase, [41](#)
- schwz::SchwarzBase< ValueType, IndexType >, [40](#)
- schwz::Settings, [45](#)
 - explicit_laplacian, [47](#)
 - naturally_ordered_factor, [47](#)
- schwz::Settings::comm_settings, [20](#)

- schwz::Settings::convergence_settings, [28](#)
- schwz::Solve< ValueType, IndexType >, [47](#)
- schwz::SolverRAS< ValueType, IndexType >, [48](#)
- schwz::SolverRAS
 - exchange_boundary, [49](#)
 - setup_local_matrices, [50](#)
 - setup_windows, [53](#)
 - SolverRAS, [49](#)
 - update_boundary, [55](#)
- schwz::SolverTools, [17](#)
- schwz::Utils< ValueType, IndexType >, [57](#)
- schwz::conv_tools, [16](#)
- schwz::device_guard, [30](#)
- setup_global_matrix
 - schwz::Initialize, [33](#)
- setup_local_matrices
 - schwz::Initialize, [34](#)
 - schwz::SolverRAS, [50](#)
- setup_vectors
 - schwz::Initialize, [35](#)
- setup_windows
 - schwz::Communicate, [26](#)
 - schwz::SolverRAS, [53](#)
- Solve, [12](#)
- SolverRAS
 - schwz::SolverRAS, [49](#)
- tolerance
 - schwz::Metadata, [38](#)
- UmfpackError, [56](#)
 - UmfpackError, [57](#)
- update_boundary
 - schwz::Communicate, [27](#)
 - schwz::SolverRAS, [55](#)
- Utils, [13](#)