CS 6015: Software Engineering

Spring 2024

Lecture 3: Version Control

Last Week

- C++ classes / declaration and implementation
- C++ header files ? Misc code snippet
- Using command line (Shell) to compile
- Makefiles

This Week

- Version/source control
- Testing
- Code review today
- Assignment 2 released due next Tuesday

Working on a project alone


- How to save your data?
 - External HDD
 - Dropbox
- What problems would you face?
 - Different saved versions
 - Early and frequent savings
 - Conflicts
- Program breaks and need to restore your code/data
 - Which is the latest copy?
 - What happens if some intermediate version of the project was not copied

Working on a project in a team


- How to save your data?
 - Shared folder
 - Exchange code via email/slack
- How would you need to handle?
 - Maintaining different versions on the shared folder.
 - Synching changes.
- Solution
 - Version control (Source control)

Version control

- Main components
 - Git: distributed version control system for source code management
 - Github: web-based hosting service to store the data remotely



Git operations: Globally



git clone <url>

 creates a local copy of the central repository


Before pushing new changes:

- **git add:** add changes in the working directory to the staging area.
- **git commit –m "msg":** Commit the staged snapshot to the project history


Then:

- git push: apply changes in local repo to central repo
- git pull: apply changes in central repot to local repo

Working folder




Working area







Local Repository




Working area






Staging area

Local Repository



Git


- Consider a supermarket program
- How to add some new features?
 - Check sold items
 - Check duplicates
 - Find total amount




- Concern
 - Decided not to go with the new features at a later stage
 - Do NOT want to change the files for the working program


Git: branches


- Solution: use branches
- Steps:
 - Create branch: *git branch <name>*
 - Move to branch: git checkout <name>





Git: branches







Add and commit changes to the branch

Once done, move back and merge to master:

- git checkout main
- git merge <branch>


Working area





Staging area

Local Repository



- The **main** branch of your Git repository is for communicating code
- The main branch is not a backup mechanism, don't have a history in main that looks like this:

```
commit a045f9 first cut
commit b788cd part way there
commit 9345ab I was confused
commit cd7723 most tests now pass
...
```

- A commit on the **main** branch should generally be a working version
- But you should absolutely back up your work along the way, and a branch other than main is a fne way to backup work

Create a work branch:

```
$ git branch -d work  // Deletes existing work branch
$ git branch work  // Creates new branch work
$ git checkout work  // Switches HEAD to work branch
```

• Create a **work** branch:


```
$ git branch -d work
$ git branch work
$ git checkout work
```

Make changes and periodically save work


```
$ git add .
$ git commit -m "whatever... work in progress"
$ git push origin work
```

At a working state, switch back to

```
$ git checkout main
$ git merge --squash work // Stages all work changes in main
$ git commit -m "nice description for others to read"
```



Exclude via .gitignore



Exclude via *.gitignore*:

- Compiled executables
- Build intermediate
- IDE ephemeral state
- Backup files
- Finder layout

Git and github: Sketching full example

- At github.com, click the + in the top right and select New repository
- Since it's for homework, make the repository **Private.**
- Your account should be the owner.
- On your machine, make a directory for your repository
- cd there, put fles there incuding .gitignore, and use

Assuming local repo exists

```
$ git init
$ git add .
$ git commit -m "initial version"

* New name of the remote repo

$ git remote add origin git@github.com:user/repo
$ git push -f -u origin main
```


Or: after creating the repo online, git clone ...

Git and github: Sketching full example

- At github.com, click the + in the top right and select New repository
- Since it's for homework, make the repository **Private.**
- Your account should be the owner.
- On your machine, make a directory for your repository
- cd there, put fles there incuding .gitignore, and use

```
$ git init
$ git add .
$ git commit -m "initial version"
$ git branch -M main
$ git remote add origin git@github.com:user/repo
$ git push -u origin main
```

Git operations



git clone <url>

 creates a local copy of the central repository

Before pushing new changes:

- **git add:** add changes in the working directory to the staging area.
- **git commit –m "msg":** Commit the staged snapshot to the project history

Then:


- git push: apply changes in local repo to central repo
- git pull: apply changes in central repot to local repo

Git and github


What could go wrong?


• Scenario 1


• Scenario 2






















Local Repo 1 (Leen's)







Local Repo 1 (Leen's)








Backup slides: More Git























git pull is essentially git fetch && git merge



git pull is essentially git fetch && git merge



git pull is essentially git fetch && git merge

