

## Lab 2 - Linux System Calls

**DUE DATE: January 19 2023**

**Assignment on Linux System Calls. File I/O, fork, signals etc. There are five parts to the assignment: A to E. All have to be done.**

*(A tutorial on basic Linux programming is also included with this assignment.)*

### **Submission Details:**

- a) Create a directory named lab2 in your home directory (use only lower case everywhere)
- b) Create executables named a, b, c, and d for the programs described under A, B, C, and D below respectively. (So, if your program A is in a.c then you do `gcc -o a a.c`)

**(A) You are to write a C program that prints out all of its command-line arguments except those that begin with a dash.** [Hint: find out about `argc` and `argv`.]

For example, after compiling your program into the file `a.out`, entering the command

`a.out arg1 -arg2 arg3`

prints

`arg1 arg3`

including a newline so your next shell prompt is not right after `arg3`. If all arguments begin with a dash, (or if there are no arguments at all) print nothing, that is, do not even print a newline. This is so that a blank line does not appear between the `a.out` command line and your next shell prompt.

**(B) You are to write another C program which will read characters from its standard input `stdin`, count the number of NON-alphabetic ones including newlines (see the file `/usr/include/cctype.h`), that is, count those characters not in the `a-z` range nor in the `A-Z` range, and write out all characters read.**

To read and write characters, this program uses only `stdin` and `stdout`, and only the `stdio` library routines (see `stdio.h`) for input and output (see `getchar` and `putchar`). When it hits EOF in its input, the program will print out the final non-alphabetic count on `stderr` using `fprintf` and then `exit(0)`.

**(C) You are to write yet another C program that reads characters from `stdin`, reverses lowercase and uppercase letters, that is, converts to lowercase all uppercase letters and vice versa (again, see `cctype.h`), and writes the results onto its standard output, `stdout`.**

All characters read should be written whether converted or not. This program uses only `stdin` and `stdout`, and the `stdio` library routines. The program will `exit(0)` when it hits EOF in its input.

---

### **Hints and Notes on Linux Programming**

#### ***Subroutines and Functions***

Declare a function to be of type `void` if it does not return a value, that is, if it is a subroutine rather than a true function. If you absolutely must ignore the output of a system, call or function, then cast the call to `void`.

### *Command-line arguments*

A C main program is actually called with two arguments: argc and argv. argc is the number of command-line arguments the program is invoked with including the program name, so argc is always at least one. argv is a pointer to an array of character strings that contain the arguments, one per string.

Here is a program that echoes its arguments to show how to use these:

```
main (int argc, char *argv[]) /* echo arguments */
/* argv is not a string but an array of pointers */
/* argv[0] is command-line program name */
{
    int i;
    for (i=1; i<argc; i++)
        printf("%s%c", argv[i], (i<argc-1) ? ' ' : '\n');
}
```

Or more cryptically:

```
main (int argc, char *argv[]) /* echo arguments */
{
    while (--argc>0)
        printf((argc>1) ? "%s " : "%s\n", *++argv);
    /* argv[i] and *(argv+i) are same */
}
```

Also argv[i][j] or (\*(argv+i))[j] is the jth character of the ith command-line argument.

### *Standard input and output*

Remember IO is not a part of the C language, but is provided in the "standard IO library" accessed by putting #include <stdio.h> at the beginning of your program or in your include files. This will provide you with the functions getchar, putchar, printf, scanf and symbolic constants like EOF and NULL.

### *File access*

It is also possible to access files other than stdin and stdout directly. First, make the declaration

```
FILE *fopen(), *fp;
```

declaring the open routine and the file pointer. Then, call the open routine

```
fp = fopen(name, mode);
```

where name is a character string and mode is "r" for read, "w" for write, or "a" for append.

Now the following routines can be used for IO:

```
c = getc(fp);
```

```
put(c, fp);
```

and also fprintf, fscanf which have a file argument.

## CS232 Operating Systems Lab - Winter 2023

The last thing to do is close the file (done automatically anyway at program termination) (fflush just to flush but keep the file open):

```
fclose(fp);
```

The three file pointers stdin, stdout, stderr are predefined and can be used anywhere fp above was. stderr is conventionally used for error messages like wrong arguments to a command:

```
if ((fp = fopen(*++argv, "r")) == NULL) {  
    fprintf(stderr, "cat: can't open %s\n", *argv);  
    exit(1); /* close files and abort */  
} else ...
```

### *Storage allocation*

To get some dynamically allocated storage, use calloc(n, sizeof(object)) which returns space for n objects of the given size and should be cast appropriately:

```
char *calloc();
```

```
int *ip;
```

```
...
```

```
ip = (int *) calloc(n, sizeof(int));
```

Use free(p) to return the space.

### *Linux system call interface*

These routines allow access to the Linux system at a lower, perhaps more efficient, level than the standard library, which is usually implemented in terms of what follows.

### *File descriptors*

Small positive integers are used to identify open files. Three file descriptors are automatically set up when a program is executed:

0 - stdin

1 - stdout

2 - stderr

which are usually connected with the terminal unless redirected by the shell or changed in the program with close and dup.

### *Low level I/O*

#### *Opening files:*

```
int fd;
```

```
fd = open(name, rwmodes);
```

## CS232 Operating Systems Lab - Winter 2023

where name is the character string file name and rwmode is 0, 1, 2 for read, write, read and write respectively. Better to use ```#include<fcntl.h>"` and defined constants like `O_RDONLY`. A negative result is returned in fd if there is an error such as trying to open a nonexistent file.

### *Creating files:*

```
fd = creat(name, pmode);
```

which creates a new file or truncates an existing file and where the octal constant pmode specifies the chmod-like 9-bit protection mode for a new file. Again a negative returned value represents an error.

### *Closing files:*

```
close(fd);
```

### *Removing files:*

```
unlink(filename);
```

### *Reading and writing files:*

```
n_read = read(fd, buf, n);
```

```
n_written = write(fd, buf, n);
```

will try to read or write n bytes from or to an opened or created file and return the number of bytes read or written in n\_read, for example

```
#define BUFSIZ 1024 /* already defined by stdio.h if included earlier */
```

```
main () /* copy input to output */
```

```
{
    char buf[BUFSIZ];
    int n;
    while ((n = read(0, buf, BUFSIZ)) > 0) write(1, buf, n);
}
```

If read returns a count of 0 bytes read, then EOF has been reached.

### *Changing File Descriptors*

If you have a file descriptor fd that you want to make stdin refer to, then the following two steps will do it:

```
close(0); /* close stdin and free slot 0 in open file table */
```

```
dup(fd); /* dup makes a copy of fd in the smallest unused
          slot in the open file table, which is now 0 */
```

### *Standard library*

Do a ```man stdio"` to find out the standard IO library.

Do a ```man printf"`, ```man getchar"`, and ```man putchar"` for even more information.

## CS232 Operating Systems Lab - Winter 2023

Do a ``man atoi" to find out ascii to integer conversion.

Do a ``man errno" to find out printing error messages and the external variable errno.

Also do a ``man strerror".

Do a ``man string" to find out the string manipulation routines available.

```
strcat    /* concatenation */
strncat
strcmp    /* compare */
strncmp
strcpy    /* copy */
strncpy
strlen    /* length */
index     /* find c in s */
rindex
```

Do a ``man 2 intro" to find out about system calls like open, read, dup, pipe, etc.

You can do a ``man 2 open", ``man 2 dup", etc. to find out more about each one (``man 3 execl", ``man 2 execve", ``man 2 write", ``man 2 fork", ``man 2 close", ``man 3 exit", ``man 2 wait", ``man 2 getpid", ``man 2 alarm", ``man 2 kill", ``man 2 signal").

/usr/include and /usr/include/sys contain .h files that can be included in C programs with the ``#include <stdio.h>" or ``#include<sys/inode.h>" statements, for example.

Other useful ones are ctype.h, errno.h, math.h, signal.h, string.h.

### ***Error messages***

This program shows how to use perror to print error messages when system calls return an error status.

```
#include <stdio.h>
#include <sys/types.h> /* fcntl.h needs this */
#include <fcntl.h>     /* for second argument of open */
#include <errno.h>
void exit(int);        /* gets rid of warning message */
main (int argc, char *argv[]) {
    if (open(argv[1], O_RDONLY) < 0) {
        fprintf(stderr, "errno=%d\n", errno);
        perror("open error in main");
    }
    exit(0);
}
```

### ***grep and find commands***

To search all .c and .h files in the current directory for a string, do this

```
grep "search string" *.c *.h
```

To search for all files with a certain string in their name in the current directory and all its subdirectories, do this

## CS232 Operating Systems Lab - Winter 2023

```
find . -name "*string*" -print
```

To search all files in the current directory and all subdirectories for a certain string, do this

```
find . -exec grep "string" {} /dev/null \;
```

The /dev/null is a LINUX guru trick to get grep to print out the file name in addition to the line containing the matching string.

---

**(D) You are to combine the C programs from (A), (B) and (C) that:**

**(1) reads from the first file argument, reverses lowercase and uppercase letters, that is, makes lowercase all uppercase letters and vice versa, and writes out all characters, whether or not reversed; and**

**(2) reads the above output, counts the number of NON-alphabetic characters (that is, those not in the a-z range nor in the A-Z range), and writes out all characters, whether counted or not, into its second file argument.**

So that you become familiar with the various LINUX system calls and libraries (fork, execl, pipe, creat, open, close, dup, stdio, exit), you will write this program in a certain contrived fashion. The program will be invoked as ``driver file1 file2". Both file arguments are required (print an error message on stderr using fprintf if either argument is missing and then exit(1)). The driver program will open the first file and creat the second file, and dup them down to stdin and stdout. The driver program sets up a pipe and then forks two children.

The first child forked will dup the read end of the pipe down to stdin and then execl the program you have written, count, which will read characters from stdin, count the non-alphabetic ones (see /usr/include/ctype.h), and write all characters out to stdout. The count program uses only stdin and stdout, and only the stdio library routines (see stdio.h) for input and output (see getchar and putchar). The program will print out the final count on stderr using fprintf and then exit(0) when it hits EOF in its input.

The second child forked will dup the write end of the pipe down to stdout and then execl the program you have written, convert, which will read characters from stdin, reverse uppercase and lowercase (again, see ctype.h), and write them all out to stdout. Like count, this program uses only stdin and stdout. Also, it uses only the stdio library routines. The program will exit(0) when it hits EOF in its input.

The reason for creating the children in this order (first the one that reads from the pipe, usually called the second in the pipeline, and then second the one that writes to the pipe, usually called the first in the pipeline -- confusing!!) is that LINUX will not let a process write to a pipe if no process has the pipe open for reading; the process trying to write would get the SIGPIPE signal. So, we create first the process that reads from the pipe to avoid that possibility.

Meanwhile, the parent process, the driver, will close its pipe file descriptors and then call wait (see /usr/include/sys/wait.h) twice to reap the zombie children processes when they finish. Then the parent will exit(0).

Remember to close all unneeded file descriptors, including unneeded pipe ones, or EOF on a pipe read may not be detected correctly. Check all system calls for the error return (-1). For all error and debug messages, use `fprintf(stderr, ...)` or use the function `perror` or the external variable `errno` (see also `/usr/include/errno.h`). Declare a function to be of type `void` if it does not return a value, that is, if it is a subroutine rather than a true function. If you absolutely must ignore the output of a system call or function, then cast the call to `void`.

---

### *Hints and Notes*

#### ***Program skeleton***

o parent opens file1:

```
#include <sys/types.h>
#include <fcntl.h> /* defines O_RDONLY etc. */
...
fd_in = open(argv[1], O_RDONLY); /* not fopen */
/* Check fd_in for -1!!! If it is, then the file does not
   exist or you do not have read permission. */
```

o parent creat's file2:

```
fd_out = creat(argv[2], 0644); /* mode = permissions, here rw-r--r-- */
/* Check fd_out for -1!!! If it is, then the file could not
   be created */
```

o parent uses `close` and `dup` so `stdin` is now file1 (done like children below)

o parent uses `close` and `dup` so `stdout` is now file2: if `dup` returns -1, then a problem has occurred

o parent calls pipe system call to create pipe file descriptors

o parent forks a child to read from pipe:

- this first child manipulates file descriptors
  - use `close`, `dup` so `stdin` is read end of pipe
  - (see text Figure 1-13, similar to else clause)
- this first child execs `count`
  - `execl("count", "count", (char *) 0)`
  - `execl` overlays the child with the binary compiled program in the file given by first argument and the process name becomes the second argument

o parent forks again a child to write to pipe:

- this second child manipulates file descriptors
  - use `close`, `dup` so `stdout` is write end of pipe
  - (similar to if clause in text Figure 1-13)

## CS232 Operating Systems Lab - Winter 2023

```
-- this second child execs convert
execl("convert", "convert", (char *) 0)
```

o parent closes both ends of pipe

o parent waits twice

```
-- use wait(&status); instead of waitpid(-1, &status, 0);
```

Before compiling and running driver, remember to:

o in count.c: `fprintf(stderr, "final count = %d\n", count);`

o `cc -o convert convert.c`, and

o `cc -o count count.c`

The two forks form nested if statements.

```
pipe(...)
if (fork() != 0) { /* parent continues here */
    if (fork() != 0) { /* parent continues here */
        close(write end of pipe...)
        wait(...)
        wait(...)
    } else {
        ... /* second child, writes to pipe */
    }

} else {
    ... /* first child, reads from pipe */
}
```

It is important to check all system calls (open, creat, dup, etc.) for a return value  $< 0$ , particularly -1, because such a return value means an error has occurred. If you just let your program continue to execute, it will just dump core at some later time and you will not know why.

It is IMPERATIVE that the parent and the first child forked (the one to read the pipe) close their write end file descriptors to the pipe. If they do not do this, then the first child will never get EOF reading from the pipe, even after the second child has sent everything. This is because EOF on a pipe is not indicated until ALL write file descriptors to the pipe are closed. If the parent and first child fail to close their file descriptors for the write end of the pipe, the program will hang forever (until killed). Furthermore, the parent must close its copy of the file descriptor to the write end of the pipe BEFORE the waits, not after, or deadlock will result. And the first child forked (the one to read the pipe) must close its file descriptor to the write end of the pipe before it starts reading the pipe, not after, or deadlock will result.

### *How dup works*

`dup(fd)` looks for the smallest unused slot in the process descriptor table and makes that slot point to the same file, pipe, whatever, that `fd` points to. For example, each process starts as



## CS232 Operating Systems Lab - Winter 2023

process descriptor table

slot #	points to
0 (stdin)	keyboard
1 (stdout)	screen
2 (stderr)	screen

If the process does a

```
fd_in = open("file1", ...  
fd_out = creat("file2", ...
```

then the table now looks like

process descriptor table

slot #	points to
0	keyboard
1	screen
2	screen
3	file1
4	file2

and fd\_in is 3 and fd\_out is 4. Now suppose the program does a

```
close(0);  
dup(fd_in);  
close(fd_in);
```

After the close(0), the table will look like

process descriptor table

slot #	points to
0	-- unused --
1	screen
2	screen
3	file1
4	file2

and after the dup(fd\_in), the table will look like

process descriptor table

slot #	points to
0	file1
1	screen

```

2      screen
3      file1
4      file2

```

and after the `close(fd_in)`, the table will look like  
process descriptor table

```

-----
slot #    points to
-----
0         file1
1         screen
2         screen
3         -- unused --
4         file2
-----

```

**(E) You are to modify part (D) of your C program. This is to get you familiar with more of the various LINUX system calls and libraries (`setjmp`, `longjmp`, `getpid`, `alarm`, `read`, `write`, `kill`, `signal`). The program will be invoked as `driver [-n] [file1] [file2]`. All arguments are optional. If there is just one file, then the parent opens it for reading, and dups it down to `stdin`. If there are two files, then we have the same situation as part (D) above. If there are no files, then the parent leaves its `stdin` and `stdout` alone. (The other case could be handled at the command level by invoking the driver as `driver [-n] >file2`).**

If the `-n` argument is present, where `n` is a positive decimal number, then the first child forked, the one that is going to overlay itself with the count program, passes the entire `-n` argument to the program `count`, which overlays it. The first child does this in its `execl` statement. (It is as if the command `count -n` had been entered).

The parent sets up a pipe and forks two children, as in part (D). Before going into its wait loop, waiting for the children to complete, the parent (worried about children getting hung) sets up a signal handler for the `SIGALRM` signal (see `/usr/include/signal.h`), using the signal system call. The parent next saves its stack environment, using the `setjmp` library routine (see `/usr/include/setjmp.h`). The parent then sets an alarm to go off in 15 seconds, using the alarm system call. Finally, the parent enters its wait loop, as in part (D). The parent looks something like Figure 1.

If both children exit normally (`exit(0)`) before the alarm goes off, then the parent prints a `normal children exit` message on `stderr`, and then does an `exit(0)` itself. On the other hand, if the alarm goes off, then the parent's signal handler for the arriving `SIGALRM` signal will do a `longjmp`, causing the parent to kill both children, using the `kill` system call, with the `SIGTERM` signal, and to print on `stderr` a message like `read timeout in second child, killing both children.` The parent then waits again for both children and does an `exit(1)`. The final possibility for the parent to handle is if one of the children terminates abnormally before the alarm goes off. (See below for the case when the program `count` can `exit(2)`.) If this happens, then the parent should print an informative message on `stderr`, try to kill the other child if it is still alive, wait again, and then `exit(1)` itself.

## CS232 Operating Systems Lab - Winter 2023

Each child, after the fork but before the `execl`, should print its pid (process id) on `stderr`, using the `getpid` system call. Both programs `convert` and `count` need to have signal handlers for the `SIGTERM` signal. The handlers should print on `stderr` a message like `"I've been killed"` and then `exit(1)`.

The second child forked operates as in part (D). However the program `convert`, which overlays the second child, needs to be modified. Instead of using `stdio`, it will use the `read` and `write` system calls directly. Pass to `read` and `write` an array of size `BUFSIZ` (defined in `stdio.h`) rather than reading one char a time. It will `exit(0)` upon hitting EOF on `stdin`. Also, you will need to add a signal handler to `convert` for the `SIGPIPE` signal that it may get (see below) if `count` terminates prematurely. The signal handler should print a message like `"I've been killed because my pipe reader died!"` on `stderr` and then `exit(2)`.

The first child forked operates as in part (D). However the program `count`, which overlays the first child, needs to be modified. If the `-n` argument has been passed to it, the program `count` reads the number `n` (see `atoi`, `strcmp`, and `/usr/include/string.h`) and uses it as the maximum number of characters to write to its `stdout`. It will `exit` after writing this number of characters to `stdout`. If there is no argument `-n` passed, then `count` writes all characters to its `stdout`.

Remember that `count` prints on `stderr` with `fprintf` the number of non-alphabetic characters read and written. Since `atoi` returns 0 if it is passed a string that is not an integer, only positive numbers are acceptable for `n`. So, if `atoi` returns 0 or a negative number, then `count` should print an informative message on `stderr` and do an `exit(2)`.

This may cause LINUX to kill the second child forked, `convert`, with a `SIGPIPE` signal. This would happen if `convert` is reading a large file and still actually writing to the pipe (the `SIGPIPE` is generated when `convert` tries to write to a pipe with no reader). Remember to add a signal handler to `convert` for this possibility. If the input file or data is short, it may happen that `convert` can run to completion and `exit` before `count` can detect an illegal `-n` argument. So a `SIGPIPE` may or may not occur when the `-n` argument is illegal. For testing your code when the `-n` argument is illegal, you can put a `sleep(5)` in `convert` so it hangs around long enough for the parent to see that `count` has done an `exit(2)`. Or have the program read from a very big file.

Note: On part (E) of the warm-up programming assignment, be careful when checking out the part of your program that deals with an invalid `"-n"` argument passed to `count`. If `count` does an `exit(2)` when it detects an invalid `"-n"` passed to it, then what actually happens is that the second child, `convert`, may get a `SIGPIPE` signal, because it might try some more writes to a pipe that now has no reader (`count` has died). So the parent will probably get an error message when it tries to kill the second child, `convert`. Not to worry: just print out an informative message if `kill` returns -1, `"second child already dead"`, and then have the parent do its `wait`s, and then `exit`. Also remember that `fork` returns to the parent the pid of the child and that `wait` returns the pid of the child reaped to the parent (or -1 if the parent has no children).

The exit status of a reaped child is returned to the parent in the status variable that the parent passed to `wait`. The include file `/usr/include/sys/wait.h` defines a macro `WEXITSTATUS(status)` that can be used to extract the number the child passed to `exit` when the child terminated. Question: `"I don't understand the purpose of WEXITSTATUS(). I thought when wait(&status) returned, status would`

## CS232 Operating Systems Lab - Winter 2023

contain the value that the child exited with. If that's the case, then why do I need WEXITSTATUS() to get the exit value?" Answer: WEXITSTATUS() is a macro defined in <wait.h> that extracts the exit value from status. The exit value is only 8 bits and it has been masked into status along with other information that you can read about in the Solaris man page.

Check all system calls for the error return (less than zero or -1). For all error and debug messages, use ``fprintf(stderr, ...)," or use the function perror (do a ``man perror" on the Suns), or use the external variable errno.

---

**Figure 1: Parent skeleton code.**

```
#include <signal.h>
#include <setjmp.h>

...
jmp_buf env;
...
main(int argc, char *argv[]) {
    ...
    signal(SIGALRM, handler);
    ...
    if (setjmp(env) != 0) {
        /* longjmp below causes setjmp to return here */
        /* kill children ... */
        /* wait loop (as below) for children ... */
        exit(1);
    }
    /* setjmp returns here first time called */
    ...
    /* open, creat, pipe, close, dup, fork 2 children ... */
    ...
    alarm(15);          /* set alarm for 15 seconds */
    while ((pid = wait(&status)) > 0) { /* wait loop */
        fprintf(stderr, "child pid=%d reaped with exit status=%d\n",
            pid, WEXITSTATUS(status));
        /* if pid is count's and exit status == 2, kill convert ... */
    }
    alarm(0);          /* cancel alarm */
    ...
    exit(0);
}

void handler() {
    fprintf(...
    longjmp(env, 1);
    exit(1);}
}
```

---