

FRMS Audit Page Requirements

UI columns, filters, detail sections, and timeline structure

1. Purpose

The Audit Page is an investigation and compliance screen. It should help an admin or fraud analyst trace the full lifecycle of a transaction across services, including transaction intake, fraud evaluation, scoring, decision, event publishing, audit creation, and analytics creation.

2. Main Audit Table Columns

Column	Source	Purpose
auditLogId	se_frms_audit_log.id	Unique audit log identifier.
transactionId	se_frms_audit_log.transaction_id	Used to open complete audit trail for one transaction.
serviceName	se_frms_audit_log.service_name	Shows which microservice generated the event.
eventType	se_frms_audit_log.event_type	Shows event type such as FRAUD_EVALUATION_COMPLETED.
referenceId	se_frms_audit_log.reference_id	Service-specific related ID, such as decisionId or scoringId.
finalDecision	eventDetails.finalDecision	ALLOW, REVIEW, or BLOCK decision.
totalRiskScore	eventDetails.totalRiskScore	Final fraud risk score.
status	se_frms_audit_log.status	Active/inactive audit record status.
performedBy	se_frms_audit_log.performed_by	Actor or service that performed the action.
createdBy	se_frms_audit_log.created_by	Creator of audit record, usually AUDIT_SERVICE.
createdAt	se_frms_audit_log.created_at	Audit record creation timestamp.
updatedAt	se_frms_audit_log.updated_at	Last updated timestamp.
action	Frontend only	View Details action.

3. Recommended Filters

Filter	Type	Backend Field
transactionId	Text / UUID	transaction_id
serviceName	Dropdown	service_name
eventType	Dropdown	event_type
finalDecision	Dropdown	event_details->finalDecision
status	Boolean dropdown	status
fromDate	Date-time	created_at
toDate	Date-time	created_at
referenceId	Text / UUID	reference_id

4. Audit Details View

- auditLogId
- transactionId
- serviceName
- eventType
- referenceId
- performedBy
- status

- createdBy
- createdAt
- updatedAt

5. Event Details Section

Field	Source	Description
scoringId	eventDetails.scoringId	Scoring record linked to the transaction.
decisionId	eventDetails.decisionId	Decision record linked to the transaction.
totalRiskScore	eventDetails.totalRiskScore	Calculated cumulative risk score.
finalDecision	eventDetails.finalDecision	Final decision from Decision Service.
decisionReason	eventDetails.decisionReason	Reason generated from policy thresholds.
triggeredRules	eventDetails.triggeredRules	Matched fraud rules and their scores.
transactionData	eventDetails.transactionData	Full transaction payload snapshot.
eventTimestamp	eventDetails.eventTimestamp	Fraud event timestamp from Fraud Engine.

6. Transaction Data Section

Field	Purpose
externalTransactionId	Bank or external reference ID for idempotency.
merchantId	Merchant identifier.
merchantName	Merchant display name.
merchantCategory	Merchant category such as RETAIL.
userId	Customer/user identifier.
customerAccountNumber	Masked customer account number.
amount	Transaction amount.
currency	Transaction currency.
channel	Channel such as UPI, WEB, ATM, POS.
transactionType	Type such as PAYMENT, TRANSFER, WITHDRAWAL.
ipAddress	IP address used for transaction.
latitude	Transaction latitude.
longitude	Transaction longitude.
deviceFingerprint	Device fingerprint value.
deviceId	Device identifier.
os	Device operating system.
appVersion	Application version.
upId	Customer UPI ID.
beneficiaryUpId	Beneficiary or merchant UPI ID.
paymentMode	Payment mode such as UPI_COLLECT.
mobile	Customer mobile number.
location	Human-readable location.

7. Triggered Rules Section

Column	Description
ruleCode	Unique rule code from monolithic fraud rule module.
ruleName	Business-readable rule name.
ruleExpression	Expression evaluated by Scoring Service.
ruleScore	Configured score from rule score module.
calculatedScore	Score added to totalRiskScore after match.
matched	Whether rule matched the transaction.
categoryName	Rule category name.

8. Transaction Timeline Section

Step	Event	Description
1	Transaction received	Transaction Service accepts request.
2	Fraud evaluation started	Transaction Service triggers Fraud Engine.
3	Rules loaded	Fraud Engine uses active rules from local cache.
4	Scoring completed	Scoring Service calculates totalRiskScore and matched rules.
5	Decision completed	Decision Service returns ALLOW, REVIEW, or BLOCK.
6	Fraud event published	Fraud Engine publishes event to Kafka.
7	Audit record created	Audit Service consumes event and stores audit log.
8	Analytics record created	Analytics Service consumes event and stores reporting record.

9. Page Layout Recommendation

- Top area: summary counters for total audit events, blocked transactions, review transactions, and failed events.
- Filter bar: transactionId, serviceName, eventType, finalDecision, date range, and status.
- Main grid: audit table with pagination and View Details action.
- Details drawer/page: audit metadata, event details, transaction data, triggered rules, and timeline.
- Use JSON viewer only as an expandable advanced section, not as the default view.

10. API Support Needed

API	Purpose
GET /api/v1/audit-logs	Paginated audit list for main table.
GET /api/v1/audit-logs/{auditLogId}	Open audit details by audit ID.
GET /api/v1/audit-logs/transaction/{transactionId}	Show full timeline for one transaction.