

```
R3#
R3#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#ip route 10.0.0.0 255.0.0.0 30.0.0.1
R3(config)#ip route 20.0.0.0 255.0.0.0 30.0.0.1
R3(config)#no sh
% Incomplete command.

R3(config)#exit
R3#
*Jul 16 06:45:58.487: %SYS-5-CONFIG_I: Configured from console by console
R3#show ip route
Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
       D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
       N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
       E1 - OSPF external type 1, E2 - OSPF external type 2
       i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
       ia - IS-IS inter area, * - candidate default, U - per-user static route
       o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
       a - application route
       + - replicated route, % - next hop override, p - overrides from PfR
```

Gateway of last resort is not set

```
S      10.0.0.0/8 [1/0] via 30.0.0.1
S      20.0.0.0/8 [1/0] via 30.0.0.1
       30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      30.0.0.0/8 is directly connected, Ethernet0/1
L      30.0.0.2/32 is directly connected, Ethernet0/1
       40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C      40.0.0.0/8 is directly connected, Ethernet0/0
L      40.0.0.1/32 is directly connected, Ethernet0/0
R3#
R3#
R3#
R3#
R3#
```

Very high UV
Now



Search



acer


```
R3#conf t
Enter configuration commands, one per line. End with CNTL/Z.
R3(config)#ip route 10.0.0.0 255.0.0.0 30.0.0.1
R3(config)#ip route 20.0.0.0 255.0.0.0 30.0.0.1
R3(config)#no sh
% Incomplete command.

R3(config)#exit
R3#
*Jul 16 06:45:58.487: %SYS-5-CONFIG_I: Configured from console by console
R3#show ip route
```

Codes: L - local, C - connected, S - static, R - RIP, M - mobile, B - BGP
D - EIGRP, EX - EIGRP external, O - OSPF, IA - OSPF inter area
N1 - OSPF NSSA external type 1, N2 - OSPF NSSA external type 2
E1 - OSPF external type 1, E2 - OSPF external type 2
i - IS-IS, su - IS-IS summary, L1 - IS-IS level-1, L2 - IS-IS level-2
ia - IS-IS inter area, * - candidate default, U - per-user static route
o - ODR, P - periodic downloaded static route, H - NHRP, l - LISP
a - application route
+ - replicated route, % - next hop override, p - overrides from PFR

Gateway of last resort is not set

```
S    10.0.0.0/8 [1/0] via 30.0.0.1
S    20.0.0.0/8 [1/0] via 30.0.0.1
    30.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     30.0.0.0/8 is directly connected, Ethernet0/1
L     30.0.0.2/32 is directly connected, Ethernet0/1
    40.0.0.0/8 is variably subnetted, 2 subnets, 2 masks
C     40.0.0.0/8 is directly connected, Ethernet0/0
L     40.0.0.1/32 is directly connected, Ethernet0/0
```

```
R3#
R3#
R3#
R3#
R3#
```

I



Very high UV
Now



Search



acer

My Computer

My Documents

My Network
Places

Recycle Bin

Internet
ExplorerCisco
ASDM-I...

Old Java ASDM

PuTTY

C:\WINDOWS\system32\cmd.exe

```
Reply from 10.0.0.1: Destination host unreachable.  
Reply from 10.0.0.1: Destination host unreachable.  
Reply from 10.0.0.1: Destination host unreachable.  
Reply from 10.0.0.1: Destination host unreachable.
```

```
Ping statistics for 40.0.0.10:  
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),  
    Approximate round trip times in milli-seconds:  
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
```

```
C:\Documents and Settings\user>ping 40.0.0.10
```

```
Pinging 40.0.0.10 with 32 bytes of data:
```

```
Reply from 40.0.0.10: bytes=32 time=3ms TTL=125  
Reply from 40.0.0.10: bytes=32 time=1ms TTL=125  
Reply from 40.0.0.10: bytes=32 time=1ms TTL=125  
Reply from 40.0.0.10: bytes=32 time=2ms TTL=125
```

```
Ping statistics for 40.0.0.10:  
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),  
    Approximate round trip times in milli-seconds:  
        Minimum = 1ms, Maximum = 3ms, Average = 1ms
```

```
C:\Documents and Settings\user>
```




My Documents

My Computer

My Network Places

Recycle Bin

Internet Explorer

Cisco ASDM-I...

Old Java ASDM

PuTTY

C:\WINDOWS\system32\cmd.exe

Microsoft Windows XP [Version 5.1.2600]
(C) Copyright 1985-2001 Microsoft Corp.

C:\Documents and Settings\user>ping 10.0.0.10

Pinging 10.0.0.10 with 32 bytes of data:

Reply from 10.0.0.10: bytes=32 time=2ms TTL=125
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125
Reply from 10.0.0.10: bytes=32 time=1ms TTL=125

Ping statistics for 10.0.0.10:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 1ms, Maximum = 2ms, Average = 1ms

C:\Documents and Settings\user>



Search

