# 2. Requirement Analysis Phase

Script-Controlled ACL: Restrict Record Access Based on Field Value

## Functional Requirements

| ID | Requirement |
|---|---|
| FR-1 | Create a test user (EEE User) and custom roles bb1, bb2, bb3 and bb4; assign all roles to the EEE User. |
| FR-2 | Create a custom table Institution Details (u_institution_details) with the required fields. |
| FR-3 | Populate the table with records for the ECE, EEE and CSE branches. |
| FR-4 | READ ACL: users with bb1 can view only records where Branch is EEE; admins see all records. |
| FR-5 | CREATE ACL: users with bb2 can use the New button. |
| FR-6 | WRITE ACL: users with bb3 can edit records. |
| FR-7 | DELETE ACL: users with bb4 can delete records. |
| FR-8 | Users without the required role must not see any records. |

## Data Requirements: u_institution_details

| Field | Type |
|---|---|
| Student Roll Number | Auto Number |
| Student Name | Reference (User) |
| Faculty Name | Reference (User) |
| Branch | Choice (ECE, EEE, CSE) |
| Email | String |
| Phone Number | String |
| Description | Multi String |

## Security Requirements

- Administrators retain full access to all records regardless of branch.
- Access is denied by default; the ACL script returns false for anyone who is not an admin or a bb1 holder.
- The security_admin role must be elevated to create or edit ACLs.

## Environment and Access Requirements

- A ServiceNow instance with **admin** access.
- Ability to elevate to **security_admin** and to impersonate users.

- Estimated effort: 3 hours.

## Assumptions

- The instance is a development or training instance, not production.
- The test user's email is eeeuser@gmail.com.