4. Project Planning Phase

Script-Controlled ACL: Restrict Record Access Based on Field Value

Scope

Deliver a working script-controlled ACL setup for the Institution Details table covering READ, CREATE, WRITE and DELETE, verified through impersonation. Total lab duration: **3 hours**.

Work Breakdown

Milestone / Task	Key activities	Suggested time
Milestone 1: Users and roles	Create EEE User; create roles bb1 to bb4; assign roles to the user	30 min
Table creation	Create u_institution_details, add 7 fields, add records for ECE, EEE and CSE	30 min
READ ACL	Elevate security_admin; create the advanced ACL with role, condition and script; impersonate and verify	40 min
CREATE ACL	Create ACL requiring bb2; verify the New button	20 min
WRITE ACL	Create ACL requiring bb3; verify editing	20 min
DELETE ACL	Create ACL requiring bb4; verify deleting	20 min
Documentation and demo	Record results and prepare the demonstration	20 min

Sequence and Dependencies

- Users and roles must exist before any ACL can reference them.
- The table and its records must exist before the ACLs are created.
- Each ACL is verified before the next one is added, because the roles build on each other.

Risks and Mitigation

Risk	Mitigation
Cannot create ACLs	Elevate the security_admin role first
Records not visible when testing	Confirm the user has the bb1 role and that records with Branch = EEE exist
Results confused between users	Impersonate one user at a time and switch back to admin between checks
Lockout from own data	Keep admin access; the script always returns true for admin

Deliverables

- Users, roles, table and records configured in the instance.

- Four ACLs (Read, Create, Write, Delete).
- Test evidence and project documentation.