6. Project Testing Phase

Script-Controlled ACL: Restrict Record Access Based on Field Value

Test Approach

Testing is done by impersonation. After each ACL is created, the relevant user is impersonated and the Institution Details list (**u_institution_details.list**) is opened. The admin account is used as the baseline.

Test Cases

ID	ACL	User / roles	Expected result
TC-1	Read	User with bb1	Can view only EEE branch records
TC-2	Read	User without bb1	Cannot view any records
TC-3	Read	Admin	Can view all records regardless of branch
TC-4	Create	User with bb1 and bb2	Sees only EEE branch records and the **New** button
TC-5	Write	User with bb1, bb2 and bb3	Can view and edit EEE branch records, and has the New button
TC-6	Delete	User with bb1, bb2, bb3 and bb4	Can view, create, edit and delete EEE branch records

Results Log

Fill in after executing each test case in your instance.

ID	Actual result	Pass / Fail	Notes
TC-1			
TC-2			
TC-3			
TC-4			
TC-5			
TC-6			

Troubleshooting Checks

- Confirm the security_admin role was elevated before editing ACLs.
- Confirm the ACL is Active and the Name is exactly u_institution_details.
- Confirm the impersonated user actually holds the expected roles.
- Confirm records exist for each branch value (ECE, EEE, CSE).