8. Project Demonstration Phase

Script-Controlled ACL: Restrict Record Access Based on Field Value

Demo Objective

Show live that access to Institution Details records changes as roles and ACLs are added, and that administrators keep full access. Suggested demo length: 10 to 15 minutes.

Demo Flow

Step	Action	What to show
1	Log in as admin; open u_institution_details.list	Records for ECE, EEE and CSE all visible
2	Show users, roles bb1 to bb4 and the ACL record with its condition and script	How the READ ACL is configured
3	Impersonate EEE User (bb1 only)	Only EEE branch records are listed
4	Impersonate a user without bb1	No records are visible
5	Switch back to admin	All records visible regardless of branch
6	Show the CREATE ACL (bb2) and test as EEE User	The New button appears
7	Show the WRITE ACL (bb3) and edit a record	Editing works
8	Show the DELETE ACL (bb4) and delete a record	Deletion works

Before You Present

- Make sure records exist for all three branches.
- Confirm EEE User holds the roles you intend to demonstrate.
- Keep the list URL (u_institution_details.list) ready in the All menu.
- Remember to end impersonation between users.

Key Talking Points

- Roles alone are too coarse; the data condition and script give record-level control.
- Admin bypass is explicit in the script; everything else is denied by default.
- Separate roles for read, create, write and delete give fine-grained control.

Closing

Summarize the outcome: script-controlled ACLs enforce record-level security across forms, lists and Service Portal interfaces, protecting sensitive data from unauthorized viewing, modification, creation and deletion.