



Permit #: 910990
API: 42-479-45468
AFE: 3205013
SPUD: 1/5/2026
RIG: Nabors X19

Galvan Ranch A933H

LAT: 28.074653° N
LONG: 99.622852° W
SUR: Fenstermaker
GL: 761.55
KB: 32.5

Top of Surface Cement
@ +/- 0' MD

Top of Intermediate Cement
@ +/- 0' MD

Top of Production Cement
@ +/- 0' MD

20" Surface Conductor @ 80' BGL

Surface Hole Size: 17.5"
Surface Casing @ +/- 2,650' BGL
13 3/8"-54.5#-J55-BTC

Intermediate Hole Size: 12.25"
Intermediate Casing @ +/- 8,530' MD
9 5/8"-40#-P110HC-BTC

Production Hole Size: 8.75"
Production Casing @ +/- 22,358' MD
5.5"-23#-P110CY-Talon

SURFACE CEMENT DATA

Shoe @	2,650'	BGL	Excess	Design		
Lead Top	0'		80% OH	To Surface	Class A @	12.2 ppg
Tail Top	2,120		20% OH	TOT @ 80% of String Length	Class A @	14.8 ppg

MUD DATA

Surface Hole	WBM	8.8 - 9.5	ppg @ TD
Intermediate Hole	OBM	12.0 - 12.5	ppg @ TD
Production Hole	OBM	13.5 - 14.0	ppg @ TD

INTERMEDIATE CEMENT DATA

Shoe @	8,530'	RKB	Excess	Design		
Slurry:			15%	To surface	Class H @	13.2 ppg
Lead Top	0'		15%	1000' Fill f/ Shoe	Class H @	16.2 ppg
Tail Top	-147'					

PRODUCTION CEMENT DATA

Shoe @	22,358'	RKB	Excess	Design		
Lead #1 Top	0'		5%	Surface	Class H @	14.5 ppg
Lead #2 Top	5,156'		5%	1,000' Above Olmos Top		14.5 ppg
Tail Top	8,655'		5%	TOT 100' Above KOP	Class H @	15.5 ppg

Directional Data

KOP @	8,726'	MD/	8,655'	TVD
EOC @	9,617'	MD/	9,228'	TVD
EOL @	22,373'	MD/	9,244'	TVD
DLS @	10"	/100 ft		

TEMPERATURE DATA

Lateral Length: 12,756'

Total Depth: 22,373' MD

Csg String	Depth Reference [ft TVD]	BHST [°F]
Surface	Top of Tail Slurry	119
	Surface CSG Shoe	128
Intermediate	Top of Tail Slurry	77
	Intermediate Casing Shoe	236
Production	Top of Lead #2 Slurry	174
	Top of Tail Slurry	225 - 227
	Production Csg Shoe	251 - 251

Drl. Engr.	Blake Ropers
Date	12/30/2025