

Week – 2 :

Session – 6 : Functional Programming using map() :

Shuffle the Array :

Program:

```
class Solution {  
  
    public int[] shuffle(int[] nums, int n) {  
  
        int[] ans = new int[2 * n];  
  
        for (int i = 0; i < n; i++) {  
  
            ans[2 * i] = nums[i];  
  
            ans[2 * i + 1] = nums[i+n];  
  
        }  
  
        return ans;  
  
    }  
}
```

Output :

The screenshot shows the LeetCode interface for the problem "1470. Shuffle the Array". The problem description states: "Given the array `nums` consisting of `2n` elements in the form $[x_1, x_2, \dots, x_n, y_1, y_2, \dots, y_n]$. Return the array in the form $[x_1, y_1, x_2, y_2, \dots, x_n, y_n]$." Three examples are provided: Example 1 with input `nums = [2,5,1,3,4,7]` and `n = 3`, output `[2,3,5,4,1,7]`; Example 2 with input `nums = [1,2,3,4,4,3,2,1]` and `n = 4`, output `[1,4,2,3,3,2,4,1]`; Example 3 with input `nums = [1,1,2,2]` and `n = 2`, output `[1,2,1,2]`. Constraints include `1 <= n <= 500`, `nums.length == 2n`, and `1 <= nums[i] <= 10^3`. The code editor shows the provided Java solution. The test result section shows "Accepted" with a runtime of 0 ms, and three test cases (Case 1, Case 2, Case 3) all passed. The input for Case 1 is `nums = [2,5,1,3,4,7]` and `n = 3`, with the expected output `[2,3,5,4,1,7]`.