

Rajalakshmi Engineering College

Name: Praveen Kumar
Email: 240801247@rajalakshmi.edu.in
Roll no: 240801247
Phone: 7550385160
Branch: REC
Department: I ECE AF
Batch: 2028
Degree: B.E - ECE

Scan to verify results



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 7_COD_Question 3

Attempt : 2
Total Mark : 10
Marks Obtained : 7.5

Section 1 : Coding

1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

Input Format

The first line consists of an integer n , representing the number of contact pairs to be inserted.

Each of the next n lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string *k*, representing the contact to be checked or removed.

Output Format

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next *n* - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!"
2. The next *n* lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

Sample Test Case

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

Answer

// You are using GCC

```
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {  
    static int i = 0;  
    strcpy(dict->pairs[i].key, key);  
    strcpy(dict->pairs[i].value, value);  
    i++;  
}
```

```

}
void removeKeyValuePair(Dictionary *dict, const char *key) {
    for(int i = 0; i < dict->capacity; i++) {
        if(strcmp(dict->pairs[i].key, key) == 0) {
            strcpy(dict->pairs[i].key, "");
            strcpy(dict->pairs[i].value, "");
            break;
        }
    }
}
int doesKeyExist(Dictionary *dict, const char *key) {
    if(strcmp(key, "") == 0) {
        return 0;
    }
    for(int i = 0; i < dict->capacity; i++) {
        if(strcmp(dict->pairs[i].key, key) == 0) {
            return 1;
        }
    }
    return 0;
}
void printDictionary(Dictionary *dict) {
    for(int i = 0; i < dict->capacity; i++) {
        if(strcmp(dict->pairs[i].key, "") == 0)
            continue;
        printf("Key: %s; Value: %s\n", dict->pairs[i].key, dict->pairs[i].value);
    }
}

```

Status : Partially correct

Marks : 7.5/10