

How to fix OOS (Out Of Sync) rows in GoldenGate replication

Fix OOS updates

```
--Run the following command as the first step of fixing data or disable/enable constraints
exec dbms_streams.set_tag (hextoraw(<number>));

--Fix single OOS row
update
  pspadm.<table_name>
set (
  <list_of_oos_column_names>
)=(select <list_of_oos_column_names_in_same_order_as_above>
  from pspadm.<table_name>@to_source
  where <primary_key_column> in ('<primary_key_value>')
)
where <primary_key_column> in ('<primary_key_value>');
--eg:
update
  pspadm.PSP_QBDT_TRANSACTION_INFO
set (
  VERSION, MODIFIED_DATE, AGENCY_NAME,
  ACCOUNT_NAME, MEMO, ON_SERVICE, CLEARED,
  COMP_ADJUST_SUBMISSION_FK, LIABILITY_ADJUSTMENT_FK
)=(select VERSION,MODIFIED_DATE,AGENCY_NAME,
  ACCOUNT_NAME,MEMO,ON_SERVICE,CLEARED,
  COMP_ADJUST_SUBMISSION_FK,LIABILITY_ADJUSTMENT_FK
  from pspadm.PSP_QBDT_TRANSACTION_INFO@to_source
  where QBDT_TRANSACTION_INFO_SEQ in ('cd48728a-e323-4616-98ae-965b228ff44e')
)
where QBDT_TRANSACTION_INFO_SEQ in ('cd48728a-e323-4616-98ae-965b228ff44e');

--validation
select * from pspadm.PSP_QBDT_TRANSACTION_INFO@to_source where QBDT_TRANSACTION_INFO_SEQ='3f77c995-4226-4229-9df0-4ed291623b16'
minus
select * from pspadm.PSP_QBDT_TRANSACTION_INFO where QBDT_TRANSACTION_INFO_SEQ='3f77c995-4226-4229-9df0-4ed291623b16';

--Fix large number of OOS rows
1. Load all primary key values in temp table
sqlldr userid=intuadmin@<db_name> control=load_<table_name>_oos_seq.ctl log=load_<table_name>_oos_seq.log
bad=load_<table_name>_oos_seq.bad

2. Update target table OOS rows as below
set serveroutput on echo on feedback on
begin
for i in (select <primary_key_column> from <temp_table> ) loop
exec dbms_streams.set_tag (hextoraw(<number>));
update <target_table_name>
  set (list_of_oos_column_names)=(select <list_of_oos_column_names_in_same_order_as_in_set_clause>
                                     from <target_table_name>@to_source
                                     where <primary_key_column>= i.<primary_key_value>)
where <primary_key_column>= i.<primary_key_value> ;
commit;
end loop;
end;
/

--eg
set serveroutput on echo on feedback on
begin
for i in (select MONEY_MOVEMENT_TRANSACTION_SEQ,COMPANY_FK from mchoubey.mmt_oos_seq ) loop
```

```

DBMS_OUTPUT.PUT_LINE (i.MONEY_MOVEMENT_TRANSACTION_SEQ);
update pspadm.PSP_MONEY_MOVEMENT_TRANSACTION
    set (VERSION,MODIFIER_ID,MODIFIED_DATE,MM_TRANSACTION_AMOUNT,STATUS)=(select VERSION,MODIFIER_ID,
MODIFIED_DATE,MM_TRANSACTION_AMOUNT,STATUS

from pspadm.PSP_MONEY_MOVEMENT_TRANSACTION@to_source

                                where MONEY_MOVEMENT_TRANSACTION_SEQ=
i.MONEY_MOVEMENT_TRANSACTION_SEQ

                                and COMPANY_FK=i.COMPANY_FK)
where MONEY_MOVEMENT_TRANSACTION_SEQ= i.MONEY_MOVEMENT_TRANSACTION_SEQ
    and COMPANY_FK=i.COMPANY_FK;
commit;
end loop;
end;
/

--validation via veridata

```

Fix OOS inserts

```

exec dbms_streams.set_tag (hextoraw(<number>));
insert into <table_name> select * from <table_name>@to_source where <primary_key_column> in
(<primary_key_values>);

--eg
insert into pspadm.PSP_TAX_PAYMENT_ON_HOLD_REASON select * from pspadm.PSP_TAX_PAYMENT_ON_HOLD_REASON@to_source
where TAX_PAYMENT_ON_HOLD_REASON_SEQ
in ('23afc387-9570-4331-875a-c85e9bb5398e', '2b35e8bc-6b70-487f-84be-e36e8e8e446b', '2c4a1456-4c81-4257-af7d-
11385d671fe8', '478f7a70-d5f9-44b7-a688-588e42b1eab2', '6440168a-7f23-49fc-bdce-de2c47bd122a',
'7f6b54dd-a0a0-4877-b7bd-66fe52993b18', '8e98011e-7fd0-4bd5-8f75-6381e2856472', '9c28613e-0ec8-4c6e-80f4-
979c32a1be9f', 'a9b73ce5-7952-457d-9bd9-d7b69b2bcaed', 'ebfc5c1b-d2d3-4c4a-9150-bbb565c9f841');

--Fix large number of OOS rows
1. Load all primary key values in temp table
sqlldr userid=intuadmin@<db_name> control=load_<table_name>_oos_seq.ctl log=load_<table_name>_oos_seq.log
bad=load_<table_name>_oos_seq.bad

2.
insert into <table_name> select * from <table_name>@to_source where <primary_key_column> in (select
<primary_key_column> from <temp_table_name> );

```

Fix OOS delete

```

exec dbms_streams.set_tag (hextoraw(<number>));
delete from <table_name> where <primary_key_column> in (<primary_key_values>);

--eg
delete from pspadm.PSP_PROPERTY_AUDIT where property_audit_seq in (select property_audit_seq from mchoubey.
propertyaudit_oos_seq);

--Fix large number of OOS rows
1. Load all primary key values in temp table
sqlldr userid=intuadmin@<db_name> control=load_<table_name>_oos_seq.ctl log=load_<table_name>_oos_seq.log
bad=load_<table_name>_oos_seq.bad

2.
delete from <table_name> where <primary_key_column> in (select <primary_key_column> from <temp_table_name>);

```