

Re-Partitioning Steps (PSP_ENTITLEMENT_MESSAGE/ PSP_PAYCHECK_USAGE)

Re-Partitioning

- Stop C2 replication for range tables.
- Stop B Extract.
- Enable Supplemental logging for column LICENSE_NUMBER -- Didn't work
- Using FetchCOLS in B extrcat parameter file
- Restart B Extrcat.
- Create new table *_NEW with new partitioning key
- Exclude the new table and its partition from C2 (C2 --> D2) extrcat. Cache Memory ISSUE
tableexclude pspadm.psp_entitlement_message_new;
tableexclude pspadm.psp_entitlement_message_p*;
- LOAD THE DATA in NEW TABLE FROM OLD table
- Check the count for both the tables.
- Enable REPLICAT IDENTITY FULL GOT THE NEW TABLE

```
alter table pspadm.psp_entitlement_message_new replica identity full;
alter table pspadm.psp_entitlement_message_p0 replica identity full;
alter table pspadm.psp_entitlement_message_p1 replica identity full;
alter table pspadm.psp_entitlement_message_p2 replica identity full;
alter table pspadm.psp_entitlement_message_p3 replica identity full;
alter table pspadm.psp_entitlement_message_p4 replica identity full;
alter table pspadm.psp_entitlement_message_p5 replica identity full;
alter table pspadm.psp_entitlement_message_p6 replica identity full;
alter table pspadm.psp_entitlement_message_p7 replica identity full;
```

- Change the replicat parameter file with new mapping.
Replicat Modification D2 (C2 --> D2)
MAP pspadm.psp_entitlement_message_p*, TARGET pspadm.psp_entitlement_message, KEYCOLS (LICENSE_NUMBER, entitlement_message_seq), thread(4);

-- STOP EXTRCAT FOR C2 (C2 --> D2)

-- Rename the existing table to psp_entitlement_message_BKP
set search_path=pspadm;
alter table pspadm.psp_entitlement_message RENAME to psp_entitlement_message_old;

-- RENAME *_NEW to ORG
set search_path=pspadm;
alter table pspadm.psp_entitlement_message_new RENAME to psp_entitlement_message;

-- Create indexes on org table on the original.
Praveen to give the script

-- Change the keycols mapping in C2 replicat (B --> C2)
Replicat Modification C2 (B --> C2)
MAP pspadm.psp_entitlement_message, TARGET pspadm.psp_entitlement_message, KEYCOLS (LICENSE_NUMBER, entitlement_message_seq), thread(4);

-- Comment the new table entry which was added its partition from C2 (C2 --> D2) extrcat due to Cache Memory ISSUE
--- tableexclude pspadm.psp_entitlement_message_old;
--- tableexclude pspadm.psp_entitlement_message_20*;

-- Create New task for C2 --> D2' for these two newly re-partitioned tables

-- Start C2 Extrcat (Check thoroughly the OLD tables are excluded)

-- Start C2 Replicat (B --> C2)

-- Check if the keycols contains the new C2 primary key (License_Number, entitlement_message_seq)

===== STEPS END =====

Rollback partitioning

pspadm.psp_entitlement_message (new partitioning)
pspadm.psp_entitlement_message_old (old partitioning)

Stop c2 to D2' dms tasks

```
set role=pspadm_owner;
drop table psp_entitlement_message_2012;
drop table psp_entitlement_message_2013;
drop table psp_entitlement_message_2014;
drop table psp_entitlement_message_2015;
drop table psp_entitlement_message_2016;
drop table psp_entitlement_message_2017;
drop table psp_entitlement_message_2018;
drop table psp_entitlement_message_2019;
drop table psp_entitlement_message_2020;
drop table psp_entitlement_message_2021;
drop table psp_entitlement_message_2022;
drop table psp_entitlement_message_2023;
drop table psp_entitlement_message_2024;
drop table pspadm.psp_entitlement_message_old;
```

create psp_entitlement_message_range with old partitioning
li create_table_pem.sql

exclude new table from extract from C2->D2
--copy data from psp_entitlement_message to psp_entitlement_message_range

```
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p0;
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p1;
```

```
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p2;
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p3;
```

```
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p4;
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p5;
```

```
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p6;
insert into pspadm.psp_entitlement_message_range select * from pspadm.psp_entitlement_message_p7;
```

check sanity count of both tables

Change D2 replicat to reflect change in partitioning
MAP pspadm.psp_entitlement_message_20*, TARGET pspadm.psp_entitlement_message, KEYCOLS (entitlement_message_seq), thread(4);

```
-- RENAME *_NEW to ORG
set search_path=pspadm;
alter table pspadm.psp_entitlement_message RENAME to psp_entitlement_message_hash;
alter table pspadm.psp_entitlement_message_range RENAME to psp_entitlement_message;
```

Enable REPLICAT IDENTITY FULL GOT THE NEW TABLE

```
alter table pspadm.psp_entitlement_message replica identity full;
alter table pspadm.psp_entitlement_message_2012 replica identity full;
alter table pspadm.psp_entitlement_message_2013 replica identity full;
alter table pspadm.psp_entitlement_message_2014 replica identity full;
alter table pspadm.psp_entitlement_message_2015 replica identity full;
alter table pspadm.psp_entitlement_message_2016 replica identity full;
alter table pspadm.psp_entitlement_message_2017 replica identity full;
alter table pspadm.psp_entitlement_message_2018 replica identity full;
alter table pspadm.psp_entitlement_message_2019 replica identity full;
alter table pspadm.psp_entitlement_message_2020 replica identity full;
alter table pspadm.psp_entitlement_message_2021 replica identity full;
alter table pspadm.psp_entitlement_message_2022 replica identity full;
alter table pspadm.psp_entitlement_message_2023 replica identity full;
alter table pspadm.psp_entitlement_message_2024 replica identity full;
alter table pspadm.psp_entitlement_message_2025 replica identity full;
alter table pspadm.psp_entitlement_message_2026 replica identity full;
```



```
create pspadm.psp_paycheck_usage_cr_date with old partitioning key
\i create_table_ppu.sql
```

```
exclude new table from extract from C2->D2
copy data from psp_paycheck_usage to psp_paycheck_usage_cr_date
```

```
insert into psp_paycheck_usage_cr_date select * from psp_paycheck_usa_old;
```

```
check sanity count of both tables
```

```
-- RENAME *_NEW to ORG
set search_path=pspadm;
alter table pspadm.psp_paycheck_usage_cr_date RENAME to psp_paycheck_usage;
```

```
Enable REPLICAT IDENTITY FULL GOT THE NEW TABLE.
alter table pspadm.psp_paycheck_usage replica identity full;
alter table pspadm.psp_paycheck_usage_2012 replica identity full;
alter table pspadm.psp_paycheck_usage_2013 replica identity full;
alter table pspadm.psp_paycheck_usage_2014 replica identity full;
alter table pspadm.psp_paycheck_usage_2015 replica identity full;
alter table pspadm.psp_paycheck_usage_2016 replica identity full;
alter table pspadm.psp_paycheck_usage_2017 replica identity full;
alter table pspadm.psp_paycheck_usage_2018 replica identity full;
alter table pspadm.psp_paycheck_usage_2019 replica identity full;
alter table pspadm.psp_paycheck_usage_2020 replica identity full;
alter table pspadm.psp_paycheck_usage_2021 replica identity full;
alter table pspadm.psp_paycheck_usage_2022 replica identity full;
alter table pspadm.psp_paycheck_usage_2023 replica identity full;
alter table pspadm.psp_paycheck_usage_2024 replica identity full;
alter table pspadm.psp_paycheck_usage_2025 replica identity full;
alter table pspadm.psp_paycheck_usage_2026 replica identity full;
```

```
--Change DMS task mappings to reflect new partitioning
```

```
--create indexes
```

```
--remove tableexclude from C2 extract (C2 ->D2)
```