

How to fix OOS (Out Of Sync) rows in GoldenGate replication

Created by Choubey, Mayank, last modified on Sept 03, 2023

Fix OOS updates

```
--Run the following command as the first step of fixing data or disable/enable constraints
exec dbms_streams.set_tag (hextoraw(<number>));

--Fix single OOS row
update
  pspadm.<table_name>
set (
  <list_of_oos_column_names>
  )=(select <list_of_oos_column_names_in_same_order_as_above>
      from pspadm.<table_name>@to_source
      where <primary_key_column> in ('<primary_key_value>'))
where <primary_key_column> in ('<primary_key_value>');
--eg:
update
  pspadm.PSP_QBDT_TRANSACTION_INFO
set (
  VERSION, MODIFIED_DATE, AGENCY_NAME,
  ACCOUNT_NAME, MEMO, ON_SERVICE, CLEARED,
  COMP_ADJUST_SUBMISSION_FK, LIABILITY_ADJUSTMENT_FK
  )=(select VERSION,MODIFIED_DATE,AGENCY_NAME,
          ACCOUNT_NAME,MEMO,ON_SERVICE,CLEARED,
          COMP_ADJUST_SUBMISSION_FK,LIABILITY_ADJUSTMENT_FK
      from pspadm.PSP_QBDT_TRANSACTION_INFO@to_source
      where QBDT_TRANSACTION_INFO_SEQ in ('cd48728a-e323-4616-98ae-965b228ff44e'))
```

```
)
where QBDT_TRANSACTION_INFO_SEQ in ('cd48728a-e323-4616-98ae-965b228ff44e');
```

```
minus
select * from pspadm.PSP_QBDT_TRANSACTION_INFO where QBDT_TRANSACTION_INFO_SEQ='3f77c995-4226-4229-9df0-4ed291623b16';

--Fix large number of OOS rows
1. Load all primary key values in temp table
sqlldr userid=intuadmin@<db_name> control=load_<table_name>_oos_seq.ctl log=load_<table_name>_oos_seq.log bad=load_<table_name>_oos_seq.log;

2. Update target table OOS rows as below
set serveroutput on echo on feedback on
begin
for i in (select <primary_key_column> from <temp_table> ) loop
exec dbms_streams.set_tag (hextoraw(<number>));
update <target_table_name>
    set (list_of_oos_column_names)=(select <list_of_oos_column_names_in_same_order_as_in_set_clause>
                                     from <target_table_name>@to_source
                                     where <primary_key_column>= i.<primary_key_value>)
where <primary_key_column>= i.<primary_key_value> ;
commit;
end loop;
end;
/

--eg
set serveroutput on echo on feedback on
begin
for i in (select MONEY_MOVEMENT_TRANSACTION_SEQ,COMPANY_FK from mchoubey.mmt_oos_seq ) loop
DBMS_OUTPUT.PUT_LINE (i.MONEY_MOVEMENT_TRANSACTION_SEQ);
update pspadm.PSP_MONEY_MOVEMENT_TRANSACTION
    set (VERSION,MODIFIER_ID,MODIFIED_DATE,MM_TRANSACTION_AMOUNT,STATUS)=(select VERSION,MODIFIER_ID,MODIFIED_DATE,MM_TRANSACTION_AMOUNT,STATUS from mchoubey.mmt_oos_seq where MONEY_MOVEMENT_TRANSACTION_SEQ=i.MONEY_MOVEMENT_TRANSACTION_SEQ);
end loop;
end;
```

```

from pspadm.PSP_MONEY_MOVEMENT_TRANSACTION
where MONEY_MOVEMENT_TRANSACTION_SEQ= i.MO

```

```

commit;
end loop;
end;
/

--validation via veridata

```

Fix OOS inserts

```

exec dbms_streams.set_tag (hextoraw(<number>));
insert into <table_name> select * from <table_name>@to_source where <primary_key_column> in (<primary_key_values>);

--eg
insert into pspadm.PSP_TAX_PAYMENT_ON_HOLD_REASON select * from pspadm.PSP_TAX_PAYMENT_ON_HOLD_REASON@to_source whe
in ('23afc387-9570-4331-875a-c85e9bb5398e','2b35e8bc-6b70-487f-84be-e36e8e8e446b','2c4a1456-4c81-4257-af7d-11385d6
'7f6b54dd-a0a0-4877-b7bd-66fe52993b18','8e98011e-7fd0-4bd5-8f75-6381e2856472','9c28613e-0ec8-4c6e-80f4-979c32a1be9

--Fix large number of OOS rows
1. Load all primary key values in temp table
sqlldr userid=intuadmin@<db_name> control=load_<table_name>_oos_seq.ctl log=load_<table_name>_oos_seq.log bad=load_

2.
insert into <table_name> select * from <table_name>@to_source where <primary_key_column> in (select <primary_key_co

```

Fix OOS delete

```
--eg
delete from pspadm.PSP_PROPERTY_AUDIT where property_audit_seq in (select property_audit_seq from mchoubey.property

--Fix large number of OOS rows
1. Load all primary key values in temp table
sqlldr userid=intuadmin@<db_name> control=load_<table_name>_oos_seq.ctl log=load_<table_name>_oos_seq.log bad=load_

2.
delete from <table_name> where <primary_key_column> in (select <primary_key_column> from <temp_table_name>);
```

No labels