

Migrate from Oracle Range Partitioning to Oracle Hash Partitioning

- If we are not restoring latest snapshot of pspsys01 RDS then create new RDS pspsys01-new using [script](#)

```
./create_rds.sh qa clusterdb pspsys01-new us-west-2 vpc-2
```

- [create tablespaces](#)

```
CREATE TABLESPACE APPBUGFIX_DATA DATAFILE SIZE 10G AUTOEXTEND ON NEXT 1G MAXSIZE UNLIMITED;  
CREATE TABLESPACE ARC_DATA01 DATAFILE SIZE 1G AUTOEXTEND ON NEXT 1G MAXSIZE UNLIMITED;  
CREATE TABLESPACE ARC_IDX01 DATAFILE SIZE 5G AUTOEXTEND ON NEXT 1G MAXSIZE UNLIMITED;  
CREATE TABLESPACE PSP_LOG DATAFILE SIZE 1G AUTOEXTEND ON NEXT 1G MAXSIZE UNLIMITED;  
CREATE TABLESPACE TOOLS DATAFILE SIZE 1G AUTOEXTEND ON NEXT 1G MAXSIZE UNLIMITED;
```

- [create target db link](#)

```
create database link to_target connect to intuadmin identified by "changeme" using '(DESCRIPTION=(ADDRESS=(PROTOCOL=TCP)(HOST= pspsys01-new.sbg-psp-ppd.a.intuit.com)(PORT=1521))(CONNECT_DATA=(SID=pspsys01)))';
```

- export pspsys01 database

```
expdp userid=intuadmin@pspuep03 directory=DATA_PUMP_DIR dumpfile=exp_pspadm_metadata.dmp SCHEMAS=PSPADM  
content=METADATA_ONLY logfile=DATA_PUMP_DIR:exp_pspadm_metadata.log
```

- RDS S3 Integration

```
aws rds --profile sbg-psp-prod --region us-east-2 add-role-to-db-instance \  
--db-instance-identifier pspuep05 \  
--feature-name S3_INTEGRATION \  
--role-arn arn:aws:iam::893547637742:role/rds-s3-integration-role
```

- [connect to pspuep05 \(DR\) and upload to S3 \(Optional\)](#)

```
SELECT rdsadmin.rdsadmin_s3_tasks.upload_to_s3(  
p_bucket_name => 'expmeta',  
p_prefix => 'exp_pspadm_metadata',  
p_s3_prefix => '',  
p_directory_name => 'DATA_PUMP_DIR')  
AS TASK_ID FROM DUAL;
```

- check task status

```
SELECT text FROM table(rdsadmin.rds_file_util.read_text_file('BDUMP','dbtask-1678855251065-2966.log'));
```

- [download dump file local](#)

- [connect to pspsys new and upload to RDS](#)

```
SELECT rdsadmin.rdsadmin_s3_tasks.download_from_s3(  
p_bucket_name => 'exporttestdump',  
p_s3_prefix => 'exp_pspadm_metadata.dmp',  
p_directory_name => 'DATA_PUMP_DIR')  
AS TASK_ID FROM DUAL;
```

- create pspadm user on pspsys01-new
host: ggpspiibob1.sbg-ppd.a.intuit.com
location: /u01/mayank/setup_new_db

```
@CREATE_USERS.SQL
```

- import schema metadata dump on pspsys01-new
impdp userid=intuadmin/changeme@pspsys01-new directory=data_pump_dir
dumpfile=exp_pspadm_metadata.dmp logfile=imp_pspadm_metadata.log
- export schema backup from pspsys01

```
nohup expdp userid=intuadmin/"changeme"@pspsys01 dumpfile=DATA_PUMP_DIR:exp_pspadm_data_%U.dmp  
parallel=4 schemas=PSPADM filesize=100G content=data_only logfile=DATA_PUMP_DIR:exp_pspadm_data.log 2>&1  
&
```

- copy dump files to pspsys01-new

```
nohup ./run_on_target.sh copy_dump_files_to_target.sql &
```

- import schema dump into pspsys01-new

```
nohup impdp userid=intuadmin/"changeme"@pspsys01 dumpfile=DATA_PUMP_DIR:exp_pspadm_data_%U.dmp  
parallel=4 schemas=PSPADM filesize=50G content=data_only logfile=DATA_PUMP_DIR:imp_pspadm_data.log 2>&1 &
```