

Oracle RDS Data guard

Created by Choubey, Mayank, last modified on Mar 25, 2022

- [Overview](#)
- [Problem Statement](#)
- [Goal](#)
- [Benefits](#)
- [Implementation](#)
- [Observations/Limitations/Restrictions](#)
- [Switchover](#)
- [Switchback](#)

Overview

PSP uses 2 databases (Monolith & Audit/IBOB). Monolith has read replica in same region(us-west-2), which is used by downstream services to pull data and by RJF application to generate reports. But this cannot be used as DR because till now it did not have switchover/switchback capability. Hence, there is need to maintain separate databases for OLAP use-cases and DR (GoldenGate Replication).

Problem Statement

- High DR replication lag(~10 hrs during peak day) and hence High RTO for DR scenario.
- Need to maintain separate read replica database for OLAP use cases.
- High RDS infrastructure Cost

Goal

- Build DR using Data Guard technology with different configuration for Primary and DR
- Switchover & Switchback capability

Benefits

- Cost reduction for RDS infrastructure
- Reduce replication lag to near zero(in milliseconds).
- Best option to serve for DR as well as OLAP use cases.

Implementation

Create	instance size: db.r5.large iops: 1000 storage: 100G	instance size: db.r5.2xlarge iops: 1000 storage: 100G	Switchover & Switchback	Successful	~5 mins
Config Change	instance size: db.r5.large iops: 1000 storage: 100G	instance size: db.r5.2xlarge iops: 3000 storage: 200G	Switchover & Switchback	Successful	~5 mins
Config Change	instance size: db.r5.large iops: 1000 storage: 100G	1. instance size: db.r5.2xlarge iops: 3000 storage: 200G 2. instance size: db.r5.large iops: 1000 storage: 100G	Switchover to 1st standby Switchover to 2nd standby Switchback to Original Primary	Successful	

Observations/Limitations/Restrictions

- Backup needs to be enabled and retention should be there at least 1 day. Otherwise creation of cross-Region replica/role reversal will fail.

```
aws rds switchover-read-replica --db-instance-identifier eqbodg69
```

primary DB instance isn't ready for a role transition. The instance must be available, have no operations pending in i

- Option group on Primary should not be part of any other Data Guard configuration/Source having Read Replica. Option group can be part of any other

```
mchoubey@:intuitdep626ed:~/intuit/sbg/psp/aws/dataguard->aws --profile sbg-qbo-ppd --region us-east-2 rds switchover
An error occurred (InvalidDBInstanceState) when calling the SwitchoverReadReplica operation: You can't switch over
```

- When you create an Oracle cross-Region replica, it does not migrate existing option group of source rds instance, it creates a dedicated option group for it. You can't remove an Oracle cross-Region replica from its dedicated option group. No other DB instances can use the dedicated option group for an Oracle cross-Region replica. You can only add or remove options from a dedicated option group (for eg: NATIVE_NETWORK_ENCRYPTION, Timezone etc.)
- There is no FailOver option available at this moment as FLASHBACK is not enabled. This would be enabled by Q4 2022.**
- Cannot create RESTORE POINT on standby as FLASHBACK is not enabled.**

Switchover

[Collapse source](#)

```
aws --profile sbg-qbo-ppd --region us-east-2 rds switchover-read-replica --db-instance-identifier eqbodg69
{
  "DBInstance": {
    "DBInstanceIdentifier": "eqbodg69",
    "DBInstanceClass": "db.r5.2xlarge",
    "Engine": "oracle-ee",
    "DBInstanceStatus": "available",
    "MasterUsername": "intuadmin",
    "DBName": "EQBOTT69",
    "Endpoint": {
      "Address": "eqbodg69.cdcigllehyqw.us-east-2.rds.amazonaws.com",
      "Port": 1521,
      "HostedZoneId": "Z2XHWR1WZ565X2"
    },
    "AllocatedStorage": 100,
```

```
"InstanceCreateTime": "2022-03-24T08:17:10.691000+00:00",  
"PreferredBackupWindow": "09:57-10:27",
```

```
{  
  "VpcSecurityGroupId": "sg-d1164eba",  
  "Status": "active"  
},  
],  
"DBParameterGroups": [  
  {  
    "DBParameterGroupName": "oracle-ee-19-max-string-size-e2e-clusterdb-vpc-2",  
    "ParameterApplyStatus": "in-sync"  
  }  
],  
"AvailabilityZone": "us-east-2b",  
"DBSubnetGroup": {  
  "DBSubnetGroupName": "e2e-clusterdb-vpc-2",  
  "DBSubnetGroupDescription": "e2e-clusterdb-vpc-2 subnet group",  
  "VpcId": "vpc-1a6c0c73",  
  "SubnetGroupStatus": "Complete",  
  "Subnets": [  
    {  
      "SubnetIdentifier": "subnet-f9304690",  
      "SubnetAvailabilityZone": {  
        "Name": "us-east-2a"  
      },  
      "SubnetOutpost": {},  
      "SubnetStatus": "Active"  
    },  
    {  
      "SubnetIdentifier": "subnet-caf33f87",  
      "SubnetAvailabilityZone": {  
        "Name": "us-east-2c"  
      },  
      "SubnetOutpost": {},
```

```

        "SubnetStatus": "Active"
    },

```

```

        Name : us-east-2b
    },
    "SubnetOutpost": {},
    "SubnetStatus": "Active"
}

]
},
"PreferredMaintenanceWindow": "fri:09:27-fri:09:57",
"PendingModifiedValues": {},
"MultiAZ": false,
"EngineVersion": "19.0.0.0.ru-2021-10.rur-2021-10.r1",
"AutoMinorVersionUpgrade": false,
"ReadReplicaSourceDBInstanceIdentifier": "arn:aws:rds:us-west-2:475968958217:db:eqbott69",
"ReadReplicaDBInstanceIdentifiers": [],
"ReplicaMode": "open-read-only",
"LicenseModel": "bring-your-own-license",
"Iops": 1000,
"OptionGroupMemberships": [
    {
        "OptionGroupName": "replica-19-f92f8d35-4b68-4443-bc9e-134dd50de921",
        "Status": "in-sync"
    }
],
"CharacterSetName": "AL32UTF8",
"NcharCharacterSetName": "AL16UTF16",
"PubliclyAccessible": false,
"StatusInfos": [
    {
        "StatusType": "read replication",
        "Normal": true,
        "Status": "replicating"
    }
]

```

```
],
  "StorageType": "io1",
```

```
    "DBInstanceArn": "arn:aws:rds:us-east-2:475968958217:db:eqbodg69",
    "IAMDatabaseAuthenticationEnabled": false,
    "PerformanceInsightsEnabled": false,
    "EnabledCloudwatchLogsExports": [
      "alert"
    ],
    "DeletionProtection": false,
    "AssociatedRoles": [],
    "TagList": [],
    "CustomerOwnedIpEnabled": false,
    "BackupTarget": "region"
  }
}
```

Switchback

[Collapse source](#)

```
aws --profile sbg-qbo-ppd --region us-west-2 rds switchover-read-replica --db-instance-identifier eqbott69
{
  "DBInstance": {
    "DBInstanceIdentifier": "eqbott69",
    "DBInstanceClass": "db.r5.large",
    "Engine": "oracle-ee",
    "DBInstanceStatus": "available",
```

```
"MasterUsername": "intuadmin",
"DBName": "EQBOTT69",
```

```
    "HostedZoneId": "Z1PVI1F0B636C1W",
  },
  "AllocatedStorage": 100,
  "InstanceCreateTime": "2022-03-24T06:50:43.924000+00:00",
  "PreferredBackupWindow": "09:57-10:27",
  "BackupRetentionPeriod": 1,
  "DBSecurityGroups": [],
  "VpcSecurityGroups": [
    {
      "VpcSecurityGroupId": "sg-c2fd32b8",
      "Status": "active"
    }
  ],
  "DBParameterGroups": [
    {
      "DBParameterGroupName": "oracle-ee-19-max-string-size-e2e-clusterdb-vpc-3",
      "ParameterApplyStatus": "in-sync"
    }
  ],
  "AvailabilityZone": "us-west-2b",
  "DBSubnetGroup": {
    "DBSubnetGroupName": "e2e-clusterdb-vpc-3",
    "DBSubnetGroupDescription": "e2e-clusterdb-vpc-3 subnet group",
    "VpcId": "vpc-83f115e5",
    "SubnetGroupStatus": "Complete",
    "Subnets": [
      {
        "SubnetIdentifier": "subnet-04d7045f",
        "SubnetAvailabilityZone": {
          "Name": "us-west-2c"
        },
        "SubnetOutpost": {},

```

```

        "SubnetStatus": "Active"
    },

```

```

        "Name": "us-west-2b",
    },
    "SubnetOutpost": {},
    "SubnetStatus": "Active"
},
{
    "SubnetIdentifier": "subnet-2fc1f048",
    "SubnetAvailabilityZone": {
        "Name": "us-west-2a"
    },
    "SubnetOutpost": {},
    "SubnetStatus": "Active"
}
]
},
"PreferredMaintenanceWindow": "fri:09:27-fri:09:57",
"PendingModifiedValues": {},
"MultiAZ": false,
"EngineVersion": "19.0.0.0.ru-2021-10.rur-2021-10.r1",
"AutoMinorVersionUpgrade": false,
"ReadReplicaSourceDBInstanceIdentifier": "arn:aws:rds:us-east-2:475968958217:db:eqbodg69",
"ReadReplicaDBInstanceIdentifiers": [],
"ReplicaMode": "open-read-only",
"LicenseModel": "bring-your-own-license",
"Iops": 1000,
"OptionGroupMemberships": [
    {
        "OptionGroupName": "tt69-oracle-ee-19-e2e-clusterdb-vpc-3",
        "Status": "in-sync"
    }
],
"CharacterSetName": "AL32UTF8",

```



```
"NcharCharacterSetName": "AL16UTF16",
"PubliclyAccessible": false,
```

```
    "Normal": true,
    "Status": "replicating"
  }
],
"StorageType": "io1",
"DbInstancePort": 0,
"StorageEncrypted": true,
"KmsKeyId": "arn:aws:kms:us-west-2:475968958217:key/7bfb025e-4bf2-4be0-acd8-e58136b2df38",
"DbiResourceId": "db-YYBNHZN3DPAB77SDZOR4O7LD44",
"CACertificateIdentifier": "rds-ca-2019",
"DomainMemberships": [],
"CopyTagsToSnapshot": true,
"MonitoringInterval": 0,
"DBInstanceArn": "arn:aws:rds:us-west-2:475968958217:db:eqbott69",
"IAMDatabaseAuthenticationEnabled": false,
"PerformanceInsightsEnabled": true,
"PerformanceInsightsKMSKeyId": "arn:aws:kms:us-west-2:475968958217:key/7bfb025e-4bf2-4be0-acd8-e58136b2df38",
"PerformanceInsightsRetentionPeriod": 7,
"DeletionProtection": true,
"AssociatedRoles": [],
"TagList": [],
"CustomerOwnedIpEnabled": false,
"BackupTarget": "region"
}
}
```

- Database status as per switchover and switchback

[Collapse source](#)

DB_UNIQUE_NAME

OPEN_MODE

DATABASE_ROLE

EQBOTT69_A	READ	WRITE	PRIMARY		
EQBOTT69	READ	WRITE	ARCHIVELOG	PRIMARY	NO
ip-172-19-2-74					
=====					
DB_UNIQUE_NAME		OPEN_MODE		DATABASE_ROLE	

EQBOTT69_B	READ ONLY WITH APPLY PHYSICAL STANDBY				
INSTANCE	OPEN_MODE	LOG_MODE	DATABASE_ROLE	FLASHBACK_ON	HOST_NAME

EQBOTT69	READ ONLY WITH	APPLY ARCHIVELOG	PHYSICAL STANDBY	NO	ip-172-31-3-154

No labels