

Schedule Veridata Jobs Using Cron from Veridata Server

1.1. Reference Doc - <https://docs.oracle.com/en/middleware/goldengate/veridata/12.2.1.2.0/gvdad/using-veridata-command-line-tool.html#GUID-0612095D-5211-4856-AA6D-CC9088BB273E>

- https://docs.oracle.com/goldengate/1213/gg-veridata/GVDAD/running_comparisons.htm#GVDAD159

1.2. 1.1 Overview of the Command Line Interface

You can use the `vericom` tool of Oracle GoldenGate Veridata to execute certain comparison tasks from the command shell of the operating system. The `vericom` tool runs the Oracle GoldenGate Veridata Command Line Interface and enables you to handle these activities with automated programs.

You can:

- Run an entire job or a specific compare pair of a job

For specific compare pairs, you can:

- Review previous out-of-sync results
- Generate out-of-sync XML from the previous run
- Override the same profile and row partition settings that are possible from the web interface

Comparisons also can be run from the Oracle GoldenGate Veridata Web interface. This interface provides greater control in configuring the objects to be compared and for controlling runtime parameter settings.

1.3. 1.2 Running Vericom Commands

The `vericom` program can be run by anyone who has the correct operating system permissions to run it.

1. On the system where the Oracle GoldenGate Veridata is installed, run the command shell of the operating system.
2. Navigate to the `VERIDATA_DOMAIN_HOME/veridata/bin` directory.
3. Use the following syntax to run the `vericom` program.

1.4. 1.3 Schedule Cron Jobs to Run Compare Jobs

To run the jobs from command line we need to input Veridata User Credentials. To run through cron jobs we can either save the password in the file or input it using the variable. But in both the cases the password is exposed and there is high risk of

security breach issues. Hence to deal with the issue Oracle has introduced a functionality of adding credential store which allows users to store the encrypted passwords.

Oracle Veridata credential store maintains the encrypted database passwords and user IDs and associate them with an alias. It is the alias, not the actual user ID or password, that is specified in a command or parameter file, and no user input of an encryption key is required. The credential store is implemented as an autologin wallet within the Oracle Credential Store Framework (CSF).

1.5. 1.3.1 Steps to Create/Add Credentialstore :

1.6. Add CredentialStore Add User Alias Run Cron Job Using the Alias

1.6.1.1. Export Java Home

```
export JAVA_HOME=/u01/veridata/jdk1.8/jdk1.8.0_131/
export JRE_HOME=/u01/veridata/jdk1.8/jdk1.8.0_131/

export PATH=$JAVA_HOME/bin:$PATH
export PATH=$JRE_HOME/bin:$PATH
```

1.6.1.2. Adding a Credential Store

The `-addCredentialStore` argument does not accept any input. The default location for credential store is `<Domain_home>/veridata/dircred`. You can change this by specifying a directory in the `veridata.cfg` file under the `credential.store.location` property. The default value of the `credential.store.location` property is `veridata/dircred` which is relative to the domain location. You can create your own credential store location and change this property before running `vericom`. The credential store wallet is created with only read and write permissions (`-rw-----`).

Example

```
vericom.sh -wuser username -wport veridata server port -addCredentialStore.
```

```
[oracle@ggpppf501 bin]$ ./vericom.sh -wuser vdata -addCredentialStore
Oracle GoldenGate Veridata Command Line Interface - Version 12.2.1.2.0  OGGVDT_12.2.1.2.0_PLATFORMS_161009.0503
For Testing Purposes Only
[Enter weblogic password:]
2023-04-19 23:12:08.767 NOTIFICATION OGGV-20074 Veridata home location : /u01/veridata/wls/veridata
2023-04-19 23:12:08.794 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-19 23:12:08.795 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-19 23:12:08.795 NOTIFICATION OGGV-20077 Veridata domain location : /u01/veridata/wls/user_projects
/domains/base_domain/
2023-04-19 23:12:08.795 NOTIFICATION OGGV-20085 Credential store folder '/u01/veridata/wls/user_projects/domains
/base_domain/veridata/dircred'
OGGV-20079: Successfully created credential store.
```

1.6.1.3. Creating an Alias

The `-createAlias` argument accepts zero or one as input. If the input is provided, then it is used as an alias name. If it is not provided, then the user name provided in the `wuser` argument is used as an alias. This alias is used in place of the user name and password, and you do not have to provide an actual user name and password.

Example 4-3 Example

```
vericom.sh -wuser username-wlport veridata server port -createAlias aliasname (optional)
```

```
[oracle@ggpppf501 bin]$ ./vericom.sh -wuser vdata -createAlias vduser
Oracle GoldenGate Veridata Command Line Interface - Version 12.2.1.2.0  OGGVDT_12.2.1.2.0_PLATFORMS_161009.0503
For Testing Purposes Only
2023-04-19 23:18:06.105 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-19 23:18:06.143 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-19 23:18:06.144 NOTIFICATION OGGV-20077 Veridata domain location : /u01/veridata/wls/user_projects
/domains/base_domain/
2023-04-19 23:18:
06.144 NOTIFICATION OGGV-20085 Credential store folder '/u01/veridata/wls/user_projects/domains/base_domain
/veridata/dircred'
[Enter weblogic password:]
OGGV-20081: Successfully created alias 'vduser' for user.
[oracle@ggpppf501 bin]$
```

1.6.1.4. Run the JOB using the newly Created Alias which doesn't require the password.

```

[oracle@ggppsppf501 bin]$ ./vericom.sh -j TEST_IMPORT_JOB -wuserAlias vduser -g
TEST_Delta_PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash -c PSP_COMPANY_EVENT=PSP_COMPANY_EVENT
Oracle GoldenGate Veridata Command Line Interface - Version 12.2.1.2.0 OGGVDT_12.2.1.2.0_PLATFORMS_161009.0503
For Testing Purposes Only
2023-04-19 23:20:54.838 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-19 23:20:54.880 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-19 23:20:54.880 NOTIFICATION OGGV-20077 Veridata domain location : /u01/veridata/wls/user_projects
/domains/base_domain/
2023-04-19 23:20:54.880 NOTIFICATION OGGV-20085 Credential store folder '/u01/veridata/wls/user_projects/domains
/base_domain/veridata/dircrd'
2023-04-19 23:20:54.883 NOTIFICATION OGGV-20078 Using alias name for user
OGGV-20024: Run ID: (5340,0,0)
OGGV-20026: Number of Compare Pairs: 1
OGGV-20027: Number of Compare Pairs With Errors: 0
OGGV-20068: Number of Compare Pairs With Out-Of-Sync: 0
OGGV-20028: Number of Compare Pairs With No Out-Of-Sync: 1
OGGV-20029: Number of Compare Pairs Cancelled: 0
OGGV-20030: Job Report Filename: /u01/veridata/wls/user_projects/domains/base_domain/veridata/reports/rpt
/TEST_IMPORT_JOB/00005340/TEST_IMPORT_JOB.rpt
OGGV-20031: Compare Pair Report Filename: /u01/veridata/wls/user_projects/domains/base_domain/veridata/reports
/rpt/TEST_IMPORT_JOB/00005340/TEST_Delta_PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash
/CP_PSP_COMPANY_EVENT=PSP_COMPANY_EVENT.rpt
OGGV-20032: Run ID: (5340,0,0)
OGGV-20033: Number of Rows Compared: 646,805
OGGV-20034: Number of Rows In Sync: 646,805
OGGV-20035: Number of Rows With Errors: 0
OGGV-20036: Number of Rows Out Of Sync: 0
OGGV-20037: Compare Pair OOSXML Directory: /u01/veridata/wls/user_projects/domains/base_domain/veridata/reports
/oosxml/TEST_IMPORT_JOB/00005340/TEST_Delta_PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash
OGGV-20038: Compare Pair OOSXML Filename:
OGGV-20039: Job Completion Status: In-Sync
[oracle@ggppsppf501 bin]$

```

1.7. Cron Schedule Tested :

Schedule the Job run using veridata_job_run.sh script as per below format.

Arguments passed with the script are as follows:-

For execution of specific Compare Pair need to pass JOB_NAME , GROUP_NAME and COMPARE_PAIR NAME as arguments

For execution of any job need to pass only the JOB_NAME as the input.

```

[oracle@ggppsppf501 ~]$ crontab -l

## TEST Veridata Job For Specific COMPARE_PAIR
45 5 * * 2,5 /bin/sh /u01/test/veridata_job_run.sh Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01
PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash_FULL PSP_ENTITLEMENT_MESSAGE=PSP_ENTITLEMENT_MESSAGE

## TEST Veridata Full Job
45 5 * * 0 /bin/sh /u01/test/veridata_job_run.sh Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01

```

LogFile will be generated as below :

```

[rrasam@ggppsppf501 test]$ cat Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01_veridata_job_run_2023-04-21_05:46:01.log
.
Compare Job Started at 2023-04-21_05:46:01
.
.
.
.
Number of Arguments Passed are 3 JOB:Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01, GROUP:
PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash_FULL, COMPARE_PAIR:PSP_ENTITLEMENT_MESSAGE=PSP_ENTITLEMENT_MESSAGE
.
.
.
Oracle GoldenGate Veridata Command Line Interface - Version 12.2.1.2.0 OGGVDT_12.2.1.2.0_PLATFORMS_161009.0503
For Testing Purposes Only
2023-04-21 05:46:01.814 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-21 05:46:01.853 NOTIFICATION OGGV-20071 veridata.cfg file location : /u01/veridata/wls/user_projects
/domains/base_domain/config/veridata/veridata.cfg
2023-04-21 05:46:01.853 NOTIFICATION OGGV-20077 Veridata domain location : /u01/veridata/wls/user_projects
/domains/base_domain/
2023-04-21 05:46:01.854 NOTIFICATION OGGV-20085 Credential store folder '/u01/veridata/wls/user_projects/domains
/base_domain/veridata/dircrd'
2023-04-21 05:46:01.856 NOTIFICATION OGGV-20078 Using alias name for user
OGGV-20024: Run ID: (5933,0,0)
OGGV-20026: Number of Compare Pairs: 1
OGGV-20027: Number of Compare Pairs With Errors: 0
OGGV-20068: Number of Compare Pairs With Out-Of-Sync: 0
OGGV-20028: Number of Compare Pairs With No Out-Of-Sync: 1
OGGV-20029: Number of Compare Pairs Cancelled: 0
OGGV-20030: Job Report Filename: /u01/veridata/wls/user_projects/domains/base_domain/veridata/reports/rpt
/Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01/00005933/Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01.rpt
OGGV-20031: Compare Pair Report Filename: /u01/veridata/wls/user_projects/domains/base_domain/veridata/reports
/rpt/Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01/00005933/PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash_FULL
/CP_PSP_ENTITLEMENT_MESSAGE=PSP_ENTITLEMENT_MESSAGE.rpt
OGGV-20032: Run ID: (5933,0,0)
OGGV-20033: Number of Rows Compared: 11,650,166
OGGV-20034: Number of Rows In Sync: 11,650,166
OGGV-20035: Number of Rows With Errors: 0
OGGV-20036: Number of Rows Out Of Sync: 0
OGGV-20037: Compare Pair OOSXML Directory: /u01/veridata/wls/user_projects/domains/base_domain/veridata/reports
/oosxml/Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01/00005933/PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash_FULL
OGGV-20038: Compare Pair OOSXML Filename:
OGGV-20039: Job Completion Status: In-Sync
.
.
.
Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01 is Successfully Completed !!!
.
.
.
.
.
COMPARE JOB FINAL STATUS JOB:"Monolith_PREPROD_Full_Comp_PSPE2EUW_And_PPSPHP01" --> GROUP:"
PREPROD_PSPE2EUW_Range_TO_PPSPHP01_Hash_FULL" --> COMPARE_PAIR:"
PSP_ENTITLEMENT_MESSAGE=PSP_ENTITLEMENT_MESSAGE" IS COMPLETED SUCCESSFULLY !!!
.
.
.
.
Compare Job Ended at 2023-04-21_10:31:33
.
[rrasam@ggppsppf501 test]$

```

Above logfile gives all the job execution details like START_TIME, Details and Number Of Arguments Passed, Job Report Filename, Job Completion Status and Completion Time of the JOB. Will also report if any errors faced during the execution.

Good Luck !!!