

Setup IBOB GG replication

- 1. Setup GG on source and target db servers puatpspdb800,puatpspdb801 and puatpspdb802
 - 1.2 Install and configure Goldengate on the source and target db server
 - 1.2.1 Install 12c Goldengate on the source and target db servers
 - 1.2.2 Configure the database for Goldengate on the source db servers
 - 1.2.3 Configure Goldengate on the source db server

1. Setup GG on source and target db servers puatpspdb800, puatpspdb801 and puatpspdb802

1.1 Setup environment on the source and target db server:

- Create the directories on the source and target db host.

```
. /l/<ORACLE_SID> # Need to replace <ORACLE_SID> with real name

sudo chown -R oracle:dba /u01/ogg
mkdir -p /u01/ogg/scripts
cd /u01/ogg/
mkdir -p $ORACLE_SID/scripts
mkdir -p $ORACLE_SID/export
mkdir -p $ORACLE_SID/logs
mkdir -p $ORACLE_SID/goldengate/binaries
mkdir -p $ORACLE_SID/goldengate/scripts
mkdir -p $ORACLE_SID/goldengate/ogg_monitoring
```

- Copy Scripts

```
cd /u01/ogg/$ORACLE_SID/goldengate/scripts
copy scripts under this location from perf/sys db server

cd /u01/ogg/scripts
copy scripts under this location from perf/sys db server
```

- You should have the following files /u01/ogg/\$ORACLE_SID/goldengate/scripts:

```
oracle@puatpspdb800.ie.intuit.net:/u01/ogg->ls pspqpf01/goldengate/scripts/
GG01_install_goldengate.log GG01_install_goldengate_12c.sh GG02_configure_db_for_goldengate_12c.sh
GG03_configure_goldengate.sh
```

- You should have the following files /u01/ogg/scripts:

```
oracle@puatpspdb800.ie.intuit.net:/u01/ogg->ls /u01/ogg/scripts/
iac_run_defgen.sh monitor_ggserr.sh monitor_gg_sync_ihp.sh monitor_gg_sync.sh monitor_gg_sync_table_ihp.
sql monitor_pqboc03.cfg rotate_ggserr.sh
```

1.2 Install and configure Goldengate on the source and target db server

1.2.1 Install 12c Goldengate on the source and target db servers

```
. /l/<Oracle sid name>
cd /u01/ogg/$ORACLE_SID/goldengate/scripts
./GG01_install_goldengate_12c.sh |tee GG01_install_goldengate.log
```

- Run environment file again since the script above updated the file and create directory for trail files

```
. /l/$ORACLE_SID

mkdir $GG_HOME/dirdat/<source_sid>
mkdir $GG_HOME/dirdat/<target_sid>
```

1.2.2 Configure the database for Goldengate on the source db servers

```
./GG02_configure_db_for_goldengate_12c.sh <ggs/ggt password> |tee GG02_configure_db_for_goldengate.log
```

Note:

1. You will get the prompt "Is the primary db in QDC? (Yes/No)?" and another prompt "Please enter the database sys password".
2. Check the error. The following errors can be ignored

```
egrep "ORA-|SP2-" GG02_configure_db_for_goldengate.log
ORA-12920: database is already in force logging mode
ORA-02379: profile GENERIC_APP_PROFILE already exists
```

Any error/warning about enable_goldengate_replication parameter if it is running against 11g database.

1.2.3 Configure Goldengate on the source db server

```
cd $GG_HOME
./ggsci
add CREDENTIALSTORE
ALTER CREDENTIALSTORE ADD USER ggs password <ggs password> alias ggsource
ALTER CREDENTIALSTORE ADD USER ggt password <ggt password> alias ggtarget
ALTER CREDENTIALSTORE ADD USER ggs@<lvdc_db> password <ggs password> alias ggsource_remote
ALTER CREDENTIALSTORE ADD USER ggt@<lvdc_db> password <ggt password> alias ggtarget_remote
info CREDENTIALSTORE
dblogin USERIDALIAS ggsource
dblogin USERIDALIAS ggtarget
dblogin USERIDALIAS ggsource_remote
dblogin USERIDALIAS ggtarget_remote
exit
echo "dblogin USERIDALIAS ggsource" > diroby/dblogin_s.oby
echo "dblogin USERIDALIAS ggtarget" > diroby/dblogin_t.oby
echo "dblogin USERIDALIAS ggsource_remote" > diroby/dblogin_s_remote.oby
echo "dblogin USERIDALIAS ggtarget_remote" > diroby/dblogin_t_remote.oby
obey ./diroby/dblogin_s.oby
obey ./diroby/dblogin_t.oby
obey ./diroby/dblogin_s_remote.oby
obey ./diroby/dblogin_t_remote.oby
```