



Module M08

Partha Pratim
Das

Objectives &
Outline

Default
Parameters

Examples
Highlights
Restrictions

Function
Overloading

Examples
Restrictions
Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples
Ambiguity

Defa. Parames in
Overloading

Module Summary

Programming in Modern C++

Module M08: Default Parameters & Function Overloading

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Module M08

Partha Pratim
Das

Objectives & Outline

Default
Parameters
Examples
Highlights
Restrictions

Function
Overloading
Examples
Restrictions
Rules

Overload
Resolution
Exact Match
Promotion &
Conversion
Examples
Ambiguity

Defa. Parames in
Overloading

Module Summary

- Introduced reference in C++
- Studied the difference between call-by-value and call-by-reference
- Studied the difference between return-by-value and return-by-reference
- Discussed the difference between References and Pointers



Module Objectives

Module M08

Partha Pratim
Das

Objectives & Outline

Default
Parameters

Examples

Highlights

Restrictions

Function
Overloading

Examples

Restrictions

Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples

Ambiguity

Defa. Parames in
Overloading

Module Summary

- Understand Default Parameters
- Understand Function Overloading and Resolution

NPTEL



Module Outline

Module M08

Partha Pratim
Das

Objectives & Outline

Default Parameters

Examples
Highlights
Restrictions

Function Overloading

Examples
Restrictions
Rules

Overload Resolution

Exact Match
Promotion &
Conversion
Examples
Ambiguity

Defa. Parames in Overloading

Module Summary

- 1 Default Parameters
 - Examples
 - Highlights
 - Restrictions on default parameters
- 2 Function Overloading
 - Examples
 - Restrictions
 - Rules
- 3 Overload Resolution
 - Exact Match
 - Promotion & Conversion
 - Examples
 - Ambiguity
- 4 How to overload Default Parameter?
- 5 Module Summary



Default Parameters

Module M08

Partha Pratim
Das

Objectives &
Outline

Default
Parameters

Examples

Highlights

Restrictions

Function
Overloading

Examples

Restrictions

Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples

Ambiguity

Defa. Parames in
Overloading

Module Summary

Default Parameters



Motivation: Example CreateWindow in MSVC++

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

Declaration of CreateWindow

```
HWND WINAPI CreateWindow(  
    _In_opt_ LPCTSTR    lpClassName,  
    _In_opt_ LPCTSTR    lpWindowName,  
    _In_      DWORD      dwStyle,  
    _In_      int        x,  
    _In_      int        y,  
    _In_      int        nWidth,  
    _In_      int        nHeight,  
    _In_opt_ HWND        hWndParent,  
    _In_opt_ HMENU        hMenu,  
    _In_opt_ HINSTANCE    hInstance,  
    _In_opt_ LPVOID        lpParam  
);
```

Calling CreateWindow

```
hWnd = CreateWindow(  
    ClsName,  
    WndName,  
    WS_OVERLAPPEDWINDOW,  
    CW_USEDEFAULT,  
    CW_USEDEFAULT,  
    CW_USEDEFAULT,  
    CW_USEDEFAULT,  
    NULL,  
    NULL,  
    hInstance,  
    NULL  
);
```

- There are **11 parameters** in **CreateWindow()**
- Of these **11, 8 parameters** (4 are **CWUSEDEFAULT**, 3 are **NULL**, and 1 is **hInstance**) usually get same values in most calls
- Instead of using these **8 fixed valued Parameters** at call, we may assign the *values in formal parameter*
- C++ allows us to do so through the mechanism called **Default parameters**



Program 08.01: Function with a default parameter

Module M08

Partha Pratim
Das

Objectives &
Outline

Default
Parameters

Examples

Highlights

Restrictions

Function
Overloading

Examples

Restrictions

Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples

Ambiguity

Defa. Parames in
Overloading

Module Summary

```
#include <iostream>
using namespace std;
```

```
int IdentityFunction(int a = 10) { // Default value for parameter a
    return (a);
}
```

```
int main() {
    int x = 5, y;

    y = IdentityFunction(x); // Usual function call. Actual parameter taken as x = 5
    cout << "y = " << y << endl;

    y = IdentityFunction(); // Uses default parameter. Actual parameter taken as 10
    cout << "y = " << y << endl;
}
```

```
-----
y = 5
y = 10
```



Program 08.02: Function with 2 default parameters

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

```
#include<iostream>
using namespace std;
```

```
int Add(int a = 10, int b = 20) {
    return (a + b);
}
```

```
int main() { int x = 5, y = 6, z;
```

```
    z = Add(x, y); // Usual function call -- a = x = 5 & b = y = 6
    cout << "Sum = " << z << endl;
```

```
    z = Add(x);      // One parameter defaulted -- a = x = 5 & b = 20
    cout << "Sum = " << z << endl;
```

```
    z = Add();        // Both parameter defaulted -- a = 10 & b = 20
    cout << "Sum = " << z << endl;
}
```

Sum = 11

Sum = 25

Sum = 30



Default Parameter: Highlighted Points

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

- C++ allows programmer to assign default values to the function parameters
- Default values are specified while prototyping the function
- Default parameters are required while calling functions with fewer arguments or without any argument
- Better to use default value for less used parameters
- Default arguments may be expressions also



Restrictions on default parameters

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

- *All parameters to the right of a parameter with default argument must have default arguments* (function `f` violates)
- *Default arguments cannot be re-defined* (second signature of function `g` violates)
- *All non-defaulted parameters needed in a call* (first call of `g()` violates)

```
#include <iostream>
```

```
void f(int, double = 0.0, char *);
```

```
// Error C2548: f: missing default parameter for parameter 3
```

```
void g(int, double = 0, char * = NULL); // OK
```

```
void g(int, double = 1, char * = NULL);
```

```
// Error C2572: g: redefinition of default parameter : parameter 3
```

```
// Error C2572: g: redefinition of default parameter : parameter 2
```

```
int main() {
```

```
    int i = 5; double d = 1.2; char c = 'b';
```

```
    g(); // Error C2660: g: function does not take 0 arguments
```

```
    g(i);
```

```
    g(i, d);
```

```
    g(i, d, &c);
```

```
}
```



Restrictions on default parameters

- Default parameters to be supplied *only in a header file* and *not in the definition* of a function

```
// Header file: myFunc.h
void g(int, double, char = 'a'); // Defaults ch
void g(int i, double f = 0.0, char ch); // A new overload. Defaults f & ch
void g(int i = 0, double f, char ch); // A new overload. Defaults i, f & ch
// void g(int i = 0, double f = 0.0, char ch = 'a'); // Alternate signature. Defaults all in one go
-----

// Source File
#include <iostream>
using namespace std;
#include "myFunc.h" // Defaults taken from header
void g(int i, double d, char c) { cout << i << ' ' << d << ' ' << c << endl; } // No defaults here
-----

// Application File
#include <iostream>
#include "myFunc.h"
int main() { int i = 5; double d = 1.2; char c = 'b';
    g();           // Prints: 0 0 a
    g(i);          // Prints: 5 0 a
    g(i, d);       // Prints: 5 1.2 a
    g(i, d, c);    // Prints: 5 1.2 b
}
```



Function Overloading

Module M08

Partha Pratim Das

Objectives &
Outline

Default
Parameters

Examples

Highlights

Restrictions

**Function
Overloading**

Examples

Restrictions

Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples

Ambiguity

Defa. Parames in
Overloading

Module Summary

Function Overloading



Function overloads: Matrix Multiplication in C

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

- *Similar functions* with *different data types* and *algorithms*

```
typedef struct { int data[10][10]; } Mat;    // 2D Matrix
typedef struct { int data[1][10]; } VecRow; // Row Vector
typedef struct { int data[10][1]; } VecCol; // Column Vector

void Multiply_M_M (Mat a,    Mat b,    Mat* c);    // c = a * b
void Multiply_M_VC (Mat a,    VecCol b, VecCol* c); // c = a * b
void Multiply_VR_M (VecRow a, Mat b,    VecRow* c); // c = a * b
void Multiply_VC_VR (VecCol a, VecRow b, Mat* c);    // c = a * b
void Multiply_VR_VC (VecRow a, VecCol b, int* c);    // c = a * b

int main() {
    Mat m1, m2, rm; VecRow rv, rrv; VecCol cv, rcv; int r;
    Multiply_M_M (m1, m2, &rm); // rm <-- m1 * m2
    Multiply_M_VC (m1, cv, &rcv); // rcv <-- m1 * cv
    Multiply_VR_M (rv, m2, &rrv); // rrv <-- rv * m2
    Multiply_VC_VR (cv, rv, &rm); // rm <-- cv * rv
    Multiply_VR_VC (rv, cv, &r);  // r <-- rv * cv
    return 0;
}
```

- 5 multiplication functions share *similar functionality* but *different argument types*
- C treats them by 5 different function names. Makes it difficult for the user to remember and use
- **C++ has an elegant solution**



Function overloads: Matrix Multiplication in C++

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

- Functions *having the same name*, *similar functionality* but *different algorithms*, and identified by *different interfaces data types*

```
typedef struct { int data[10][10]; } Mat;    // 2D Matrix
typedef struct { int data[1][10]; } VecRow; // Row Vector
typedef struct { int data[10][1]; } VecCol;  // Column Vector
```

```
void Multiply(const Mat& a,    const Mat& b,    Mat& c);    // c = a * b
void Multiply(const Mat& a,    const VecCol& b, VecCol& c); // c = a * b
void Multiply(const VecRow& a, const Mat& b,    VecRow& c); // c = a * b
void Multiply(const VecCol& a, const VecRow& b, Mat& c);    // c = a * b
void Multiply(const VecRow& a, const VecCol& b, int& c);    // c = a * b
```

```
int main() {
    Mat m1, m2, rm; VecRow rv, rrv; VecCol cv, rcv; int r;
    Multiply(m1, m2, rm); // rm <-- m1 * m2
    Multiply(m1, cv, rcv); // rcv <-- m1 * cv
    Multiply(rv, m2, rrv); // rrv <-- rv * m2
    Multiply(cv, rv, rm); // rm <-- cv * rv
    Multiply(rv, cv, r); // r <-- rv * cv
    return 0;
}
```

- These **5 functions** having *different argument types* are represented as *one function name* (Multiply) in C++
- This is called **Function Overloading** or **Static Polymorphism**



Program 08.03/04: Function Overloading

Module M08

Partha Pratim Das

- Define *multiple functions* having the *same name*
- Binding* happens at **compile time**

Same # of Parameters

```
#include <iostream>
using namespace std;
int Add(int a, int b) { return (a + b); }
double Add(double c, double d) { return (c + d); }
int main() {
    int x = 5, y = 6, z;
    z = Add(x, y); // int Add(int, int)
    cout << "int sum = " << z;

    double s = 3.5, t = 4.25, u;
    u = Add(s, t); // double Add(double, double)
    cout << "double sum = " << u << endl;
}
```

int sum = 11 double sum = 7.75

- Same **Add** function to add two **ints** or two **doubles**
- Same # of parameters but *different types*

Different # of Parameters

```
#include <iostream>
using namespace std;
int Area(int a, int b) return (a * b);
int Area(int c) { return (c * c); }
int main() {
    int x = 10, y = 12, z = 5, t;
    t = Area(x, y); // int Area(int, int)
    cout << "Area of Rectangle = " << t;

    int z = 5, u;
    u = Area(z); // int Area(int)
    cout << " Area of Square = " << u << endl;
}
```

Area of Rectangle = 12 Area of Square = 25

- Same **Area** function for *rectangles* and for *squares*
- Different number of parameters*



Program 08.05: Restrictions in Function Overloading

- Two functions having the *same signature* but *different return types* cannot be overloaded

```
#include <iostream>
using namespace std;

int    Area(int a, int b) { return (a * b); }
double Area(int a, int b) { return (a * b); }
// Error C2556: double Area(int,int): overloaded function differs only by return type
//           from int Area(int,int)
// Error C2371: Area: redefinition; different basic types

int main() {
    int x = 10, y = 12, z = 5, t;
    double f;

    t = Area(x, y);
    // Error C2568: =: unable to resolve function overload
    // Error C3861: Area: identifier not found

    cout << "Multiplication = " << t << endl;

    f = Area(y, z); // Errors C2568 and C3861 as above
    cout << "Multiplication = " << f << endl;
}
```




Function Overloading: Summary of Rules

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

- The *same function name* may be used in *several definitions*
- Functions with the *same name* must have *different number of formal parameters* and/or *different types of formal parameters*
- Function selection is based on the *number* and the *types of the actual parameters* at the places of invocation
- Function selection (*Overload Resolution*) is performed by the compiler
- Two functions having the same signature but different return types will result in a compilation error due to *attempt to re-declare*
- Overloading allows **Static Polymorphism**



Overload Resolution

Module M08

Partha Pratim Das

Objectives &
Outline

Default
Parameters

Examples

Highlights

Restrictions

Function
Overloading

Examples

Restrictions

Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples

Ambiguity

Defa. Parames in
Overloading

Module Summary

Overload Resolution



Overload Resolution

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

- To resolve overloaded functions with one parameter
 - Identify the set of *Candidate Functions*
 - From the set of candidate functions identify the set of *Viable Functions*
 - Select the *Best viable function* through (*Order is important*)
 - ▷ *Exact Match*
 - ▷ *Promotion*
 - ▷ *Standard type conversion*
 - ▷ *User defined type conversion*



Overload Resolution: Exact Match

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

- *lvalue-to-rvalue conversion*: Read the value from an object

- Most common

- *Array-to-pointer conversion*

Definitions: `int ar[10];`
`void f(int *a);`

Call: `f(ar)`

Definitions: `typedef int (*fp) (int);`
`void f(int, fp);`

- *Function-to-pointer conversion*

`int g(int);`

Call: `f(5, g)`

- *Qualification conversion*

- Converting pointer (only) to `const` pointer



Overload Resolution: Promotion & Conversion

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

- **Promotion**

- Objects of an integral type can be converted to another wider integral type, that is, a type that can represent a larger set of values. This widening type of conversion is called *integral promotion*
- C++ promotions are *value-preserving*, as the value after the promotion is guaranteed to be the same as the value before the promotion
- Examples
 - ▷ `char` to `int`; `float` to `double`
 - ▷ `enum` to `int` / `short` / `unsigned int` / ...
 - ▷ `bool` to `int`



Overload Resolution: Promotion & Conversion

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

• Standard Conversions

- *Integral conversions* between *integral types* – `char`, `short`, `int`, and `long` with or without qualifiers `signed` or `unsigned`
- *Floating point Conversions* from *less precise floating type* to a *more precise floating type* like `float` to `double` or `double` to `long double`. Conversion can happen to a *less precise* type, if it is in a range representable by that type
- *Conversions between integral and floating point types*: Certain expressions can cause objects of floating type to be converted to integral types, or vice versa. **May be dangerous!**
 - ▷ When an object of *integral type* is converted to a *floating type*, and the original value is not representable exactly, the result is either the next higher or the next lower representable value
 - ▷ When an object of *floating type* is converted to an *integral type*, the fractional part is truncated, or rounded toward zero. A number like 1.3 is converted to 1, and -1.3 is converted to -1
- *Pointer Conversions*: Pointers can be converted during assignment, initialization, comparison, and other expressions
- *Bool Conversion*: `int` to `bool` or vice versa based on the context



Example: Overload Resolution with one parameter

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

- In the context of a list of function prototypes:

```
int g(double);           // F1
void f();                 // F2
void f(int);              // F3
double h(void);           // F4
int g(char, int);         // F5
void f(double, double = 3.4); // F6
void h(int, double);      // F7
void f(char, char *);     // F8
```

The call site to resolve is:

`f(5.6);`

- Resolution:
 - *Candidate functions* (by name): F2, F3, F6, F8
 - *Viable functions* (by # of parameters): F3, F6
 - *Best viable function* (by type double – Exact Match): F6



Example: Ambiguity in Overload Resolution

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

- Consider the overloaded function signatures:

```
int fun(float a) {...}           // Function 1
int fun(float a, int b) {...}    // Function 2
int fun(float x, int y = 5) {...} // Function 3
```

```
int main() {
    float p = 4.5, t = 10.5;
    int s = 30;

    fun(p, s); // CALL - 1
    fun(t);    // CALL - 2
    return 0;
}
```

- CALL - 1:** Matches Function 2 & Function 3
- CALL - 2:** Matches Function 1 & Function 3
- Results in ambiguity for both calls



Default Parameters in Overloading

Module M08

Partha Pratim
Das

Objectives &
Outline

Default
Parameters

Examples

Highlights

Restrictions

Function
Overloading

Examples

Restrictions

Rules

Overload
Resolution

Exact Match

Promotion &
Conversion

Examples

Ambiguity

Defa. Parames in
Overloading

Module Summary

Default Parameters in Overloading



Program 08.06/07: Default Parameter & Function Overload

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Default Parameters in Overloading

Module Summary

- Compilers deal with *default parameters* as a special case of *function overloading*
- These need to be mixed carefully

| Default Parameters | Function Overload |
|---|---|
| <pre>#include <iostream> using namespace std; int f(int a = 1, int b = 2); int main() { int x = 5, y = 6; f(); // a = 1, b = 2 f(x); // a = x = 5, b = 2 f(x, y); // a = x = 5, b = y = 6 }</pre> | <pre>#include <iostream> using namespace std; int f(); int f(int); int f(int, int); int main() { int x = 5, y = 6; f(); // int f(); f(x); // int f(int); f(x, y); // int f(int, int); }</pre> |
| <ul style="list-style-type: none">• Function f has 2 parameters defaulted• f can have 3 possible forms of call | <ul style="list-style-type: none">• Function f is overloaded with up to 2 parameters• f can have 3 possible forms of call• <i>No overload</i> here use <i>default parameters</i>. Can it? |



Program 08.08: Default Parameter & Function Overload

- *Function overloading* can use *default parameter*
- However, *with default parameters*, the overloaded functions should *still be resolvable*

```
#include <iostream>
using namespace std;
// Overloaded Area functions
int Area(int a, int b = 10) { return (a * b); }
double Area(double c, double d) { return (c * d); }
int main() { int x = 10, y = 12, t; double z = 20.5, u = 5.0, f;
    t = Area(x);    // Binds int Area(int, int = 10)
    cout << "Area = " << t << endl; // Area = 100

    t = Area(x, y);    // Binds int Area(int, int = 10)
    cout << "Area = " << t << endl; // Area = 120

    f = Area(z, u); // Binds double Area(double, double)
    cout << "Area = " << f << endl; // Area = 102.5

    f = Area(z); // Binds int Area(int, int = 10)
    cout << "Area = " << f << endl; // Area = 200

    // Un-resolvable between int Area(int a, int b = 10) and double Area(double c, double d)
    f = Area(z, y); // Error: call of overloaded Area(double&, int&) is ambiguous
}
```



Program 08.09: Default Parameter & Function Overload

- Function overloading with default parameters may fail

```
#include <iostream>
using namespace std;
int f();
int f(int = 0);
int f(int, int);

int main() {
    int x = 5, y = 6;

    f();          // Error C2668: f: ambiguous call to overloaded function
                  // More than one instance of overloaded function f
                  // matches the argument list:
                  //     function f()
                  //     function f(int = 0)

    f(x);          // int f(int);
    f(x, y);       // int f(int, int);

    return 0;
}
```



Module Summary

Module M08

Partha Pratim Das

Objectives & Outline

Default Parameters

Examples

Highlights

Restrictions

Function Overloading

Examples

Restrictions

Rules

Overload Resolution

Exact Match

Promotion & Conversion

Examples

Ambiguity

Defa. Parames in Overloading

Module Summary

- Introduced the notion of Default parameters and discussed several examples
- Identified the necessity of function overloading
- Introduced static Polymorphism and discussed examples and restrictions
- Discussed an outline for Overload resolution
- Discussed the mix of default Parameters and function overloading