



Module M07

Partha Pratim
Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

Programming in Modern C++

Module M07: Reference & Pointer

Partha Pratim Das

Department of Computer Science and Engineering
Indian Institute of Technology, Kharagpur

ppd@cse.iitkgp.ac.in

All url's in this module have been accessed in September, 2021 and found to be functional



Module Recap

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

- Revisited manifest constants from C
- Understood `const`-ness, its use and advantages over manifest constants, and its interplay with pointers
- Understood the notion and use of `volatile` data
- Revisited macros with parameters from C
- Understood `inline` functions, their advantages over macros, and their limitations



Module Objectives

Module M07

Partha Pratim
Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by- Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

- Understand References in C++
- Compare and contrast References and Pointers



Module Outline

Module M07

Partha Pratim
Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

- 1 Reference Variable
 - Pitfalls in Reference
- 2 Call-by-Reference
 - Simple C Program to swap
 - Simple C/C++ Program to swap two numbers
 - const Reference Parameter
- 3 Return-by-Reference
 - Pitfalls of Return-by Reference
- 4 I/O Parameters of a Function
- 5 Recommended Call and Return Mechanisms
- 6 Difference between Reference and Pointer
- 7 Module Summary



Reference Variable

Module M07

Partha Pratim Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

Reference Variable



Reference

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

- A reference is an **alias** / **synonym** for an existing variable

```
int i = 15; // i is a variable
```

```
int &j = i; // j is a reference to i
```

i ← variable

15 ← memory content

200 ← address **&i = &j**

j ← alias or reference



Program 07.01: Behavior of Reference

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

```
#include <iostream>
using namespace std;

int main() {
    int a = 10, &b = a; // b is reference of a

    // a and b have the same memory location
    cout << "a = " << a << ", b = " << b << ". " << "&a = " << &a << ", &b = " << &b << endl;

    ++a; // Changing a appears as change in b
    cout << "a = " << a << ", b = " << b << endl;

    ++b; // Changing b also changes a
    cout << "a = " << a << ", b = " << b << endl;
}
```

```
a = 10, b = 10. &a = 002BF944, &b = 002BF944
a = 11, b = 11
a = 12, b = 12
```

- **a** and **b** have the *same memory location* and hence *the same value*
- Changing one changes the other and vice-versa



Pitfalls in Reference

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

Wrong declaration	Reason	Correct declaration
<pre>int& i; int& j = 5; int& i = j + k;</pre>	<p>no variable (address) to refer to – must be initialized</p> <p>no address to refer to as 5 is a constant</p> <p>only temporary address (result of j + k) to refer to</p>	<pre>int& i = j; const int& j = 5; const int& i = j + k;</pre>
<pre>#include <iostream> using namespace std; int main() { int i = 2; int& j = i; const int& k = 5; // const tells compiler to allocate a memory with the value 5 const int& l = j + k; // Similarly for j + k = 7 for l to refer to cout << i << ", " << &i << endl; // Prints: 2, 0x61fef8 cout << j << ", " << &j << endl; // Prints: 2, 0x61fef8 cout << k << ", " << &k << endl; // Prints: 5, 0x61fefc cout << l << ", " << &l << endl; // Prints: 7, 0x61ff00 }</pre>		



Call-by-Reference

Module M07

Partha Pratim
Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

Call-by-Reference



C++ Program 07.02: Call-by-Reference

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

```
#include <iostream>
using namespace std;
```

```
void Function_under_param_test( // Function prototype
    int&, // Reference parameter
    int); // Value parameter
```

```
int main() { int a = 20;
    cout << "a = " << a << ", &a = " << &a << endl << endl;
    Function_under_param_test(a, a); // Function call
}
```

```
void Function_under_param_test(int &b, int c) { // Function definition
    cout << "b = " << b << ", &b = " << &b << endl << endl;
    cout << "c = " << c << ", &c = " << &c << endl << endl;
}
```

----- Output -----

a = 20, &a = 0023FA30

b = 20, &b = 0023FA30 // Address of b is same as a as b is a reference of a

c = 20, &c = 0023F95C // Address different from a as c is a copy of a

- Param **b** is *call-by-reference* while param **c** is *call-by-value*
- Actual param **a** and formal param **b** get the *same value* in called function
- Actual param **a** and formal param **c** get the *same value* in called function
- Actual param **a** and formal param **b** get the *same address* in called function
- However, actual param **a** and formal param **c** have *different addresses* in called function



C Program 07.03: Swap in C

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

Call-by-value – wrong

```
#include <stdio.h>

void swap(int, int); // Call-by-value
int main() { int a = 10, b = 15;
    printf("a= %d & b= %d to swap\n", a, b);
    swap(a, b);
    printf("a= %d & b= %d on swap\n", a, b);
}

void swap(int c, int d) { int t;
    t = c; c = d; d = t;
}
```

- a= 10 & b= 15 to swap
- a= 10 & b= 15 on swap // No swap

- Passing values of a=10 & b=15
- In callee; c = 10 & d = 15
- Swapping the values of c & d
- No change for the values of a & b in caller
- Swapping the value of c & d instead of a & b

Call-by-address – right

```
#include <stdio.h>

void swap(int *, int *); // Call-by-address
int main() { int a=10, b=15;
    printf("a= %d & b= %d to swap\n", a, b);
    swap(&a, &b); // Unnatural call
    printf("a= %d & b= %d on swap\n", a, b);
}

void swap(int *x, int *y) { int t;
    t = *x; *x = *y; *y = t;
}
```

- a= 10 & b= 15 to swap
- a= 15 & b= 10 on swap // Correct swap

- Passing Address of a & b
- In callee x = Addr(a) & y = Addr(b)
- Values at the addresses is swapped
- Desired changes for the values of a & b in caller
- It is correct, but C++ has a better way out



Program 07.04: Swap in C & C++

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

C Program: Call-by-value – wrong

```
#include <stdio.h>

void swap(int, int); // Call-by-value
int main() { int a = 10, b = 15;
    printf("a= %d & b= %d to swap\n",a,b);
    swap(a, b);
    printf("a= %d & b= %d on swap\n",a,b);
}
void swap(int c, int d) { int t ;
    t = c; c = d; d = t;
}
```

- a= 10 & b= 15 to swap
- a= 10 & b= 15 on swap // No swap

- Passing values of a=10 & b=15
- In callee; c = 10 & d = 15
- Swapping the values of c & d
- No change for the values of a & b in caller
- Here c & d do not share address with a & b

C++ Program: Call-by-reference – right

```
#include <iostream>
using namespace std;
void swap(int&, int&); // Call-by-reference
int main() { int a = 10, b = 15;
    cout<<"a= "<<a<<" & b= "<<b<<"to swap"<<endl;
    swap(a, b); // Natural call
    cout<<"a= "<<a<<" & b= "<<b<<"on swap"<<endl;
}
void swap(int &x, int &y) { int t ;
    t = x; x = y; y = t;
}
```

- a= 10 & b= 15 to swap
- a= 15 & b= 10 on swap // Correct swap

- Passing values of a = 10 & b = 15
- In callee: x = 10 & y = 15
- Swapping the values of x & y
- Desired changes for the values of a & b in caller
- x & y having same address as a & b respectively



Program 07.05: Reference Parameter as const

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

- A reference parameter may get changed in the called function
- Use **const** to stop reference parameter being changed

const reference – bad	const reference – good
<pre>#include <iostream> using namespace std; int Ref_const(const int &x) { ++x; // Not allowed return (x); } int main() { int a = 10, b; b = Ref_const(a); cout << "a = " << a << " and" << " b = " << b; }</pre>	<pre>#include <iostream> using namespace std; int Ref_const(const int &x) { return (x + 1); } int main() { int a = 10, b; b = Ref_const(a); cout << "a = " << a << " and" << " b = " << b; }</pre>
<ul style="list-style-type: none">• Error: Increment of read only Reference 'x'	<p>a = 10 and b = 11</p>
<ul style="list-style-type: none">• Compilation Error: Value of x cannot be changed• Implies, a cannot be changed through x	<ul style="list-style-type: none">• No violation



Return-by-Reference

Module M07

Partha Pratim Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

**Return-by-
Reference**

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

NPTEL

Return-by-Reference



Program 07.06: Return-by-Reference

- A function can return a value by reference (**Return-by-Reference**)
- C uses **Return-by-value**

Return-by-value

```
#include <iostream>
using namespace std;
int Function_Return_By_Val(int &x) {
    cout << "x = " << x << " &x = " << &x << endl;
    return (x);
}
int main() { int a = 10;
    cout << "a = " << a << " &a = " << &a << endl;
    const int& b = // const needed. Why?
        Function_Return_By_Val(a);
    cout << "b = " << b << " &b = " << &b << endl;
}
```

```
a = 10 &a = 00DCFD18
x = 10 &x = 00DCFD18
b = 10 &b = 00DCFD00 // Reference to temporary
```

- Returned variable is **temporary**
 - Has a **different address**
- Programming in Modern C++

Return-by-reference

```
#include <iostream>
using namespace std;
int& Function_Return_By_Ref(int &x) {
    cout << "x = " << x << " &x = " << &x << endl;
    return (x);
}
int main() { int a = 10;
    cout << "a = " << a << " &a = " << &a << endl;
    const int& b = // const optional
        Function_Return_By_Ref(a);
    cout << "b = " << b << " &b = " << &b << endl;
}
```

```
a = 10 &a = 00A7F8FC
x = 10 &x = 00A7F8FC
b = 10 &b = 00A7F8FC // Reference to a
```

- Returned variable is **an alias of a**
 - Has the **same address**
- Partha Pratim Das



Program 07.07: Return-by-Reference can get tricky

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

Return-by-reference

```
#include <iostream>
using namespace std;
int& Return_ref(int &x) {

    return (x);
}

int main() { int a = 10, b = Return_ref(a);
    cout << "a = " << a << " and b = "
        << b << endl;

    Return_ref(a) = 3; // Changes variable a
    cout << "a = " << a;
}
```

a = 10 and b = 10
a = 3

- Note how *a value is assigned to function call*
- This can change a local variable

Return-by-reference – Risky!

```
#include <iostream>
using namespace std;
int& Return_ref(int &x) {
    int t = x;
    t++;
    return (t);
}

int main() { int a = 10, b = Return_ref(a);
    cout << "a = " << a << " and b = "
        << b << endl;

    Return_ref(a) = 3; // Changes local t
    cout << "a = " << a;
}
```

a = 10 and b = 11
a = 10

- We expect *a* to be 3, *but it has not changed*
- It *returns reference to local*. This is *risky*



I/O Parameters of a Function

Module M07

Partha Pratim Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

I/O Parameters of a Function



I/O of a Function

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

- In C++ we can change values with a function as follows:

I/O of Function	Purpose	Mechanism
Value Parameter	Input	Call-by-value
Reference Parameter	In-Out	Call-by-reference
<code>const</code> Reference Parameter	Input	Call-by-reference
Return Value	Output	Return-by-value Return-by-reference <code>const</code> Return-by-reference

- In addition, we can use the **Call-by-address** (**Call-by-value** with pointer) and **Return-by-address** (**Return-by-value** with pointer) as in C
- But it is neither required nor advised



Recommended Mechanisms

Module M07

Partha Pratim Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

Recommended Mechanisms



Recommended Mechanisms

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

- **Call**

- Pass parameters of **built-in types** *by value*
 - ▷ Recall: *Array parameters* are passed *by reference* in **C** and **C++**
- Pass parameters of **user-defined types** *by reference*
 - ▷ Make a *reference parameter* **const** if it is not used for output

- **Return**

- Return **built-in types** *by value*
- Return **user-defined types** *by reference*
 - ▷ Return value *is not copied back*
 - ▷ May be *faster* than returning a value
 - ▷ **Beware:** Calling function *can change returned object*
 - ▷ **Never return a local variables by reference**



Difference between Reference and Pointer

Module M07

Partha Pratim
Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

NPTEL

Difference between Reference and Pointer



Difference between Reference and Pointer

Module M07

Partha Pratim Das

Objectives & Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference Parameter

Return-by-Reference

Pitfalls

I/O Params of a Function

Recommended Mechanisms

References vs. Pointers

Module Summary

Pointers

- Refers to an *address (exposed)*
- Pointers can point to **NULL**

```
int *p = NULL; // p is not pointing
```

- Pointers can point to *different variables* at *different times*

```
int a, b, *p;
```

```
p = &a; // p points to a
```

```
...
```

```
p = &b; // p points to b
```

- **NULL** checking *is required*
- *Allows* users to *operate on the address*
- diff pointers, increment, etc.
- *Array of pointers* can be *defined*

References

- Refers to an *address (hidden)*
- References cannot be **NULL**

```
int &j ; // wrong
```

- For a reference, its *referent is fixed*

```
int a, c, &b = a; // Okay
```

```
...
```

```
&b = c // Error
```

- *Does not require* **NULL** checking
- Makes code *faster*
- *Does not allow* users to *operate on the address*
- All operations are interpreted for the referent
- *Array of references* *not allowed*



Module Summary

Module M07

Partha Pratim
Das

Objectives &
Outlines

Reference

Pitfalls

Call-by-Reference

Swap in C

Swap in C++

const Reference
Parameter

Return-by-
Reference

Pitfalls

I/O Params of a
Function

Recommended
Mechanisms

References vs.
Pointers

Module Summary

- Introduced reference in C++
- Studied the difference between call-by-value and call-by-reference
- Studied the difference between return-by-value and return-by-reference
- Discussed the difference between References and Pointers