Status	Finished
Started	Friday, 30 October 2026, 11:20 PM
Completed	Friday, 30 October 2026, 11:22 PM
Duration	2 mins 20 secs
Grade	**14.00** out of 15.00 (**93.33**%)

Question **1**

Complete

Mark 1.00 out of 1.00

Algorithm design technique used in merge sort algorithm is

- a. Greedy method
- b. Dynamic programming
- c. Divide and conquer
- d. Backtracking

The correct answer is:
Divide and conquer

Question **2**

Complete

Mark 1.00 out of 1.00

Which of the following is not an in-place sorting algorithm?

- a. Quick sort
- b. Merge sort
- c. Selection sort
- d. Heap sort

The correct answer is:
Merge sort

Question **3**

Complete

Mark 1.00 out of 1.00

Why is it advantageous to sort data before performing duplicate analysis?

a. It has no effect on the analysis process
b. It makes the analysis slower
c. It complicates the analysis process
d. It allows for quicker identification of duplicates

The correct answer is: It allows for quicker identification of duplicates

Question **4**

Complete

Mark 1.00 out of 1.00

Which sorting algorithm is described as making multiple passes through a list, comparing elements, and swapping adjacent items that are out of order?

a. Merge Sort
b. Insertion Sort
c. Quick Sort
d. Bubble Sort

The correct answer is: Bubble Sort

Question **5**

Complete

Mark 1.00 out of 1.00

What does the Bubble Sort algorithm primarily focus on during each pass?

a. Bubbling up the smallest element
b. Dividing the list into halves
c. Sorting the entire list in one pass
d. Bubbling up the largest element to its correct position

The correct answer is: Bubbling up the largest element to its correct position

Question **6**

Complete

Mark 1.00 out of 1.00

How does Merge Sort achieve its efficiency?

a. By sorting data in a single pass
b. By breaking the input into smaller parts and merging them
c. By comparing elements sequentially
d. By using the bubble-up method

The correct answer is: By breaking the input into smaller parts and merging them

Question **7**

Complete

Mark 1.00 out of 1.00

Which sorting algorithm would be preferred for its divide-and-conquer approach?

a. Merge Sort
b. Linear Search
c. Binary Search
d. Bubble Sort

The correct answer is: Merge Sort

Question **8**

Complete

Mark 1.00 out of 1.00

Which sorting algorithm is known for its simplicity and sequential comparison of elements?

a. Merge Sort
b. Bubble Sort
c. Quick Sort
d. Heap Sort

The correct answer is: Bubble Sort

Question **9**

Complete

Mark 0.00 out of 1.00

What is mean by stable sorting algorithm?

- a. A sorting algorithm is stable if it preserves the order of all keys
- b. A sorting algorithm is stable if it doesn't preserver the order of duplicate keys
- c. A sorting algorithm is stable if it preserves the order of duplicate keys
- d. A sorting algorithm is stable if it preserves the order of non-duplicate keys

The correct answer is:
A sorting algorithm is stable if it preserves the order of duplicate keys

Question **10**

Complete

Mark 1.00 out of 1.00

_____is putting an element in the appropriate place in a sorted list yields a larger sorted order list.

- a. Selection
- b. Insertion
- c. Extraction
- d. Distribution

The correct answer is:
Insertion

Question **11**

Complete

Mark 1.00 out of 1.00

Which Python function would you use to sort a list in-place?

- a. sorted()
- b. arrange()
- c. sort()
- d. order()

The correct answer is: sort()

Question **12**

Complete

Mark 1.00 out of 1.00

What is a key disadvantage of Bubble Sort compared to more advanced algorithms like Merge Sort?

a. Bubble Sort cannot handle duplicate elements
b. Bubble Sort is difficult to implement
c. Bubble Sort is less efficient for large lists
d. Bubble Sort does not guarantee sorted order

The correct answer is: Bubble Sort is less efficient for large lists

Question **13**

Complete

Mark 1.00 out of 1.00

What is the primary benefit of using sorting algorithms in programming?

a. Decreases the efficiency of algorithms
b. Makes data harder to manage
c. Provides a basis for other algorithms to work efficiently
d. Makes code execution slower

The correct answer is: Provides a basis for other algorithms to work efficiently

Question **14**

Complete

Mark 1.00 out of 1.00

What is one of the key advantages of using the built-in sorted() function in Python?

a. It is less efficient than custom sorting algorithms
b. It only works with integer arrays
c. It requires external libraries
d. It sorts data out of the box efficiently

The correct answer is: It sorts data out of the box efficiently

Question **15**

Complete

Mark 1.00 out of 1.00

Which of the following is a key reason for the importance of sorting algorithms?

- a. Sorting helps in finding duplicates quickly
- b. Sorting is rarely used in programming
- c. Sorting decreases the efficiency of selection operations
- d. Sorting makes it harder to search for items

The correct answer is: Sorting helps in finding duplicates quickly

Status	Finished
Started	Friday, 30 October 2026, 11:23 PM
Completed	Friday, 30 October 2026, 11:28 PM
Duration	4 mins 59 secs
Grade	**10.00** out of 10.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

To find the frequency of numbers in a list and display in sorted order.

Constraints:

1<=n, arr[i]<=100

Input:

1 68 79 4 90 68 1 4 5

output:

1 2

4 2

5 1

68 2

79 1

90 1

For example:

Input	Result
4 3 5 3 4 5	3 2 4 2 5 2

Answer: (penalty regime: 0 %)

```
from collections import Counter

arr = list(map(int, input().split()))

freq = Counter(arr)

for num in sorted(freq):
    print(num, freq[num])
```

	Input	Expected	Got	
✓	4 3 5 3 4 5	3 2 4 2 5 2	3 2 4 2 5 2	✓
✓	12 4 4 4 2 3 5	2 1 3 1 4 3 5 1 12 1	2 1 3 1 4 3 5 1 12 1	✓

	Input	Expected	Got	
✓	5 4 5 4 6 5 7 3	3 1 4 2 5 3 6 1 7 1	3 1 4 2 5 3 6 1 7 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **2**

Correct

Mark 1.00 out of 1.00

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in wrong order. You read an list of numbers. You need to arrange the elements in ascending order and print the result. The sorting should be done using bubble sort.

Input Format: The first line reads the number of elements in the array. The second line reads the array elements one by one.

Output Format: The output should be a sorted list.

For example:

Input	Result
6 3 4 8 7 1 2	1 2 3 4 7 8
5 4 5 2 3 1	1 2 3 4 5

Answer: (penalty regime: 0 %)

```
n = int(input())
arr = list(map(int, input().split()))

for i in range(n):
    for j in range(0, n - i - 1):
        if arr[j] > arr[j + 1]:
            arr[j], arr[j + 1] = arr[j + 1], arr[j]

print(*arr)
```

	Input	Expected	Got	
✓	6 3 4 8 7 1 2	1 2 3 4 7 8	1 2 3 4 7 8	✓
✓	6 9 18 1 3 4 6	1 3 4 6 9 18	1 3 4 6 9 18	✓
✓	5 4 5 2 3 1	1 2 3 4 5	1 2 3 4 5	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **3**

Correct

Mark 1.00 out of 1.00

Objective:

Develop a Python program to find the k-th maximum value in a given list of integers. The program should handle various edge cases, including lists with duplicate values, empty lists, and invalid values of k. The k-th maximum value refers to the k-th largest distinct element in the list.

Background:

Finding the k-th maximum value in a list is a common problem in computer science, often encountered in fields like data analysis, competitive programming, and software development. This problem requires an understanding of sorting algorithms, data structures, and efficient problem-solving techniques. By solving this problem, one gains insights into how to handle large datasets and optimize performance in practical applications.

Problem Description:

Given a list of integers, the task is to determine the k-th maximum value in the list. The program should meet the following requirements:

1. **Input:**
    - A list of integers, which can contain both positive and negative values.
    - An integer k, representing the position of the maximum value to find.
2. **Output:**
    - The k-th maximum value in the list.
    - If k is greater than the number of distinct elements in the list or if the list is empty, the program should return an appropriate message indicating the error.

Constraints:

- The list may contain duplicate values.
- The value of k should be a positive integer.
- The list may contain up to 10^6 elements, and each element can be as large as 10^9 in magnitude.

Examples:

Consider the following examples for better understanding:

1. **Example 1:**
    - **Input:** list = [3, 1, 5, 4, 2], k = 2
    - **Output:** 4
    - **Explanation:** The distinct elements in the list are [1, 2, 3, 4, 5]. The 2nd maximum value is 4.
2. **Example 2:**
    - **Input:** list = [7, 7, 7, 7, 7], k = 1
    - **Output:** 7
    - **Explanation:** The distinct elements in the list are [7]. The 1st maximum value is 7.
3. **Example 3:**
    - **Input:** list = [2, 1, 2, 1, 2], k = 3
    - **Output:** -1
    - **Explanation:** The distinct elements in the list are [1, 2]. There is no 3rd maximum value.

For example:

Input	Result
5 3 1 5 4 2 2	4
6 7 7 7 7 7 7 1	7
10 2 1 2 1 2 1 2 1 2 1 3	-1

Answer: (penalty regime: 0 %)

```
n = int(input())
arr = list(map(int, input().split()))
k = int(input())

unique = sorted(set(arr), reverse=True)

if k <= 0 or k > len(unique):
    print(-1)
else:
    print(unique[k - 1])
```

	Input	Expected	Got	
✓	5 3 1 5 4 2 2	4	4	✓
✓	6 7 7 7 7 7 7 1	7	7	✓
✓	10 2 1 2 1 2 1 2 1 2 1 3	-1	-1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **4**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums`, return *an integer array* `counts` *where* `counts[i]` *is the number of smaller elements to the right of* `nums[i]`.

Example 1:

```
Input: nums = [5,2,6,1]
Output: [2,1,1,0]
Explanation:
To the right of 5 there are 2 smaller elements (2 and 1).
To the right of 2 there is only 1 smaller element (1).
To the right of 6 there is 1 smaller element (1).
To the right of 1 there is 0 smaller element.
```

Example 2:

```
Input: nums = [-1]
Output: [0]
```

Example 3:

```
Input: nums = [-1,-1]
Output: [0,0]
```

Constraints:

- `1 <= nums.length <= 10^5`
- `-10^4 <= nums[i] <= 10^4`

For example:

Test	Result
`print(countSmaller([5,2,6,1]))`	`[2, 1, 1, 0]`
`print(countSmaller([-1]))`	`[0]`

Answer: (penalty regime: 0 %)

Reset answer

```python
def countSmaller(nums):
    sorted_nums = sorted(set(nums))
    rank = {num: i + 1 for i, num in enumerate(sorted_nums)}

    n = len(nums)
    tree = [0] * (len(sorted_nums) + 1)
    counts = [0] * n

    def update(i):
        while i < len(tree):
            tree[i] += 1
            i += i & -i

    def query(i):
        total = 0
        while i > 0:
            total += tree[i]
            i -= i & -i
        return total

    for i in range(n - 1, -1, -1):
        r = rank[nums[i]]
        counts[i] = query(r - 1)
        update(r)

    return counts
```

	Test	Expected	Got	
✓	`print(countSmaller([5,2,6,1]))`	`[2, 1, 1, 0]`	`[2, 1, 1, 0]`	✓
✓	`print(countSmaller([50,20,60,10]))`	`[2, 1, 1, 0]`	`[2, 1, 1, 0]`	✓
✓	`print(countSmaller([-1]))`	`[0]`	`[0]`	✓
✓	`print(countSmaller([-1, -1]))`	`[0, 0]`	`[0, 0]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **5**

Correct

Mark 1.00 out of 1.00

Given an array of integers `nums`, sort the array in **increasing** order based on the frequency of the values. If multiple values have the same frequency, sort them in **decreasing** order.

Print the *sorted array*.

Example 1:

```
Input:
6
1 1 2 2 2 3

Output:
3 1 1 2 2 2

Explanation: '3' has a frequency of 1, '1' has a frequency of 2, and '2' has a frequency of 3.
```

Example 2:

```
Input:
5
2 3 1 3 2
Output:
1 3 3 2 2
Explanation: '2' and '3' both have a frequency of 2, so they are sorted in decreasing order.
```

Example 3:

```
Input:
9
-1 1 -6 4 5 -6 1 4 1
Output:
5 -1 4 4 -6 -6 1 1 1
```

Constraints:

- `1 <= nums.length <= 100`
- `-100 <= nums[i] <= 100`

For example:

Input	Result
6 1 1 2 2 2 3	3 1 1 2 2 2
5 2 3 1 3 2	1 3 3 2 2

Answer: (penalty regime: 0 %)

```
from collections import Counter

n = int(input())
nums = list(map(int, input().split()))

freq = Counter(nums)

nums.sort(key=lambda x: (freq[x], -x))

print(*nums)
```

	Input	Expected	Got	
✓	6 1 1 2 2 2 3	3 1 1 2 2 2	3 1 1 2 2 2	✓
✓	5 2 3 1 3 2	1 3 3 2 2	1 3 3 2 2	✓
✓	9 -1 1 -6 4 5 -6 1 4 1	5 -1 4 4 -6 -6 1 1 1	5 -1 4 4 -6 -6 1 1 1	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **6**

Correct

Mark 1.00 out of 1.00

Given an integer array `nums` sorted in **non-decreasing** order, return *an array of **the squares of each number** sorted in non-decreasing order*.

Example 1:

```
Input: nums = [-4,-1,0,3,10]
Output: [0,1,9,16,100]
Explanation: After squaring, the array becomes [16,1,0,9,100].
After sorting, it becomes [0,1,9,16,100].
```

Example 2:

```
Input: nums = [-7,-3,2,3,11]
Output: [4,9,9,49,121]
```

Constraints:

- `1 <= nums.length <= 10^4`
- `-10^4 <= nums[i] <= 10^4`
- `nums` is sorted in **non-decreasing** order.

For example:

Test	Result
`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`

Answer: (penalty regime: 0 %)

Reset answer

```
def sortedSquares(nums):
    left = 0
    right = len(nums) - 1
    result = []

    while left <= right:
        if abs(nums[left]) > abs(nums[right]):
            result.append(nums[left] ** 2)
            left += 1
        else:
            result.append(nums[right] ** 2)
            right -= 1

    return result[::-1]
```

	Test	Expected	Got	
✓	`print(sortedSquares([-4,-1,0,3,10]))`	`[0, 1, 9, 16, 100]`	`[0, 1, 9, 16, 100]`	✓
✓	`print(sortedSquares([-7,-3,2,3,11]))`	`[4, 9, 9, 49, 121]`	`[4, 9, 9, 49, 121]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **7**

Correct

Mark 1.00 out of 1.00

Write a Python program to sort a list of elements using the merge sort algorithm.

For example:

Input	Result
5 6 5 4 3 8	3 4 5 6 8

Answer: (penalty regime: 0 %)

```
def mergeSort(arr):
    if len(arr) <= 1:
        return arr

    mid = len(arr) // 2
    left = mergeSort(arr[:mid])
    right = mergeSort(arr[mid:])

    result = []
    i = j = 0

    while i < len(left) and j < len(right):
        if left[i] <= right[j]:
            result.append(left[i])
            i += 1
        else:
            result.append(right[j])
            j += 1

    result.extend(left[i:])
    result.extend(right[j:])

    return result


n = int(input())
arr = list(map(int, input().split()))

sorted_arr = mergeSort(arr)
print(*sorted_arr)
```

	Input	Expected	Got	
✓	5 6 5 4 3 8	3 4 5 6 8	3 4 5 6 8	✓
✓	9 14 46 43 27 57 41 45 21 70	14 21 27 41 43 45 46 57 70	14 21 27 41 43 45 46 57 70	✓
✓	4 86 43 23 49	23 43 49 86	23 43 49 86	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **8**

Correct

Mark 1.00 out of 1.00

Given an listof integers, sort the array in ascending order using the *Bubble Sort* algorithm above. Once sorted, print the following three lines:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

For example, given a worst-case but small array to sort: a=[6,4,1]. It took 3 swaps to sort the array. Output would be

```
Array is sorted in 3 swaps.
```

```
First Element: 1
```

```
Last Element: 6
```

Input Format

The first line contains an integer,n , the size of the list a .
The second line contains n, space-separated integers a[i].

Constraints

· 2<=n<=600

· 1<=a[i]<=$2x10^6$.

Output Format

You must print the following three lines of output:

1. List is sorted in numSwaps swaps., where numSwaps is the number of swaps that took place.
2. First Element: firstElement, the *first* element in the sorted list.
3. Last Element: lastElement, the *last* element in the sorted list.

Sample Input 0

3

1 2 3

Sample Output 0

List is sorted in 0 swaps.

First Element: 1

Last Element: 3

For example:

Input	Result
3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3
5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9

Answer: (penalty regime: 0 %)

```
n = int(input())
arr = list(map(int, input().split()))

numSwaps = 0

for i in range(n):
    swapped = False

    for j in range(n - i - 1):
        if arr[j] > arr[j + 1]:
```

```
            arr[j], arr[j + 1] = arr[j + 1], arr[j]
            numSwaps += 1
            swapped = True

    if not swapped:
        break

print("List is sorted in", numSwaps, "swaps.")
print("First Element:", arr[0])
print("Last Element:", arr[-1])
```

	Input	Expected	Got	
✓	3 3 2 1	List is sorted in 3 swaps. First Element: 1 Last Element: 3	List is sorted in 3 swaps. First Element: 1 Last Element: 3	✓
✓	5 1 9 2 8 4	List is sorted in 4 swaps. First Element: 1 Last Element: 9	List is sorted in 4 swaps. First Element: 1 Last Element: 9	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **9**

Correct

Mark 1.00 out of 1.00

The problem is that we want to reverse a array in O(N) linear time complexity and we want the algorithm to be in-place as well!
For example: input is [1,2,3,4,5] then the output is [5,4,3,2,1]
Input
5
1 2 3 4 5
Output
5 4 3 2 1

For example:

Input	Result
5 1 2 3 4 5	5 4 3 2 1

Answer: (penalty regime: 0 %)

```
n = int(input())
arr = list(map(int, input().split()))

left = 0
right = n - 1

while left < right:
    arr[left], arr[right] = arr[right], arr[left]
    left += 1
    right -= 1

print(*arr)
```

	Input	Expected	Got	
✓	5 1 2 3 4 5	5 4 3 2 1	5 4 3 2 1	✓
✓	10 0 2 4 6 8 1 3 5 7 9	9 7 5 3 1 8 6 4 2 0	9 7 5 3 1 8 6 4 2 0	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

Question **10**

Correct

Mark 1.00 out of 1.00

Given an array of integers `arr`, replace each element with its rank.

The rank represents how large the element is. The rank has the following rules:

- Rank is an integer starting from 1.
- The larger the element, the larger the rank. If two elements are equal, their rank must be the same.
- Rank should be as small as possible.

Example 1:

```
Input: arr = [40,10,20,30]
Output: [4,1,2,3]
Explanation: 40 is the largest element. 10 is the smallest. 20 is the second smallest. 30 is the third smallest.
```

Example 2:

```
Input: arr = [100,100,100]
Output: [1,1,1]
Explanation: Same elements share the same rank.
```

Example 3:

```
Input: arr = [37,12,28,9,100,56,80,5,12]
Output: [5,3,4,2,8,6,7,1,3]
```

Constraints:

- $0 <= arr.length <= 10^5$
- $-10^9 <= arr[i] <= 10^9$

For example:

Test	Result
print(arrayRankTransform([40,10,20,30]))	[4, 1, 2, 3]

Answer: (penalty regime: 0 %)

Reset answer

```
def arrayRankTransform(arr):
    sorted_unique = sorted(set(arr))
    rank = {value: i + 1 for i, value in enumerate(sorted_unique)}

    return [rank[num] for num in arr]
```

	Test	Expected	Got	
✓	`print(arrayRankTransform([40,10,20,30]))`	`[4, 1, 2, 3]`	`[4, 1, 2, 3]`	✓
✓	`print(arrayRankTransform([100,100,100]))`	`[1, 1, 1]`	`[1, 1, 1]`	✓
✓	`print(arrayRankTransform([37,12,28,9,100,56,80,5,12]))`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	`[5, 3, 4, 2, 8, 6, 7, 1, 3]`	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.