Agenda of thursday.



Trapping Rain water:

1m³ = volum?
↳ 1000 Litre



Amount of water store b/w building ?

water in terms of volume, water on head of iᵗʰ building

Bruteforce - ⓪ →

* Reach at Every building & find leftmax & Right max
* find water on head of iᵗʰ building

Bruteforce ① →

Manage lmax & rmax from an array,

← left → right

highest building in left

highest building in Right

water += min(lmax, rmax) × 1 (width) − ht[i] × 1 (occupied by building) — volume, height

How we get lmax & rmax. ??

Trapping Rain water using STACK



next greater Element

Stack order
↳ Decreasing from Bottom to top

rmax = 4, rmaxindex = 6
current height = 0
lmax = 8, lmax index = 4.
water += ht of wall



rmax = 8, rmax index = 4.
current height = 4, 6, 7
size = peek(
lmax = 6, 7, 10; lmax index = 2, 1, 0
width = rmax index − lmax index − 1;
water += [min(lmax, rmax) − current height] * width
height

rmax = 2
index = st.pop(); = 5
curr building = height[index]
lmax index = 0
water += .

width

This Approach is Application of next greater on right

Trapping Rain water using two pointer Approach:

Think About head of building.



left = 0 1 2 3 4

leftmax = 10 12

right = 13 12 11 10 8 8 7 6 5 4

rightmax = 7 8 11

```
while( left < right) {
    leftmax = max(leftmax, ht[left]);
    rightmax = max(rightmax, ht[right]);
    if(leftmax < rightmax) {
        water += leftmax - ht[left];
        left ++;
    } else {
        water += rightmax - ht[right];
        right --;
    }
}
```

water = 0 + 3 + 8 + 2 + 4 + 3 + 4 + 6 + 7 + 11 = 48

= Result

overall res = 0+3+4+6 + 11+7 +3 +8+2 +4




```
if(max <= ht[i]){
  max = ht[i];
  overall res += water;
  water = 0;
}
water = max - currht
```

water = 0 +3 +4 +6 + 0 +11 +7 + 0 +8 +6 +12 +4 +8 +5 +

max = ~~10~~ ~~11~~ 12

max index

water = 0+3 + 0 +8 +2 +4

max = ~~7~~ 8 → iteration from Right to left

↳ stop at max index (old)

j

"35 + 27 - 8"

i

"35" → String to int