

dedicated

O Dedicated Servers

- o Single Processor Servers
- o <u>Dual Processor Servers</u>
- O Quad Processor Servers
- O Colocation Services
- O View & Compare Servers

O Dedicated Add-Ons

- o <u>Firewall</u>
- O Load Balancers
- O Backup & Storage
- o <u>SAN Solutions</u>
- o Private Switch
- o Remote KVM
- o PCI Compliance

• storm servers

O Storm Servers

- The Storm Platform
- o Storm Dedicated Servers
- o Storm VPS
- o Storm SSD
- Why Storm Servers?
- Pricing
- o Create a Storm Server

• vps

O Virtual Private Servers

- o Managed VPS Hosting
- O View & Compare Plans

• web hosting

O Expert Web Hosting

- O Standard Plan
- o <u>Webmaster Plan</u>
- o <u>Professional Plan</u>
- O View & Compare Plans

• solutions

Solutions

- O Hybrid Hosting
- O High Performance
- Enterprise Class Servers
- Linux Hosting
- CloudLinux Hosting
- O Windows Hosting
- o Small & Medium Businesses
- o <u>Disaster Recovery</u>
- o <u>HIPAA Compliant Hosting</u>
- o Game Server Hosting

Chat with a Hero

services

O Hosting Services

- O DDoS Attack Protection
- Security Services
- Content Delivery Network
- o E-Mail Hosting
- O Database Hosting
- o Media Servers
- o <u>E-Commerce Hosting</u>
- Blog Hosting
- o CMS Hosting
- O Ruby on Rails Hosting
- o <u>IPv6 Transition</u>
- O Windows Resource Manager
- WHMCS Plugin

• data centers

O Liquid Web Data Centers

- o Colocation Services
- o Michigan Data Centers
- O Arizona Data Center
- o SSAE-16 Compliance
- The Liquid Web Network

• support

O Heroic Support

- o <u>Heroic Promise</u>
- Support Overview
- o Support Comparison
- o Knowledge Base
- o <u>Tutorials</u>

CONNECT WITH US:



About Liquid Web

A Leader In Managed Hosting since 1997

Our Heroic Support technicians are located on-site at each of our data centers.

Liquid Web Heroic Support On-Site Support, Available 24/7/365. Our Support Team is available to you anytime via Phone, Help Desk, or E-Mail.

- Support Overview
- Knowledge Base
- Tutorials

Liquid Web Knowledge Base



2 of 5



Popular Tags Click to view related articles Billing + Manage

account management apache apache cassandra Centos centos 6 centos 6 centos 7 cli Command line

core managed cpanel database dns email fedora fedora 20 fedora 21 firewall ftp linux LTS manage management mariadb mysql name servers nosql plesk Security Server SSh ssl storm system systemctl systemd tools tutorial ubuntu ubuntu 12.04 ubuntu 14.04 update whm windows



Subscribe by E-Mail

Enter Your E-mail Add



Knowledge Base

New User Tutorial: Basic File Permissions

Filed under: Featured Articles, Technical Support

Understanding file permissions is key to running a web server. Permissions control which users can read a file, make changes to a file, or execute a file/script/etc.

File permissions on a Linux server are always listed in a series of three, meaning when you are viewing permissions for a file you are actually looking at the permissions for three different roles: The user who owns the file, the group that is also assigned to the file, and everyone else (a.k.a "world" permissions).

Each of these sets has three different permission types that can be on or off: Read (r), Write(w), and Execute (x).

Illustrated visually:



The directory bit indicates that the item is a folder/directory and not a normal file. This can appear as a few different items, but **d** (directory) and **- (dash)** (regular file) are most commonly seen on the server.

Symbolic Permission Notation

--- no permission
--x execute
-w- write
-wx write and execute
r-- read
r-x read and execute
rw- read and write
rwx read, write and execute

Numeric Permission Notation

The numeric notation system uses the digits 1 through 7, with each corresponding to a different symbolic permission set:

0 --- no permission
1 --x execute

2 -w- write

3 -wx write and execute

4 r-- read

3 of 5

```
5 r-x read and execute
6 rw- read and write
7 rwx read, write and execute
```

What Each Type Controls

Read

Display the contents of a file. You may be able to open it in text editors like Vim, but you will not be able to save any changes to the file unless you also have Write permissions.

Write

Make changes to a file or folder/directory.

Execute

Execute (a.k.a. Run) a file. Examples include compiled binaries and shell scripts.

Working With Existing Permissions

Say you want to figure out what the existing permissions are on your **public_html** folder. Your web designer friend asks you "Is your public_html folder using 644 permissions or 755?"

You ssh into your Linux server and take a look:

```
root@host [/home/user]# 1s -lah
drwx--x--x 17 user user 4.0K Oct 27 17:04 ./
drwx--x--x 25 root root 4.0K Oct 22 09:59 ../
drwxrwx--- 7 user user 4.0K Oct 13 09:28 mail/
drwxr-x--- 3 user user 4.0K May 16 2008 public_ftp/
drwxr-xr-x 12 user nobody 4.0K Oct 28 14:03 public_html/
drwxr-xr-x 7 user user 4.0K Oct 13 09:28 tmp/
```

In order to figure out the existing permissions of public_html we are only concerned with this line:

```
drwxr-xr-x 12 user nobody 4.0K Oct 28 14:03 public_html/
```

Most public_html folders use permissions that range from 644 to 755.

Using the numeric notation above, 644 translates into the symbolic notation as:

```
6 - rw-
4 - r--
4 - r--
```

Now you simply combine the three symbolic parts and you end up with:

```
rw-r--r--
```

Same process for 755 permissions:

```
7 - rwx
5 - r-x
5 - r-x
So 755 = rwxr-xr-x
```

Now we know that the existing permissions on the public_html folder in the example above are 755.

Changing Permissions and Ownership

Users can only change permissions and ownership on files that are owned by them. The root user can modify any permissions, regardless of existing permissions. As always, please remember that the root user can cause a lot of damage if you are not extremely careful.

To change permissions, use the **chmod** command.

Examples:

```
chmod 644 file.php
```

Changes the permissions on file.php to 644.

```
chmod -R 644 folderb/
```

Changes the permissions on the directory called folderb, and everything inside of it, to 644.

To change which user or group owns a file, use the **chown** command.

Examples:

```
chown bob:bob file.php
```

Changes the ownership of file.php to the user and group bob.

```
chown -R bob:bob folderb/
```

Changes the ownership of the directory called folderb, and everything inside of it, to the user and group bob.

When using chown the new ownership is specified using a **user:group** syntax. Many Linux servers create both a corresponding group name that matches the username in order to keep various server accounts from being able to access other web site's files on the same server. If you have a Linux server running cPanel this is what you will see.

4 of 5

Liquid Web's Heroic Support is always available to assist customers with this or any other issue. If you need our assistance please contact us:

Toll Free 1.800.580.4985

International 517.322.0434

support@liquidweb.com

https://manage.liquidweb.com/

Be Sociable, Share!





Did You Find This Article Helpful?

Subscribe to our Knowledge Base for more useful articles and information.

Enter Your E-mail Add Subscribe



Related Articles

- New User Tutorial: Basic SSH
- New User Tutorial: Basic Shell Commands
- How To: Give a Linux User Root-level Access Using sudo
- Managing Time On A Linux Server
- Apache Error: "semget: No space left on device"
- About Liquid Web
 - o Our Company
 - Our Data Centers
 - Employment Opportunities
 - O Preferred Partners Program
 - o Press Releases
- Hosting Products
 - o Managed Dedicated Hosting
 - o Enterprise Hosting Solutions
 - O Virtual Private Servers
 - Expert Web Hosting
- <u>Solutions</u>
 - Liquid Web Select
 - E-Mail Hosting
 - Blog Hosting
 - E-Commerce Hosting
 - O Database Solutions
- Solutions Cont.
 - o CMS Solutions
 - Backup & Recovery
 - O Sonar Monitoring
 - Media Solutions
- <u>Support</u>
 - O Support Overview
 - Knowledge Base
 - O Site Map
- Contact Us
 - o 24 Hr Support 800-580-4985
 - Start a Live Chat
 - <u>E-Mail Us</u>
 - , aliquidweb

Copyright © 2011 Liquid Web, Inc. All Rights Reserved.

10-02-2015 2:09 AM 5 of 5