

[Home](#)   [Basic MySQL](#)   [MySQL Stored Procedures](#)   [MySQL Triggers](#)   [MySQL Views](#)  
[MySQL Functions](#)   [MySQL Administration](#)   [MySQL Tips](#)

## MySQL Triggers Implementation



**Summary:** in this tutorial, you will learn about **MySQL triggers implementation**. In addition, we will show you how MySQL stores trigger definitions and the limitations of triggers in MySQL.

### Introduction to MySQL triggers

In MySQL, a trigger is a set of SQL statements that is invoked automatically when a change is made to the data on the associated table. A trigger can be defined to be invoked either before or after the data is changed by [INSERT](#), [UPDATE](#) or [DELETE](#) statements. MySQL allows you to define maximum six triggers for each table.

- ▶ `BEFORE INSERT` – activated before data is inserted into the table.
- ▶ `AFTER INSERT` - activated after data is inserted into the



### MySQL Tutorial Newsletter

[Sign up](#) to receive updates about MySQL Tutorials and find out what's new in MySQL.

table.

## About MySQL Tutorial Website

► **BEFORE UPDATE** - activated before data in the table is updated.

► **AFTER UPDATE** - activated after data in the table is updated.

MySQLTutorial.org is a [website](#) dedicated to MySQL database.

► **BEFORE DELETE** - activated before data is removed from the table.

We regularly publish useful MySQL tutorials to help web developers and database administrators learn MySQL fast and use MySQL effectively.

► **AFTER DELETE** - activated after data is removed from the table.

When you use a statement that makes change to the table but does not use **INSERT**, **DELETE** or **UPDATE** statement, the trigger is not invoked. For example, **TRUNCATE** statement removes the whole data of a table but does not invoke the trigger with SQL script and associated with that table.

screenshots available.

[More](#)

[About Us](#)

There are some statements that use the **INSERT** statement.

MySQL is trademark of Oracle

behind the scenes such as **REPLACE** statement and **LOAD DATA** statement.

If you use these statements, the corresponding triggers associated with the tables if available will be invoked.

Triggers defined for a table must have a unique name. You can have the same trigger name that defines for [different tables](#) but it is not recommended. In practice, the names of triggers follow the following naming convention:

```
1 | (BEFORE | AFTER)_tableName_(INSERT|UPDATE | DELETE)
```

## MySQL Triggers Storage

MySQL stores triggers in a data directory e.g.,

/data/classicmodels/ with the files named

tablename.TRG and triggername.TRN :

- The **tablename.TRG** file maps the trigger to the corresponding table.
- the **triggername.TRN** file contains the trigger definition.

## Recent MySQL Tutorials

[MySQL Export Table to CSV](#)

[Raising Error Conditions with](#)

[SIGNAL / RESIGNAL](#)

[Statements](#)

[MySQL Error Handling in](#)

[Stored Procedures](#)

[MySQL Stored Function](#)

[Import CSV File into MySQL](#)

[Table TRUNCATE statement](#)

[MySQL Not Invoke the trigger](#)

[ORDER BY Clause](#)

[Modifying MySQL Events](#)

[Working with MySQL](#)

[Scheduled Event and LOAD](#)

[PHP MySQL BLOB](#)

[PHP MySQL Transaction](#)



## Site Links

[About Us](#)

[Contact Us](#)

[Request a Tutorial](#)

[Privacy Policy](#)

## MySQL Quick Start

[Install MySQL Database Server](#)

[Download MySQL Sample Database](#)

[Load Sample Database](#)

## MySQL Programming Interfaces

[PHP MySQL Tutorial](#)

[Perl MySQL Tutorial](#)

## Other Tutorials

[MySQL Full-Text Search](#)

[MySQL Cheat Sheet](#)

[MySQL Books](#)

[MySQL Hosting](#)

[MySQL Resources](#)

You can back up the MySQL triggers by copying the trigger files to the backup folder. You can also backup the triggers using the *mysqldump* tool.

## MySQL Trigger Limitations

MySQL triggers have all features in standard SQL however there are some limitations that you should know before using them in your applications.

MySQL triggers cannot:

- ▶ Use `SHOW` , `LOAD DATA` , `LOAD TABLE` , `BACKUP DATABASE`, `RESTORE` , `FLUSH` and `RETURN` statements.
- ▶ Use statements that commit or rollback implicitly or explicitly such as `COMMIT` , `ROLLBACK` , `START TRANSACTION` , `LOCK/UNLOCK TABLES` , `ALTER` , `CREATE` , `DROP` , `RENAME` , etc.
- ▶ Use [prepared statements](#) such as `PREPARE` , `EXECUTE` , etc.
- ▶ Use dynamic SQL statements.
- ▶ Call a [stored procedure](#) or stored function.

In this tutorial, we have shown you how triggers are implemented in MySQL. We also discussed about trigger's storage as well as trigger's limitations in MySQL.

## Related Tutorials

- ▶ [Introduction to SQL Trigger](#)
- ▶ [Create Trigger in MySQL](#)
- ▶ [Managing Trigger in MySQL](#)

---

Share this:



Previous Tutorial:

[Introduction to SQL Trigger](#)

Next Tutorial:



