Website Vulnerability Scanner Report

✔ **https://thehoneycake.com.au/**
Target added due to a redirect from http://thehoneycake.com.au/

The Light Website Scanner didn't check for critical issues like SQLi, XSS, Command Injection, XXE, etc.
Upgrade to run Deep scans with 40+ tests and detect more vulnerabilities.

Summary

Overall risk level:
Medium

Risk ratings:

Critical:	0
High:	0
Medium:	4
Low:	5
Info:	2

Scan information:

Start time:	Apr 03, 2026 / 13:21:43 UTC+08
Finish time:	Apr 03, 2026 / 13:22:58 UTC+08
Scan duration:	1 min, 15 sec
Tests performed:	39
Scan status:	Finished

Findings

Insecure cookie setting: missing HttpOnly flag
port 443/tcp

CONFIRMED

URL	Cookie Name	Evidence
https://thehoneycake.com.au/	localization, cart_currency, _shopify_y, _shopify_s	The server responded with Set-Cookie header(s) that does not specify the HttpOnly flag: Set-Cookie: localization=AU Set-Cookie: cart_currency=AUD Set-Cookie: _shopify_y=162f2819-9004-47f7-a088-6e510ee105cf Set-Cookie: _shopify_s=0b45cd09-9bea-4e4c-821e-1cbc93d5306e Request / Response

Details

Risk description:
The risk is that an attacker who injects malicious JavaScript code on the page (e.g. by using an XSS attack) can access the cookie and can send it to another site. In case of a session cookie, this could lead to session hijacking.

Recommendation:
Ensure that the HttpOnly flag is set for all cookies.

References:
https://owasp.org/www-community/HttpOnly

Classification:
CWE : CWE-1004
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A02 - Security Misconfiguration

Insecure cookie setting: missing Secure flag
port 443/tcp

CONFIRMED

URL	Cookie Name	Evidence

https://thehoneycake.com.au/	localization, cart_currency, _shopify_y, _shopify_s	Set-Cookie: localization=AU Set-Cookie: cart_currency=AUD Set-Cookie: _shopify_y=162f2819-9004-47f7-a088-6e510ee105cf Set-Cookie: _shopify_s=0b45cd09-9bea-4e4c-821e-1cbc93d5306e Request / Response

Details

Risk description:
The risk exists that an attacker will intercept the clear-text communication between the browser and the server and he will steal the cookie of the user. If this is a session cookie, the attacker could gain unauthorized access to the victim's web session.

Recommendation:
Whenever a cookie contains sensitive information or is a session token, then it should always be passed using an encrypted channel. Ensure that the secure flag is set for cookies containing such sensitive information.

References:
https://owasp.org/www-project-web-security-testing-guide/stable/4-Web_Application_Security_Testing/06-Session_Management_Testing/02-Testing_for_Cookies_Attributes.html

Classification:
CWE : CWE-614
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A02 - Security Misconfiguration

Vulnerabilities found for bootstrap 3.3.7
port 443/tcp

CVE	CVSS	EPSS Score	EPSS Percentile	Summary
CVE-2024-6484	6.4	0.00049	0.15167	A vulnerability has been identified in Bootstrap that exposes users to Cross-Site Scripting (XSS) attacks. The issue is present in the carousel component, where the data-slide and data-slide-to attributes can be exploited through the href attribute of an <a> tag due to inadequate sanitization. This vulnerability could potentially enable attackers to execute arbitrary JavaScript within the victim's browser.
CVE-2019-8331	6.1	0.01668	0.82051	In Bootstrap before 3.4.1 and 4.3.x before 4.3.1, XSS is possible in the tooltip or popover data-template attribute.
CVE-2018-20677	6.1	0.11866	0.93704	In Bootstrap before 3.4.0, XSS is possible in the affix configuration target property.
CVE-2018-20676	6.1	0.06144	0.90774	In Bootstrap before 3.4.0, XSS is possible in the tooltip data-viewport attribute.
CVE-2018-14042	6.1	0.02276	0.84604	In Bootstrap before 4.1.2, XSS is possible in the data-container property of tooltip.

Details

Risk description:
The risk is that an attacker could search for an appropriate exploit (or create one himself) for any of these vulnerabilities and use it to attack the system.

Since the vulnerabilities were discovered using only version-based testing, the risk level for this finding will not exceed 'high' severity. Critical risks will be assigned to vulnerabilities identified through accurate active testing methods.

Recommendation:
In order to eliminate the risk of these vulnerabilities, we recommend you check the installed software version and upgrade to the latest version.

Classification:
EPSS score : 0.11866
EPSS percentile : 0.93704

CISA KEV: False
CVE : CVE-2024-6484, CVE-2019-8331, CVE-2018-20677, CVE-2018-20676, CVE-2018-14042
CVSS V3 : 6.4
CWE : CWE-1035

Vulnerabilities found for jquery 2.2.4

port 443/tcp

CVE	CVSS	EPSS Score	EPSS Percentile	Summary
CVE-2020-11023	6.9	0.36851	0.97125	In jQuery versions greater than or equal to 1.0.3 and before 3.5.0, passing HTML containing <option> elements from untrusted sources - even after sanitizing it - to one of jQuery's DOM manipulation methods (i.e. .html(), .append(), and others) may execute untrusted code. This problem is patched in jQuery 3.5.0.
CVE-2020-11022	6.9	0.03251	0.87079	In jQuery versions greater than or equal to 1.2 and before 3.5.0, passing HTML from untrusted sources - even after sanitizing it - to one of jQuery's DOM manipulation methods (i.e. .html(), .append(), and others) may execute untrusted code. This problem is patched in jQuery 3.5.0.
CVE-2019-11358	6.1	0.02717	0.85871	jQuery before 3.4.0, as used in Drupal, Backdrop CMS, and other products, mishandles jQuery.extend(true, {}, ...) because of Object.prototype pollution. If an unsanitized source object contained an enumerable __proto__ property, it could extend the native Object.prototype.
CVE-2015-9251	6.1	0.27164	0.96358	jQuery before 3.0.0 is vulnerable to Cross-site Scripting (XSS) attacks when a cross-domain Ajax request is performed without the dataType option, causing text/javascript responses to be executed.

Details

Risk description:

The risk is that an attacker could search for an appropriate exploit (or create one himself) for any of these vulnerabilities and use it to attack the system.

Since the vulnerabilities were discovered using only version-based testing, the risk level for this finding will not exceed 'high' severity. Critical risks will be assigned to vulnerabilities identified through accurate active testing methods.

Recommendation:

In order to eliminate the risk of these vulnerabilities, we recommend you check the installed software version and upgrade to the latest version.

Classification:

EPSS score : 0.36851
EPSS percentile : 0.97125
CISA KEV: False
CVE : CVE-2020-11023, CVE-2020-11022, CVE-2019-11358, CVE-2015-9251
CVSS V3 : 6.9
CWE : CWE-1035

Missing security header: Referrer-Policy

CONFIRMED

port 443/tcp

URL	Evidence
https://thehoneycake.com.au/	Response headers do not include the Referrer-Policy HTTP security header as well as the <meta> tag with name 'referrer' is not present in the response. Request / Response

Details

Risk description:

The risk is that if a user visits a web page (e.g. "http://example.com/pricing/") and clicks on a link from that page going to e.g. "https://www.google.com", the browser will send to Google the full originating URL in the `Referer` header, assuming the Referrer-Policy header is not set. The originating URL could be considered sensitive information and it could be used for user tracking.

Recommendation:

The Referrer-Policy header should be configured on the server side to avoid user tracking and inadvertent information leakage. The value `no-referrer` of this header instructs the browser to omit the Referer header entirely.

References:

https://developer.mozilla.org/en-US/docs/Web/Security/Referer_header:_privacy_and_security_concerns

Classification:

CWE : CWE-693
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A02 - Security Misconfiguration

Unsafe security header: Content-Security-Policy

CONFIRMED

port 443/tcp

URL	Evidence

https://thehoneycake.com.au/	Response headers include the HTTP Content-Security-Policy security header with the following security issues:
	`object-src: Missing object-src allows the injection of plugins which can execute JavaScript. We recommend setting it to 'none'.`
	`default-src: The default-src directive should be set as a fall-back when other restrictions have not been specified.`
	`script-src: script-src directive is missing.`
	`base-uri: Missing base-uri allows the injection of base tags. They can be used to set the base URL for all relative (script) URLs to an attacker controlled domain. We recommend setting it to 'none' or 'self'.`
	
	Request / Response

Details

Risk description:

For example, if the unsafe-inline directive is present in the CSP header, the execution of inline scripts and event handlers is allowed. This can be exploited by an attacker to execute arbitrary JavaScript code in the context of the vulnerable application.

Recommendation:

Remove the unsafe values from the directives, adopt nonces or hashes for safer inclusion of inline scripts if they are needed, and explicitly define the sources from which scripts, styles, images or other resources can be loaded.

References:

https://cheatsheetseries.owasp.org/cheatsheets/Content_Security_Policy_Cheat_Sheet.html
https://developer.mozilla.org/en-US/docs/Web/HTTP/Headers/Content-Security-Policy

Classification:

CWE : CWE-1021
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A02 - Security Misconfiguration

Robots.txt file found

CONFIRMED

port 443/tcp

URL
https://thehoneycake.com.au/robots.txt

Details

Risk description:

There is no particular security risk in having a robots.txt file. However, it's important to note that adding endpoints in it should not be considered a security measure, as this file can be directly accessed and read by anyone.

Recommendation:

We recommend you to manually review the entries from robots.txt and remove the ones which lead to sensitive locations in the website (ex. administration panels, configuration files, etc).

References:

https://www.theregister.co.uk/2015/05/19/robotstxt/

Classification:

OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A06 - Insecure Design

Password Submitted in URL

port 443/tcp

UNCONFIRMED

URL	Method	Parameters	Evidence

https://thehoneycake.com.au/products/gluten-free-small-box	GET	**Headers:**
		User-Agent=Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/108.0.0.0 Safari/537.36
		Cookies:
		_shopify_analytics=:AZ1RylWPAAEAzDWITaVhlb7mq-h3qkhH2OcwRKoiB8UUnCSFE5982mwoY5lSEtbmTzIe9xQUFX12Phr4Um1ou5rddsRsiRg4wiM9Ug:
		_shopify_essential...
			The following form sends inputs of type password plainly in the URL:
			`<form id="CustomerRegisterForm" class="wait_li_form">`
			`<div class="wla_input wla_first_name">`
			`<input type="text" id="wl_customer_first_name" placeholder="First Name" value="" required>`
			`<span id="wl_customer_first_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_last_name">`
			`<input type="text" id="wl_customer_last_name" placeholder="Last Name" value="" required>`
			`<span id="wl_customer_last_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_email">`
			`<input type="email" id="wl_customer_email" placeholder="Email" required>`
			`<span id="wl_customer_email_error"></span>`
			`</div>`
			`<div class="wla_input wla_password">`
			`<input type="password" id="wl_customer_password" placeholder="Password" required>`
			`<span id="wl_customer_password_error"></span>`
			`</div>`
			`<button type="submit" class="wla_button" id="wl_register_button">Register & Join Waiting List</button>`
			`<span id="error_field"></span>`
			`</form>`
			Request / Response

https://thehoneycake.com.au/products/premium-gift-box-original-10-serves	GET	**Headers:**
		User-Agent=Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/108.0.0.0 Safari/537.36
		Cookies:
		_shopify_analytics=:AZ1RyIWPAAEAzDWITaVhIb7mq-h3qkhH2OcwRKoiB8UUnCSFE5982mwoY5lSEtbmTzIe9xQUFX12Phr4Um1ou5rddsRsiRg4wiM9Ug:
		_shopify_essential...
			The following form sends inputs of type password plainly in the URL:
			`<form id="CustomerRegisterForm" class="wait_li_form">`
			`<div class="wla_input wla_first_name">`
			`<input type="text" id="wl_customer_first_name" placeholder="First Name" value="" required>`
			`<span id="wl_customer_first_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_last_name">`
			`<input type="text" id="wl_customer_last_name" placeholder="Last Name" value="" required>`
			`<span id="wl_customer_last_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_email">`
			`<input type="email" id="wl_customer_email" placeholder="Email" required>`
			`<span id="wl_customer_email_error"></span>`
			`</div>`
			`<div class="wla_input wla_password">`
			`<input type="password" id="wl_customer_password" placeholder="Password" required>`
			`<span id="wl_customer_password_error"></span>`
			`</div>`
			`<button type="submit" class="wla_button" id="wl_register_button">Register & Join Waiting List</button>`
			`<span id="error_field"></span>`
			`</form>`
			
			Request / Response

https://thehoneycake.com.au/products/the-honeycake-caramel-cheesecake-medium	GET	**Headers:**
		User-Agent=Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/108.0.0.0 Safari/537.36
		Cookies:
		_shopify_analytics=:AZ1RylWPAAEAzDWITaVhIb7mq-h3qkhH2OcwRKoiB8UUnCSFE5982mwoY5ISEtbmTzIe9xQUFX12Phr4Um1ou5rddsRsiRg4wiM9Ug:
		_shopify_essential...
			The following form sends inputs of type password plainly in the URL:
			`<form id="CustomerRegisterForm" class="wait_li_form">`
			`<div class="wla_input wla_first_name">`
			`<input type="text" id="wl_customer_first_name" placeholder="First Name" value="" required>`
			`<span id="wl_customer_first_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_last_name">`
			`<input type="text" id="wl_customer_last_name" placeholder="Last Name" value="" required>`
			`<span id="wl_customer_last_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_email">`
			`<input type="email" id="wl_customer_email" placeholder="Email" required>`
			`<span id="wl_customer_email_error"></span>`
			`</div>`
			`<div class="wla_input wla_password">`
			`<input type="password" id="wl_customer_password" placeholder="Password" required>`
			`<span id="wl_customer_password_error"></span>`
			`</div>`
			`<button type="submit" class="wla_button" id="wl_register_button">Register & Join Waiting List</button>`
			`<span id="error_field"></span>`
			`</form>`
			
			Request / Response

https://thehoneycake.com.au/products/traditional-round-original	GET	**Headers:**
		User-Agent=Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/108.0.0.0 Safari/537.36
		Cookies:
		_shopify_analytics=:AZ1RyIWPAAEAzDWITaVhIb7mq-h3qkhH2OcwRKoiB8UUnCSFE5982mwoY5lSEtbmTzIe9xQUFX12Phr4Um1ou5rddsRsiRg4wiM9Ug:
		_shopify_essential...
			The following form sends inputs of type password plainly in the URL:
			`<form id="CustomerRegisterForm" class="wait_li_form">`
			`<div class="wla_input wla_first_name">`
			`<input type="text" id="wl_customer_first_name" placeholder="First Name" value="" required>`
			`<span id="wl_customer_first_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_last_name">`
			`<input type="text" id="wl_customer_last_name" placeholder="Last Name" value="" required>`
			`<span id="wl_customer_last_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_email">`
			`<input type="email" id="wl_customer_email" placeholder="Email" required>`
			`<span id="wl_customer_email_error"></span>`
			`</div>`
			`<div class="wla_input wla_password">`
			`<input type="password" id="wl_customer_password" placeholder="Password" required>`
			`<span id="wl_customer_password_error"></span>`
			`</div>`
			`<button type="submit" class="wla_button" id="wl_register_button">Register & Join Waiting List</button>`
			`<span id="error_field"></span>`
			`</form>`
			
			Request / Response

https://thehoneycake.com.au/products/traditional-round-pandan-coconut	GET	**Headers:**
		User-Agent=Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/108.0.0.0 Safari/537.36
		Cookies:
		_shopify_analytics=:AZ1RylWPAAEAzDWITaVhIb7mq-h3qkhH2OcwRKoiB8UUnCSFE5982mwoY5ISEtbmTzIe9xQUFX12Phr4Um1ou5rddsRsiRg4wiM9Ug:
		_shopify_essential...
			The following form sends inputs of type password plainly in the URL:
			`<form id="CustomerRegisterForm" class="wait_li_form">`
			`<div class="wla_input wla_first_name">`
			`<input type="text" id="wl_customer_first_name" placeholder="First Name" value="" required>`
			`<span id="wl_customer_first_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_last_name">`
			`<input type="text" id="wl_customer_last_name" placeholder="Last Name" value="" required>`
			`<span id="wl_customer_last_name_error"></span>`
			`</div>`
			`<div class="wla_input wla_email">`
			`<input type="email" id="wl_customer_email" placeholder="Email" required>`
			`<span id="wl_customer_email_error"></span>`
			`</div>`
			`<div class="wla_input wla_password">`
			`<input type="password" id="wl_customer_password" placeholder="Password" required>`
			`<span id="wl_customer_password_error"></span>`
			`</div>`
			`<button type="submit" class="wla_button" id="wl_register_button">Register & Join Waiting List</button>`
			`<span id="error_field"></span>`
			`</form>`
			
			Request / Response

Details

Risk description:
Passwords submitted in URLs have a higher chance of being leaked. The main reason is that URLs can be leaked in browser cross-site requests via the Referer header. Additionally, URLs are usually stored in all kinds of logs. If any access or error logs of the server were publicly accessible, an attacker could also harvest password from it.

Recommendation:
You should submit passwords using POST rather than GET. This way sensitive data won't be shared to other locations via URLs.

References:
https://developer.mozilla.org/en-US/docs/Web/Security/Referer_header:_privacy_and_security_concerns

Classification:
CWE : CWE-598
OWASP Top 10 - 2021 : A4 - Insecure Design
OWASP Top 10 - 2025 : A06 - Insecure Design

Server software and technology found

port 443/tcp

UNCONFIRMED

Software / Version	Category
Amazon Web Services	PaaS

Amazon S3	CDN
cdnjs	CDN
jQuery CDN	CDN
Facebook Pixel 2.9.291	Analytics
Flickity	JavaScript libraries
Font Awesome 5.13.0	Font scripts
Bootstrap 3.3.7	UI frameworks
LazySizes	JavaScript libraries, Performance
core-js 2.6.12	JavaScript libraries
Google Analytics	Analytics
Google Font API	Font scripts
GSAP 1.20.3	JavaScript frameworks
HTTP/3	Miscellaneous
jQuery 2.2.4	JavaScript libraries
Judge.me	Reviews
Open Graph	Miscellaneous
Google Pay	Payment processors
PayPal	Payment processors
PhotoSwipe	Photo galleries, JavaScript libraries
Preact	JavaScript libraries
Shop Pay	Payment processors
Shopify	Ecommerce
Vue.js	JavaScript frameworks
Priority Hints	Performance
American Express	Payment processors
Apple Pay	Payment processors
Cloudflare	CDN
reCAPTCHA	Security
Google Tag Manager	Tag managers
jsDelivr	CDN
Klaviyo	Marketing automation
Marsello	Loyalty & rewards
Mastercard	Payment processors
HSTS	Security
Visa	Payment processors
Cart Functionality	Ecommerce

Zapiet	Ecommerce

Details

Risk description:
The risk is that an attacker could use this information to mount specific attacks against the identified software type and version.

Recommendation:
We recommend you to eliminate the information which permits the identification of software platform, technology, server and operating system: HTTP server headers, HTML meta information, etc.

References:
https://owasp.org/www-project-web-security-testing-guide/stable/4-Web_Application_Security_Testing/01-Information_Gathering/02-Fingerprint_Web_Server.html

Classification:
CWE : CWE-200
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A02 - Security Misconfiguration

Security.txt file is missing

CONFIRMED

port 443/tcp

URL
Missing: https://thehoneycake.com.au/.well-known/security.txt

Details

Risk description:
There is no particular risk in not having a security.txt file for your server. However, this file is important because it offers a designated channel for reporting vulnerabilities and security issues.

Recommendation:
We recommend you to implement the security.txt file according to the standard, in order to allow researchers or users report any security issues they find, improving the defensive mechanisms of your server.

References:
https://securitytxt.org/

Classification:
CWE : CWE-1188
OWASP Top 10 - 2017 : A6 - Security Misconfiguration
OWASP Top 10 - 2021 : A5 - Security Misconfiguration
OWASP Top 10 - 2025 : A02 - Security Misconfiguration

Email Address Exposure

UNCONFIRMED

port 443/tcp

URL	Method	Parameters	Evidence
https://thehoneycake.com.au/	GET	**Headers:** User-Agent=Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/108.0.0.0 Safari/537.36	Email Address: info@thehoneycake.com orders@thehoneycake.com Request / Response

Details

Risk description:
The risk is that exposed email addresses within the application could be accessed by unauthorized parties. This could lead to privacy violations, spam, phishing attacks, or other forms of misuse.

Recommendation:
Compartmentalize the application to have 'safe' areas where trust boundaries can be unambiguously drawn. Do not allow email addresses to go outside of the trust boundary, and always be careful when interfacing with a compartment outside of the safe area.

References:

https://owasp.org/Top10/A04_2021-Insecure_Design/

Classification:

CISA KEV: False
CVE : -1
CWE : CWE-200
OWASP Top 10 - 2017 : A6: Security Misconfiguration
OWASP Top 10 - 2021 : A4: Insecure Design
OWASP Top 10 - 2025 : A06 - Insecure Design

Scan coverage information

List of tests performed (39)

Port 443

- ✔ Scanned for HttpOnly flag of cookie
- ✔ Scanned for Secure flag of cookie
- ✔ Scanned for version-based vulnerabilities of server-side software
- ✔ Scanned for version-based vulnerabilities of server-side software
- ✔ Scanned for missing HTTP header - Referrer
- ✔ Scanned for passwords submitted in URLs
- ✔ Scanned for robots.txt file
- ✔ Scanned for website technologies
- ✔ Scanned for unsafe HTTP header Content Security Policy
- ✔ Scanned for emails
- ✔ Scanned for absence of the security.txt file
- ✔ Scanned for client access policies
- ✔ Scanned for use of untrusted certificates
- ✔ Scanned for enabled HTTP debug methods
- ✔ Scanned for enabled HTTP OPTIONS method
- ✔ Scanned for secure communication
- ✔ Scanned for directory listing
- ✔ Scanned for passwords submitted unencrypted
- ✔ Scanned for error messages
- ✔ Scanned for debug messages
- ✔ Scanned for code comments
- ✔ Scanned for missing HTTP header - Strict-Transport-Security
- ✔ Scanned for missing HTTP header - Content Security Policy
- ✔ Scanned for missing HTTP header - X-Content-Type-Options
- ✔ Scanned for domain too loose set for cookies
- ✔ Scanned for mixed content between HTTP and HTTPS
- ✔ Scanned for cross domain file inclusion
- ✔ Scanned for internal error code
- ✔ Scanned for login interfaces
- ✔ Scanned for secure password submission
- ✔ Scanned for sensitive data
- ✔ Scanned for OpenAPI files
- ✔ Scanned for file upload
- ✔ Scanned for SQL statement in request parameter
- ✔ Scanned for password returned in later response
- ✔ Scanned for Path Disclosure
- ✔ Scanned for Session Token in URL
- ✔ Scanned for API endpoints
- ✔ Scanned for missing HTTP header - Rate Limit

Scan parameters

target:	https://thehoneycake.com.au/
scan_type:	Light
authentication:	False

Scan stats

Unique Injection Points Detected:	110
URLs spidered:	17
Total number of HTTP requests:	26
Average time until a response was received:	233ms