

```

87 --QUESTION1
88 SELECT A.user_id,
89        A.user_name,
90        B.subscription_id,
91        B.start_date
92 FROM exercise4.KPM.users AS A
93 INNER JOIN exercise4.KPM.subscriptions AS B
94 ON A.user_id=B.user_id;
95 --QUESTION 2
96 SELECT B.subscription id,

```

Add parameter

Table +

	1 ² ₃ user_id	A ^B _C user_name	1 ² ₃ subscription_id	📅 start_date
	1	Nomvula	503	2026-03-10
	2	David	502	2026-02-01
	3	Anele	505	2026-04-05
	1	Nomvula	501	2026-01-15
	1	Nomvula	503	2026-03-10

8 rows | 0.504s runtime [See performance \(1\)](#) ✓ Checked for improvements

```

96 --QUESTION 2
97 SELECT B.subscription_id,
98        B.user_id,
99        C.plan_name,
100       C.monthly_price
101 FROM exercise4.KPM.subscriptions AS B
102 INNER JOIN exercise4.KPM.plans AS C
103 ON B.plan_id=C.plan_id;
104 --QUESTION3
105 SELECT D.session id,

```

Add parameter

Table +

	1 ² ₃ subscription_id	1 ² ₃ user_id	A ^B _C plan_name	1 ² ₃ monthly_price
1	501	1	Basic	79
2	504	6	Standard	129
3	503	1	Premium	199
4	505	3	Family	249
5	502	2	Standard	129

5 rows | 0.547s runtime [See performance \(1\)](#) ✓ Checked for improvements

```

104 --QUESTION3
105 SELECT D.session_id,
106        D.user_id,
107        E.show_title,
108        E.genre,
109        D.watch_minutes
110 FROM exercise4.KPM.viewing_sessions AS D
111 INNER JOIN exercise4.KPM.shows AS E
112 ON D.show_id = E.show_id;
113 --QUESTION 4
114 SELECT A.user_name,
115        A.country,
116        D.session_id,

```

Add parameter

	¹ ₃ session_id	¹ ₃ user_id	^A _C show_title	^A _C genre	¹ ₃ watch_minutes
1	904	7	Comedy Hour	Comedy	20
2	903	1	Crime Time	Drama	60
3	902	2	Tech Tales	Documentary	30
4	901	1	Comedy Hour	Comedy	45

```

113 --QUESTION 4
114 SELECT A.user_name,
115        A.country,
116        D.session_id,
117        D.show_id,
118        D.watch_minutes
119 FROM exercise4.KPM.users AS A
120 INNER JOIN exercise4.KPM.viewing_sessions AS D
121 ON A.user_id = D.user_id;
122 --QUESTION 5
123 SELECT A.user_name,
124        A.country,
125

```

Add parameter

	^A _C user_name	^A _C country	¹ ₃ session_id	¹ ₃ show_id	¹ ₃ watch_minutes
1	Nomvula	Johannesburg	901	701	45
2	David	Cape Town	902	703	30
3	Nomvula	Johannesburg	903	702	60
4	Anele	Durban	905	705	90

```

122  --QUESTION 5
123  SELECT A.user_name,
124         A.country,
125         C.plan_name,
126         C.monthly_price,
127         B.start_date
128  FROM exercise4.KPM.users AS A
129  INNER JOIN exercise4.KPM.subscriptions AS B ON A.user_id = B.user_id
130  INNER JOIN exercise4.KPM.plans AS C ON B.plan_id = C.plan_id;
131  --QUESTION 6
132  SELECT A.user_id,
133         A.user_name,

```

Add parameter

	^A _C user_name	^A _C country	^A _C plan_name	¹ ₃ monthly_price	 start_date
1	Nomvula	Johannesburg	Premium	199	2026-03-10
2	David	Cape Town	Standard	129	2026-02-01
3	Anele	Durban	Family	249	2026-04-05
4	Nomvula	Johannesburg	Basic	79	2026-01-15

```

131  --QUESTION 6
132  SELECT A.user_id,
133         A.user_name,
134         B.subscription_id,
135         B.start_date
136  FROM exercise4.KPM.users AS A
137  LEFT JOIN exercise4.KPM.subscriptions AS B
138  ON A.user_id = B.user_id;
139  --QUESTION 7
140  SELECT C.plan_id,
141         C.plan_name,
142         B.subscription_id,
143         B.user_id

```

Add parameter

	¹ ₃ user_id	^A _C user_name	¹ ₃ subscription_id	 start_date
1	1	Nomvula	503	2026-03-10
2	2	David	502	2026-02-01
3	3	Anele	505	2026-04-05
4	4	Kabelo	null	null
5	5	Lerato	null	null

```

139 --QUESTION7
140 SELECT C.plan_id,
141        .....C.plan_name,
142        .....B.subscription_id,
143        .....B.user_id
144 FROM exercise4.KPM.plans AS C
145 LEFT JOIN exercise4.KPM.subscriptions AS B
146 ON C.plan_id = B.plan_id;
147 | SELECT E.show_id,

```

Add parameter

Table  

	1 ² ₃ plan_id	A ^B _C plan_name	1 ² ₃ subscription_id	1 ² ₃ user_id
1	10	Basic	501	1
2	11	Standard	504	6
3	12	Premium	503	1
4	13	Family	505	3
5	14	Mobile	null	null

  6 rows | 0.630s runtime [See performance \(1\)](#)  Checked for improvements

```

147 --QUESTION 8
148 SELECT E.show_id,
149        .....E.show_title,
150        .....D.session_id,
151        .....D.watch_minutes
152 FROM exercise4.KPM.shows AS E
153 LEFT JOIN exercise4.KPM.viewing_sessions AS D
154 ON E.show_id = D.show_id;
155 --QUESTION 9
156 SELECT A.user_name,
157        A.country,
158        C.plan_name,

```

Add parameter

Table  

	1 ² ₃ show_id	A ^B _C show_title	1 ² ₃ session_id	1 ² ₃ watch_minutes
1	701	Comedy Hour	904	20
2	702	Crime Time	903	60
3	703	Tech Tales	902	30
4	704	Cooking Lab	null	null
5	705	World Earth	null	null

```

155  --QUESTION 9
156  SELECT A.session_id,
157         .....A.show_id,
158         .....A.watch_minutes,
159         .....B.user_id,
160         .....B.user_name
161  FROM exercise4.KPM.viewing_sessions AS A
162  LEFT JOIN exercise4.KPM.users AS B
163  ON A.user_id = B.user_id;
164  --QUESTION 10
165  SELECT A.session_id,

```

Add parameter

Table  

	¹ ₂ ³ session_id	¹ ₂ ³ show_id	¹ ₂ ³ watch_minutes
1	901	701	45
2	902	703	30
3	903	702	60
4	904	701	20
5	905	705	90

```
165 --QUESTION 10
166 SELECT A.user_name,
167        .....A.country,
168        .....C.plan_name,
169        .....C.monthly_price
170 FROM exercise4.KPM.users AS A
171 LEFT JOIN exercise4.KPM.subscriptions AS B ON A.user_id = B.user_id
172 LEFT JOIN exercise4.KPM.plans AS C ON B.plan_id = C.plan_id;
173 --QUESTION 11
174 SELECT A.user_id,
175        A.user_name,
176        B.subscription_id,
177        B.start_date
178 FROM exercise4.KPM.users AS A
```

Add parameter

Table  

	^A _C user_name	^A _C country	^A _C plan_name	¹ ₃ monthly_price
1	Nomvula	Johannesburg	Premium	199
2	David	Cape Town	Standard	129
3	Anele	Durban	Family	249
4	Kabelo	Pretoria	null	null
5	Lerato	Pretoria	null	null

```

181 --QUESTION 12
182 SELECT C.plan_id,
183        .....C.plan_name,
184        .....B.subscription_id,
185        .....B.user_id
186 FROM exercise4.KPM.plans AS C
187 FULL OUTER JOIN exercise4.KPM.subscriptions AS B
188 ON C.plan_id = B.plan_id;

```

Add parameter

Table  

	1 ² ₃ plan_id	A ^B _C plan_name	1 ² ₃ subscription_id	1 ² ₃ user_id
1	12	Premium	503	1
2	10	Basic	501	1
3	13	Family	505	3
4	14	Mobile	null	null
5	11	Standard	504	6

  6 rows | 0.850s runtime [See performance \(1\)](#)  Checked for improvements

```

189 --QUESTION13
190 SELECT E.show_id,
191        .....E.show_title,
192        .....D.session_id,
193        .....D.watch_minutes
194 FROM exercise4.KPM.shows AS E
195 FULL OUTER JOIN exercise4.KPM.viewing_sessions AS D
196 ON E.show_id = D.show_id;
197 SELECT A.user_id,

```

Add parameter

Table  

	1 ² ₃ show_id	A ^B _C show_title	1 ² ₃ session_id	1 ² ₃ watch_minutes
1	703	Money Heist	902	30
2	701	The Mandalorian	901	45
3	701	The Mandalorian	904	20
4	702	The Queens Gambit	903	60
5	705	The Crown	905	90

```

197 --QUESTION 14
198 SELECT A.user_id,
199        A.user_name,
200        D.session_id,
201        D.show_id,
202        D.watch_minutes
203 FROM exercise4.KPM.users AS A
204 FULL OUTER JOIN exercise4.KPM.viewing_sessions AS D
205 ON A.user_id = D.user_id;
206 --QUESTION 15
207 SELECT A.user_id,
208        A.user_name,
209        B.subscription_id,

```

Add parameter

Table  

	1 ² ₃ user_id	A ^B _C user_name	1 ² ₃ session_id	1 ² ₃ show_id	1 ² ₃ watch_minutes
1	1	Nomvula	901	701	45
2	1	Nomvula	903	702	60
3	3	Anele	905	705	90
4	2	David	902	703	30
5	null	null	904	701	20

```

206 --QUESTION 15
207 SELECT A.user_id,
208        A.user_name,
209        B.subscription_id,
210        C.plan_id,
211        C.plan_name
212 FROM exercise4.KPM.users AS A
213 FULL OUTER JOIN exercise4.KPM.subscriptions AS B ON A.user_id = B.user_id
214 FULL OUTER JOIN exercise4.KPM.plans AS C ON B.plan_id = C.plan_id;

```

Add parameter

Table  

	1 ² ₃ user_id	A ^B _C user_name	1 ² ₃ subscription_id	1 ² ₃ plan_id	A ^B _C plan_name
4	1	Nomvula	501	10	Basic
5	3	Anele	505	13	Family
6	3	Anele	505	13	Family
7	5	Lerato	null	null	null