Use-Case Flow Specification

Use Case: Identify Recurring Subscriptions

Actors: Individual User (primary), Finance Auditor (secondary/viewer)
Trigger: User imports a new transaction file, or a scheduled daily sync pulls new transactions.

Preconditions

- User has a registered account.
- At least one transaction log (CSV/OFX) has been successfully imported.
- Imported data has passed the secure-parsing check (NFR-001).

Postconditions

- Success: Newly detected recurring transactions are tagged as subscriptions, with provider name, amount, cadence, and next renewal date stored.
- Failure: No new subscriptions are tagged; existing tagged data remains unchanged; an error/log entry is recorded.

Main Success Scenario

1. User imports a transaction log (CSV/OFX) or a scheduled sync retrieves new transactions.
2. System parses the file and normalizes each transaction (payee, amount, date, currency).
3. System groups transactions by normalized payee and compares amount and interval similarity across the group.
4. System flags groups meeting the recurrence threshold as candidate subscriptions.
5. System calculates the projected next renewal date for each flagged subscription.
6. System stores the subscription record and includes it in the monthly burn-rate calculation.
7. System displays the updated subscription list to the user.

Alternate Flow A1: Ambiguous / Borderline Pattern

1. At step 4, a transaction group meets some but not all recurrence criteria
2. System marks the group as 'Unconfirmed' rather than auto-tagging it as a subscription.
3. System surfaces the unconfirmed group to the user for manual review
4. If the user confirms it as a subscription, resume Main Success Scenario at step 5; if rejected, the group is tagged 'One time' and excluded from burn rate.

Special Requirements: Recurrence detection must not store raw bank credentials (NFR-001); classification results must be available for Finance Auditor export.