Status	Finished
Started	Thursday, 1 October 2026, 2:08 PM
Completed	Thursday, 1 October 2026, 2:15 PM
Duration	7 mins 22 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What will be the output of following Python code?

```
set1={0,0,9}

print(set1)
```

a. {9}

b. It will throw an error as there are two 0 while creating the set.

c. {0,9} ✓

d. {0,0,9}

Question **2**

Correct

Mark 1.00 out of 1.00

What will be the output of the below Python code?

t1=(55,12,78,64,25)

t1.pop(12)

print(tuple1)

a. Error ✓

b. 12

c. (12)

d. (55,78,64,25)

Question **3**

Correct

Mark 1.00 out of 1.00

What is printed when the following code is run?

```
tup = ('30', '3', '2', '8')
print(sorted(tup,reverse = True))
```

a. ['2', '3', '30', '8']

b. ['30', '8', '3', '2']

c. ['2', '3', '8', '30']

d. ['8', '30', '3', '2'] ✓

Question **4**

Correct

Mark 1.00 out of 1.00

What is the output of the following union operation

```
set1 = {10, 20, 30, 40}
set2 = {50, 20, "10", 60}

set3 = set1.union(set2)
print(set3)
```

a. SynatxError: Different types cannot be used with sets

b. {40, '10', 50, 20, 60, 30}

c. {40, 10, '10', 50, 20, 60, 30} ✓

d. {40, 10, 50, 20, 60, 30}

Question **5**

Correct

Mark 1.00 out of 1.00

What is the output of the following code

```
aSet = {1, 'rec', ('cse', 'ece'), True}
print(aSet)
```

a. {'rec', 1, ('cse', 'ece')} ✓

b. {'rec', True, ('cse', 'ece')}

c. Error

d. {'rec', 1, ('cse', 'ece'),True}

Question **6**

Correct

Mark 1.00 out of 1.00

What is the output of the following set operation

```
sampleSet = {"Yellow", "Orange", "Black"}
sampleSet.update(["Blue", "Green", "Red"])
print(sampleSet)
```

a. Name Error

b. TypeError: update() doesn't allow list as a argument.

c. {'Yellow', 'Orange', 'Red', 'Black', 'Green', 'Blue'} ✓

d. {'Yellow', 'Orange', 'Black', ["Blue", "Green", "Red"]}

Question **7**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

```
t1 = (1,2,3)
t2 = (4,5,6)
x = t1+t2
print(x)
```

- a. (1,2,3,4,5,6) ✓
- b. Error
- c. (1,2,3,3,2,1)
- d. (1,2,3)(4,5,6)

Question **8**

Correct

Mark 1.00 out of 1.00

What will be printed when the following code executes?

```
a = ("Python Programming")
```

```
print type(a)
```

```

```

- a. <class 'tuple'>
- b. <class 'str'> ✓
- c. <class 'int'>
- d. str

Question **9**

Correct

Mark 1.00 out of 1.00

What is the output of the given below program?

t = (58, 47, 36, 25, 14, 3)

x = t[2:-1]

print(x)

a. Error

b. (3,14,25)

c. (36, 25, 14) ✓

d. (58,47,36,25)

Question **10**

Correct

Mark 1.00 out of 1.00

Which of the following options will produce the same output?

```
t = (15, 83, 21, 49, 60,45,52,85,100)
# options i, ii, iii, or iv
print(t[:-1])
print(t[0:5])
print(t[0:8])
print(t[-7:])
```

a. i,ii

b. ii,iv

c. i,iii ✓

d. iii,iv

Question **11**

Correct

Mark 1.00 out of 1.00

Select which is true for Python tuple?

a. A tuple is unordered

b. A tuple maintains the order of items ✓

c. We can change the tuple once created

d. None of these

Question **12**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
>>>t = (1, 2, 4, 3, 8, 9)
>>>[t[i] for i in range(0, len(t), 2)]
```

a. [2, 3, 9]

b. [1, 2, 4, 3, 8, 9]

c. [1, 4, 8] ✓

d. (1, 4, 8)

Question **13**

Correct

Mark 1.00 out of 1.00

Find the output of the given Python program?

```
t1 = (1,2,3,(4,5))
t2 = (3,2,1,(4,5))
print(t1>t2)
```

a. Error

b. Error

c. True

d. False ✓

Question **14**

Correct

Mark 1.00 out of 1.00

Which of the following Python code will create a set?

(i) set1=set((0,9,0))
(ii) set1=set([0,2,9])
(iii) set1={}

a. ii
b. All of the above
c. i,ii ✓
d. iii

Question **15**

Correct

Mark 1.00 out of 1.00

If a=(15,16,17,18,19,25), then a[1:-1] will be

Note :

a=(15,16,17,18,19,25)

print((a[1:-1]))

a. Error
b. (16,17,18,19) ✓
c. (25,19,18,17)
d. (16,17,18)