

Applied Machine Learning



Simple Neural Network Classifier

Simple Neural Network Classifier

- Structure of a Unit in a Neural Network
- Example of activation function: Rectified Linear Unit - ReLU
- Simple Neural Network classifier
 - ReLU and Softmax layers
- Classification process

Neural Network Unit

- One unit
- Input: vector \mathbf{x}
- Parameters:
 - Weights: vector \mathbf{w}
 - Bias: scalar b
- Associated function:
 - Linear part: $u = \sum_i w_i x_i + b$. Vectorized: $u = \mathbf{w}^T \mathbf{x} + b$
 - Activation:
 - nonlinear Rectified Linear Unit - **ReLU**: $F(u) = \max(0, u)$
 - 0: point at one side of plane
 - u : point at other side of plane
 - grows with distance from plane



Simple Neural Network Classifier

- One unit per class
 - output: probability that input features correspond to class

- Classifier for C classes


- outputs: $\mathbf{o} = \begin{bmatrix} o_1 \\ \vdots \\ o_C \end{bmatrix}$, o_j : output of unit j

- Parameters of unit j

- weights: vector $\mathbf{w}^{(j)} = \begin{bmatrix} w_1^{(j)} \\ \vdots \\ w_n^{(j)} \end{bmatrix}$, bias: scalar $b^{(j)}$

- Goal: output of unit j models probability of input \mathbf{x}_i to correspond to class j
- Softmax function for vector with C class outputs \mathbf{o}

- $\text{softmax}(u) = \mathbf{s}(\mathbf{o}) = \frac{1}{\sum_k e^{o_k}} \begin{bmatrix} e^{o_1} \\ \vdots \\ e^{o_C} \end{bmatrix}$



- Class for data item \mathbf{x}_i :

- one-hot vector: $\mathbf{y}_i = \begin{bmatrix} y_0 \\ \vdots \\ y_C \end{bmatrix}$ $y_j = 1, y_{i \neq j} = 0$

- Probability of input \mathbf{x}_i corresponding to class j
 - $p(y_j = 1 \mid \mathbf{x}_i, \mathbf{w}^{(j)}, b^{(j)}) = s_j(\mathbf{o}(\mathbf{x}_i, \mathbf{w}^{(j)}, b^{(j)}))$

Simple Neural Network Classifier


- Classifying among two classes: \times , \circ

- ReLU units: u_1, u_2

- $\times : \begin{cases} u_1 & \text{grows with distance to plane} \\ u_2 & 0 \end{cases}$


- $\circ : \begin{cases} u_1 & 0 \\ u_2 & \text{grows with distance to plane} \end{cases}$

- $\square : \begin{cases} u_1 = 0 & \Rightarrow s_1 = \frac{e^0}{e^0 + e^0} = \frac{1}{2} \\ u_2 = 0 & \Rightarrow s_2 = \frac{e^0}{e^0 + e^0} = \frac{1}{2} \end{cases}$




Simple Neural Network Classifier

- Classifying among two classes: \times , \circ
 - ReLU units: u_1, u_2
 - $\times : \begin{cases} u_1 & \text{grows with distance to plane} \\ u_2 & 0 \end{cases}$
 - $\circ : \begin{cases} u_1 = 0 & \Rightarrow s_1 = \frac{e^0}{e^0 + e^\delta} = \frac{1}{1 + e^\delta} \\ u_2 = \delta & \Rightarrow s_2 = \frac{e^\delta}{e^0 + e^\delta} = \frac{e^\delta}{1 + e^\delta} \end{cases}$
 - $\square : \begin{cases} u_1 = 0 & \Rightarrow s_1 = \frac{e^0}{e^0 + e^0} = \frac{1}{2} \\ u_2 = 0 & \Rightarrow s_2 = \frac{e^0}{e^0 + e^0} = \frac{1}{2} \end{cases}$



Classification Regions

- Regions
 - only X: positive for u_1
 - only O: positive for u_2
 - both X and O: positive for both u_1 and u_2
 - split in two parts
 - higher probability for u_1 : X
 - higher probability for u_2 : O
- no dataset item in region, probabilities: $\frac{1}{2}$



Simple Neural Network Classifier

- Structure of a Unit in a Neural Network
- Example of activation function: Rectified Linear Unit - ReLU
- Simple Neural Network classifier
 - ReLU and Softmax layers
- Classification process

Applied Machine Learning

Simple Neural Network Classifier