

Move Hash to Front

- **Problem:** Given a string containing some '#' characters, write a function to move all the '#' characters to the front of the string and return the modified string.
- **Input:** A string, e.g., "Move#Hash#to#Front"
- **Output:** The string with all '#' moved to the front, e.g., "###MoveHashtoFront"
- **Approach:**
 - Iterate through the string.
 - Collect '#' characters in one array and non-'#' characters in another.
 - Concatenate the '#' array with the non-'#' array to form the result.

Reduce String with Repeated Characters

- **Problem:** Given a string with consecutively repeated characters, reduce it by representing each sequence of repeated characters as the character followed by its count (if count > 1).
- **Input:** A string, e.g., "abbccccc"
- **Output:** Reduced string, e.g., "ab2c5"
- **Approach:**
 - Iterate through the string, counting consecutive occurrences of each character.
 - If a character appears once, output it as is; if more than once, output the character followed by its count.

Spiral Matrix

- **Problem:** Given a 2D matrix, traverse it in a spiral order (clockwise from top-left).
- **Input:** A 2D matrix, e.g., [[1,2,3,4], [5,6,7,8], [9,10,11,12], [13,14,15,16], [17,18,19,20]]
- **Output:** Elements in spiral order, e.g., [1,2,3,4,8,12,16,20,19,18,17,13,9,5,6,7,11,15,14,10]
- **Approach:**
 - Use four pointers (row_start, row_end, col_start, col_end) to track boundaries.
 - Traverse right, down, left, and up while updating boundaries and checking for overlap.

Reverse Each Word in a Sentence

- **Problem:** Reverse each word in a sentence while keeping the word order intact.
- **Input:** A sentence, e.g., "hello world"
- **Output:** Reversed words, e.g., "olleh dlrow"
- **Approach:**
 - Split the sentence into words.
 - Reverse each word individually and join them back with spaces.

Capitalize/Decapitalize

Problem statement : You're given a function that accepts the following, a string1, its length and a character c. Your job is to replace all the occurrences of character c in string1 and capitalize it or decapitalize it based on the character c.

Example 1

Input :

hello world

l

Output :

heLLo worLd

Example 2

Input :

prepinsta

p

Output :

PrePinsta

The Celebrity Problem



Difficulty: **Medium**

Accuracy: **38.33%**

Submissions: **385K+**

Points: **4**

Average Time: **30m**

A celebrity is a person who is known to all but **does not know** anyone at a party. A party is being organized by some people. A square matrix **mat[][]** of size $n \times n$ is used to represent people at the party such that if an element of row **i** and column **j** is **set to 1** it means **ith person knows jth person**. You need to return the **index** of the **celebrity** in the party, if the celebrity does not exist, return **-1**.

Note: Follow **0-based** indexing.

Examples:

Input: `mat[][] = [[1, 1, 0],
 [0, 1, 0],
 [0, 1, 1]]`

Output: 1

Explanation: 0th and 2nd person both know 1st person and 1st person does not know anyone. Therefore, 1 is the celebrity person.

Input: `mat[][] = [[1, 1],
 [1, 1]]`

Output: -1

Explanation: Since both the people at the party know each other. Hence none of

