```
#include <stdio.h>
int main() {
    int n, i;
    printf("Enter number of processes: ");
    scanf("%d", &n);
    int at[n], bt[n], rt[n], ct[n], tat[n], wt[n];
    for(i = 0; i < n; i++) {
        printf("Enter Arrival Time and Burst Time for P%d: ", i+1);
        scanf("%d %d", &at[i], &bt[i]);
        rt[i] = bt[i];
    }
    int current_time = 0, completed = 0;
    while(completed < n) {
        int min_rt = 9999, index = -1;
        for(i = 0; i < n; i++) {
            if(at[i] <= current_time && rt[i] > 0) {
                if(rt[i] < min_rt) {
                    min_rt = rt[i];
                    index = i;
                }
            }
        }
        if(index == -1) {
            current_time++;
        }
        else {
            rt[index]--;
            current_time++;
            if(rt[index] == 0) {
                completed++;
```

```
            ct[index] = current_time;
            tat[index] = ct[index] - at[index];
            wt[index] = tat[index] - bt[index];
        }
    }
}
printf("\nP\tAT\tBT\tCT\tTAT\tWT\n");
for(i = 0; i < n; i++) {
    printf("P%d\t%d\t%d\t%d\t%d\t%d\n",
    i+1, at[i], bt[i], ct[i], tat[i], wt[i]);
}

return 0;
}
```

OUTPUT:

```
1WA24CS217
Enter number of processes: 5
Enter Arrival Time and Burst Time for P1: 3 1
Enter Arrival Time and Burst Time for P2: 1 4
Enter Arrival Time and Burst Time for P3: 4 2
Enter Arrival Time and Burst Time for P4: 0 6
Enter Arrival Time and Burst Time for P5: 2 3

P       AT      BT      CT      TAT     WT
P1      3       1       4       1       0
P2      1       4       6       5       1
P3      4       2       8       4       2
P4      0       6       16      16      10
P5      2       3       11      9       6
```