Grundlagen der Betriebssysteme Prof. Dr.-Ing. Franz J. Hauck

```
void trig_rept_task() {
  #if EBOARD_NANO == 0x0|
    | defined(DOC) if (_pwm
           Value!=_OpwmValue) { ana
               logWrite(PIN_MOTOR_SPE,
                  ogwrte(Fin_notux_SPE,
    _pwmValue);_OpwmValue =
    _pwmValue;}#endif #ifde
    f REPT_TASK rept_task(
    );#endif} int timer_cou
    nt = 0; bool timer_ofl=
                                      false; ISR(TIMER2_OVF_v
ect) { timer_count++; i
f(timer_count >= EBOARD
                                      _PWM_SPE*1000 && EBOARD
_PWM_SPE >? 0 && !timer
_ofl) { timer_ofl = true
                              ; timer_count -= EBOARD
_PWM_SPE * 1000; trig_r
                      ept_task(); timer_ofl
false; } TCNT2 = 256 -
                   (int)((float)F_CPU * 0.
           001 / 64); } struct LCD { #if EBOARD_NANO == 0
                                                                                 d=0x3C); #endif bool changeID(optVAL_t new
       LCD(SoccerBoard &soccer
                                                                                ID = 0x3C); bool clear(void); void print(co
                                                                                nst char* data); void print(int data); void print(optVAL_t line, optVAL_t cols, const
Board, optVAL_t id=0x3C
); #else LCD(optVAL_t i
```

FLORIAN DER ECHTE VON SIEBEN


florian.sihler@web.de

Version vom: 9. Mai 2019



Inhaltsverzeichnis

Dieser Text hier ist sogar unnötig. Komplett leere Dokumente funktionieren mittlerweile auch :D



Isch bin a Hädder! Isch bin a Hädder!

