

```
In [1]: import numpy as np
import pandas as pd
import sklearn
import matplotlib.pyplot as plt
import seaborn as sns
import scipy
import keras
import tensorflow as tf
from keras.utils import to_categorical
```

```
In [2]: data = pd.read_csv("breast-cancer.data", header=None)
data.columns = ['Class', 'age', 'menopause', 'tumor-size', 'inv-nodes', 'node-caps', 'deg-malig', 'breast', 'breast-quad', 'irradiat']
```

```
In [3]: data
```

```
Out[3]:
```

	Class	age	menopause	tumor-size	inv-nodes	node-caps	deg-malig	breast	breast-quad	irradiat
0	no-recurrence-events	30-39	premeno	30-34	0-2	no	3	left	left_low	no
1	no-recurrence-events	40-49	premeno	20-24	0-2	no	2	right	right_up	no
2	no-recurrence-events	40-49	premeno	20-24	0-2	no	2	left	left_low	no
3	no-recurrence-events	60-69	ge40	15-19	0-2	no	2	right	left_up	no
4	no-recurrence-events	40-49	premeno	0-4	0-2	no	2	right	right_low	no
...
281	recurrence-events	30-39	premeno	30-34	0-2	no	2	left	left_up	no
282	recurrence-events	30-39	premeno	20-24	0-2	no	3	left	left_up	yes
283	recurrence-events	60-69	ge40	20-24	0-2	no	1	right	left_up	no
284	recurrence-events	40-49	ge40	30-34	3-5	no	3	left	left_low	no
285	recurrence-events	50-59	ge40	30-34	3-5	no	3	left	left_low	no

286 rows × 10 columns

```
In [4]: from sklearn.preprocessing import LabelEncoder
le = LabelEncoder()
for i in data:
    data[i] = le.fit_transform(data[i])
```

```
In [5]: x= data.drop("irradiat",axis=1)
y = data["irradiat"]
```

```
In [6]: x
```

```
Out[6]:
```

	Class	age	menopause	tumor-size	inv-nodes	node-caps	deg-malig	breast	breast-quad
0	0	1	2	5	0	1	2	0	2
1	0	2	2	3	0	1	1	1	5
2	0	2	2	3	0	1	1	0	2
3	0	4	0	2	0	1	1	1	3
4	0	2	2	0	0	1	1	1	4
...
281	1	1	2	5	0	1	1	0	3
282	1	1	2	3	0	1	2	0	3
283	1	4	0	3	0	1	0	1	3
284	1	2	0	5	4	1	2	0	2
285	1	3	0	5	4	1	2	0	2

286 rows × 9 columns

```
In [7]: y
```

```
Out[7]:
```

0	0
1	0
2	0
3	0
4	0
...	..
281	0
282	1
283	0
284	0
285	0

Name: irradiat, Length: 286, dtype: int32

```
In [8]: x.shape
```

```
Out[8]: (286, 9)
```

```
In [9]: y.shape
```

```
Out[9]: (286,)
```

```
In [10]: from sklearn.model_selection import train_test_split
xtrain,xtest,ytrain,ytest = train_test_split(x,y,test_size=0.25,random_state=0)
```

```
In [11]: xtrain1 = np.array(xtrain)
xtest1 = np.array(xtest)
ytrain1 = np.array(ytrain)
ytest1 = np.array(ytest)
```

```
In [12]: xtrain1 = xtrain1.reshape(xtrain1.shape[0],xtrain1.shape[1],1)
xtest1 = xtest1.reshape(xtest1.shape[0],xtest1.shape[1],1)
```

```
In [13]: xtrain1.shape
```

```
Out[13]: (214, 9, 1)
```

```
In [14]: xtest1.shape
```

```
Out[14]: (72, 9, 1)
```

```
In [15]: ytrain1.shape
```

```
Out[15]: (214,)
```

```
In [16]: ytest1.shape
```

```
Out[16]: (72,)
```

```
In [17]: from keras.layers import LSTM,Dense,Activation,Flatten
from keras.models import Sequential
```

```
In [18]: model = Sequential()
model.add(LSTM(100,input_shape=(xtrain1.shape[1],1)))
model.add(Dense(10))
model.add(Dense(8))
model.add(Dense(1))
model.summary()
```

Model: "sequential"

Layer (type)	Output Shape	Param #
=====	=====	=====
lstm (LSTM)	(None, 100)	40800
dense (Dense)	(None, 10)	1010
dense_1 (Dense)	(None, 8)	88
dense_2 (Dense)	(None, 1)	9
=====	=====	=====
Total params: 41,907		
Trainable params: 41,907		
Non-trainable params: 0		
=====		

```
In [19]: model.compile(metrics= ["accuracy"],optimizer="adam",loss="categorical_crossentropy")
```

```
In [20]: history = model.fit(xtrain1, ytrain1,batch_size=10,epochs=250)
```

```
Epoch 1/250
22/22 [=====] - 0s 9ms/step - loss: 2.8410e-08 - accuracy: 0.7617
Epoch 2/250
22/22 [=====] - 0s 7ms/step - loss: 2.8410e-08 - accuracy: 0.7617
Epoch 3/250
22/22 [=====] - 0s 6ms/step - loss: 2.8410e-08 - accuracy: 0.7617
Epoch 4/250
22/22 [=====] - 0s 7ms/step - loss: 2.8410e-08 - accuracy: 0.7617
Epoch 5/250
22/22 [=====] - 0s 7ms/step - loss: 2.8410e-08 - accuracy: 0.7617
Epoch 6/250
22/22 [=====] - 0s 6ms/step - loss: 2.8410e-08 - accuracy: 0.7617
Epoch 7/250
22/22 [=====] - 0s 6ms/step - loss: 2.8410e-08 - accuracy: 0.7617
```

```
In [21]: history = pd.DataFrame(history.history)
history
```

```
Out[21]:
```


	loss	accuracy
--	------	----------

0	2.840969e-08	0.761682
1	2.840969e-08	0.761682
2	2.840969e-08	0.761682
3	2.840969e-08	0.761682
4	2.840969e-08	0.761682
...
245	2.840969e-08	0.761682
246	2.840969e-08	0.761682
247	2.840969e-08	0.761682
248	2.840969e-08	0.761682
249	2.840969e-08	0.761682

250 rows × 2 columns

```
In [22]: history.plot(figsize=(15,10))
```

```
Out[22]: <AxesSubplot:>
```



```
In [23]: ypredict = np.argmax(model.predict(xtest1), axis=-1)
```

```
In [24]: from sklearn.metrics import accuracy_score  
accuracy_score(ytest1,ypredict)
```

```
Out[24]: 0.7638888888888888
```