

Polymer Simulation with a Flat Histogram Stochastic Growth Algorithm

Thomas Prellberg

`thomas.prellberg@qmul.ac.uk`

School of Mathematical Sciences
Queen Mary, University of London

joint work with

J. Krawczyk, TU Clausthal


A. Rechnitzer and A.L. Owczarek, Uni Melbourne

- Polymers in solution:
 - Equilibrium statistical mechanics, lattice model
- Algorithm:
 - Stochastic growth & flat histogram (flatPERM)
- Applications:
 - Bulk phenomena (previous work)
 - polymer collapse, protein groundstates
 - Surface phenomena (this talk)
 - confined polymers, force-induced desorption, interplay of collapse and adsorption
- Work in progress:
 - off-lattice models, extended Domb-Joyce model, . . .

Introduction

Modelling of Polymers in Solution


- Polymers:
long chains of monomers
- “Coarse-Graining”:
beads on a chain
- “Excluded Volume”:
minimal distance
- Contact with solvent:
effective short-range interaction
- Good/bad solvent:
repelling/attracting interaction
- Surface interaction treated analogously



Pedagogical Setting: Lattice Model

Self-Avoiding Walks with Interactions


- Physical space \rightarrow simple cubic lattice \mathbb{Z}^3
- Polymer \rightarrow self-avoiding random walk (SAW)
- Quality of solvent \rightarrow short-range interaction ϵ



Pedagogical Setting: Lattice Model

Self-Avoiding Walks with Interactions

- Physical space \rightarrow simple cubic lattice \mathbb{Z}^3
- Polymer \rightarrow self-avoiding random walk (SAW)
- Quality of solvent \rightarrow short-range interaction ϵ




Why Simulations?

- Most interesting open questions for dense and geometrically restricted configurations
- There is little theory and

this is notoriously difficult to simulate

Application: Pulling of Collapsed and Adsorbed Polymers

- In addition to
 - solvent modelling (bulk interaction)
- add
 - adsorption (surface interaction)
 - micromechanical deformations e.g. force on chain end (optical tweezers)
- Complete description through three-dimensional density of states:
(a) bulk energy, (b) surface energy, (c) position of chain end







Stochastic Growth Algorithm

PERM: “Go With The Winners”

PERM = Pruned and Enriched Rosenbluth Method

Grassberger, Phys Rev E 56 (1997) 3682

● Rosenbluth Method: kinetic growth




PERM: “Go With The Winners”

PERM = Pruned and Enriched Rosenbluth Method

Grassberger, Phys Rev E 56 (1997) 3682

- Rosenbluth Method: kinetic growth




- Enrichment: weight too large \rightarrow make copies of configuration
- Pruning: weight too small \rightarrow remove configuration occasionally

PERM: “Go With The Winners”

PERM = Pruned and Enriched Rosenbluth Method

Grassberger, Phys Rev E 56 (1997) 3682

- Rosenbluth Method: kinetic growth



- Enrichment: weight too large \rightarrow make copies of configuration
- Pruning: weight too small \rightarrow remove configuration occasionally

Current work: flatPERM = flat histogram PERM

TP and JK, PRL 92 (2004) 120602, TP, JK, and AR, Athens Proceedings 2004

- flatPERM samples a generalised multicanonical ensemble
- Determines the whole density of states in *one* simulation!

Algorithm details

View kinetic growth as *approximate enumeration*

Algorithm details

View kinetic growth as *approximate enumeration*

- Exact enumeration: choose *all* a continuations with equal weight
- Kinetic growth: chose *one* continuation with a -fold weight

Algorithm details

View kinetic growth as *approximate enumeration*

- Exact enumeration: choose *all* a continuations with equal weight
- Kinetic growth: chose *one* continuation with a -fold weight
- An n step configuration gets assigned a weight

$$W = \prod_{k=0}^{n-1} a_k$$

Algorithm details

View kinetic growth as *approximate enumeration*

- Exact enumeration: choose *all* a continuations with equal weight
- Kinetic growth: chose *one* continuation with a -fold weight
- An n step configuration gets assigned a weight

$$W = \prod_{k=0}^{n-1} a_k$$

- S growth chains with weights $W_n^{(i)}$ give an estimate of the total number of configurations, $C_n^{est} = \langle W \rangle_n = \frac{1}{S} \sum_i W_n^{(i)}$

Algorithm details

View kinetic growth as *approximate enumeration*

- Exact enumeration: choose *all* a continuations with equal weight
- Kinetic growth: chose *one* continuation with a -fold weight
- An n step configuration gets assigned a weight

$$W = \prod_{k=0}^{n-1} a_k$$

- S growth chains with weights $W_n^{(i)}$ give an estimate of the total number of configurations, $C_n^{est} = \langle W \rangle_n = \frac{1}{S} \sum_i W_n^{(i)}$
- Add pruning/enrichment with respect to ratio $r = W_n^{(S+1)} / C_n^{est}$

Algorithm details

View kinetic growth as *approximate enumeration*

- Exact enumeration: choose *all* a continuations with equal weight
- Kinetic growth: chose *one* continuation with a -fold weight
- An n step configuration gets assigned a weight

$$W = \prod_{k=0}^{n-1} a_k$$

- S growth chains with weights $W_n^{(i)}$ give an estimate of the total number of configurations, $C_n^{est} = \langle W \rangle_n = \frac{1}{S} \sum_i W_n^{(i)}$
- Add pruning/enrichment with respect to ratio $r = W_n^{(S+1)} / C_n^{est}$
- Number of samples generated for each n is roughly constant
- We have a flat histogram algorithm in system size

From PERM to flatPERM

- Consider athermal case
- PERM: estimate number of configurations C_n
 - $C_n^{est} = \langle W \rangle_n$
 - $r = W_n^{(i)} / C_n^{est}$

From PERM to flatPERM



- Consider athermal case
 - PERM: estimate number of configurations C_n
 - $C_n^{est} = \langle W \rangle_n$
 - $r = W_n^{(i)} / C_n^{est}$
- Consider energy E , temperature $\beta = 1/k_B T$
 - thermal PERM: estimate partition function $Z_n(\beta)$
 - $Z_n^{est}(\beta) = \langle W \exp(-\beta E) \rangle_n$
 - $r = W_n^{(i)} \exp(-\beta E^{(i)}) / Z_n^{est}(\beta)$

From PERM to flatPERM


- Consider athermal case
 - PERM: estimate number of configurations C_n
 - $C_n^{est} = \langle W \rangle_n$
 - $r = W_n^{(i)} / C_n^{est}$
- Consider energy E , temperature $\beta = 1/k_B T$
 - thermal PERM: estimate partition function $Z_n(\beta)$
 - $Z_n^{est}(\beta) = \langle W \exp(-\beta E) \rangle_n$
 - $r = W_n^{(i)} \exp(-\beta E^{(i)}) / Z_n^{est}(\beta)$
- Consider parametrisation \vec{m} of configuration space
 - flatPERM: estimate density of states $C_{n,\vec{m}}$
 - $C_{n,\vec{m}}^{est} = \langle W \rangle_{n,\vec{m}}$
 - $r = W_{n,\vec{m}}^{(i)} / C_{n,\vec{m}}^{est}$

Simulation Results

Simulation results: ISAW






- 2d ISAW up to $n = 1024$
 - One simulation suffices
 - 400 orders of magnitude
- (only 2d shown, 3d similar)



TP and JK, PRL 92 (2004) 120602

2-Dimensional Density of States



- Force-induced desorption of adsorbed polymers
 - Relevance: optical tweezers, AFM; related to DNA unzipping
- 3-dim polymer in a half space, one simulation, up to $n = 256$




JK et al, JSTAT (2004) P10004

2-Dimensional Density of States

- Layering transitions of adsorbed polymers in poor solvents





- whole phase diagram at once
- low temperatures accessible
- hierarchy of layering transitions
- resolved controversy over “surface attached globule”



JK et al, Europhys Lett, in print

3-Dimensional Density of States

- Pulling adsorbing and collapsing polymers off a surface



$$\epsilon_s = \alpha, \epsilon_b = 1 - \alpha$$

- simulations up to $n = 91$ (4-dimensional histogram)
- interplay of (both force-induced and thermal) desorption ($\alpha = 1$) and stretching ($\alpha = 0$)

JK et al, JSTAT, in print

Summary and Outlook

Conclusion: A Promising New Algorithm

- Presented “flat histogram” version of PERM
- *One* simulation for complete density of states!
(the range can also be selectively restricted)

Conclusion: A Promising New Algorithm

- Presented “flat histogram” version of PERM
 - *One* simulation for complete density of states!
(the range can also be selectively restricted)
- Simulations of polymers:
 - collapsed polymers
 - force-induced desorption of adsorbed polymers
 - interplay adsorption/collapse
 - force-induced stretching/desorption

Conclusion: A Promising New Algorithm

- Presented “flat histogram” version of PERM
 - *One* simulation for complete density of states!
(the range can also be selectively restricted)
- Simulations of polymers:
 - collapsed polymers
 - force-induced desorption of adsorbed polymers
 - interplay adsorption/collapse
 - force-induced stretching/desorption
- Outlook: applications to further models, e.g.
 - off-lattice simulations
 - extended Domb-Joyce model

The End