TOPSTECHNOLOGIES
Training | Outsourcing | Placement | Study Abroad

Comptia N+ Assignment

[N+ - Network security, Maintenance and Troubleshooting procedures]

DNS Server Configuration

How DNS resolves domain names to IPs. Configure a DNS server and test domain resolution.

Task: Document the configuration and troubleshooting steps.

1. **Install and set up a DNS server on your local machine or a VM using BIND (Linux) or Simple DNS Plus (Windows), then create a new DNS zone for the domain musicmania.in.**

   ➢ **Aim**
   - To install and configure a DNS server using BIND9 on a Linux machine, create a DNS zone for the domain musicmania.in, and test domain name resolution by converting domain names into IP addresses.

   ➢ **Introduction**
   - **DNS (Domain Name System)** is a naming system used to translate human-readable domain names into IP addresses. Computers use IP addresses to communicate with other devices and servers over a network.


- For example, when a user enters www.musicmania.in in a web browser, the DNS server searches for the corresponding IP address and returns it to the user's computer.
- **BIND9 (Berkeley Internet Name Domain)** is a widely used DNS server software for Linux. It allows network administrators to create DNS zones, add DNS records, and manage domain name resolution.

➢ **How DNS Resolves Domain Names to IP Addresses**

➢ DNS resolution generally takes place through the following steps:

1) The user enters a domain name, such as www.musicmania.in, in a web browser.
2) The computer checks its local DNS cache to see whether the IP address is already available.
3) If the address is not cached, the computer sends a DNS query to its configured DNS server.
4) The DNS server searches its DNS records for the requested domain name.
5) If a matching record is found, the DNS server returns the corresponding IP address.
6) The browser uses that IP address to establish communication with the destination server.


➢ **DNS Resolution Diagram**



v
DNS Query
|
v
DNS Server
(BIND9)
|
v
Searches DNS Zone Records
|
v
Finds the IP Address
192.168.1.10
|
v
Returns IP to Browser
|
v
Domain Resolution
Successful

- **Tools and Requirements**
  - Ubuntu Linux operating system or virtual machine
  - Internet connection for installing BIND9
  - Terminal
  - BIND9 DNS server software
  - DNS utilities such as dig and nslookup

- **Procedure for Installing and Configuring BIND9**
- **Step 1: Update the Linux Package List**
- Open the Ubuntu Terminal and execute:
  sudo apt update
- This command updates the package information available on the Linux system.
- **Step 2: Install BIND9**
- Execute the following command:
  sudo apt install bind9 bind9-utils dnsutils
- This installs:
  - **BIND9:** DNS server software.
  - **BIND9 Utilities:** Tools for checking DNS configuration.
  - **DNS Utilities:** Commands such as dig and nslookup for testing DNS.



- **Step 3: Check the BIND9 Service**
- Execute:
  sudo systemctl status bind9
- This command checks whether the BIND9 DNS service is running.
- If the service is not running, start it using:

sudo systemctl start bind9

- **Step 4: Create a DNS Zone**
- Open the BIND9 local configuration file:
  sudo nano /etc/bind/named.conf.local
- Add the following configuration:

```
zone "musicmania.in" {
    type master;
    file "/etc/bind/db.musicmania.in";
};
```

- Save the file and exit the editor.
- **Explanation:**
  - zone: Defines the domain name.
  - musicmania.in: The domain for which the DNS zone is created.
  - type master: Defines this server as the primary authoritative DNS server for the zone.
  - file: Specifies the location of the DNS zone file.




- **Step 5: Create the DNS Zone File**
- Create a new zone file:
  sudo nano /etc/bind/db.musicmania.in

- Enter the following DNS records:

```
$TTL 86400
@   IN  SOA ns1.musicmania.in. admin.musicmania.in. (
        2026110401
        3600
        1800
        604800
        86400
    )


    @       IN  NS  ns1.musicmania.in.
    ns1     IN  A   192.168.1.10
    @       IN  A   192.168.1.10
    www     IN  A   192.168.1.10
    mail    IN  A   192.168.1.20
```



- **Explanation of DNS Records:**

Record	Purpose
SOA	Contains important information about the DNS zone and its administrator.
NS	Identifies the authoritative name server for the domain.
A	Maps a domain name to an IPv4 address.
TTL	Specifies how long DNS information can be cached.


- The IP addresses used above are example addresses for a private lab network. Replace them with the actual addresses configured in your lab if necessary.
- **Step 6: Check the DNS Configuration**
- First, check the main BIND9 configuration:
- sudo named-checkconf
- Next, check the newly created DNS zone:
- sudo named-checkzone musicmania.in /etc/bind/db.musicmania.in
- If the configuration is correct, the zone check should report that it loaded successfully.



- **Step 7: Restart the BIND9 Service**
- Execute:
- sudo systemctl restart bind9
- Then verify the service:
- sudo systemctl status bind9
- The service should show an active or running status.

- **Testing DNS Domain Resolution**
- After configuring the DNS zone, use the following commands to test domain name resolution.
- **Test 1: Using the dig Command**
- Execute:
- dig @127.0.0.1 musicmania.in A
- This command sends a DNS query to the local BIND9 server and requests the IPv4 address of musicmania.in.
- **Test 2: Test the www Subdomain**
- Execute:
- dig @127.0.0.1 www.musicmania.in A
- The DNS server should return the configured IPv4 address for www.musicmania.in.
- **Test 3: Using nslookup**
- Execute:
- nslookup www.musicmania.in 127.0.0.1
- This command checks whether the local DNS server can resolve the domain name.

- **Expected result:** The DNS server should return 192.168.1.10 for www.musicmania.in, provided the zone has been configured correctly.



- **Troubleshooting Steps**
- If DNS resolution does not work, the following troubleshooting steps can be performed:

Problem	Possible Cause	Solution
BIND9 service is not running	Service stopped or configuration problem	Check and restart the BIND9 service.
Zone file error	Incorrect DNS record syntax	Check the zone file using named-checkzone.
Configuration error	Incorrect configuration in named.conf.local	Run named-checkconf and correct the errors.

Domain not resolving	Missing or incorrect DNS records	Verify the A and NS records in the zone file.
DNS query timed out	DNS service not responding or blocked by firewall	Check the service, network settings, and DNS port 53 access.
Old IP address returned	Cached DNS information	Clear the DNS cache or wait for the TTL to expire.

- **Observation**
- The following table shows the expected DNS configuration and testing results for the lab setup.

No.	**Domain Name**	**DNS Record**	**Expected IP Address**
1	musicmania.in	A	192.168.1.10
2	www.musicmania.in	A	192.168.1.10

3	ns1.musicmania.in	A	192.168.1.10
4	mail.musicmania.in	A	192.168.1.20

- The actual observation should be recorded according to the output displayed by the DNS testing commands.

- **Result**
- BIND9 was installed and configured on the Linux system. A DNS zone named musicmania.in was created, and DNS records were added for the main domain and its subdomains. Domain resolution was tested using dig and nslookup.

2. Add an A record in your DNS server configuration to map www.musicmania.in to the IP address 192.168.1.50, then use the nslookup or dig command to verify the mapping works.

- **Aim**
  - To add an A (Address) record in the BIND9 DNS server configuration to map www.musicmania.in to the IPv4 address 192.168.1.50 and verify the mapping using nslookup or dig.

- **Introduction**
  - A **DNS A Record (Address Record)** is used to map a domain name or hostname to an IPv4 address. It helps computers locate servers using easy-to-remember domain names instead of numerical IP addresses.

- For example, when a user enters www.musicmania.in in a browser, the DNS server checks its A record and returns the corresponding IP address 192.168.1.50.
- In this practical, an A record is added to the existing musicmania.in DNS zone using BIND9 on Linux.

➢ **Requirements**
- Ubuntu Linux or a Linux virtual machine
- BIND9 DNS server installed and running
- Existing DNS zone: musicmania.in
- Terminal
- nslookup or dig command

➢ **Procedure**
➢ **Step 1: Open the DNS Zone File**
➢ Open the terminal and execute:
sudo nano /etc/bind/db.musicmania.in
➢ This command opens the DNS zone file of musicmania.in.
➢ **Step 2: Add the A Record**
➢ Add the following record to the zone file:
www IN A 192.168.1.50
➢ **Explanation:**
- www: The hostname or subdomain.
- IN: Represents the Internet DNS class.
- A: Specifies an IPv4 address record.
- 192.168.1.50: The IPv4 address mapped to the hostname.

➢ Save the file and exit the editor.



- **Step 3: Update the Zone Serial Number**
- Inside the SOA record, increase the serial number whenever the zone file is modified.
- For example:
  2026110401
- can be changed to:
  2026110402
- This helps DNS servers identify that the zone information has been updated.
- **Step 4: Verify the Zone Configuration**
- Execute:
  sudo named-checkzone musicmania.in /etc/bind/db.musicmania.in
- If the configuration is correct, the command should display a successful zone-loading message followed by OK.



- **Step 5: Restart the BIND9 Service**

- Execute:
  sudo systemctl restart bind9
- Check the service status:
  sudo systemctl status bind9
- The service should show an active or running status.

- **Testing and Verification**
- After updating the DNS zone, use the following commands to verify the A record.
- **Method 1: Using nslookup**
- Execute:
  nslookup www.musicmania.in 127.0.0.1
- The expected output should show:
  Server: 127.0.0.1
  Address: 127.0.0.1#53

  Name: www.musicmania.in
  Address: 192.168.1.50
- **Method 2: Using dig**
- Execute:
  dig @127.0.0.1 www.musicmania.in A
- The ANSWER SECTION should contain:
  www.musicmania.in. 86400 IN A 192.168.1.50
- This confirms that the DNS server is returning the correct IPv4 address for the hostname.



- **Observation Table**

No.	Domain Name	DNS Record	Configured IP Address	Expected Result
1	www.musicmania.in	A	192.168.1.50	Successful resolution

- **Result**
- An A record was added successfully to the BIND9 DNS zone for musicmania.in. The hostname www.musicmania.in was mapped to the IPv4 address 192.168.1.50. The configuration was tested using nslookup or dig.

3. **Simulate a typo by adding a CNAME record for play.musicmania.in that points to www.musicmania.in, then test if accessing play.musicmania.in resolves to the correct IP address.**

➢ **Aim**

- To create a CNAME (Canonical Name) record in the BIND9 DNS server for play.musicmania.in, pointing to www.musicmania.in, and verify that it resolves to the correct IPv4 address.


➢ **Introduction**

- A **CNAME (Canonical Name) Record** is a type of DNS record that maps one domain name or hostname to another domain name. It is commonly used to create an alias for an existing domain name.
- For example, play.musicmania.in can be configured as an alias of www.musicmania.in. When a user accesses play.musicmania.in, the DNS server follows the CNAME record and resolves the target hostname to its corresponding IP address.
- In this practical, a CNAME record is added to the existing musicmania.in DNS zone using BIND9.

➢ **Requirements**

- Ubuntu Linux or a Linux virtual machine
- BIND9 DNS server installed and running
- Existing DNS zone: musicmania.in
- Existing A record for www.musicmania.in
- Terminal
- dig or nslookup command

- **Procedure**
- **Step 1: Open the DNS Zone File**
- Open the terminal and execute:
  sudo nano /etc/bind/db.musicmania.in
- This command opens the DNS zone file of musicmania.in.
- **Step 2: Add the CNAME Record**
- Add the following record to the zone file:
  play IN CNAME www.musicmania.in.
- **Explanation:**
  - play: The hostname or alias being created.
  - IN: Represents the Internet DNS class.
  - CNAME: Specifies a Canonical Name record.
  - www.musicmania.in.: The target hostname to which the alias points.
- The final dot indicates that the target is a fully qualified domain name.



- **Step 3: Update the Zone Serial Number**
- Whenever a DNS zone file is modified, increase the serial number in its SOA record.
- For example, change:

2026110402

- to:
  2026110403
- This indicates that the DNS zone has been updated.
- Save the file and exit the editor.
- **Step 4: Verify the DNS Zone Configuration**
- Execute:
  sudo named-checkzone musicmania.in /etc/bind/db.musicmania.in
- If the configuration is correct, the command should display a successful zone-loading message followed by:
  OK




- **Step 5: Restart the BIND9 Service**
- Execute:
  sudo systemctl restart bind9
- Check the service status:
  sudo systemctl status bind9
- The service should show an active or running status.

- **Testing and Verification**
- After adding the CNAME record, use the following commands to test DNS resolution.
- **Test 1: Check the CNAME Record Using dig**
- Execute:
  dig @127.0.0.1 play.musicmania.in CNAME

- The expected ANSWER SECTION should contain:
  play.musicmania.in. 86400 IN CNAME www.musicmania.in.
- This confirms that play.musicmania.in points to www.musicmania.in.
- **Test 2: Check the Final IP Address**
- Execute:
  dig @127.0.0.1 play.musicmania.in A
- The expected result should contain:
  play.musicmania.in. 86400 IN CNAME www.musicmania.in.
  www.musicmania.in. 86400 IN A 192.168.1.50
- The DNS server follows the CNAME record and returns the IPv4 address of the target hostname.
- **Test 3: Verify Using nslookup**
- Execute:
  nslookup play.musicmania.in 127.0.0.1
- The expected output should show the resolved address:
  Server: 127.0.0.1
  Address: 127.0.0.1#53

  Name: www.musicmania.in
  Address: 192.168.1.50
  Aliases: play.musicmania.in
- The exact formatting may differ depending on the DNS utility.



- **Observation Table**

No.	Domain Name	DNS Record	Target Domain	Resolved IP
1	play.musicmania.in	CNAME	www.musicmania.in	192.168.1.50

- **Result**
- A CNAME record was successfully added to the BIND9 DNS zone for musicmania.in. The hostname play.musicmania.in was configured as an alias of www.musicmania.in. DNS testing demonstrated that the alias resolves to the IPv4 address 192.168.1.50.

4. **Your DNS server is not resolving the domain musicmania.in as expected. Document the step-by-step troubleshooting process you would follow, including checking configuration files, restarting the DNS service, and testing with nslookup or dig. Include at least three different troubleshooting commands or checks in your documentation.**

➢ **Aim**

- To identify and troubleshoot DNS resolution problems in a BIND9 DNS server by checking configuration files, verifying DNS records, restarting the DNS service, and testing domain resolution using nslookup and dig.

➢ **Introduction**

- **DNS (Domain Name System)** translates human-readable domain names into IP addresses. It allows users to access websites and network services using domain names instead of numerical IP addresses.
- Sometimes, a DNS server may fail to resolve a domain name because of incorrect configuration files, missing DNS records, a stopped DNS service, firewall restrictions, or network connectivity problems.
- In this practical, the domain musicmania.in is used to understand the troubleshooting process of a BIND9 DNS server running on Linux.


➢ **Common Causes of DNS Resolution Problems**

➢ The following issues may prevent a DNS server from resolving domain names:

1) Incorrect DNS zone configuration.
2) Missing or incorrect A or CNAME records.
3) BIND9 service is stopped or not running.

4) Incorrect DNS server address on the client computer.
5) Firewall blocking DNS traffic on port 53.
6) Errors in the DNS zone file or SOA serial number not updated.

- **Step-by-Step DNS Troubleshooting Process**
- **Step 1: Check the BIND9 Service Status**
- First, check whether the BIND9 DNS service is running.
- Execute:
  sudo systemctl status bind9
- **Explanation:**
- This command displays the current status of the BIND9 service.
  - If the service shows active (running), the DNS service is running.
  - If the service is inactive or failed, it may need to be started or repaired.
- To start the service, execute:
  sudo systemctl start bind9



- **Step 2: Check the Main DNS Configuration File**
- Check the BIND9 configuration for syntax errors.
- Execute:
  sudo named-checkconf
- **Explanation:**
- This command checks the main BIND9 configuration files for syntax errors. If no errors are reported, the configuration syntax is valid.
- Also check the local zone configuration:
  sudo nano /etc/bind/named.conf.local
- Verify that the musicmania.in zone is configured correctly:


```
zone "musicmania.in" {
    type master;
    file "/etc/bind/db.musicmania.in";
};
```

- **Step 3: Check the DNS Zone File**
- Open the DNS zone file:
  sudo nano /etc/bind/db.musicmania.in
- Check whether the required DNS records are present and correctly written.
- Example:


```
$TTL 86400
@   IN  SOA ns1.musicmania.in. admin.musicmania.in. (
        2026110403
        3600
        1800
        604800
        86400
)
```

```
@       IN  NS      ns1.musicmania.in.
ns1     IN  A       192.168.1.10
@       IN  A       192.168.1.10
www     IN  A       192.168.1.50
play    IN  CNAME   www.musicmania.in.
```

- **Explanation:**
  - SOA contains important information about the DNS zone.
  - NS identifies the authoritative name server.
  - A maps a hostname to an IPv4 address.
  - CNAME creates an alias for another domain name.
- If any record is missing or incorrect, correct the zone file and increase the SOA serial number.



- **Step 4: Validate the DNS Zone File**
- Execute:
  sudo named-checkzone musicmania.in /etc/bind/db.musicmania.in
- **Explanation:**
- This command checks the DNS zone file for syntax and record errors.
- If the zone is configured correctly, the output should show:
  zone musicmania.in/IN: loaded serial 2026110403
  OK
- If an error appears, correct the relevant DNS record or zone file syntax.




- **Step 5: Restart the BIND9 DNS Service**
- After correcting the configuration, restart the DNS service.
- Execute:
  sudo systemctl restart bind9
- Then verify its status:

sudo systemctl status bind9

- The service should show active (running).
- **Step 6: Check DNS Port 53**
- DNS commonly uses port 53 for both UDP and TCP communication.
- Execute:
  sudo ss -tulnp | grep ':53'
- **Explanation:**
- This command checks whether a DNS service is listening on port 53.
- If the service is not listening on the expected address and port, investigate the BIND9 service and its listening configuration.
- If a firewall is enabled, check its status:
  sudo ufw status
- Ensure that the required DNS traffic is permitted according to the network's security policy.
- **Step 7: Test Domain Resolution Using dig**
- Execute:
  dig @127.0.0.1 musicmania.in A
- **Explanation:**
- This command sends a DNS query directly to the local BIND9 server and requests the IPv4 address of musicmania.in.
- A successful response should show the configured A record in the ANSWER SECTION.
- **Step 8: Test Domain Resolution Using nslookup**
- Execute:
  nslookup musicmania.in 127.0.0.1
- **Explanation:**

- This command checks whether the local DNS server can resolve musicmania.in.
- If the DNS configuration is correct, it should return the configured IP address.
- **Step 9: Check DNS Service Logs**
- If the problem still exists, examine the DNS service logs.
- Execute:
  sudo journalctl -u bind9 -n 50 --no-pager
- **Explanation:**
- This command displays the latest 50 log entries related to BIND9. It can help identify service failures, configuration errors, and other DNS-related problems.



- **Important Troubleshooting Commands**

No.	Command	Purpose

1	sudo systemctl status bind9	Checks DNS service status.
2	sudo named-checkconf	Checks BIND9 configuration syntax.
3	sudo named-checkzone musicmania.in /etc/bind/db.musicmania.in	Validates the DNS zone file.
4	sudo systemctl restart bind9	Restarts the DNS service.
5	sudo ss -tulnp | grep ':53'	Checks whether DNS is listening on port 53.
6	dig @127.0.0.1 musicmania.in A	Tests DNS resolution using dig.
7	nslookup musicmania.in 127.0.0.1	Tests domain resolution using nslookup.
8	sudo journalctl -u bind9 -n 50 --no-pager	Checks recent DNS service logs.

- **Result**
- The DNS troubleshooting process for the domain musicmania.in was studied. BIND9 service status, configuration files, DNS zone records, port 53, and service logs were checked. Domain resolution can be tested using dig and nslookup after correcting any configuration problems.